



KEY	DESCRIPTION	SYM.	DET/SHT
<b>SHELL</b>			
(E)	ENTRY VESTIBULE CEILING		
(E)	EXTERIOR AWNING SYSTEM		
<b>CONSTRUCTION</b>			
(C)	GYP. BOARD CEILING W/ CEILING JOISTS, CENTER LINE U.O.N.		C0-3
(P)	PROVIDE ACoustICAL CEILING PER FINISH SCHEDULE		A1-A1
<b>LIGHTING</b>			
(L)	EXTERIOR WALL MOUNTED LIGHTING		SEE ELEC
(L)	EXTERIOR LIGHTING, CENTERED ABOVE DOOR		SEE ELEC
(L)	ILLUMINATED EXIT SIGN		SEE ELEC
(L)	FACE-LIT CHANNEL LETTERS MOUNTED TO EIFS (BREEZEWAY)		SEE ELEC
(L)	FACE-LIT CHANNEL LETTERS MOUNTED TO EIFS (SCREEN WALL)		A11-0
(L)	ILLUMINATED BLADE SIGN, SUSPENDED FROM BREEZEWAY		A11-0
(L)	4'-0" OR 8'-0" LONG FLUORESCENT STRIP FIXTURE, MOUNT TO CONTINUOUS TRACK, SYMMETRICAL REFLECTORS ON STOCK AREA FIXTURES, U.O.N.		SEE ELEC
(L)	4'-0" LONG FLUORESCENT STRIP FIXTURE, SURFACE MOUNT TO BOTTOM OF GYP CEILING		SEE ELEC
(L)	4'-0" OR 8'-0" LONG FLUORESCENT FIXTURE W/ ASYMMETRICAL REFLECTOR, MOUNT TO SIDE OF UNISTRUT		SEE ELEC
(L)	4'-0" OR 8'-0" LONG FLUORESCENT STRIP FIXTURE MOUNTED TO TRACK, TRACK SECURED TO UNISTRUT		SEE ELEC
(L)	2 HEADS CENTERED WITHIN EACH BAY SPACED AT 12" APART O.C. EA. HEAD TO BE AIMED AS SHOWN ON PLANS AT 45 DEGREE ANGLES / TYP. ENTIRE LENGTH		SEE ELEC
(L)	2 TRACK HEADS MOUNTED BETWEEN PENDANT & END OF TRACK. EA. HEAD TO BE AIMED AS SHOWN ON PLANS AT 45 DEGREE ANGLES		SEE ELEC
(L)	CONTINUOUS TRACK W/ HEADS SPACED 5'-0" O.C. MOUNT TO B.O. UNISTRUT		SEE ELEC
(L)	CONTINUOUS TRACK W/ HEADS MOUNTED 4'-0" O.C. MOUNT TO B.O. UNISTRUT		SEE ELEC
(L)	CONTINUOUS TRACK W/ HEADS MOUNTED 3'-0" O.C. MOUNT TO WALL AT 6" ABOVE STOREFRONT		SEE ELEC
(L)	WHITE PENDANT FIXTURE, B.O. FIXTURE AT 9'-6" A.F.F. MOUNT TO LIGHT TRACK, SPACE AS DIMENSIONED.		SEE ELEC
(L)	BLUE PENDANT FIXTURE, B.O. FIXTURE AT 9'-6" A.F.F. MOUNT TO LIGHT TRACK, SPACE AS DIMENSIONED.		SEE ELEC
(L)	(N) PEOPLE COUNTER		SEE ELEC
(L)	ILLUMINATED EXIT SIGN, SUSPEND B.O. FIXTURE AT 11'-0" AFF. SURFACE MOUNT B.O. FIXTURE AT 7'-6" AFF.		SEE ELEC
(L)	MUSIC SPEAKER LOCATE IN CENTER OF BAY. VENDOR TO MOUNT B.O. SPEAKER AT 13'-6" A.F.F. GO TO PROVIDE & INSTALL UNISTRUT		8 / A4-1
(L)	PORCELAIN SOCKET FIXTURE WITH MOTION SENSOR		SEE ELEC
(L)	4'-0" FLUORESCENT FIXTURE WITH MOTION SENSOR		SEE ELEC
(L)	RECESSED CEILING MOUNTED SPEAKER - CENTER BETWEEN LIGHT FIXTURES		10 / A10-1
(L)	6" RECESSED LED DOWNLIGHT		SEE ELEC
(L)	6" RECESSED LED DOWNLIGHT AT ENTRY PORTAL		SEE ELEC
(L)	JELLY JAR FIXTURE WALL MOUNTED ON EITHER SIDE OF MIRROR		SEE ELEC
(L)	4'-0" LONG EMERGENCY FLUORESCENT STRIP FIXTURE MOUNT TO UNISTRUT AT 13'-6" A.F.F.		SEE ELEC
<b>SYMBOLS LEGEND</b>			
1. ALL DIMENSIONS FOR LOCATING FIXTURES ARE FROM FACE OF WALL FINISH TO CENTERLINE OF FIXTURE U.O.N.			
2. ALL CEILING HEIGHTS ARE FROM TOP OF FINISH FLOOR TO UNDERSIDE OF FINISH DECK, U.O.N.			
3. PROVIDE ADEQUATE CLEARANCES FOR FIXTURES, DUCTS, CEILINGS AND RELATED PERTINENT ITEMS NECESSARY TO MAINTAIN THE SPECIFIED HEIGHTS A.F.F.			
4. ARCHITECTURAL DWGS DETERMINE LOCATION OF LUMINAIRES AND SUPERCEED MEP.			
5. SEE ELECTRICAL DWGS FOR FIXTURE MODEL NUMBERS KEYED TO FIXTURE TYPE ON LEGEND THIS PAGE.			
6. ADDITIONAL HANGER AND SAFETY WIRES FOR LIGHT FIXTURES, SPEAKERS & DUCTWORK, AS REQUIRED BY LOCAL CODES, TO BE THE RESPONSIBILITY OF THE G.C.			
7. SEE MECHANICAL DRAWINGS FOR DIFFUSER LOCATIONS.			
8. SEE ELECTRICAL DWGS FOR SOUND SYSTEM REQUIREMENTS AND SCOPE OF WORK.			
9. REAR EXIT DOOR EXTERIOR LIGHT FIXTURES TO CONNECT WITH LL ELECTRICAL PANEL.			
<b>GRAPHICS / SIGNAGE</b>			
(G)	CASHWRAP ENTRY SIGN - VENDOR TO MOUNT B.O. SIGN AT 8'-6" A.F.F. - G.C. TO PROVIDE UNISTRUT AND POWER		7 / A11-1
(G)	FITTING ROOM DIRECTION SIGN - VENDOR TO MOUNT B.O. SIGN AT 8'-6" A.F.F. - G.C. TO PROVIDE UNISTRUT AND POWER		9 / A11-1
(G)	FITTING ROOM SIGN - VENDOR TO MOUNT B.O. SIGN AT 8'-6" A.F.F. - G.C. TO PROVIDE UNISTRUT		8 / A11-1
(G)	TOILET ROOM SIGN - VENDOR TO MOUNT B.O. SIGN AT 8'-6" A.F.F. - G.C. TO PROVIDE UNISTRUT AND POWER		12 / A11-1
(G)	WOOD SLAT GRID TO BE CONSTRUCTED TO FIT WITHIN UNISTRUT GRID. HANG INDEPENDENTLY WITH CABLE ATTACHED DIRECTLY TO DECK ABOVE - ALIGN METAL FRAME WITH UNISTRUT GRID		5, 6, 9 / A4-1
(G)	(2) ROSE SYSTEM TRACK - MOUNT 6" ABOVE STOREFRONT, AT 18" AND 27" FROM GLAZING. SEE STOREFRONT ELEVATION ON SHEET A2-1 FOR GLAZING DIMENSION TO DETERMINE FRAME KITS SIZING.		A2-1 10 / A4-1
<b>MEP</b>			
(M)	SLOT DIFFUSERS		SEE MECH
(M)	WALL MOUNTED WATER HEATER - MOUNTED ABOVE MOP SINK - REFER TO PLUMBING SHEETS		11 / A10-1 SEE PLUMB
(M)	DROP POWER AT THIS LOCATION FOR F.L. LIGHTS. RUN 1/2" ELEC. CONDUIT ALONG SIDES & BACK OF ROOMS & KEEP CONDUIT TIGHT TO FITTING ROOMS		8 / A7-0 SEE ELEC.
(M)	ACCESS POINT, J-BOX BY G.C.		SEE ELEC.
(M)	POWER / DATA DROP FOR CASHWRAP/CREDENZA		

**NEW STORE**

**OLD NAVY**

CAPAC. ARCHITECTURE  
CORPORATE ARCHITECTURE  
HARRISON STREET  
SAN FRANCISCO, CA 94105

REPS. I.D.: 0000054156

STORE NUMBER: 4458

STORE LOCATION: VINELAND  
8231 VINELAND AVENUE  
SUITE 2151  
ORLANDO, FLORIDA 32821

DESIGN TYPE: P3  
GENERATION: 170/12  
PROTOTYPE DATE: 07/18/16  
OPENING: 2017

CONSULTANT INFO.

PROFESSIONAL STAMP:

ARCHITECT INFO:

**B | R | R**  
architecture

ARCHITECT OF RECORD: BRR ARCHITECTURE, INC.  
6750 ANTOCH PLAZA, SUITE 200, PERRIS, KANSAS 66504

ISSUE TYPE:

PERMIT/BID: 04/07/17

REVISIONS:

DRAWN BY: EE  
A/E JOB NUMBER: 65013011

TITLE SHEET:  
REFLECTED CEILING PLAN

SHEET NUMBER:  
**A1-1b**