



G.P.F. INC.
CORPORATE ARCHITECTURE
HARRIS STREET
SAN FRANCISCO, CA 94105


REPS. I.D.: 000054156

STORE NUMBER: 4458
STORE LOCATION: VINELAND
8231 VINELAND AVENUE
SUITE 2151
ORLANDO, FLORIDA 32821

DESIGN TYPE: P3
GENERATION: 17Q12
PROTOTYPE DATE: 07/18/16
OPENING: 2017

CONSULTANT INFO:

EEA Consulting Engineers
6615 Vaught Ranch Road, Suite 100
Austin, Texas 78730-2314 USA
512.744.4400 main 512.744.4444 fax
www.eea.com
State of Registration: FLORIDA
Firm Registration No. 26645
EEA Project No. 20169549



ARCHITECT INFO:

ARCHITECT OF RECORD: BRR ARCHITECTURE, INC.
6700 AVYTOCH PLAZA, SUITE 300, MERRILL, KANSAS 66504

ISSUE TYPE:
PERMIT/BID: 04/07/17

REVISIONS:

DRAWN BY: DPR
A/E JOB NUMBER: 65013011
TITLE SHEET:
LIGHT FIXTURE
SCHEDULE

SHEET NUMBER:
E4-0

LIGHT FIXTURE SCHEDULE

TAG	PROVIDED BY		DESCRIPTION	MANUFACTURER CATALOG NUMBER	LAMP	BALLAST MANUFACTURER CATALOG NUMBER	WATTS	VOLTS	MOUNTING LOCATION	REMARKS
	OWNER	LANDLORD								
D1	X		UNISTRUT MOUNTED DUAL CIRCUIT TRACK LENGTH AS INDICATED PER DRAWINGS.	CON-TECH LT28P SERIES	N/A	N/A	N/A	120	SALES FLOOR DISPLAY WINDOWS	3
D1-1	X		UNISTRUT MOUNTED ONE CIRCUIT TRACK LENGTH AS INDICATED PER DRAWINGS, WHITE FINISH	CON-TECH LT8P SERIES	N/A	N/A	N/A	120	SALES FLOOR WHERE THERE ARE NO FLUORESCENT TRACK MOUNTED	3
F1A-4	X		1 ROW 4' FLUORESCENT STRIP WITH ACRYLIC SNAP A WRAP COVER	MERCURY MM-132-OCT-ELB SAW1L4FOOT	PHILIPS (1) F32T8ADV841XLL 25 WATT	ADVANCE REL-1P32-SC	24	120	FITTING ROOM BEHIND MIRROR PROVIDED BY FIT RM MFG	2,4
F14ASY	X		4' SURFACE-MOUNTED FLUORESCENT LIGHT FIXT WITH ASSYMETRICAL REFLECTOR WHITE FINISH	MERCURY MM132-OCT-ELB-UNI/MMR132A	PHILIPS 32W T8 (1) F32T8ADV841XLL 25 WATT	ADVANCE REL-1P32-SC	24	120	SALES FLOOR MOUNTED TO TOP OF UNISTRUT REFLECTOR PUSHING LIGHT TO WALL	2
F18ASY	X		8' SURFACE-MOUNTED FLUORESCENT LIGHT FIXT WITH ASSYMETRICAL REFLECTOR WHITE FINISH	MERCURY MM132-OCT/8T-ELB-UNI/(2)MMR132A	PHILIPS 32W T8 (2) F32T8ADV841XLL 25 WATT	ADVANCE REL-2P32-SC	46	120	SALES FLOOR MOUNTED TO TOP OF UNISTRUT REFLECTOR PUSHING LIGHT TO WALL	2
F14U	X		4' SURFACE-MOUNTED FLUORESCENT LIGHT FIXT INTEGRAL ELECTRONIC BALLAST WITH TRACK ADAPTORS, WHITE FINISH WITH LOUVERS	CON-TECH CTL4132TMAMX-P	PHILIPS 32W T8 (1) F32T8ADV841XLL 32WATT	ADVANCE TBD	30	120	SALES FLOOR MOUNTED TO TRACK	2
F18U	X		8' SURFACE-MOUNTED FLUORESCENT LIGHT FIXT INTEGRAL ELECTRONIC BALLAST WITH TRACK ADAPTORS, WHITE FINISH AND LOUVERS	CON-TECH CTL8132TMAMX-P	PHILIPS 32W T8 (2) F32T8ADV841XLL 32 WATT	ADVANCE TBD	60	120	SALES FLOOR MOUNTED TO TRACK	2
F2-8W	X		2 ROW 8' FLUORESCENT STRIP FLUORESCENT CHANNEL WITH WIRE GUARD	MERCURY MM-232-OCT / 8T-ELB- (2)WGMM240	PHILIPS (4) F32T8ADV841-EW LL25 WATT	ADVANCE 1ZT-4PSP32-G	92	120 / 277	PENDANT (SALES/FITTING)	2
F2E-8W	X		2 ROW 8' FLUORESCENT STRIP FLUORESCENT CHANNEL WITH WIRE GUARD, AND EMERGENCY PACK	MERCURY MM-232-OCT / 8T-ELB-EM (2) WGMM240	PHILIPS (4) F32T8ADV841-EW LL25 WATT	ADVANCE 1ZT-4PSP32-G	92	120 / 277	PENDANT (SALES/FITTING)	1,2
P18	X		18" DIAMETER PENDANT WITH WHITE 15' CORD WHITE FINISH, 10 WATT MAX LABEL, WHITE CANOPY,	HI-LITE H-16118-93-CW15-93-10WMAX	GREEN CREATIVE (1) A19G4DIM/840	N/A	10	120	SALES AND CASHWRAP	
R9	X		RECESSED LED DOWNLIGHT 4" APERTURE SPECULAR REFLECTOR WIDE BEAM CLEAR RELFECTOR INTEGRAL LED DRIVER INTEGRAL LED 2000 LUMENS 4000K, 29 WATT, 120 VOLT 0-10V DIMMING	CON-TECH RA4LNC-240K-12D2-CTR4322LW-CLR	N/A	INTEGRAL	29	120	HALLWAY FOR 277 USE 27D2	
R9E	X		RECESSED LED DOWNLIGHT 4" APERTURE SPECULAR REFLECTOR WIDE BEAM CLEAR RELFECTOR INTEGRAL LED DRIVER INTEGRAL LED 2000 LUMENS 4000K, 29 WATT, 120 VOLT 0-10V DIMMING WITH EM BATTERY PACK	CON-TECH RA4LNC-240K-12D2-EBL-CTR4322LW-CLR-EBL	N/A	INTEGRAL	29	120	RESTROOM FOR 277 USE 27D2	
L-EM	X		2 ROW 4' FLUORESCENT STRIP FLUORESCENT CHANNEL 0-10V DIMMING BALLAST AND EMERGENCY PACK	CREE LS4-40L-40K-10V-EB14	INCLUDED WITH FIXTURE	N/A	44	120	PENDANT (SALES/FITTING)	1,2
S9	X		WALL MOUNTED FIXTURE WITH FROSTED GLASS	HI-LITE H-CGU-1B-93-FR-18/CFL-RB	INCLUDED WITH FIXTURE	RB3	21	120	RESTROOM WALL	
X1	X		LED EXIT SIGN WITH 90 MINUTE BATTERY BACK-UP	HIGH LITES BP-PLC-S-R (RED LETTERS) BP-PLC-S-G (GREEN LETTERS) * LETTER COLOR PER CODE REQUIREMENT	INCLUDED WITH FIXTURE	N/A	5	120	EXIT SIGNS	
X1E	X		LED EXIT SIGN WITH 90 MINUTE BATTERY BACK-UP WITH CAPACITY TO POWER (2) REMOTE MOUNTED LAMP HEADS	PHOTALUMS 12W/12V/ED/O LETTER COLOR PER CODE REQUIREMENT	N/A	N/A	5	120	EXIT SIGNS AT DOORS (SPECIAL CONDITIONS AS REQUIRED BY CODE)	
X2E	X		REMOTE MOUNTED LAMP HEADS	PHOTALUMS 12W/12V/ED/O	12 WATT INCLUDED WITH FIXTURE	N/A	12	6	WALL (EXTERIOR ABOVE EXIT DOORS)	

REMARKS:
1. EMERGENCY PACK TO BE A MINIMUM OF 1300 LUMENS.
2. LINEAR FLUORESCENT FIXTURES SHALL HAVE AN INTERNAL DISCONNECTING MEANS FOR SERVICE OF THE BALLAST AS PER CODE.
3. CONTRACTOR SHALL PROVIDE ALL NECESSARY COMPONENTS TO COMPRISE A FULLY FUNCTIONING SYSTEM.
4. PROVIDED BY FIT ROOM MANUFACTURER.

UNISTRUT GENERAL NOTES

- PATCH AND REPAIR (E) FIREPROOFING AS REQUIRED TO MATCH (E) RATING
- ALL UNISTRUT AND ASSEMBLY TO BE PAINTED IN FIELD.
- PROVIDE SEISMIC BRACING ONLY WHEN REQUIRED BY CODE.
- UNISTRUT TO RUN LENGTH OF TRACK AT TRACK LOCATIONS. DO NOT RUN UNISTRUT OR POWER STRUT PAST ENDS OF FIXTURES.
- THE CEILING CONNECTION SHOWN IS PREFERRED. IF BEAM-CLAMP IS NOT ACCEPTABLE UNDER SITE-SPECIFIC CONDITIONS, USE UNISTRUT AS JOIST CONNECTION. DIRECTLY ATTACHING THREADED ROD OR POWER STRUT TO UNDERSIDE OF ROOF DECK IS NOT ACCEPTABLE.

Order Plans