TOILET PLUMBING FIXTURE SCHEDULE

ALL PRODUCTS ON THIS SCHEDULE ARE FURNISHED BY OWNER AND INSTALLED BY CONTRACTOR. REFER TO SPECIFICATIONS.

MARK	FIXTURE	BRANCH SIZES (MIN) CW	HW	WASTE	VENT	MANUFACTURER / CATALOG NUMBER OPTION #1	OPTION #2	OPTION #3	TRIM AND ACCESSORIES	NOTES
CC1	WATER CLOSET CARRIER DOUBLE HORIZONTAL			4"	2"	JOSAM 12694	WADE 310ND		ADJUSTABLE COATED CAST IRON SHORT BARREL 4" NO HUB FITTING WITH 2" NO HUB VENT, ABS EXTENSION WITH TEST CAP, CHROME PLATED HARDWARE, NEOPRENE FITTING AND FIXTURE GASKETS. AND HUSKY SD4000 COUPLINGS.	A
CC1H	WATER CLOSET CARRIER DOUBLE HORIZONTAL ACCESSIBLE			4"	2"	JOSAM 12694-S5	WADE 310ND-H		ADJUSTABLE COATED CAST IRON SHORT BARREL 4" NO HUB FITTING WITH 2" NO HUB VENT, ABS EXTENSION WITH TEST CAP, CHROME PLATED HARDWARE, NEOPRENE FITTING AND FIXTURE GASKETS. AND HUSKY SD4000 COUPLINGS.	A
CC2	WATER CLOSET CARRIER SINGLE HORIZONTAL RIGHT			4"	2"	JOSAM 12684	WADE 310NR-UA		ADJUSTABLE COATED CAST IRON SHORT BARREL 4" NO HUB FITTING WITH 2" NO HUB VENT, FACTORY TAPPED 2" NO HUB URINAL CONNECTION, ABS EXTENSION WITH TEST CAP, CHROME PLATED HARDWARE, NEOPRENE FITTING AND FIXTURE GASKETS, AND HUSKY SD4000 COUPLINGS. FLOW DIRECTION (RIGHT) IS FROM SEATED FIXTURE USER'S POINT OF REFERENCE.	A
EWC2	ELECTRIC WATER COOLER (SPLIT-LEVEL)	1/2"		1 1/2"	1 1/4"	OASIS PGBACSL	HALSEY TAYLOR HACBFSSL-Q-ADA OR HACSFSSLR-Q-ADA		STAINLESS STEEL TOP AND CABINET, FRONT AND SIDE PUSH BARS, MATCHING UPPER UNIT APRON, LEAD FREE, WATER SAVER BUBBLER WITH FLEXIBLE BUBBLER GUARD (FOR HALSEY TAYLOR - SMARTFLOW BUBBLER KIT), STOP, 3/8"x1/2" SS BRAIDED WATER SUPPLY, P-TRAP WITH CLEANOUT AND ESCUTCHEON. CARRIER: JOSAM 17560-WCBL, WADE 440-AM11	A, C
HB6	TOILET ROOM HOSE BIBB	3/4"				WOODFORD B24	ACORN 6151	BRADLEY 7910	POLISHED FINISH WITH STAINLESS STEEL OR CHROME HINGED BOX, INTEGRAL VACUUM BREAKER, AND LOOSE TEE KEY.	
L2	LAVATORY	1/2"	1/2"	1 1/2"	1 1/2"	SLOAN SS-3003	TOTO LT307.4		FAUCET: TOTO TEL3LS-10 - 0.5 GPM SENSOR OPERATED SELF- GENERATING POWER SYSTEM. STANDARD SPOUT 4" COVER PLATE, GRID STRAINER WITH TAILPIECE. P-TRAP WITH CLEANOUT. STOP VALVES. SS BRAIDED WATER SUPPLIES AND ESCUTCHEONS. CARRIER: JOSAM 17100, WADE W-630. LAVATORY ENCLOSURE: TRUEBRO LAV-SHIELD 2018 L2 ASSE 1070 THERMOSTATIC MIXING VALVE: ZURN ZW3870XLT	A, B
L2S	LAVATORY 2-STATION WITH TRASH	1/2"	1/2"	1 1/2"	1 1/2"	LEVANTINA Q3302T			LEVANTINA: WALL MOUNTED, ONE-PIECE QUARTZIA DECK -DECK COLOR: SNOWFALL -BOWL: CHINA SHELL CH-6360 UNDERMOUNT 18"x13" CHINA BOWL (S) -BASE: ACORN STAINLESS STEEL APRON, AP-3. 3 BOWL; AP-1, 1 BOWL; AP-2, 2 BOWL -CONTINUOUS WASTE PIPING AND P-TRAP -FAUCET: TOTO TEL145-D10E - 0.5 GPM SENSOR OPERATED SELF-GENERATING POWER SYSTEM. CHROME PLATED BRASS P-TRAP WITH CLEANOUT, GRID STRAINER WITH TAILPIECE. FOR L2/L2S/L2E: (2) STOP VALVES PER DECK, THERMOSTATIC MIXING VALVE KIT (TMV, HOSES & FITTINGS); SET TMV TO 105°F FOR L2SL/L2SLM: (1) STOP VALVE, (1) 3/8"X1/2" SS BRAIDED WATER SUPPLY PER FAUCET, TMV NOT REQUIRED.	B
UC1	URINAL CARRIER					JOSAM 17580-UR	WADE 400.AM11		FLOOR MOUNTED WITH HANGER AND BEARING PLATES, WELDED FEET, ADJUSTABLE SUPPORTING RODS, STRUCTURAL UPRIGHTS, AND CHROME PLATED TRIM.	A
UR2	URINAL ACCESSIBLE	3/4"		2"	1 1/2"	ZURN Z5798	TOTO UT105U TEU1UA12#CP	SLOAN SU-1003-A	HIGH EFFICIENCY URINAL (HEU) SYSTEM. CHINA URINAL AND .9 125 GPF TURBINE OR BATTERY POWERED. WALL MOUNTED SENSOR OPERATED FLUSH VALVE WITH MANUAL OVERRIDE AND VANDAL RESISTANT SET SCREW ESCUTCHEON AND STOP CAP. CARRIER: UC1	E
WC3	WATER CLOSET (WALL MOUNT)	1 1/4"		4"	2"	TOTO CT708E	SLOAN ST-2059-A		FLUSH VALVE: TOTO TETFLA3#GP#W - 1.28 GPF SENSOR OPERATED SELF GENERATING POWER SYSTEM WITH MANUAL OVERRIDE AND VANDAL RESISTANT SET SCREW ESCUTCHEON AND STOP CAP. ELONGATED SEAT: BEMIS 1055SSC. MAINLINE ML1055SSC	
WC4	WATER CLOSET ACCESSIBLE (WALL MOUNT)	1 1/4"		4"	2"	TOTO CT708E	SLOAN ST-2059-A		FLUSH VALVE: TOTO TETFLA3#GP#W - 1.28 GPF SENSOR OPERATED SELF GENERATING POWER SYSTEM WITH MANUAL OVERRIDE AND VANDAL RESISTANT SET SCREW ESCUTCHEON AND STOP CAP. ELONGATED SEAT: BEMIS 1055SSC. MAINLINE ML1055SSC	D

1.0 GENERAL INFORMATION (ALL FIXTURES):
1.1 SUBSTITUTIONS NOT PERMITTED. REF SPECIFICATIONS FOR APPROVED MANUFACTURERS OF THE FOLLOWING TRIM AND ACCESSORIES:
2.0 -P-TRAP WITH CLEANOUT PLUG AND SINK CONTINUOUS WASTES: POLISHED CHROME-PLATED TUBULAR BRASS, 17 GAUGE WITH BRASS NUTS AND SLIP INSERTS.
3.0 -SS BRAIDED WATER SUPPLY: FLEXIBLE BRAIDED STAINLESS STEEL (SS) OUTER SHEATHING WITH REINFORCED PVC INNER TUBING.
4.0 -STOP VALVES: CHROME PLATED BRASS, QUARTER TURN ANGLE STOP VALVES.
5.0
6.0 NOTES:
A.0 INSTALL FURNISHED 1/2" X 3 3/4" STAINLESS STEEL SIMPSON WEDGE-ALL WEDGE ANCHORS FOR ALL FIXTURE CARRIERS
B.0 INSTALL FURNISHED THERMOSTATIC MIXING VALVE.
C.0 REFERENCE ARCHITECTURAL DRAWINGS FOR EWC2 ORIENTATION.
D.0 COORDINATE WATER ROUGH-IN HEIGHT FROM MANUFACTURER'S INSTALLATION INSTRUCTIONS WITH GRAB BAR LOCATION. REF ARCH.
E.0 USE SAME MANUFACTURER FOR UR1 AND UR2.

WATER HEATERS / STORAGE TANKS

ALL PRODUCTS ON THIS SCHEDULE ARE FURNISHED BY OWNER AND INSTALLED BY CONTRACTOR. REFER TO SPECIFICATIONS.

MARK	AREA SERVED	MANUFACTURER / MODEL NUMBER OPTION #1	OPTION #2	OPTION #3	TANK SIZE (GAL)	HEAT INPUT MBH	ELECTRICAL KW	V	PH	HZ	NOTES
WH31 (ELEC)	GROCERY	A.O. SMITH MASTER-FIT BTR-198	RHEEM UNIVERSAL G100-200	BRADFORD WHITE MAGNUM D-100L-199-3N	100	45	120	1	60	A. B. C. D	

EXPANSION TANKS

MARK	MANUFACTURER / MODEL OPTION #1	OPTION #2	OPTION #3	OPTION #4	DESCRIPTION
ETB	AMTROL ST-42V	FLEXCON WHV-75	WATTS DETA-A2	WILKINS WXTP-75V	FIXED BLADDER TYPE EXPANSION TANK. 17.5 GALLON MINIMUM TOTAL CAPACITY, FACTORY STANDARD PRECHARGE CAPACITY.

RECIRCULATION PUMP

MARK	MANUFACTURER / MODEL OPTION #1	OPTION #2	OPTION #3	PUMP POWER W	HP	V	ELECTRICAL PH	HZ	GPM	HEAD (FT)	DESCRIPTION
P10	BELL & GOSSETT ONE-LINE PL-39	GRUNDFOS UP26-96BF	ARMSTRONG ARMFLO ST-2B	0 ---	0.083	120	1	60	5	20	LEAD-FREE BRONZE WET ROTOR INLINE CIRCULATOR PUMP WITH 1" FLANGED CONNECTIONS

1.0 GENERAL INFORMATION (ALL UNITS):
1.1 PROVIDE INCO-LOY HEATING ELEMENTS FOR ELECTRIC WATER HEATERS.
2.0 PROVIDE ASME TEMPERATURE AND PRESSURE RELIEF VALVE FOR ALL WATER HEATERS AND STORAGE TANKS.
3.0 PROVIDE VACUUM RELIEF VALVES FOR ALL BOTTOM-FED WATER HEATERS AND STORAGE TANKS.
4.0
5.0 NOTES:
A.0 INSTALL WATER HEATER ON HOUSEKEEPING PAD, REF ARCH.
B.0 PROVIDE EXPANSION TANK ETB.
C.0 140 DEGREE FAHRENHEIT OUTLET TEMPERATURE.
D.0 RECOVERY RATE: 193 GPH AT 100°F RISE.

SPECIALTY PLUMBING FIXTURE SCHEDULE

MARK	FIXTURE	MANUFACTURER / CATALOG NUMBER OPTION #1	OPTION #2	OPTION #3	OPTION #4	OPTION #5	OPTION #6	OPTION #7	FIXTURE DESCRIPTION
WPG	WATER PRESSURE GAUGE	AMETEK 656	TREKICE D63LFSS2202BA050	WEISS INSTRUMENTS LF252					2.5 INCH STAINLESS STEEL CASE, ALL WETTED PARTS STAINLESS STEEL, LIQUID FILLED, 1/4 INCH NPT CONNECTION, 1.6% ACCURACY, 30" HG VAC TO 100 PSI RANGE.
WHA	WATER HAMMER ARRESTOR	JOSAM SERIES 75000	PRECISION PLUMBING PRODUCTS STAINLESS STEEL #316 SERIES	WATTS SS SERIES	WILKINS MODEL 1250/XL SERIES	JAY R. SMITH HYDROTROLS	SIOUX CHIEF HYDRA-RESTER	MIFAB MWH	LEAD FREE CONSTRUCTION TO PDI WH-201, ANSI A112.26.1M, ASSE 1010
---	DOUBLE-CHECK VALVE BACKFLOW PREVENTER	WATTS LF007QT OR LF709	BEECO FDC-LF	FEBCO LF860	WILKINS 350XL OR 950XLT-2				LEAD FREE, INCLUDE TWO INDEPENDENT-ACTING CHECK VALVES, SHUTOFF VALVES AND REQUIRED MEANS FOR TESTING FOR BACKFLOW. MINIMUM 175 PSI WORKING PRESSURE.
---	REDUCED PRESSURE BACKFLOW PREVENTER	WATTS LF009QT OR LF998	BEECO FRP-LF	FEBCO LF860	WILKINS 375XL OR 975XL				LEAD FREE, INCLUDE STRAINER, SHUT-OFF VALVES AND TEST COCKS. SUPPLIED COMPLETE WITH AIR GAP ASSEMBLY TO RECEPTACLE. MEETS LOCAL AUTHORITY HAVING JURISDICTION. MINIMUM 175 PSI WORKING PRESSURE.
---	TRAP PRIMER (MULTIPLE TRAPS)	PRECISION PLUMBING PRODUCTS PRIME-RITE OR OREGON #1	MIFAB M-500-NPB	JOSAM 88500	SIOUX CHIEF SERIES 695				LEAD FREE, PROVIDE BRONZE PRIMER VALVE WITH REMOVABLE OPERATING PARTS, INTEGRAL VACUUM BREAKER, AND GASKETED ACCESS COVER AND MULTIPLE TRAP CAPABILITY
---	TRAP PRIMER (SINGLE TRAP)	PRECISION PLUMBING PRODUCTS PRIME-RITE OR OREGON #1	SIOUX CHIEF 695						LEAD FREE, PROVIDE ALL BRONZE PRIMER VALVE WITH REMOVABLE OPERATING PARTS, INTEGRAL VACUUM BREAKER, AND GASKETED ACCESS COVER.
---	VALVES	RED-WHITE 5044AB OR 5046AB	APOLLO SERIES 70 LF	CRANE LF9210 SERIES	WATTS LFFBV-3C OR LFBV5-3C	NIBCO FP-600-A-LF			LEAD FREE FULL PORT BRASS BALL VALVE WITH PLASTIC JACKETED LEVER TYPE HANDLE.

PLUMBING FIXTURE SCHEDULE

ALL PRODUCTS ON THIS SCHEDULE ARE FURNISHED BY OWNER AND INSTALLED BY CONTRACTOR. REFER TO SPECIFICATIONS.

MARK	FIXTURE	BRANCH SIZES (MIN) CW	HW	WASTE	VENT	MANUFACTURER / CATALOG NUMBER OPTION #1	OPTION #2	OPTION #3	OPTION #4	DESCRIPTION, TRIM AND ACCESSORIES	NOTES
ETMV	EMERGENCY THERMOSTATIC MIXING VALVE					BRADLEY S19-2000		POWERS ES150-11		HEAVY CAST BRONZE BODY VALVE, ROUGH BRONZE FINISH, BIMETAL THERMOSTAT OR THERMAL MOTOR, INTEGRAL CHECK STOPS AND VANDAL RESISTANT LIMIT STOP SET AT 85° F. MINIMUM FLOW RATE 1.0 GPM	
EW1	EYEWASH		1/2"	1 1/2"	1 1/4"	BRADLEY S19-224	SPEAKMAN SC-580	ENCON 01203401	GUARDIAN G1914P	WALL MOUNTED, GALVANIZED STEEL PIPE, CHROME PLATED BRASS VALVE, YELLOW PLASTIC BOWL WITH DUST COVER, 304 SS HANDLE. PROVIDE SUMP AND TAILPIECE WHERE APPLICABLE ON PLANS	A
PRV	WATER PRESSURE REGULATOR					WATTS LF223	WILKINS 500XL			LEAD FREE BRONZE BODY VALVE WITH SHUT-OFF VALVES FOR SIZES UP TO 2". CAST IRON BODY FOR 3" AND ABOVE. MAXIMUM OPERATING PRESSURE OF 300 PSI. CONFORM TO ASSE 1003.	
PVB2	PRESSURE VACUUM BREAKER					WATTS LF008PCQT				LEAD FREE HIGH-HAZARD ANTI-SIPHON, ANTI-SPILL VACUUM BREAKER AND INTEGRAL OUTLET SHUT-OFF VALVES. CONFORM TO ASSE 1056.	
S2	SINK (PHARMACY) 1-COMPARTMENT STAINLESS STEEL	1/2"	1/2"	2"	1 1/2"	DAYTON BY ELKAY D-12521	KOHLER K-3348			4 HOLES, 2.2 GPM FLOW RESTRICTOR AND AERATOR. FAUCET LEAD FREE: ELKAY LK-1000, KOHLER K15071-4P MAXIMUM DEPTH DRAIN: ELKAY LK-35, KOHLER K8801	C, E
S3	SINK (LOUNGE) 2-COMPARTMENT STAINLESS STEEL	1/2"	1/2"	2"	1 1/2"	ELKAY LRAD2918	JUST DL-ADA-1829-A			4 HOLES, DROP-IN STYLE. 2.2 GPM FLOW RESTRICTOR, AERATOR AND SPRAY WAND. MAXIMUM DEPTH FAUCET LEAD FREE: ELKAY LK-1091, JUST JG01 DRAIN: ELKAY LK-35, JUST JS-99	C
SS1	SERVICE SINK, (TERRAZZO) 24" x 24" x 12"	3/4"	3/4"	3"	2"	STERN-WILLIAMS SB-800	FIAT TSB-200	ACORN TSH-24-SSC-LB		CHROME PLATED FAUCET WITH VACUUM BREAKER, HOSE BRACKET (MOUNTED DIRECTLY ABOVE WALL GUARD), MOP HANGER (60°AFF) FAUCET: CHICAGO 897-CP (WITH STANDARD SUPPLY ARMS & CONNECT (2) GC-KCP SUPPLY ARMS (USING (2) 897-CPXRCF ADAPTERS); ZURN Z843M1-CS, T&S BRASS B-0665-BSTP; OMNI CARTRIDGES & SPRING CHECKS HOSE/BRACKET: STERN WILLIAMS T-35, FIAT 882-AA, ACORN KH38 MOP HANGER: STERN WILLIAMS T-40, FIAT 886-CC, ACORN KMH	B
SS4	SERVICE SINK, (TERRAZZO) 24" x 24" x 12" 6" DROP FRONT	3/4"	3/4"	3"	2"	STERN-WILLIAMS HL-1610-LS	FIAT TSB-3000	ACORN TGF-24-SSC-LB		CHROME PLATED FAUCET WITH VACUUM BREAKER, CHECK VALVES, HOSE, BRACKET (MOUNTED DIRECTLY ABOVE WALL GUARD), MOP HANGER (60°AFF), LINT BASKET, & S.S. CAP ON ALL SIDES FAUCET: CHICAGO 897-CP (WITH STANDARD SUPPLY ARMS & CONNECT (2) GC-KCP SUPPLY ARMS (USING (2) 897-CPXRCF ADAPTERS); ZURN Z843M1-CS, T&S BRASS B-0665-BSTP; OMNI CARTRIDGES & SPRING CHECKS HOSE/BRACKET: STERN WILLIAMS T-35, FIAT 882-AA, ACORN KH38 MOP HANGER: STERN WILLIAMS T-40, FIAT 886-CC, ACORN KMH	B
TMV	THERMOSTATIC MIXING VALVE	3/4"	3/4"			LAWLER 570	LEONARD 170-LF	ZURN ZW3870XLT		LEAD FREE, HEAVY CAST BRONZE BODY VALVE, ROUGH BRONZE FINISH, BIMETAL THERMOSTAT OR THERMAL MOTOR, INTEGRAL CHECK VALVES, LIMIT STOP SET AT 105°F UNLESS NOTED OTHERWISE. MINIMUM FLOW RATE 0.5 GPM. CONFORM TO ASSE 1017/1070.	

1.0 GENERAL INFORMATION (ALL FIXTURES):
1.1 SUBSTITUTIONS NOT PERMITTED. REF SPECIFICATIONS FOR APPROVED MANUFACTURERS OF THE FOLLOWING TRIM AND ACCESSORIES:
2.0 -P-TRAP WITH CLEANOUT PLUG AND SINK CONTINUOUS WASTES: POLISHED CHROME-PLATED TUBULAR BRASS, 17 GAUGE WITH BRASS NUTS AND SLIP INSERTS.
3.0 -SS BRAIDED WATER SUPPLY: FLEXIBLE BRAIDED STAINLESS STEEL (SS) OUTER SHEATHING WITH REINFORCED PVC INNER TUBING.
4.0 -STOP VALVES: CHROME PLATED BRASS, QUARTER TURN ANGLE STOP VALVES.
5.0
6.0 NOTES:
A.0 MOUNT EYEWASH 36" AFF TO TOP OF HEAD SPRAY. EYEWASH SUPPLIED WITH TEPID WATER.
B.0 INSTALL MOP SINK FAUCET AT 32" AFF AND LOCATE TWO MOP HANGER BRACKETS SIDE BY SIDE ON CORNER MOP SINK.
C.0 INSTALL FURNISHED TMV UNLESS SERVED WITH TEMPERED WATER OR NOTED OTHERWISE ON PLUMBING DRAWINGS. SET AT 120°F.
D.0 TRIM WITH OFFSET TAILPIECE AT 18" ARMAFLEX INSULATION EXPOSED WATER SUPPLY AND DRAIN LINES. HOLD ALL EXPOSED PIPING HIGH AS POSSIBLE.
E.0 INSTALL FURNISHED 1/2" X 3 3/4" STAINLESS STEEL SIMPSON WEDGE-ALL WEDGE ANCHORS FOR ALL FIXTURE CARRIERS.
F.0 INSTALL FURNISHED ESCUTCHEON PLATE FOR 3.5 HOLE SINK AND LOOSE KEY SINGLE-HANDLE FAUCET IN LEFT MOST FAUCET SINK HOLE.

DOMESTIC WATER BOOSTER PUMP SCHEDULE

MARK	SERVICE	MANUFACTURER	MODEL	NUMBER PUMPS	TOTAL HP	VOLTS	PHASE	SYSTEM FLOW RATE (GPM)	HEAD (PSI)
P3	DOMESTIC BOOSTER	GRUNDFOS	PRIMO E2.20	2	6	480	3	150	30

1.0 GENERAL INFORMATION:
1.1 TO BE FURNISHED BY OWNER. INSTALLATION AND STARTUP BY CONTRACTOR.
2.0 SYSTEM SETTINGS: PRESSURE: 60 PSI
3.0 PACKAGED SYSTEM: THIRD PARTY CERTIFIED QCZJ PACKAGED PUMPING STATION WITH PANEL MOUNTED VARIABLE FREQUENCY DRIVE. STAINLESS STEEL CENTRIFUGAL PUMPS, LOW SUCTION PRESSURE SWITCH AND DISCHARGE PRESSURE TRANSDUCER.
4.0 CONTROL PANEL: NEMA RATED CONTROLLER WITH NEMA1 ENCLOSURE AND FULL GASKET ON DOOR. 256 COLOR NEMA 4" 6" TOUCHSCREEN. AUTOMATIC NO-FLOW SHUT-OFF, ADJUSTABLE PRESSURE SET POINT, PUMP OPERATION AND FAULT STATUS, AUTOMATIC RESET.
5.0 MANUFACTURER'S CONTACT:
PRIMARY: T & S SYSTEM SALES, LLC
P.O. BOX 21, JACKSONVILLE, AR 72076
PH: 501-628-7704
TIM SOUTHERLAND
EMAIL: TIM@TSSALES.BID
SECONDARY: QUANTUMFLO, INC.
210 SPRINGVIEW COMMERCE DRIVE, BLDG. #150, DEBARY, FL 32713
PH: 386-753-9702 FAX: 386-753-9703
ROBERT MANN: ROBERT@QUANTUMFLO.COM

PLUMBING SYMBOLS

SS — SANITARY SEWER	CD — CONDENSATE DRAIN	M — WATER/FLOW METER	
GW — GREASE WASTE	RO-S / RO-D — REVERSE OSMOSIS WATER (STORE/DISPENSER)	WHA — WATER HAMMER ARRESTOR	
OW — OIL WASTE	PLUMBING VENT	T & P RELIEF VALVE	
ST — STORM SEWER	UNION	TMV — THERMOSTATIC MIXING VALVE	
SIPHONIC ROOF DRAIN LINE	GAS PRESSURE REGULATOR	FD — FLOOR DRAIN	
ST / OST — GRAVITY ROOF DRAIN (PRIMARY/OVERFLOW)	ELBOW - TURNED DOWN	FS — FLOOR SINK	
DOMESTIC COLD WATER	ELBOW - TURNED UP	BWV — BACKWATER VALVE	
DOMESTIC HOT WATER	TEE - TURNED DOWN	RD — ROOF DRAIN	
DOMESTIC HOT WATER RETURN	TEE - TURNED UP	FCO — FLOOR CLEANOUT	
IW — IRRIGATION WATER	BALL VALVE	YCO — YARD CLEANOUT	
HWR — HOT WATER RETURN	CHECK VALVE	FPWH — FREEZE PROOF WALL HYDRANT	
F — FILTERED WATER	SHUT-OFF VALVE IN VERTICAL LINE	HB — HOSE BIBB	
G — NATURAL GAS	WATER PRESSURE REGULATOR	WC / CO — WALL CLEANOUT/CLEANOUT	
A — COMPRESSED AIR	BACKFLOW PREVENTER	VT — VENT THRU ROOF	

GROCERY PLUMBING EQUIPMENT CONNECTION SCHEDULE

MARK	FIXTURE	BRANCH SIZES (MINIMUM) HW	WASTE	TRAP	ROUGH-IN REQUIREMENTS	NOTES
B079E	RACK OVEN	3/4"	2"		WATER: 8'-4" AFF	A, E, M
D065	STACKED COMBI OVEN	3/4"	2"		WATER: 44" AFF & 72" AFF, WASTE: PROVIDE 2 CONNECTIONS	A, E, L
MG010	EQUIPMENT				WATER: 72" AFF	A, E, G, L
MG011	RO DISPENSER	3/4"	1/2"		RO WATER: 18" AFF	A, E, G, J
MG012	WASTE HOLDING OIL TANK			2"	OUTLET: 2" PIPE	
MG013	ICE BAR MACHINE	3/4"	3/4"		WATER: 30" AFF (PROVIDE TWO VALVED 1/2" CONNECTIONS)	A, E, K, L
MG014	ICEE MACHINE				SEE NOTES FOR ROUGH-IN AND CONNECTION INFORMATION	U
MG045	COFFEE BREWER				SEE NOTES FOR ROUGH-IN AND CONNECTION INFORMATION	U
MG046	CAPPUCCINO				SEE NOTES FOR ROUGH-IN AND CONNECTION INFORMATION	U
MG056	COMMERCIAL BLENDER				SEE NOTES FOR ROUGH-IN AND CONNECTION INFORMATION	U
MG066	BEVERAGE DISPENSER				SEE NOTES FOR ROUGH-IN AND CONNECTION INFORMATION	E, T, U
MG085	ICE TEA DISPENSER				SEE NOTES FOR ROUGH-IN AND CONNECTION INFORMATION	U
MG097	PRODUCE MISTING SYSTEM	3/4"			RO WATER: 84" AFF	A, H, M
SS004	WALL MOUNTED HAND SINK	1/2"	1/2"	1 1/2"	WATER: 18" AFF, WASTE: 18" AFF	B, C, F, N, O
SS021	3-COMPARTMENT SINK	3/4"	3/4"	3" 1 1/2"	WATER: 12" AFF, WASTE: 12" AFF	B, C, D, F, R, S

GENERAL INFORMATION (ALL EQUIPMENT):
1.0 EQUIPMENT AND TRIM FURNISHED BY OWNER. ROUGH-IN AND FINAL CONNECTIONS BY PLUMBING CONTRACTOR, UNLESS NOTED OTHERWISE.

NOTES:
A.0 PROVIDE SHUT-OFF VALVES.
B.0 PROVIDE P-TRAP WITH CLEANOUT PLUG AND ESCUTCHEON.
C.0 PROVIDE CHROME PLATED ANGLE SUPPLY, FLEXIBLE RISER, AND WHEEL HANDLE WITH ESCUTCHEON.
D.0 SINK FAUCETS PROVIDED WITH INTEGRAL CHECK VALVES.
E.0 PROVIDE FULL-SIZE DRAIN LINE FROM EQUIPMENT, END OPEN OVER RECEPTOR WITH 2" AIR GAP.
F.0 IF PLUMBING PLAN AND RISER SHOWS THE SINK INDIRECTLY CONNECTED TO FLOOR SINK, THEN WASTE ROUGH-IN HEIGHT AND VENT SIZE AND NOTE B DO NOT APPLY.
G.0 RO VENDOR SHALL BE RESPONSIBLE FOR LOCATIONS OF DRINK DISPENSER AND WATER FILTRATION EQUIPMENT AND ALL FINAL CONNECTIONS.
H.0 REFRIGERATION CONTRACTOR TO INSTALL MISTING SYSTEM. SUPPLY SIDE ROUGH-IN AND FINAL CONNECTION BY PLUMBING CONTRACTOR.
I.0 PROVIDE 1 1/2" P-TRAP AT 12"AFF WITH 1 1/2" TO 3/4" REDUCER FOR CONNECTION TO RO WATER DISPENSER DRAIN.
J.0 PROVIDE 3/4" I.D. FEMALE FITTING AND SHUT-OFF FOR RO DISPENSER WATER CONNECTION AT 18"AFF.
K.0 PLUMBING CONTRACTOR SHALL PROVIDE INLINE FILTER PER MANUFACTURER'S RECOMMENDATIONS.
L.0 PROVIDE DOUBLE CHECK BACKFLOW PREVENTER ON WATER SUPPLY. PROVIDE FEMALE NPT VALVE DOWNSTREAM OF BACKFLOW PREVENTER FOR CONNECTION BY OTHERS.
M.0 PROVIDE STAINLESS STEEL DOUBLE CHECK BACKFLOW PREVENTER ON RO WATER SUPPLY. PROVIDE PEX TUBING ON DOWNSTREAM SIDE OF BACKFLOW PREVENTER.
N.0 INSTALL THERMOSTATIC MIXING VALVE FURNISHED WITH SINK WITH HARD-PIPED CONNECTIONS TO ANGLE STOPS AND FLEXIBLE CONNECTIONS BETWEEN THERMOSTATIC MIXING VALVE, FOOT PEDAL (PEDESTAL HAND SINK) OR KNEE LEVER (WALL MOUNTED HAND SINK) OR WRIST BLADE LEVERS (ADA WALL MOUNTED HAND SINK) AND SINK. SET AT 105°F.
O.0 REFER TO ARCHITECTURAL DRAWINGS FOR HAND SINK LEFT (L) AND RIGHT (R) DESIGNATIONS WHICH INDICATE INTEGRAL SPLASHGUARD LOCATIONS OR HAND SINK (H) FOR ADA DESIGNATION.
P.0 PROVIDE 36" FLEXIBLE GAS CONNECTION.
Q.0 PROVIDE 48" FLEXIBLE GAS CONNECTION WITH QUICK DISCONNECT AND UPSTREAM GAS SHUT-OFF VALVE. FLEX LINE SIZE SHALL MATCH LINE SIZE SHOWN ON PLAN.
R.0 INSTALL 1.2 GPM SPRAY HEAD ON PRE-RINSE SPRAYER FURNISHED BY FIXTURE MANUFACTURER. PLUMBING CONTRACTOR SHALL FURNISH ORIGINAL SPRAY HEAD TO OWNER.
S.0 ATTACH SINK TO WALL WITH CONTRACTOR-PROVIDED STAINLESS STEEL SLOTTED ROUND HEAD FASTENERS OR SHEET METAL SCREWS INSTALLED THROUGH HOLES DRILLED BY CONTRACTOR THROUGH TOP FLANGE OF SINK BACKSPLASH. FOR FRAMED WALLS, USE TWO EVENLY SPACED FASTENERS FOR PREP SINKS AND THREE EVENLY SPACED FASTENERS FOR 3-COMPARTMENT SINKS TO WALL STUDS. FOR SINKS INSTALLED ON COOLER PANEL, ATTACH SINKS TO COOLER PANEL OUTER SHEET METAL WITH SCREWS AT 12" CENTERS ALONG BACKSPLASH.
T.0 EQUIPMENT FURNISHED WITH INTEGRAL BACKFLOW PREVENTER FOR CARBONATED WATER LINE.
U.0 FILTERED WATER PIPING TO EQUIPMENT IS FURNISHED UNDER SEPARATE CONTRACT.

FLOOR DRAIN SCHEDULE

ALL PRODUCTS ON THIS SCHEDULE (EXCEPT FD2 HUB DRAINS) ARE FURNISHED BY OWNER AND INSTALLED BY CONTRACTOR. REFER TO SPECIFICATIONS

MARK	DESCRIPTION	MANUFACTURER / MODEL NUMBER OPTION #1	OPTION #2	OPTION #3
FD2	HUB DRAIN SAME AS SANITARY WASTE PIPING MATERIAL UNLESS NOTED OTHERWISE ON PLANS			
FD3	LIGHT DUTY PVC WITH 9" DIAMETER LOOSE SET PVC HALF GRATE	SIOUX CHIEF 860		
FD4	LIGHT DUTY ADJUSTABLE PVC WITH THREADED ADAPTER AND 6" SQUARE NICKEL BRONZE RING AND FASTENED GRATE	SIOUX CHIEF 842	JOSAM VEF 400J	OATEY 72000
FD5	POLYPROPYLENE OR HOPE TRENCH DRAIN WITH HEAVY DUTY SLOTTED GALVANIZED STEEL GRATE AND FRAME ASSEMBLY. PROVIDE CATCH BASIN WHERE INDICATED ON PLAN. MODEL#: TRENCH/GRATE/CATCH BASIN	SMITH/ACO 9931/9870-42S-SHD/9936	ZURN Z886-HDR/GRC-887-HD	
FD10	HEAVY DUTY STAINLESS STEEL (SS) WITH SLAB ANCHOR, 8.5" MIN. DIAMETER SS GRATE WITH TWO 1" DIAMETER CENTRAL LIFTING HOLES 3" APART, SCH 40 OUTLET, AND SS SEDIMENT BUCKET WITH HANDLE AND SIDE AND BOTTOM DRAIN HOLES. DRAIN INTERIOR, GRATE AND BUCKET SHALL HAVE SMOOTH BEAD BLASTED FINISH WITH NO VISIBLE INTERNAL WELDS OR SEAMS. ENTIRE DRAIN INTERIOR SHALL BE VISIBLE FOR INSPECTION.	SIOUX CHIEF 869-48S	KUSEL KEW	STAINLESSDRAINS.COM SD12WSCH40
FD11	HEAVY DUTY PVC WITH CAST IRON 8" DIAMETER LOOSE SET RING AND GRATE AND SLOTTED PVC SEDIMENT BUCKET.	SIOUX CHIEF 869		
FS1	LIGHT DUTY, ACID RESISTANT, WHITE PVC FLOOR SINK WITH 12" SQUARE WHITE PVC HALF GRATE AND STAINLESS STEEL DEBRIS BUCKET WITH LIFTING HANDLE. REF PLANS FOR LOCATIONS WHERE FULL GRATES ARE SPECIFIED.	SIOUX CHIEF 861		

ROOF DRAIN SCHEDULE

MARK	DESCRIPTION	MANUFACTURER / MODEL NUMBER OPTION #1	OPTION #2	OPTION #3	OPTION #4	OPTION #5
CR	PVC SCHEDULE 40 DWV CONCENTRIC REDUCER COUPLING. REF PLANS FOR INLET AND OUTLET SIZES	PLASTIC TRENDS D60 SERIES	GPK 309 CONCENTRIC SERIES			
RD3	SIPHONIC ROOF DRAIN WITH EPOXY COATED CAST IRON BODY, UNDERDECK CLAMP, MEMBRANE CLAMP DEVICE AND AIR BAFFLE/INDUCER. 304 STAINLESS STEEL HARDWARE AND NO-HUB BOTTOM OUTLET.	MIFAB HYDROMAX MH-300 (3") MH-400 (4") MH-500 (5") MH-600 (6")				

CLEANOUT SCHEDULE

MARK	DESCRIPTION	MANUFACTURER / MODEL NUMBER OPTION #1	OPTION #2	OPTION #3	OPTION #4	OPTION #5	OPTION #6	OPTION #7
CO	THREADED, COUNTERSUNK BRONZE OR POLYPROPYLENE PLUG