


PLUMBING SCHEDULE										
ITEM NO	EQUIPMENT CATEGORY	COLD WATER SIZE (IN)	COLD WATER AFF (IN)	HOT WATER SIZE (IN)	HOT WATER AFF (IN)	DIRECT DRAIN SIZE (IN)	DIRECT DRAIN AFF (IN)	INDIRECT DRAIN SIZE (IN)	INDIRECT DRAIN AFF (IN)	ITEM NO
1	DISHTABLE, 1' SHAPE, 14 GAUGE	1/2	18	1/2	18	-	-	1-1/2	-	1
2	WAREWASHER, DOOR TYPE, HIGH TEMP	-	-	3/4	42	-	-	-	-	2
5	SINK, HAND, PEDESTAL BASE	1/2	18	1/2	18	1-1/2	18	-	-	5
9	MOP SINK STORAGE CABINET	1/2	36	1/2	36	2.0	2.75	-	-	9
10	SINK, NSF, 3 COMP, 14 GAUGE	1/2	18	1/2	18	-	-	1-1/2	-	10
18	TABLE, ENCLOSED BASE, BEVERAGE	1/2	18	1/2	18	-	-	1-1/2	-	18
19	COFFEE MAKER, INSULATED SERVER, AUTOMATIC	-	-	-	-	-	-	1.0	-	19
20	ICED TEA BREWER	1/2	42	-	-	-	-	-	-	20
26	DROP-IN, ICE BIN	-	-	-	-	-	-	1/2	-	26
31	FRYER, DEEP FAT, GAS W/FILTER	-	-	-	-	-	-	1-1/2	80	31
33	GRIDDLE, HEAVY DUTY, GAS	-	-	-	-	-	-	3/4	30	33
34	CHAR BROILER, HEAVY DUTY, GAS	-	-	-	-	-	-	3/4	30	34
35	RANGE, RESTAURANT, GAS	-	-	-	-	-	-	2.0	30	35
70	UNDER MOUNT RINSE FAUCET	1/2	18	-	-	-	-	1/2	-	70
71	UNDERBAR HANDSINK	1/2	6	1/2	6	-	-	1-1/2	-	71
73	UNDERBAR BLENDER STATION	1/2	6	1/2	6	-	-	-	-	73
74	UNDERBAR FILLERS & DRAINBOARDS	-	-	-	-	-	-	-	-	74
75	UNDERBAR ICE CHEST	-	-	-	-	-	-	3/4	-	75
76	WAREWASHER, UNDERCOUNTER, HIGH TEMP	-	-	1/2	-	-	-	1.5	-	76
77	UNDERBAR SINK	6	1/2	6	-	-	-	1-1/2	-	77
78	UNDERBAR GLASS RACK	-	-	-	-	-	-	1-1/2	-	78
79	UNDERBAR FILLERS & DRAINBOARDS	-	-	-	-	-	-	1-1/2	-	79
80	UNDERBAR FILLERS & DRAINBOARDS	-	-	-	-	-	-	1-1/2	-	80
85	DRIP TROUGH WITH RINSE FAUCET	1/2	-	-	-	-	-	1/2	-	85
91	ESPRESSO CAPSULE MACHINE	-	-	-	-	-	-	3/4	-	91
94	SINK, DROP-IN	1/2	18	1/2	18	-	-	1-1/2	-	94
98	SINK, DROP-IN	1/2	18	1/2	18	-	-	1-1/2	-	98
99	DISPENSER, ICE/WATER UNDERCOUNTER W/ W/FAUCET	1/2	18	-	-	-	-	-	-	99

- PLUMBING NOTES**
- THESE DRAWINGS ARE TO BE USED AS AN INSTRUMENT OF REFERENCE BY ALL OTHER TRADES AND CONTRACTORS. ALL TRADES SHALL VERIFY THE INFORMATION AS INDICATED ON THESE PLANS.
 - DIMENSIONS AND REQUIREMENTS FOR ALL EQUIPMENT THAT IS LISTED AS EXISTING, PROVIDED BY OTHERS OR PROVIDED BY OWNER, MUST BE VERIFIED WITH THE APPROPRIATE PARTIES.
 - ALL LOCAL, STATE AND NATIONAL CODES SHALL APPLY.
 - THESE UTILITY REQUIREMENT DRAWINGS INDICATE THE UTILITY AND LOCATION OF REQUIREMENTS BASED ON THE EQUIPMENT SPECIFIED.
 - ALL EQUIPMENT SHALL BE PLUMBING IN STRICT CONFORMANCE WITH THE MANUFACTURER'S INSTRUCTIONS AND/OR SHOP DRAWINGS.
 - UNLESS OTHERWISE NOTED, ALL DIMENSIONS SHOWN ON THIS PLAN ARE FROM THE FINISHED FLOOR, CEILING, WALLS OR COLUMN CENTERLINES TO THE CENTERLINE OF THE ROUGH-IN.
 - ALL PLUMBING CONNECTIONS SHALL BE EXTENDED AND INTERCONNECTED TO CONNECTION POINTS ON THE EQUIPMENT BY OTHERS UNLESS SPECIFIED. ALL HARDWARE REQUIRED FOR THESE CONNECTIONS SHALL BE SUPPLIED BY THE PLUMBING CONTRACTOR.
 - SURFACE MOUNTED PIPING WILL NOT BE ALLOWED. ALL PIPING SHALL BE EXTENDED THROUGH AND OUT OF BUILDING WALLS WHERE POSSIBLE. WHERE SURFACE MOUNTED PLUMBING IS UNAVOIDABLE, IT MUST BE COORDINATED WITH HOCKENBERGERS.
 - ROUGH-IN OUT OF FLOOR SHOULD BE 5" TUBED UP 4" ABOVE FINISHED FLOOR AND BROUGHT TO THE REQUIRED HEIGHT AFTER EQUIPMENT IS SET IN PLACE.
 - ONLY COMPONENTS SUPPLIED STANDARD BY THE MANUFACTURER ARE INCLUDED. ALL HARDWARE REQUIRED FOR CONNECTIONS SHALL BE SUPPLIED BY THE PLUMBING CONTRACTOR. SUCH COMPONENTS INCLUDE BUT ARE NOT LIMITED TO, SHUT-OFFS, PRESSURE REGULATORS, VACUUM BREAKERS, P-TRAPS, BACKFLOW PREVENTERS, ETC.
 - PLUMBING CONTRACTOR TO VERIFY THAT ALL APPLIANCES ARE SUPPLIED WITH APPROPRIATE GAS PRESSURE AND THAT ANY VARIANCES IN GAS PRESSURE BE CLEARLY IDENTIFIED AND BROUGHT TO THE IMMEDIATE ATTENTION OF HOCKENBERGERS.
 - ALL INDIRECT WASTE AND CONDENSATE DRAIN LINES SHALL BE EXTENDED FROM EQUIPMENT FITTINGS TO APPROPRIATE DRAINS AS CODES REQUIRE, BY OTHERS.
 - UNLESS OTHERWISE SPECIFIED, HOT WATER SUPPLIED TO BOOSTER HEATER SHALL BE A MINIMUM TEMPERATURE OF 140° F.
 - PLUMBING CONTRACTOR TO VERIFY WATER TEMPERATURE REQUIREMENTS FOR EACH PIECE OF EQUIPMENT. ANY DISCREPANCY BETWEEN MANUFACTURER'S REQUIREMENTS AND TEMPERATURES PROVIDED SHALL BE CLEARLY IDENTIFIED AND BROUGHT TO THE IMMEDIATE ATTENTION OF HOCKENBERGERS.
 - PLUMBING CONTRACTOR TO PROVIDE INSULATED HOT WATER CONNECTIONS BETWEEN BOOSTER HEATER AND DISH-MACHINE.
 - UNLESS OTHERWISE SPECIFIED BY CODE, ALL DRAIN LINES FOR DISPOBSERS SHALL BY-PASS GREASE INTERCEPTORS.

PLUMBING SYMBOLS

ITEM NUMBER CONNECTION NUMBER	PLUMBING ROUGH-IN NOTE (SEE SCHEDULE)
—	COLD WATER CONNECTION
—	HOT WATER CONNECTION
—	HOT WATER CONNECTION - 140° MINIMUM
—	FLOOR SINK
—	FLOOR SINK - HALF COVER
—	FLOOR DRAIN
—	FUNNEL FLOOR DRAIN
—	FILTERED COLD WATER
—	INDIRECT DRAIN
—	DIRECT DRAIN
—	HUB DRAIN
—	GAS



Order Plans

WWW.LDLINE.COM

555 Round Rock West Drive
Suite 1710
Round Rock, TX 78681
Phone: (512) 412-8887
Fax: (512) 412-8887

Hockenbergs
DESIGN • SUPPLY • SERVICE
FOOD SERVICE EQUIPMENT DESIGN

AC HOTEL BY MARRIOTT
PROJECT ADDRESS
MIAMI, FLORIDA

PLUMBING REQUIREMENTS PLAN

Scale: _____
 Release Date: _____
 Drawn By: _____
 Project Number: _____

K-3