


1 FLOOR COVERING AND WALL FINISH PLAN
 A203 1/8" = 1'-0"



FLOORING LEGEND	
	POLISHED CONCRETE
	EPOXY

- NOTES**
- SEE SHEET A701 FOR FINISH SCHEDULE AND LEGEND.
 - THESE DRAWINGS ARE BASED ON A LIMITED AMOUNT OF INFORMATION FOR AN EXISTING BUILDING. CONTRACTOR MUST FIELD VERIFY CONDITIONS AND NOTIFY ARCHITECT AND ENGINEER IF CONDITIONS ARE OTHER THAN IS SHOWN PRIOR TO MODIFICATION.
 - ALL DIMENSIONS SHOWN ARE FOR GENERAL REFERENCE ONLY. THE CONTRACTOR IS RESPONSIBLE FOR VERIFYING ALL DIMENSIONS AND ANY DISCREPANCIES MUST BE BROUGHT TO THE ATTENTION OF THE ARCHITECT AND ENGINEER IMMEDIATELY.
 - INTERIOR WALL, CEILING, AND FLOOR FINISHES SHALL BE MINIMUM CLASS C.
 - CENTER FLOOR TRANSITION UNDER CENTER OF DOORS WHERE APPLICABLE.
 - REPAIR AND PREPARE FLOOR TO RECEIVE NEW FLOORING.
 - PAINT ALL COLUMNS P-6
 - GC TO PROVIDE NEW SLAB ON GRADE AT EXISTING LEAVE OUT AREA (REAR OF SPACE). SLAB ON GRADE SHALL BE 4" CONC. SLAB W/ 6x6 W1.4xW1.4 WWF ON 2" CLEAN SAND OVER 6 MIL THICK POLYETHYL VAPOR BARRIER.

Order Plans @

WWW.LDILine.com