

LIGHTING FIXTURE SCHEDULE

TYPE	MANUFACTURER	CATALOG NUMBER	LAMPS LAMP/TX WATTS	TYPE	MTG. TYPE	MTG. HT.	REC. DEPTH	DESCRIPTION	
A	TRACELITE	LP24-36-35K	LOT	39	LED	U	C	2 1/5"	2"x4" LED LAY-IN LIGHT FIXTURE WITH WHITE LENS, 3500K COLOR TEMPERATURE, 4000K COLOR TEMPERATURE, ELECTRONIC DIMMING DRIVER, AND EMERGENCY BATTERY PACK.
A1	TRACELITE	LP24-36-35K-LEDEM-10W	LOT	39	LED	U	C	2 1/5"	2"x4" LED LAY-IN LIGHT FIXTURE WITH WHITE LENS, 3500K COLOR TEMPERATURE, 4000K COLOR TEMPERATURE, ELECTRONIC DIMMING DRIVER, AND EMERGENCY BATTERY PACK.
E	AXIS LIGHTING	SCS-500-80-35-F-S#78-C-UNV-D-1	-	-	LED	S	C	-	2" WIDE, 7"-8" LONG SURFACE LINEAR LED LIGHT FIXTURE WITH EXTRUDED ALUMINUM HOUSING, SPOTLESS LENS, 1 CIRCUIT, DIMMABLE LED DRIVER RATED FOR MINIMUM LIFE OF 50,000 HOURS, 80CRI, 3500K LAMP, MINIMUM 5 YEAR DRIVER AND LED ENGINE WARRANTY, SHALL BE LM79 & LM80 TESTED, CUSTOM FINISH TO BE SELECTED BY ARCHITECT. LENGTH TO BE VERIFIED.
E1	AXIS LIGHTING	SCS-500-80-35-F-S#19-C-UNV-D-1	-	-	LED	S	C	-	2" WIDE, 11"-9" LONG SURFACE LINEAR LED LIGHT FIXTURE WITH EXTRUDED ALUMINUM HOUSING, SPOTLESS LENS, 1 CIRCUIT, DIMMABLE LED DRIVER RATED FOR MINIMUM LIFE OF 50,000 HOURS, 80CRI, 3500K LAMP, MINIMUM 5 YEAR DRIVER AND LED ENGINE WARRANTY, SHALL BE LM79 & LM80 TESTED, CUSTOM FINISH TO BE SELECTED BY ARCHITECT. LENGTH TO BE VERIFIED.
E2	AXIS LIGHTING	SCS-500-80-35-F-S#12-C-UNV-D-1	-	-	LED	S	C	-	2" WIDE, 12" LONG SURFACE LINEAR LED LIGHT FIXTURE WITH EXTRUDED ALUMINUM HOUSING, SPOTLESS LENS, 1 CIRCUIT, DIMMABLE LED DRIVER RATED FOR MINIMUM LIFE OF 50,000 HOURS, 80CRI, 3500K LAMP, MINIMUM 5 YEAR DRIVER AND LED ENGINE WARRANTY, SHALL BE LM79 & LM80 TESTED, CUSTOM FINISH TO BE SELECTED BY ARCHITECT. LENGTH TO BE VERIFIED.
E3	AXIS LIGHTING	SCS-500-80-35-F-S#13-C-UNV-D-1	-	-	LED	S	C	-	2" WIDE, 15"-7" LONG SURFACE LINEAR LED LIGHT FIXTURE WITH EXTRUDED ALUMINUM HOUSING, SPOTLESS LENS, 1 CIRCUIT, DIMMABLE LED DRIVER RATED FOR MINIMUM LIFE OF 50,000 HOURS, 80CRI, 3500K LAMP, MINIMUM 5 YEAR DRIVER AND LED ENGINE WARRANTY, SHALL BE LM79 & LM80 TESTED, CUSTOM FINISH TO BE SELECTED BY ARCHITECT. LENGTH TO BE VERIFIED.
G	COOPER	ASNE-LD4-47S-LW-UNV-1832-CO1-U-ATC-CHAIN/SET	-	50	LED	CH	C	-	4 FOOT LED STRIP WITH DIFFUSE LENS, DIMMABLE LED DRIVER, LED DRIVER RATED FOR MINIMUM LIFE OF 50,000 HOURS, 80CRI, 3500K LAMP, MINIMUM 5 YEAR DRIVER AND LED LAMP WARRANTY, SHALL BE LM79 & LM80 TESTED, 85CRI, 3500K COLOR TEMPERATURE, 45" ADJUSTABLE STEM SET.
G1	COOPER	ASNE-LD4-47S-LW-UNV-EL14W-1832-CO1-U-ATC-CHAIN/SET	-	-	LED	CH	C	-	4 FOOT LED STRIP WITH MEDIUM DIFFUSE LENS, DIMMABLE LED DRIVER, LED DRIVER RATED FOR MINIMUM LIFE OF 50,000 HOURS, 80CRI, 3500K LAMP, MINIMUM 5 YEAR DRIVER AND LED LAMP WARRANTY, SHALL BE LM79 & LM80 TESTED, 85CRI, 3500K COLOR TEMPERATURE, 45" ADJUSTABLE STEM SET.
H	PRESCOLITE	LDB9-15-D010-EUB9-1020-80-35-8LB-M-1-HB26	LOT	15	LED	R	C	6 7/8"	6" DIAMETER LED DOWNLIGHT WITH DIMMABLE LED DRIVER RATED FOR MINIMUM LIFE OF 50,000 HOURS, SEMI-SPECULAR CLEAR ALZAK REFLECTOR, AND 80CRI, 3500K LAMP, 1500 LUMEN OUTPUT, MEDIUM BEAM REFLECTOR, MINIMUM 5 YEAR DRIVER AND LED LAMP WARRANTY WITH ALUMINUM HEAT SINK AND WHITE FLANGE, AND SHALL BE LM79 & LM80 TESTED.
H1	PRESCOLITE	LDB9-15-D010-EM14-EUB9-1020-80-35-8LB-M-1-HB26	LOT	16	LED	R	C	5 7/8"	6" DIAMETER LED DOWNLIGHT WITH DIMMABLE LED DRIVER RATED FOR MINIMUM LIFE OF 50,000 HOURS, SEMI-SPECULAR CLEAR ALZAK REFLECTOR, AND 80CRI, 3500K LAMP, 1500 LUMEN OUTPUT, MEDIUM BEAM REFLECTOR, EMERGENCY BATTERY PACK, MINIMUM 5 YEAR DRIVER AND LED LAMP WARRANTY WITH ALUMINUM HEAT SINK AND WHITE FLANGE, AND SHALL BE LM79 & LM80 TESTED.
H2	PRESCOLITE	LDB9-10-D010-EUB9-1020-80-35-8LB-M-1-HB26	LOT	11	LED	R	C	6 7/8"	6" DIAMETER LED DOWNLIGHT WITH DIMMABLE LED DRIVER RATED FOR MINIMUM LIFE OF 50,000 HOURS, SEMI-SPECULAR CLEAR ALZAK REFLECTOR, AND 80CRI, 3500K LAMP, 1000 LUMEN OUTPUT, MEDIUM BEAM REFLECTOR, MINIMUM 5 YEAR DRIVER AND LED LAMP WARRANTY WITH ALUMINUM HEAT SINK AND WHITE FLANGE, AND SHALL BE LM79 & LM80 TESTED.
H3	PRESCOLITE	LDB9-15-D010-EM14-EUB9-1020-80-35-8LB-M-1-HB26	LOT	11	LED	R	C	5 7/8"	6" DIAMETER LED DOWNLIGHT WITH DIMMABLE LED DRIVER RATED FOR MINIMUM LIFE OF 50,000 HOURS, SEMI-SPECULAR CLEAR ALZAK REFLECTOR, AND 80CRI, 3500K LAMP, 1000 LUMEN OUTPUT, MEDIUM BEAM REFLECTOR, EMERGENCY BATTERY PACK, MINIMUM 5 YEAR DRIVER AND LED LAMP WARRANTY WITH ALUMINUM HEAT SINK AND WHITE FLANGE, AND SHALL BE LM79 & LM80 TESTED.
I	LITHONIA	UWO-80012-21W-N-W35-A-120/277V-RT-F	LOT	21	LED	R	C	4"	6" DIAMETER LED DOWNLIGHT WITH DIMMABLE LED DRIVER RATED FOR MINIMUM LIFE OF 50,000 HOURS, HOUGH IN TRAY, FROSTED LENS, AND 80CRI, 3500K LAMP, NARROW BEAM SPREAD, MINIMUM 5 YEAR DRIVER AND LED LAMP WARRANTY WITH ALUMINUM HEAT SINK AND WHITE FLANGE, AND SHALL BE LM79 & LM80 TESTED.
J	LITHONIA	WST-LED-85-40K-VF-MVOLT-DOBXD-EXOWH	LOT	25	LED	S	-	-	TRAPEZOIDAL SHAPE WALL MOUNTED LED EXTERIOR WALL SCONCE WITH 3500 LUMENS, ALUMINUM HOUSING, DARK BRONZE FINISH, IP65 RATED, EMERGENCY BATTERY PACK.
T	HALO	SLD012830WUNVB	LOT	15	LED	S	C	-	SURFACE MOUNTED 6" DIAMETER LED LUMINAIRE WITH ACRYLIC DIFFUSER, ENERGY STAR RATED, 3000K COLOR TEMPERATURE, 1110 LUMEN OUTPUT, FIVE YEAR LAMP & DRIVER WARRANTY, AND FINISH TO BE SELECTED BY ARCHITECT.
Y	LITHONIA	DSX2-LED-80C-530-40K-1218-1M-VOL-1-SPA-DOBXD	LOT	113	LED	POLE	-	22'AFG	POLE MOUNTED LED PARKING LOT LIGHT FIXTURE WITH 4000K COLOR TEMPERATURE, 12180 LUMEN OUTPUT, ALUMINUM HOUSING, AND TYPE 2 DISTRIBUTION WITH SPILL CONTROL. LED LAMP AND DRIVER SHALL BE GUARANTEED BY AT LEAST A FIVE YEAR WARRANTY AND SHALL BE LM79 & LM80 TESTED. COLOR TO BE SELECTED BY ARCHITECT. 20 FOOT SQUARE STRAIGHT STEEL POLE WITH 2' BASE.
Y1	LITHONIA	DSX2-LED-80C-530-40K-1218-1M-VOL-1-SPA-DOBXD	LOT	113	LED	POLE	-	22'AFG	POLE MOUNTED LED PARKING LOT LIGHT FIXTURE WITH 4000K COLOR TEMPERATURE, 12180 LUMEN OUTPUT, ALUMINUM HOUSING, AND TYPE 3 DISTRIBUTION WITH SPILL CONTROL. LED LAMP AND DRIVER SHALL BE GUARANTEED BY AT LEAST A FIVE YEAR WARRANTY AND SHALL BE LM79 & LM80 TESTED. COLOR TO BE SELECTED BY ARCHITECT. 20 FOOT SQUARE STRAIGHT STEEL POLE WITH 2' BASE.
Y1	LITHONIA	DSX2-LED-80C-530-40K-1218-1M-VOL-1-SPA-DOBXD	LOT	226	LED	POLE	-	22'AFG	2 POLE MOUNTED LED PARKING LOT LIGHT FIXTURES WITH 4000K COLOR TEMPERATURE, 12180 LUMEN OUTPUT PER HEAD, ALUMINUM HOUSING, AND TYPE 3 DISTRIBUTION WITH SPILL CONTROL. LED LAMP AND DRIVER SHALL BE GUARANTEED BY AT LEAST A FIVE YEAR WARRANTY AND SHALL BE LM79 & LM80 TESTED. COLOR TO BE SELECTED BY ARCHITECT. 20 FOOT SQUARE STRAIGHT STEEL POLE WITH 2' BASE.
XL	EXITRONIX	ILX-G-AC-WH	FURNISHED WITH UNIT	-	-	-	-	-	SINGLE FACE THERMOPLASTIC LED EXIT SIGN WITH SINGLE, WHITE HOUSING, AND GREEN LETTERS, AC ONLY.
XL1	EXITRONIX	ILX-G-AC-WH	FURNISHED WITH UNIT	-	-	-	-	-	DOUBLE FACE THERMOPLASTIC LED EXIT SIGN WITH DOUBLE, WHITE HOUSING, AND GREEN LETTERS & CHEVRONS, AC ONLY (SEE FLOOR PLAN FOR DIRECTIONS).
XL2	EXITRONIX	GVEX-WP-1-LB-WH	FURNISHED WITH UNIT	-	-	-	-	-	SINGLE FACE, VANDAL RESISTANT, ARROWS AS SHOWN ON DRAWINGS.

ABBREVIATIONS: U-LAY-IN C-CEILING LG-LENS GASKETING GMF-INTERNAL SLOW BLOW FUSE FL-FLUORESCENT MH-METAL HALIDE HO-HIGH OUTPUT  
 AFT-ABOVE FINISH FLOOR F-RECESSED FC-FROM CEILING R-RECESSED F-ABOVE MIRROR W-WALL W-ABOVE WINDOW  
 S-SURFACE DTI-DOUBLE TWIN TUBE FLUORESCENT CA-CANOPY TC-TOP OF METAL CANOPY AW-ABOVE WINDOW

LIGHTING FIXTURE SCHEDULE GENERAL NOTES:

- EACH LIGHT FIXTURE SHALL BE EQUIPPED WITH LAMPS, FURNISH AND INSTALL LAMPS AS SHOWN IN SCHEDULE AND IN SPECIFICATIONS.
- FIXTURE OUTLET BOX LOCATIONS SHOWN ON THE DRAWINGS ARE DIAGRAMMATIC AND APPROXIMATE IN LOCATION. EXACT POSITION OF THE OUTLET BOX SHALL DEPEND ON THE FIXTURE AND THE MOUNTING DETAIL.
- MOUNTING AND SUPPORT DETAILS FOR LIGHTING FIXTURES SHALL BE SUBMITTED TO AND APPROVED BY THE ENGINEER BEFORE THE FIXTURES ARE INSTALLED. NO COMBUSTIBLE MATERIALS SHALL BE USED.
- WET LOCATION FIXTURES SHALL BE MOUNTED IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATION SO AS TO ENSURE THE PREVENTION OF MOISTURE FROM ENTERING THE FIXTURE. IN ADDITION, EACH CONDUIT ENTRY WILL BE SEALED BY USE OF AN APPROVED SWEDGE FITTING WITH A NEOPRENE SEAL, AS MANUFACTURED BY JOHN REMKE COMPANY OR APPROVED EQUAL.
- OUTLET BOXES SERVING WET LOCATION FIXTURE SHALL BE CODE SIZE, WITH A WATERTIGHT SOLID CAST TOP. CONDUIT ENTRIES SHALL BE THREADED.

Order Plans @



HOMWOOD PATRIOT PARK POOL  
 HOMWOOD PARKS & RECREATION

HOMWOOD PARKS AND RECREATION  
 HOMWOOD, AL

DAVIS ARCHITECTS  
 OWNER: HOMWOOD PARKS AND RECREATION  
 1632 OAKWOOD ROAD  
 HOMWOOD, AL 35209  
 205-322-6704  
 ATTN: BENJELYN SQUIRES  
 ARCHITECT: DAVIS ARCHITECTS, INC.  
 120 23RD STREET SOUTH  
 BIRMINGHAM, AL 35233  
 205-322-7482  
 ATTN: JIM HARTSELL  
 LANDSCAPE ARCHITECT: HNP  
 1914 26TH AVE S.  
 BIRMINGHAM, AL 35209  
 205-324-4447  
 ATTN: TAMMY HOLCOMBE / ED NORTON  
 CONSTRUCTION MANAGER: BL HARBERT  
 820 SHADES CREEK PARKWAY, SUITE 3000  
 BIRMINGHAM, AL 35209  
 205-902-2800  
 ATTN: JOHN HANSON  
 STRUCTURAL ENGINEER: LEVD INC.  
 716 SOUTH 30TH STREET  
 BIRMINGHAM, AL 35233  
 205-251-4500  
 ATTN: WIM BISHOP / BRAD CHRISTOPHER  
 MECHANICAL ENGINEER: WHITAKER & RAWSON  
 3332 OLD MONTGOMERY HIGHWAY  
 SUITE 103  
 BIRMINGHAM, AL 35209  
 205-870-6801  
 ATTN: DAN WHITAKER, ERIK HARTWIG, AND MARK D'ANDREA  
 CIVIL ENGINEER: LEVD INC.  
 716 SOUTH 30TH STREET  
 BIRMINGHAM, AL 35233  
 205-251-4500  
 ATTN: CURTIS EATMAN AND BRAIN HATCHER  
 ELECTRICAL ENGINEER: FISHER ARNOLD  
 1507 ALEX DR.  
 SUITE 101  
 BIRMINGHAM, AL 35210  
 205-833-7033  
 ATTN: JOSEPH KUMU AND NICHOLAS BROWN  
 PLUMBING / FIRE PROTECTION ENGINEER: EDMONDS ENGINEERING  
 2 RIVERCHASE OFFICE PLAZA  
 SUITE 205  
 BIRMINGHAM, AL 35244  
 205-988-2069  
 ATTN: CAROL JOHNSON  
 POOL CONSULTANT: COUNSELLMAN HUNSAKE  
 10733 SUNSET OFFICE DRIVE  
 SUITE 400  
 ST. LOUIS, MO 63127  
 314-894-1245  
 ATTN: JEFF NODORFT

REV DATE DESCRIPTION

DATE: OCTOBER 6, 2017  
 PROJECT: 100% CONSTRUCTION DOCUMENTS  
 SHEET: DAVIS ARCHITECTS PROJECT NO. 3822  
 SHEET TITLE: FIXTURE SCHEDULE

DRAWING NO.:  
 FISHER ARNOLD  
 1507 Alex Drive, Suite 101 | Birmingham, AL 35210  
 205.833.7033 | Fax: 205.833.7030 | farnold@aarnold.com  
 PROJ: 110405  
 E0.01