H1A — PANELBOARD

480V, 3PH, 3W
600 A, M.L.O.
(7) AIC, FULLY RATED
SURFACE MOUNT
GROUND BUS

SERVES: HVAC
LOCATION: EDC1
PANEL PROVIDED WITH EDC

	DESCRIPTION	WIRE	BRKR	PL	A	B	C	PL	BRKR	WIRE	DESCRIPTION	
1					12.91 6.73							2
3	RTU19 (6) 20 TON	3	50 A	3		12.91 6.73		3	30 A	6	RTU20 (6) 10 TON	4
5							12.91 6.73					6
7					12.91 6.73							8
9	RTU21 (6) 20 TON	4	50 A	3		12.91 6.73		3	30 A	6	RTU22 (6) 10 TON	10
11							12.91 6.73					12
13					3.60 12.91							14
15	RTU23 (6) 5 TON	8	20 A	3		3.60 12.91		3	50 A	4	RTU24 (6) 20 TON	16
17							3.60 12.91					18
19					12.91 12.91							20
21	RTU25 20 TON	8	50 A	3		12.91 12.91		3	50 A	6	RTU26 (6) 20 TON	22
23							12.91 12.91					24
25					6.10 6.73							26
27	RTU27 (6) 10 TON	6	30 A	3		6.10 6.73		3	30 A	10	RTU28 10 TON	28
29							6.10 6.73					30
31					2.49 6.73							32
33	RTU29 3 TON	12	15 A	3		2.49 6.73		3	30 A	10	RTU30 10 TON	34
35							2.49 6.73					36
37					3.27 6.73							38
39	RTU31 5 TON	12	20 A	3		3.27 6.73		3	30 A	10	RTU32 10 TON	40
41							3.27 6.73					42
43					6.73 6.73							44
45	RTU33 (6) 10 TON	8	30 A	3		6.73 6.73		3	30 A	10	RTU34 10 TON	46
47							6.73 6.73					48
49					3.27 0.00			--	--	--	SPACE	50
51	RTU35 (6) 5 TON	10	20 A	3		3.27 0.00		--	--	--	SPACE	52
53							3.27 0.00	--	--	--	SPACE	54

TOTAL CONNECTED:	130.45	130.45	130.45	KVA
TOTAL CONNECTED:	470.71	470.71	470.71	AMPS
TOTAL LOAD:	391.34	KVA	470.71	AMPS
PER NEC ARTICLE 220 FEEDER LOAD:	391.34	KVA	470.71	AMPS

H2A — PANELBOARD

480V, 3PH, 3W
400 A, M.L.O.
(7) AIC, FULLY RATED
SURFACE MOUNT
GROUND BUS

SERVES: HVAC
LOCATION: EDC2
PANEL FURNISHED WITH EDC, INSTALLED BY E.C.

	DESCRIPTION	WIRE	BRKR	PL	A	B	C	PL	BRKR	WIRE	DESCRIPTION	
1					6.10 12.91							2
3	RTU1 (5) 10 TON	6	30 A	3		6.10 12.91		3	50 A	4	RTU2 (6) 20 TON	4
5							6.19 12.91					6
7					3.60 6.73							8
9	RTU3 (6) 5 TON	10	20 A	3		3.60 6.73		3	30 A	8	RTU4 (6) 10 TON	10
11							3.89 6.73					12
13					3.27 3.27							14
15	RTU5 5 TON	12	20 A	3		3.27 3.27		3	20 A	12	RTU6 5 TON	16
17							3.27 3.27					18
19					3.27 3.27							20
21	RTU7 5 TON	12	20 A	3		3.27 3.27		3	20 A	12	RTU8 5 TON	22
23							3.27 3.27					24
25					2.49 3.27							26
27	RTU9 3 TON	12	15 A	3		2.49 3.27		3	20 A	12	RTU10 5 TON	28
29							2.49 3.27					30
31					3.27 6.73							32
33	RTU11 5 TON	12	20 A	3		3.27 6.73		3	30 A	10	RTU12 10 TON	34
35							3.27 6.73					36
37					2.49 2.49							38
39	RTU13 3 TON	12	15 A	3		2.49 2.49		3	15 A	12	RTU14 3 TON	40
41							2.49 2.49					42
43					2.49 12.91							44
45	RTU15 3 TON	12	15 A	3		2.49 12.91		3	50 A	6	RTU16 (6) 20 TON	46
47							2.49 12.91					48
49					12.91 6.73							50
51	RTU17 20 TON	8	50 A	3		12.91 6.73		3	30 A	10	RTU18 10 TON	52
53							12.91 6.73					54

TOTAL CONNECTED:	98.24	98.24	98.24	KVA
TOTAL CONNECTED:	354.50	354.50	354.50	AMPS
TOTAL LOAD:	294.73	KVA	354.50	AMPS
PER NEC ARTICLE 220 FEEDER LOAD:	294.73	KVA	354.50	AMPS

H1B — PANELBOARD

480Y/277 V, 3PH, 4W
400 A, M.L.O.
(7) AIC, FULLY RATED
SURFACE MOUNT
GROUND BUS

SERVES: 480V DISTRIBUTION
LOCATION: EDC1
PANEL PROVIDED WITH EDC

	DESCRIPTION	WIRE	BRKR	PL	A	B	C	PL	BRKR	WIRE	DESCRIPTION	
1					6.41							2
3	TRANSFORMER T1D (6.9) 150 KVA, 480/3	225 A	3			45.55		3	20 A	12	DOMESTIC BOOSTER PUMP (2) (2) @ 3 HP EA, 480/3	4
5							44.84 2.86					6
7	COMPACTOR					0.00		--	--	--	SPACE	8
9	10 HP, 460/3	10	1		3.88	0.00		--	--	--	SPACE	10
11							3.88 0.00	--	--	--	SPACE	12
13	GR BALER				3.88			--	--	--	SPACE	14
15	10 HP, 460/3	10	30 A	3		3.88 0.00		--	--	--	SPACE	16
17							3.88 0.00	--	--	--	SPACE	18
19	CMP				3.88	0.00		--	--	--	SPACE	20
21	10 HP					3.88 0.00		--	--	--	SPACE	22
23							3.88 0.00	--	--	--	SPACE	24
25					0.58 0.00			--	--	--	SPACE	26
27	JOCKEY P	12	20 A	3		0.58 0.00		--	--	--	SPACE	28
29	7.5 HP, 460/3						0.58 0.00	--	--	--	SPACE	30
31					1.67 0.00			--	--	--	SPACE	32
33	FIRE PUMP (5)	12	20 A	3		1.67 0.00		--	--	--	SPACE	34
35	5 KW, 480/3						1.67 0.00	--	--	--	SPACE	36
37								--	--	--	SPACE	38
39	WH-1 (SUMP METEERING (3) (VOLTAGE REFERENCE)	12	15 A	3	1.25 0.00			--	--	--	SPACE	40
41						1.25 0.00		--	--	--	SPACE	42

TOTAL CONNECTED:	66.21	63.35	62.63	KVA
TOTAL CONNECTED:	239.43	229.06	226.12	AMPS
TOTAL LOAD:	192.19	KVA	231.17	AMPS
PER NEC ARTICLE 220 FEEDER LOAD:	146.56	KVA	176.69	AMPS

H1P — POWER SWITCHING PANELBOARD

480Y/277 V, 3PH, 4W
225 A, M.L.O.
(7) AIC, SERIES RATED
SURFACE MOUNT
GROUND BUS

SERVES: LIGHTING
LOCATION: EDC1
PANEL PROVIDED WITH EDC

	DESCRIPTION	WIRE	BRKR	PL	A	B	C	PL	BRKR	WIRE	DESCRIPTION	
1	GM SALES LTG ROWS (6,X)	10	20 A	1	4.09 3.69			1	20 A	8	COFFIN CASE LIGHTING (6,X)	2
3	GM SALES LTG ROWS (6,X)	10	20 A	1		4.09 1.54		1	20 A	12	SECURITY LIGHTING (13,X)	4
5	GM SALES LTG ROWS (6,X)	10	20 A	1			4.09 0.00	--	--	--	DEDICATED SPACE	6
7	GM SALES LTG ROWS (X)	12	20 A	1	4.09 0.34			1	20 A	12	OUTSIDE BAG GOODS (13,X)	8
9	GM SALES LTG ROWS (X)	12	20 A	1		4.09 0.00		--	--	--	DEDICATED SPACE	10
11	GM SALES LTG ROWS (X)	12	20 A	1			3.96 0.80	1	20 A	12	TLE CUSTOMER LTG (13,X)	12
13	GM SALES LTG ROWS (6,X)	10	20 A	1	3.96 0.00			--	--	--	DEDICATED SPACE	14
15	GM SALES LTG ROW (6,X)	10	20 A	1		4.09 0.00		1	20 A	--	SPARE (X)	16
17	GM SALES LTG ROW (6,X)	10	20 A	1			4.09 0.00	--	--	--	SPACE	18
19	GM SALES LTG ROW (6,X)	8	20 A	1	4.09 0.00			--	--	--	SPACE	20
21	GM SALES LTG ROW (6,X)	8	20 A	1		4.09 0.00		--	--	--	SPACE	22
23	GM SALES LTG ROW (6,X)	10	20 A	1			2.11 0.00	--	--	--	SPACE	24
25	GR SALES LTG ROWS (6,X)	8	20 A	1	3.63 0.00			--	--	--	SPACE	26
27	GR SALES LTG ROWS (6,X)	8	20 A	1		3.04 0.00		--	--	--	SPACE	28
29	GR SALES LTG ROWS (6,X)	8	20 A	1			3.30 0.00	--	--	--	SPACE	30
31	GR SALES LTG ROWS (6,X)	8	20 A	1	3.23 0.00			--	--	--	SPACE	32
33	GC SALES LTG ROWS (6,X)	8	20 A	1		3.76 0.00		--	--	--	SPACE	34
35	REAR PERIMETER LIGHTING (6,X)	10	20 A	1			3.70 0.86	2	20 A		PARKING LOT LIGHTING (10,X)	36
37	GM PERIMETER LIGHTING (6,X)	10	20 A	1	2.35 0.86			2	20 A			38
39	DEDICATED SPACE	--	--	--		0.00 0.29		2	20 A		TRUCKWELL SECURITY LTG (10,X)	40
41	TLE SERVICE LIGHTING (6,13,X)	10	20 A	1			3.89 0.28					42
43	STOCKROOM LIGHTING	12	20 A	1	2.54 2.95			1	20 A	12	REAR HALLWAY LIGHTING	44
45	RECEIVING LIGHTING	12	20 A	1		2.64 1.88		1	20 A	12	REAR OFFICE LIGHTING	46
47	RECEIVING LIGHTING	12	20 A	1			1.78 3.09	1	20 A	8	HALLWY / COOLER / FRZR LTG	48
49					0.60 0.42			1	20 A	12	SALES FLOOR EMERGENCY LTG (3)	50
51	SPD (3,9) (SURGE SUPPRESSION)	--	30 A	3		0.00 0.00		1	20 A	--	SPARE	52
53							0.00 0.00	1	20 A	--	SPARE	54

TOTAL CONNECTED:	36.26	29.25	31.46	KVA
TOTAL CONNECTED:	132.10	105.60	114.80	AMPS
TOTAL LOAD:	96.56	KVA	116.63	AMPS
PER NEC ARTICLE 220 FEEDER LOAD:	121.21	KVA	145.79	AMPS

H2B — PANELBOARD

480Y/277 V, 3PH, 4W
400 A, M.L.O.
(7) AIC, SERIES RATED
SURFACE MOUNT
GROUND BUS

SERVES: 480V DISTRIBUTION
LOCATION: EDC2
PANEL PROVIDED WITH EDC

	DESCRIPTION	WIRE	BRKR	PL	A	B	C	PL	BRKR	WIRE	DESCRIPTION	
1					12.44 0.00			--	--	--	SPACE	2
3	PANEL H2P1 (8,9) 480/277/3	150 A	3			12.74 0.00		--	--	--	SPACE	4
5							11.38 0.00	--	--	--	SPACE	6
7					7.[illegible] 0.00			--	--	--	SPACE	8
9	PANEL H2P2 (8,9) 480/277/3	[illegible]				6.17 0.00		--	--	--	SPACE	10
11							4.80 0.00	--	--	--	SPACE	12
13					44.64 0.00			--	--	--	SPACE	14
15	TRANSFORMER T2D (8,9) 150 KVA, 480/3	225 A	3			49.46 0.00		--	--	--	SPACE	16
17							46.80 0.00	--	--	--	SPACE	18
19					[illegible] 0.00			--	--	--	SPACE	20
21	SUB-METERING (3) (VOLTAGE REFERENCE)		3			0.14 0.00		--	--	--	SPACE	22
23							0.14 0.00	--	--	--	SPACE	24
25	SPACE	--	--	--	0.00 0.00			--	--	--	SPACE	26
27	SPACE	--	--	--		0.00 0.00		--	--	--	SPACE	28
29	SPACE	--	--	--			0.00 0.00	--	--	--	SPACE	30
31	SPACE	--	--	--	0.00 0.00			--	--	--	SPACE	32
33	SPACE	--	--	--		0.00 0.00		--	--	--	SPACE	34
35	SPACE	--	--	--			0.00 0.00	--	--	--	SPACE	36
37	SPACE	--	--	--	0.00 0.00			--	--	--	SPACE	38
39	SPACE	--	--	--		0.00 0.00		--	--	--	SPACE	40
41	SPACE	--	--	--			0.00 0.00	--	--	--	SPACE	42

TOTAL CONNECTED:	64.55	66.51	63.11	KVA
TOTAL CONNECTED:	233.86	246.14	227.64	AMPS
TOTAL LOAD:	196.19	KVA	235.97	AMPS
PER NEC ARTICLE 220 FEEDER LOAD:	165.58	KVA	223.22	AMPS

H2P1 — POWER SWITCHING PANELBOARD

480Y/277 V, 3PH, 4W
225 A, M.L.O.
(7) AIC, SERIES RATED
SURFACE MOUNT
GROUND BUS

SERVES: LIGHTING
LOCATION: EDC2
PANEL PROVIDED WITH EDC

	DESCRIPTION	WIRE	BRKR	PL	A	B	C	PL	BRKR	WIRE	DESCRIPTION	
1	DEDICATED SPACE	--	--	--	0.00 2.50			1	20 A	12	FRONT PERIMETER LIGHTING (X)	2
3	PHARMACY LIGHTING (13,X)	12	20 A	1		0.91 4.12		1	20 A	8	GC PERIMETER LIGHTING (6,X)	4
5	OFFICE / COURTESY DESK LTG	12	20 A	1			2.45 2.66	1	20 A	8	GR PERIMETER LIGHTING (6,X)	6
7	GM VESTIBULE LTG	12	20 A	1	1.14 1.95			1	20 A	10	GC LIVE GOODS (6,13,X)	8
9	PHARMACY SALES LTG (X)	12	20 A	1		1.06 0.00		--	--	--	DEDICATED SPACE	10
11	PRODUCE STRIP LIGHTING (6,X)	10	20 A	1			2.72 0.93	1	20 A	12	TENANT SPACE LTG (13,X)	12
13	PRODUCE STRIP LIGHTING (6,X)	10	20 A	1	2.80 0.00			--	--	--	DEDICATED SPACE	14
15	PRODUCE PENDANT LTG (X)	12	20 A	1		1.73 0.00		1	20 A	12	STORE FRONT SIGN (X)	16
17	DEDICATED SPACE	--	--	--			0.00 0.86	1	20 A	12	PICKUP SIGN (X)	18
19	VISION CENTER LIGHTING (13,X)	12	20 A	1	2.62 0.66			1	20 A	12	TENANT SIGN (X)	20
21	DEDICATED SPACE	--	--	--		0.00 0.66		1	20 A	12	STORE FRONT SIGN (X)	22
23	TENANT SPACE LTG (13,X)	12	20 A	1			0.93 0.66	1	20 A	12	TENANT SIGN (X)	24
25	DEDICATED SPACE	--	--	--	0.00 0.66			1	20 A	12	TENANT SIGN (X)	26
27	PICKUP ALCOVE LTG (13,X)	12	20 A	1		0.34 0.00		--	--	--	SPACE	28
29	PICKUP CANOPY LIGHTING (X)	12	20 A	1			0.18 0.00	--	--	--	SPACE	30
31	DEDICATED SPACE	--	--	--	0.00 0.00			--	--	--	SPACE	32
33	BAKERY / DELI LIGHTING (6,13,X)	8	20 A	1		3.92 0.00		--	--	--	SPACE	34
35	DEDICATED SPACE	--	--	--			0.00 0.00	--	--	--	SPACE	36
37	FOOD TENANT LIGHTING (13,X)	12	20 A	1	0.00 0.00			--	--	--	SPACE	38
39	SPARE (X)	--	20 A	1		0.00 0.00		--	--	--	SPACE	40
41	SPARE	--	20 A	1			0.00 0.00	--	--	--	SPACE	42

TOTAL CONNECTED:	12.44	12.74	11.38	KVA
TOTAL CONNECTED:	45.46	46.57	41.07	AMPS
TOTAL LOAD:	36.55	KVA	43.96	AMPS
PER NEC ARTICLE 220 FEEDER LOAD:	44.86	KVA	53.96	AMPS

H2P2 — POWER SWITCHING PANELBOARD

480Y/277 V, 3PH, 4W
225 A, M.L.O.
(7) AIC, SERIES RATED
SURFACE MOUNT
GROUND BUS

SERVES: LIGHTING
LOCATION: EDC2
PANEL PROVIDED WITH EDC

	DESCRIPTION	WIRE	BRKR	PL	A	B	C	PL	BRKR	WIRE	DESCRIPTION	
1	STORE MONUMENT SIGN (10,X)		20 A	2	1.13 0.00							2
3						1.13 0.00		3	30 A	10	SPD (3,9) (SURGE PROTECTION)	4
5	PARKING LOT LIGHTING (10,X)		20 A	2			0.96 0.00					6
7					0.96 1.13			2	20 A		STORE MONUMENT SIGN (10,X)	8
9	PARKING LOT LIGHTING (10,X)		20 A	2		0.86 1.13						10
11							0.96 1.06	2	20 A		PARKING SECURITY LIGHTING (10,X)	12
13	PARKING LOT LIGHTING (10,X)		20 A	2	0.90 1.06							14
15						0.80 0.30						16
17	PARKING LOT LIGHTING (10,X)		20 A	2			0.97 0.30	2	20 A		FUTURE SIGN (10,X)	18
19					0.97 0.30							20
21	PARKING LOT LIGHTING (10,X)		20 A	2		0.85 0.30		2	20 A		FUTURE SIGN (10,X)	22
23							0.65 0.00	--	--	--	SPACE	24
25	PARKING LOT LIGHTING (10,X)		20 A	2	0.90 0.00			--	--	--	SPACE	26
27						0.90 0.00		--	--	--	SPACE	28
29	SPACE	--	--	--			0.00 0.00	--	--	--	SPACE	30
31	SPACE	--	--	--	0.00 0.00			--	--	--	SPACE	32
33	SPACE	--	--	--		0.00 0.00		--	--	--	SPACE	34
35	SPACE	--	--	--			0.00 0.00	--	--	--	SPACE	36
37	SPACE	--	--	--	0.00 0.00			--	--	--	SPACE	38
39	SPACE	--	--	--		0.00 0.00		--	--	--	SPACE	40
41	SPACE	--	--	--			0.00 0.00	--	--	--	SPACE	42

TOTAL CONNECTED:	7.35	6.17	4.80	KVA
TOTAL CONNECTED:	27.33	23.05	17.31	AMPS
TOTAL LOAD:	19.90	KVA	22.04	AMPS
PER NEC ARTICLE 220 FEEDER LOAD:	23.90	KVA	26.54	AMPS

H3B — PANELBOARD

480Y/277 V, 3PH, 4W
125 A, M.L.O.
14,000 AIC
SURFACE MOUNT
GROUND BUS

SERVES: 480V TLE EQUIPMENT
LOCATION: EDC3
PANEL PROVIDED WITH EDC

	DESCRIPTION	WIRE	BRKR	PL	A	B	C	PL	BRKR	WIRE	DESCRIPTION	
1					11.80 3.88							2
3	TRANSFORMER T3D (8,9) 45 KVA, 480/3			3		12.08 3.88		3	30 A	10	AIR COMPRESSOR 10 HP, 460/3	4
5							13.36 3.88					6
7	SPACE	--	--	--	0.00 0.00			--	--	--	SPACE	8
9	SPACE	--	--	--		0.00 0.00		--	--	--	SPACE	10
11	SPACE	--	--	--			0.00 0.00	--	--	--	SPACE	12
13	SPACE	--	--	--	0.00 0.00			--	--	--	SPACE	14
15	SPACE	--	--	--		0.00 0.00		--	--	--	SPACE	16
17	SPACE	--	--	--			0.00 0.00	--	--	--	SPACE	18
19	SPACE	--	--	--	0.00 0.00			--	--	--	SPACE	20
21	SPACE	--	--	--		0.00 0.00		--	--	--	SPACE	22
23	SPACE	--	--	--			0.00 0.00	--	--	--	SPACE	24
25	SPACE	--	--	--	0.00 0.00			--	--	--	SPACE	26
27	SPACE	--	--	--		0.00 0.00		--	--	--	SPACE	28
29	SPACE	--	--	--			0.00 0.00	--	--	--	SPACE	30
31	SPACE	--	--	--	0.00 0.00			--	--	--	SPACE	32
33	SPACE	--	--	--		0.00 0.00		--	--	--	SPACE	34
35	SPACE	--	--	--			0.00 0.00	--	--	--	SPACE	36
37	SPACE	--	--	--	0.00 0.00			--	--	--	SPACE	38
39	SPACE	--	--	--		0.00 0.00		--	--	--	SPACE	40
41	SPACE	--	--	--			0.00 0.00	--	--	--	SPACE	42

TOTAL CONNECTED:	15.68	15.96	17.24	KVA
TOTAL CONNECTED:	56.81	57.76	62.40	AMPS
TOTAL LOAD:	48.68	KVA	58.79	AMPS
PER NEC ARTICLE 220 FEEDER LOAD:	48.98	KVA	58.81	AMPS

H4B — PANELBOARD

480Y/277 V, 3PH, 4W
800 A, M.L.O.
(7) AIC, SERIES RATED
SURFACE MOUNT
GROUND BUS

SERVES: GROCERY 480V EQUIPMENT
LOCATION: EDC4
PANEL PROVIDED WITH EDC

	DESCRIPTION	WIRE	BRKR	PL	A	B	C	PL	BRKR	WIRE	DESCRIPTION	
1					88.93 1.36							2
3	TRANSFORMER T4D (8,9) 225 KVA, 480/3		350 A	3		79.98 1.76		3	50 A		PANEL H4C (6,9) 480/277/3	4
5							81.62 2.44					6
7					27.71 11.09							8
9	AHU1 480/3	2	125 A	3		27.71 11.09		3	40 A	8	B508L PAN WASHER (2) 37.1 A, 480/3	10
11							27.71 11.09					12
13					0.00 6.00			2	35 A	8	D026C VAT BIB W/ SHUNT-TRIP (2)	14
15	TRANSFORMER TFS (8,9) 75 KVA, 480/3		100 A	3		0.00 6.00						16
17							0.00 11.92					18
19	SPACE	--	--	--	0.00 11.92			3	60 A	6	D026C.1 FRYER (2) 43.0 A, 480/3 D026C.1 SHUNT-TRIP BREAKER	20
21	SPACE	--	--	--		0.00 11.92						22
23	SPACE	--	--	--			0.00 11.92					24
25	SPACE	--	--	--	0.00 11.92			3	60 A	6	D026C.1 FRYER (2) 43.0 A, 480/3 D026C.1 SHUNT-TRIP BREAKER	26
27	SPACE	--	--	--		0.00 11.92						28
29	SPACE	--	--	--			0.00 15.66					30
31	SPACE	--	--	--	0.00 15.66			3	70 A	4	D052A OVEN (BOTTOM) (2) 56.5 A, 480/3 D052A SHUNT-TRIP BREAKER	32
33	SPACE	--	--	--		0.00 15.66						34
35	SPACE	--	--	--			0.00 0.00	--	--	--	SPACE	36
37					0.14 0.00			--	--	--	SPACE	38
39	SUB-METERING (3) (VOLTAGE REFERENCE)	12	15 A	3		0.14 0.00		--	--	--	SPACE	40
41							0.14 0.00	--	--	--	SPACE	42

TOTAL CONNECTED:	174.71	165.17	162.49	KVA
TOTAL CONNECTED:	632.79	601.94	586.60	AMPS
TOTAL LOAD:	503.37	KVA	605.46	AMPS
PER NEC ARTICLE 220 FEEDER LOAD:	415.73	KVA	590.04	AMPS

H4C — PANELBOARD

480Y/277 V, 3PH, 4W
125 A, M.L.O.
(7) AIC, SERIES RATED
SURFACE MOUNT
GROUND BUS

SERVES: GROCERY LIGHTING
LOCATION: EDC4
PANEL PROVIDED WITH EDC

	DESCRIPTION	WIRE	BRKR	PL	A	B	C	PL	BRKR	WIRE	DESCRIPTION	
1	GR VESTIBULE LIGHTING	12	20 A	1	1.39 0.00			--	--	--	SPACE	2
3	HALLWAY / COOLER / PREP LTG	12	20 A	1		1.76 0.00		--	--	--	SPACE	4
5	GM / OOP STORAGE	12	20 A	1			2.44 0.00	--	--	--	SPACE	6
7	SPARE	--	20 A	1	0.00 0.00			--	--	--	SPACE	8
9	SPARE	--	20 A	1		0.00 0.00		--	--	--	SPACE	10
11	SPACE	--	--	--			0.00 0.00	--	--	--	SPACE	12
13	SPACE	--	--	--	0.00 0.00			--	--	--	SPACE	14
15	SPACE	--	--	--		0.00 0.00		--	--	--	SPACE	16
17	SPACE	--	--	--			0.00 0.00	--	--	--	SPACE	18

TOTAL CONNECTED:	1.39	1.76	2.44	KVA
TOTAL CONNECTED:	4.89	6.58	9.05	AMPS
TOTAL LOAD:	3.56	KVA	6.69	AMPS
PER NEC ARTICLE 220 FEEDER LOAD:	6.95	KVA	8.38	AMPS

PANELBOARD NOTES

(1) TERMINATE GROUND ON ISOLATED GROUND BUS.

(2) INSTALL LOCKING DEVICE FURNISHED WITH PANELBOARD (LOCK-OFF FOR MAINTENANCE).

(3) INSTALL LOCKING DEVICE FURNISHED WITH PANELBOARD (LOCK-ON FOR CRITICAL LOAD).

(4) GFI BREAKER FOR PERSONNEL PROTECTION (5 mA).

(5) GFI BREAKER FOR EQUIPMENT PROTECTION (30 mA).

(6) CONDUCTOR SIZE HAS BEEN INCREASED FOR VOLTAGE DROP. SIZE EQUIPMENT GROUNDING CONDUCTOR PROPORTIONALLY PER NEC.

(7) REFER TO ONE-LINE DIAGRAM FOR AVAILABLE FAULT CURRENT FOR INTERRUPTING RATING.

(8) REFER TO ONE-LINE DIAGRAM FOR WIRE SIZES.

(9) FACTORY WIRED TO [illegible].

(10) REFER TO SITE LIGHTING PLAN FOR [illegible] SIZES.

(11) THRU CONTACTOR.

(12) FACTORY PROVIDED WITH RED LABEL FOR FIRE ALARM CIRCUIT.

(13) DUAL TAP BRE