

Old Navy 2016 CCTV/BA Specifications Closed Circuit Television

- NVR: IPS-4000-DT-5000-40370 EXACQ DESKTOP SERVER 6TB OR 8TB W/UPGRADED PROCESSOR.
- DVR monitor: VZ-185LED 18.5 FLAT SCREEN MONITOR
- Sales Floor & Stockroom Fixed Cameras: M3005-V INDOOR DOME 2.8MM 2MP CAMERA
 - Camera height 10' AFF.
 - Cameras may be lowered to 9.5' if lighting causes obstruction of view.
- Register/Front Safe Camera: FE8172 2 FISHEYE NETWORK 5MP CAMERA - VIVOTECH 360
 - Must see all register drawers. Must not obstruct or be obstructed by any permanent Marketing. Make sure the camera hangs at 12'-0" AFF and below the 13'-0" cashwrap wall. If the camera is too high we risk the camera seeing inside the fitting room. Tech to validate before completing installation. Ideal height between 12'-0" and 12'-6" A.F.F..
- Entry/Exit PVM: VIEWZ 32-IN PVM WITH INTEGRATED 2MP IP CAMERA iPad-style white monitor offset to right side (as customer enters), about 12 feet inside store, 9' AFF.
- Any other ceiling-mounted PVMs shall be mounted at 9' AFF.
- Camera plan for each site shall be generated by Vector and sent to Britanya Hehn for approval. Camera plan shall be based on the below standards.
- Techs must contact field LP leader for a walk through prior to prewire install and for final sign-off. If an attempt has been made to contact the field LP leader with no response, please escalate to Britanya Hehn.

FOR STORE SPECIFIC CONDITIONS/QUESTIONS, CONTACT GAP LOSS PREVENTION:

Gap Inc. LP Team:

- Britanya Hehn, Old Navy Manager LP Ops (LP Technology) (208) 887-4943 (Idaho Office - Primary) (503) 956-8634 (Cell - Secondary) (415) 832-3217 (MB Office - Third) Britanya_Hehn@Gap.com
- Jeanne Ann Songy, Gap Inc. LP Ops (855) 817-5225 (Office) (513) 520-5392 (Cell) Jeanne_Songy@Gap.com
- Naz Amirsoleymani, Gap Inc. LP Technology (415) 427-0382 (2F Office)

ALL Stores

- NVR- 6TB Desktop Server
- 1- 32 Inch IP PVM at Customer Entrance
- 1- 360 Fisheye Camera at Registers (Front Safe and ALL Registers)
- 1- 1MP Camera in Cash Office (Primary shot- Back Safe, Secondary Shot- Office Door when possible.)
- 1- 1MP Camera at EACH Perimeter Door (Between 1 and 3 cameras depending on layout)
- 1- 1MP Camera shooting into Sales Floor Hotspots (Between 5 and 10 cameras depending on the risk)

For Relocations

- Reuse NVR's less than 5 years old.
- Do **NOT** reuse any analog multiplex, DVR or 3VR.
- Plan to reuse PT2's
 - Not to exceed 6 per store
 - (Relocate matrix switch, touch tracker and monitor)
- Plan to use flat screen PVM with integrated cameras and encoders
 - One per store at Fitting Room entrance
- Turn in any additional PVM's, DVR's, 3VRS and analog cameras to MLPM.

Burglar Alarm Specifications

- All perimeter openings shall have door contacts backed up by motion detectors.
- Front of sales floor shall be covered by wall-mount motion detectors mounted between 9'-6" to 11'-0" AFF.
- Front doors shall have surface-mounted door contacts.
- Exterior glass shall be covered by glass break detectors.
- Manager's office shall have a ceiling-mount motion detector.
- Holdup buttons located on the underside of counter (three inches from the front) at both safe locations.
- Siren at burglar alarm panel. Siren in rafters above cash wrap.
- Keypad at store front and on any shipment or employee entrance door mounted @48" max AFF
- BA plan for each site shall be validated by Britanya Hehn.
- For relocations, do not reuse burglar alarm systems. Install new.

SYMBOLS

	LONG RANGE MOTION SENSOR
	MOTION SENSOR
	RECESSED DOOR CONTACT
	SURFACE DOOR CONTACT
	OVERHEAD DOOR CONTACT
	HOLD UP BUTTON
	GLASS BREAK SENSOR
	KEY PAD
	BURGLAR ALARM CONTROL PANEL
	ALARM SOUNDER
	360° MOTION DETECTOR
	EAS PEDESTAL
	CAMERA
	CAMERAS FOR FULL PACKAGE
	MONITOR & INTELLEX
	ROLL DOWN GRILLE
	BOLLARD
	ANTI-GRAFFITI FILM

REMODEL STORE

OLD NAVY

GAP INC.
STORE DEVELOPMENT
1 FOLSOM STREET
SAN FRANCISCO, CA 94105

REPS. I.D.: 00000131847

STORE NUMBER: 5724

STORE LOCATION: BUCKHEAD STATION
1 BUCKHEAD LOOP NE
ATLANTA, GA 30326

DESIGN TYPE: P3
GENERATION: 18012
PROTOTYPE DATE: 08/31/17
OPENING: 2018

CONSULTANT INFO:

PROFESSIONAL STAMP:

FOR REFERENCE ONLY

ARCHITECT INFO:

brr

ARCHITECT OF RECORD:
BOYD W. BAU
6700 ANTIPOCH PLAZA
SUITE 300
MERRILL, AS 66204
www.brrarch.com
TEL: 913-262-9095
FAX: 913-262-9044

ISSUE TYPE:
BID/PERMIT 01/05/18

REVISIONS:

DRAWN BY: CAR
AVE JOB NUMBER: 65013029

TITLE SHEET:
LOSS PREVENTION

SHEET NUMBER:
A1-2a