

**Table I
Device Spacing**

Speed (mph)	Max. Distance Between Devices (ft.)	
	Cones or Tubular Markers	Type I or Type II Barricades or Vertical Posts or Delineators
25	25	50
35	35	70
45	45	90
55	55	110
65	65	130

**Table II
Taper Length - Shoulder**

Speed (mph)	Taper Length (ft.)			Notes
	8'	10'	12'	
25	25	25	42	1 - 20' to 50'
35	35	35	42	
45	45	45	42	1 - 20' to 50'
55	55	55	42	
65	65	65	42	1 - 20' to 50'
75	75	75	42	

**Table III
Work Area**

Speed (mph)	Work Area Length (ft.)
25	200
35	250
45	300
55	350
65	400
75	450

GENERAL NOTES:

- When there are more than two vehicles within the through traffic lanes in a one hour period, the following conditions shall exist: a) The work area shall be constructed to the minimum length for the duration of the project; b) The work area shall be constructed to the minimum length for the duration of the project; c) The work area shall be constructed to the minimum length for the duration of the project.

SYMBOLS:

- Work Area
- Channelizing Device (See Table III, Note 1)
- Work Zone Sign
- Automated Flagging Assistance Device (SAFAD) Sign
- Sign Located Within a Shoulder of Traffic

INDEX NO. 602 SHEET NO. 1 of 1

**Table I
Device Spacing**

Posted Speed	Maximum Spacing of Cones or Tubular Markers		Maximum Spacing of Type I or Type II Barricades/Parade Signs		Distance Between Signs	Buffer Space
	On a Taper	On a Flare	A	B		
25	25	50	25	50	250	100
35	35	75	35	75	350	125
45	45	100	45	100	450	150
55	55	125	55	125	550	175
65	65	150	65	150	650	200
75	75	175	75	175	750	225

GENERAL NOTES:

- Special Functions may be required to accommodate the following: a) ... b) ... c) ...
- When there are more than two vehicles within the through traffic lanes in a one hour period, the following conditions shall exist: a) ... b) ... c) ...

SYMBOLS:

- Work Area
- Channelizing Device (See Table III, Note 1)
- Work Zone Sign
- Automated Flagging Assistance Device (SAFAD) Sign
- Sign Located Within a Shoulder of Traffic

INDEX NO. 603 SHEET NO. 1 of 3

SHEET NO. 600

CONTENTS

1. Manual on Uniform Traffic Control Devices
2. Symbols
3. Preface
4. Manual on Uniform Traffic Control Devices
5. Preface
6. Manual on Uniform Traffic Control Devices
7. Symbols
8. Preface
9. Manual on Uniform Traffic Control Devices
10. Symbols
11. Preface
12. Manual on Uniform Traffic Control Devices
13. Symbols

INDEX NO. 600 SHEET NO. 1 of 1

DEFINITIONS

Regulation Speed (In Work Zones)

Advisory Speed

Travel Way

Detour, Lane Shift, and Diversion

Overhead Hazard

TEMPORARY TRAFFIC CONTROL DEVICES

PEDESTRIAN AND BICYCLIST

OPTION 1 (OVERHEAD WORK USING A MODIFIED LANE CLOSURE)

OPTION 2 (OVERHEAD WORK ABOVE AN OPEN TRAFFIC LANE)

OPTION 3 (OVERHEAD WORK ADJACENT TO AN OPEN TRAFFIC LANE)

OPTION 4 (OVERHEAD WORK MAINTAINING TRAFFIC WITH NO ENCRoACHMENT BELOW THE OVERHEAD WORK AREA)

OPTION 5 (CONDUCTOR/CABLE PULLING ABOVE AN OPEN TRAFFIC LANE)

RAILROADS

SIGHT DISTANCE

ABOVEGROUND HAZARD

GENERAL INFORMATION FOR TRAFFIC CONTROL THROUGH WORK ZONES

INDEX NO. 600 SHEET NO. 2