



GENERAL NOTES:
20 GAGE MINIMUM DEEP LEG TRACK OR SLOTTED TRACK TO ALLOW 3/4" DEFLECTION. MAINTAIN DEFLECTION CAPACITY AND FIRE-RATING AT ALL STRUCTURAL MEMBERS

STUDS CUT 3/4" SHORT TO ALLOW 3/4" DEFLECTION

AT TOP OF FINISH MATERIALS (WHERE OCCURS) PROVIDE 3/4" CLEAR SPACE TO ALLOW 3/4" DEFLECTION. DO NOT SCREW FINISH MATERIALS INTO TOP TRACK - FASTEN INTO STUDS ONLY

AT PARTITIONS WITH ACoustical INSULATION, INSTALL GYPSUM BOARD 2" TO ACCOMMODATE LARGER ACOUSTICAL SEALANT JOINT NEEDS TO ACHIEVE 3/4" DEFLECTION

Order Plans

OWNER:
WILLIAMS-SONOMA, INC.
3250 Van Ness Avenue
San Francisco, CA 94109
T 415 616 8602
F 415 439 8164
www.williams-sonoma.com

CALLISONRTKL
A DESIGN CONSULTANCY OF ARCADIS
CALLISONRTKL INC.
www.callisonrtkl.com

POTTERY BARN
WILLIAMS-SONOMA
Town Center Virginia Beach
173/177 Central Park Avenue
Virginia Beach, VA 23462
PROJECT #006-151817.00/#006-151412.00

ISSUED / REVISED	DATE
FEASIBILITY SET	08/10/17
PRELIMINARY SET	09/28/17
LL CD SET	11/30/17
PERMIT SET	12/18/17
BID SET	01/04/18

WALL DETAILS

A-802