

(A) REFER TO PROJECT MANUAL FOR ADDITIONAL REQUIREMEN

© REFER TO INTERIOR FINISH SCHEDULES FOR MATERIA COLORS AND FINISHES.

## KEY NOTE

MING ATTACHED TO ROOF STRUCTURE

FORM METAL FRAMING AT 24" O.C., REFER TO

OLD FORM METAL STUDS DOUBLED AT CONTROL JOINT.

(20 GA.) COLD FORM METAL JOIST FRAMING AT 24" O.C.,

(7) GYPSUM BOARD CORNER BEAD CONTINUOUS.

(8) GYPSUM BOARD "J" MOLDING CONTINUOUS.

 $\overleftarrow{\text{10}}$  FIRE TREATED 2X NAILERS OR BLOCKING.

(11) (2) FIRE TREATED 2X NAILERS.

(12) 1X4 WOOD TRIM (PAINT GRADE PINE) ATTACHED TO METAL STUD FRAMING WITH TECH 12 SCREWS AT 24" O.C. SET FLUSH. PAINT EXPOSED SURFACES TO MATCH WALL FINISH.

(13) 6" UNFACED SOUND BATT INSULATION.

(14) 3 1/2" UNFACED SOUND BATT INSULATION.

 $\stackrel{\textstyle <}{\text{ (15)}}$  ALUMINUM WINDOW SYSTEM, REFER TO FLOOR PLAN AND WINDOW SCHEDULE FOR TYPES.

(16) PRE-FINISHED SHEET METAL (24 GA.) COLUMN ENCLOSURE TO EXTEND THRU FINISH CEILING SYSTEM. COLOR TO MATCH WINDOW FRAMING FINISH. NO EXPOSED HORIZONTAL SEAMS PERMITTED.

(18) FINISH FLOORING AND BASE, REFER TO INTERIOR FINISH SCHEDULE FOR TYPES AND LOCATIONS.

(19) OWNER FURNISHED AND INSTALLED FIXTURE, REFER TO INTERIOR FINISH PLAN FOR LAYOUT. REFER TO SCOPE OF WORK SCHEDULE.)

**GENERAL NOTES** 

(B) DIMENSIONS ARE TO ROUGH FACE OF CONCRETE, MASONRY FRAMING, OR CENTER LINE OF STRUCTURE UNLESS OTHERWINDICATED.

(6) 5/8" TYPE "X" GYPSUM BOARD. REFER TO INTERIOR WALL TYPES AND FOR ADDITIONAL REQUIREMENTS.

(9) GYPSUM BOARD CONTINUES ONE PIECE VEE-SHAPED SLOT CONTROL JOINT (1/4" X 7/16") AT BOTH SIDES OF WALL.

(17) SUSPENDED ACOUSTICAL CEILING SYSTEM, REFER TO INTERIOR FINISH SCHEDULE FOR TYPES AND LOCATIONS.

(20) 5/8" FIRE TREATED PLYWOOD BACKING TO BACK SIDE OF STUD INTERIOR FLANGE ON EACH EXPOSED WALL FACE FROM 8-9" TO 10-0" A.F.F. FOR INSTALLATION OF SECURITY MIRRORS (OWNER FURNISHED AND INSTALLED).

Schneider, 

1736 Sprin PARTS STORE

AUTO PARTS

DATE: