

accesses queeness. Averagello sheet Writiste eric 4., 5° shet 5°.
Anchele lasso les fabricates from fell roblet carbon sloel plate o embraning le
ARTH AGS, that ones or excessed a minimum yield streeth of \$0.00° pct. Nor ancher lasse is provided with shared fabric. Bosse care in finished or martir pade.
A frontfolde hearing command discreptions of 3° x 5° for all states. Included is a
correct with adaptational sources.

A hand-halle beinting (comment contemporate to a copier within flational section all violi-mount poles.

Top cop provided section all violi-mount poles.

Fascement are light-strength golvenized, pino-plated or statistics steel.

PRISE II — Dark policy (1908) policy light policy indicated provider siteration. Other creshibles for several policy several being several policy several poli

SQUARE STRAIGHT STEEL

ORDEF	RING IN A MATION Less times	will ary depending on optic	ons selected. Consult with yo Example	our sales representative. e: SSS 20 5C DM19 DDB	
s:	25	DM19, DM28		DDB	
- 0		1 28048865	Makous	Trainer 1	
	Dourse Minds staff base special model from the special model from th	ModelPring	FT floor too	Speriolard Losions  Sides Gook Losions  Sides	
NOTES:	A Handhole	DAMO S. ot 50° DAMO G. ot 50° AERISCOMERG DElinearisine' DAMAS 1 de 100° DAMAS 2 at 50°	NPLS4xx 3/4 threaded rippile <sup>5</sup> NPLTsz 1 <sup>5</sup> threadist ségde <sup>5</sup> Hillor Estra Handfocke <sup>65</sup>	Artification Lines (pooder finish)	
pote, tolic	bring tenon mounting and drill manufing for the same on this example: DM28(T2). The combination archides a cotro, handhola.	DASSAS Suc 56" DASSAS 4 sc 50"			
on the for	og tempiste at he used har a perdenter knokesine depends nimalise that is used. Roter to the Tachtscal Data Section talen Binder to Drilling Targelates.	AERIS Superint Drill mounting **  DMEAST 1 or 50°  DMEAST 2 or 180°			
fosset ?	or 'F' to designate factors exact e.g. DM194S72	DMRSAST 2 of 30°			
	toation and orientation when ordering aption.	BMASAGT_ 3: or ser			
For 1st X	Specify the height in fact spoke base of pole. Exemple: 5tt - 5 and 20tt - 20	DMISAST_ 4 at 99° OMERC Suspend Orli recording <sup>62</sup>			
For 2rst x		DMISWRT_ 1 at 90°			
	he Hendhole Driemmijon diegrem on tim page.	DN/DSMRT 7 of 180.			
	Larm to 18" x 2-3/8" U.U. tonon standard.	DM29MRT_ 2 at 96"			
6. Combination of tenon too and drill mount requires onto handholo.		\$4539,69T_ 3 or 505			
7 Ambiticos	entres socilable, soo ones libbonio entresta olivis or	D64694RT_ 4 at 98°			

BASE DETAIL



\$\$\$20\$66 30 \$50×30.0 \$0.188 7 10.7 27 6.7 167 3.9 100 10-12 \$\$\$20\$66 30 6.0×30.0 0.169 7 18.0 475 12.2 30 9.0 225 11-13 \$\$\$52\$566 30 5.9×30.0 0.168 7 5.9 30 2.5 100 -- 10-12

## 2 A 5 SOURCES 5 8 107 2 S/A-24 8' ASTEMPATE PARCOCA ARREST-46 10 -12 2 S/A-24 8' ASTEMPATE PARCOCA ARREST-46 10 -12 3 S/A-24 12 107 ASTEMPATE PARCOCA ARREST-47 10 -12 3 S/A-24 12 107 ASTEMPATE PARCOCA ARREST-47 10 -12 3 S/A-24 12 107 ASTEMPATE PARCOCA ARREST-47 10 -12 3 S/A-24 12 107 ASTEMPATE PARCOCA ARREST-47 10 -12 3 S/A-24 12 107 ASTEMPATE PARCOCA ARREST-47 10 -12 3 S/A-24 12 107 ASTEMPATE PARCOCA ARREST-47 10 -12 3 S/A-24 12 107 ASTEMPATE PARCOCA ARREST-47 10 -12 3 S/A-24 12 107 ASTEMPATE PARCOCA ARREST-47 10 -12 3 S/A-24 12 107 ASTEMPATE PARCOCA ARREST-47 10 -12 3 S/A-24 12 107 ASTEMPATE PARCOCA ARREST-47 10 -12 3 S/A-24 12 107 ASTEMPATE PARCOCA ARREST-47 10 -12 3 S/A-24 12 107 ASTEMPATE PARCOCA ARREST-47 10 -12 3 S/A-24 12 107 ASTEMPATE PARCOCA ARREST-47 10 -12 3 S/A-24 12 107 ASTEMPATE PARCOCA ARREST-47 10 -12 3 S/A-24 12 107 ASTEMPATE PARCOCA ARREST-47 10 -12 3 S/A-24 12 107 ASTEMPATE PARCOCA ARREST-47 10 -12 3 S/A-24 12 107 ASTEMPATE PARCOCA ARREST-47 10 -12 3 S



35 6.0 x 35.0 0,188 39 6.0 x 39.0 0,188

An SAcultyBrands Company



## **INTERPLAN**

ARCHITECTURE ENGINEERING INTERIOR DESIGN PROJECT MANAGEMENT

604 COURTLAND STREET SUITE 100 ORLANDO, FLORIDA 32804 PH 407.645.5008 FX 407.629.9124

THIS DOCUMENT IS 'NOT FOR CONSTRUCTION UNLESS THE ARCHITECT OR ENGINEER'S SIGNATURE AND SEAL APPEAR BELOW.

STUART ANDERSON, P.E.

## Cobb FSR 4 SE.

3100 SOUTH COBB DRIVE SMYRNA, GEORGIA 30080 South CHICK SAR

FSR# 0810

REVISION SCHEDULE
NO. DATE DESCRIPTION

CONSULTANT PROJECT#	2017.0165
PRINTED FOR	Permit
DATE	10/2017
DRAWN BY	MJ
CHECKED BY	GEG

SHEET SITE LIGHTING

Sheat #: Pole-SSS P1-320