PROJECT DATA:

2012 INTERNATIONAL BUILDING CODE
2012 INTERNATIONAL RESIDENTIAL CODE
2012 INTERNATIONAL RESIDENTIAL CODE
2012 INTERNATIONAL EXISTING BUILDING CODE
2012 INTERNATIONAL MECHANICAL CODE
2019 STATE PLUMBING CODE, AS AMENDED
2011 NATIONAL ELECTRICAL CODE
EBRR UNIFED DEVELOPMENT CODE
EBRR SUBPED DEVELOPMENT CODE
EBRR SUBPINIONEON RESIDIATIONS
EBRR SUBDINISION RESIDIATIONS
EBRR FULDON DAMAGE PREVENTION ORDINANCE

PROPOSED REUSE OF FORMER RESTAURANT SPACE WITH DRIVE THRU ADDITION

BUILDING AREA: EXISTING: 3,285 SQ. FT. ADDITION: 126 SQ. FT. RENOVATED: 3,411 SQ. FT.

OCCUPANCY TYPE: GROUP A-2 - ASSEMBLY CONSTRUCTION TYPE: V - B

FOR TYPE V-B CONSTRUCTION NO FIRE RATINGS ARE REQUIRED.

BASED ON DISTANCE TO THE PROPERTY LINE NO OPENING PROTECTIVES REQUIRED

INTERIOR FINISHES:

EXIT ENCLOSURES AND EXIT PASSAGEWAYS CORRIDORS ROOMS AND EMCLOSED SPACES ALL INTERIOR FINISHES MEET CLASS C FLAME SPREAD REQUIREMENTS

FIRE PROTECTION SYSTEMS:

MEANS OF EGRESS:

OCCUPANCY	FLOOR AREA PER OCC	AREA	OCC. LOAI
KITCHEN, COMMERCIAL	200 GR066	671 S.F.	4
STORAGE/ACCESSORY	300 GR056	704 S.F.	3
RESTROOMS	ACCESSORY	221 S.F.	-
OFFICE	100 GR095	34 S.F.	1
DINING AREA	15 NET	1133 S.F.	76
STANDING/COUNTER	5 NET	169 S.F.	34
TOTAL OCCUPANT LOAD	⊅:		118

CAPACITY OF EGRESS COMPONENTS:

REQUIRED WIDTH BY OCC, LOAD (118) X 0.2 WIDTH FACTOR 29.6' MINMUM CLEAR WIDTH OF DOORS PER BC 1008.1.1 52° PROPOSED WIDTH OF DOORS: 36°

MINIMUM NUMBER OF EXITS PER OCCUPANT LOAD 2 REQUIRED/ 5 PROPOSED

PLUMBING FIXTURE REQUIREMENTS

PER IPC TABLE 403.1
MINIMA NIMBER OF REQUIRED PLIMBING FIXTURES;
MATER CLOSETS; MALE I PER 13 FEMALE I PER 15
LAVATORES: 1 PER 200
DRINNING FOUNTAIN, NOT REQUIRED PER IPC 410.3
(RESTAURANT PROVIDES CUP OF WATER FREE OF CHARGE)
SERVICE SINT I REQUIRED, I MOP BINK REQUIRED
PROVIDING MENS AND WOMENS SINGLE OCCUPANCY TOLLET
AND LAVATORY

GENERAL NOTES:

GENERAL NOTES:

1. ALL MORK SHALL BE COMPLETED IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL CODE ORDINANCES AND DAYS. YESIPY EXISTING.

2. THAN LOCAL CODE ORDINANCES AND DAYS. YESIPY EXISTING.

2. CADITIONS, AND NOTIFY THE ARCHITECT OF ANY DECREPANCES PRIOR TO SUBMITTING A BID AND/OR BEGINNING ANY CONSTRUCTION WORK.

3. ALL MORK WHEN COMPLETED, SHALL COMPORM TO THE AMERICANS WITH DISABILITIES ACT ACCESSIBILITY SUDDELINES.

3. THE CONTRACTOR SHALL NOTIFY THE ARCHITECT OF ANY DISCREPANCIES FOUND BETWEEN THE DRAWINGS AND SPECIFICATIONS FOR RESOLUTION. DIS CONTRACTOR SHALL NOTIFY THE ARCHITECT OF ANY DISCREPANCIES FOUND BETWEEN THE DRAWINGS AND SPECIFICATIONS FOR RESOLUTION. DISCREPANCIES FOUND BETWEEN THE DRAWINGS AND SPECIFICATIONS FOR RESOLUTION. DISCREPANCIES FOUND BETWEEN THE DRAWINGS AND SPECIFICATIONS FOR RESOLUTION. DISCREPANCIES THE DRAWINGS AND SPECIFICATION FOR RESOLUTION. DISCREPANCIES THE DRAWINGS AND SPECIFICATION OF THE JOB STEADY OF THE PROJECT.

5. THE CONTRACTOR SHALL BE RESPONSED ET PORT MAININGS AT THE LODG SITE AND THE JOB STEADY OF THE PROJECT.

6. REFER TO INDIVIDUAL DE PRIOR SHALL IN THE PROJECT OF A RODITIONAL SENERAL NOTES.

7. THE CONTRACTOR SHALL BE RESPONSED ET PORT TOROUGHLY CLEANING THAT SOME PORTION OF THE PROJECT OF ANY THE PROJECT OF THE CONTRACTOR OF A SHALL BE SHALL S

SONIC America's Privella


STORE #6679


6808 SIEGEN LANE BATON ROUGE, LA 70809


PROJ # 1722



MITY MAP - N.T.S.









STORE #6679

6808 SIEGEN LANE BATON ROUGE, LA 70809

PROJ. NO.: 1722

DATE:

TITLE SHEET

SHEET NO.:

60.00

NOTICE OF CO

HEALTH DEPARTMENT:

FIRE DEPARTMENT

- 1. THIS FOOD SERVICE FACLITY IS SERVED BY MUNICIPAL MATER.
 2. THIS FOOD SERVICE FACLITY IS SERVED BY A MUNICIPAL SEVER DISTRICT.
 3. ALL EQUIPMENT AND INSTALLATION SHALL MEET MATIONAL BANTATION FOUNDATION (NSF) STANDARDS

 1. FROVIDE MALL MOUNTED SINGLE SERVICE TOWEL, SOAP DISPENSER AND NALL SKUSH AT ALL HAND WASHING SINKS.

 1. THE BUILDING STRUCTURE. AND GAS LINES SHALL BE CONCEALED WITHIN THE BUILDING STRUCTURE. AND GAS LINES SHALL BE CONCEALED WITHIN STANDING STRUCTURE.

 2. ALL SHELVING OVER WET AREAS (SINK, MOP SINKS, ETC.) SHALL BE NETAL.

- I HE DULLING OVER WET AREAS (SINK, MOP SINKS, ETC.) STRULL JUL METAL. PROVIDE A SPLASH BARRIER AT ALL HAND SINKS WHERE THERE IS LESS THAN 18" HORIZONTAL DISTANCE FROM MORKTABLE OR DRAIN BOARDS