

**1 PLAN**  
 SCALE: 1"=10'


**2 JOINT LEGEND**

- N.I.C. BUTT JOINT - TYPE 1 (RE: 6/C13)
- I.J.-1 ISOLATION JOINT - TYPE 1 (RE: 9/C13)  
 STAR DRILLING AND EPOXY ANCHORING OF SMOOTH DOWELS REQUIRED INTO EXISTING PAVEMENT.
- I.J.-2 ISOLATION JOINT - TYPE 2 (RE: 8/C13)
- C.J.-1 LONGITUDINAL CONSTRUCTION JOINT - TYPE 1 (RE: 2/C13)
- C.J.-2 LONGITUDINAL CONSTRUCTION JOINT - TYPE 2 (RE: 4/C13)
- D.J. CONTRACTION (DUMMY) JOINT (RE: 5/C13)
- E.J. EXPANSION JOINT (RE: 3/C13)  
 (MAX. SPACING 120')
- T.E. THICKENED EDGE (RE: 10/C13)
- N.I.C. SPECIAL REINFORCEMENT: 3 NO. 4 BARS 24" LONG AT 8" O.C. CENTERED, AT END OF DEAD END JOINT OR AT STRUCTURE CORNERS
- N.I.C. IRREGULAR PANELS TO BE REINFORCED WITH NO. 4 BARS @ 12" O.C.E.W. (BARS NOT TO EXTEND THROUGH JOINTS)
- STANDARD DUTY CONCRETE PAVEMENT (5" THICK)(RE: 2/C12)
- HEAVY DUTY CONCRETE PAVEMENT (6" THICK)(RE: 2/C12)

\* ALL PAVEMENT PANELS TO HAVE 6x6xW2.9xW2.9 WELDED WIRE FABRIC (SHEET TYPE ONLY) INSTALLED (W.W.F. NOT TO EXTEND THROUGH JOINTS).

**3 JOINT LAYOUT PLAN NOTES**

1. JOINTS SHALL INCLUDE JOINT SEALANT RESERVOIR AND JOINT SEALANT (RE: 8/9)
2. REINFORCING DOWELS AND BARS TO BE SUPPORTED BY AN APPROVED DEVICE.



JOINT LAYOUT PLAN

THIS DRAWING IS APPROVED FOR CONSTRUCTION.  
 THIS DRAWING IS NOT APPROVED FOR CONSTRUCTION.

DRAWN BY P.A.E.  
 DATE 2/18

REVISION	DATE
CHECKED T.C.D	
BOOK NO. N/A	
JOB NO. 10893	

DWG. NO. 12833  
 SCALE SHOWN

OWNER KERGAN BROTHERS - SONIC DRIVE-IN RESTAURANT  
 PROJECT SONIC DRIVE-IN RESTAURANT #6679  
 6808 SIEGEN LANE  
 BATON ROUGE, LA 70809

SHEET NUMBER  
**8**  
 OF 14

THE LOCATION OF EXISTING UNDERGROUND UTILITIES ARE SHOWN IN AN APPROXIMATE WAY ONLY. THE CONTRACTOR SHALL DETERMINE THE EXACT LOCATION OF ALL EXISTING UTILITIES BEFORE COMMENCING WORK. HE AGREES TO BE FULLY RESPONSIBLE FOR ANY AND ALL DAMAGES WHICH MIGHT BE OCCASIONED BY HIS FAILURE TO EXACTLY LOCATE AND PRESERVE ANY AND ALL UNDERGROUND UTILITIES.



CALL LOUISIANA ONE CALL - JUST DIAL 811  
 LOUISIANA STATE LAW, SECTION R.S. 40:1749.15, REQUIRES EXCAVATORS AND DEMOLISHERS TO NOTIFY A REGIONAL NOTIFICATION CENTER BY TELEPHONE 48 HOURS TO 120 HOURS IN ADVANCE OF ANY EXCAVATION OR DEMOLITION ACTIVITY. THE OWNERS/OPERATORS OF ANY UNDERGROUND FACILITY MUST THEN MARK THE AREA OR PROVIDE INFORMATION THAT WILL ENABLE AN EXCAVATOR OR DEMOLISHER TO DETERMINE THE LOCATION OF UNDERGROUND FACILITIES.

THESE DRAWINGS DO NOT INCLUDE COMPONENTS FOR CONSTRUCTION SAFETY.

SCALE NOTE  
 SCALE BAR SHOWN IS ONE INCH LONG AT FULL SCALE WHEN SCALING DRAWINGS. MEASURE BAR TO DETERMINE IF SCALE SHOWN WILL REQUIRE ADJUSTING.



ONE INCH