

Owner:  
Georgetown County  
716 Prince Street  
Georgetown, SC 29442


SGA ARCHITECTURE  
Pawleys Island / Charleston  
245 Business Center Lane / PO Box 1859  
Pawleys Island, SC 29385  
Phone: 843.237.2421 / Fax: 843.237.1992  
www.sgaarchitecture.com

Civil Consultant:  
**ETS**  
ENGINEERING AND TECHNICAL SERVICES  
38 Northpark Lane  
North Charleston, SC 29405  
Phone: 843.237-3002 Fax: 843.237-2889

MEP Consultant:  
**Charleston Engineering**  
103 B. Wagon Wheel Dr.  
Charleston, SC 29412  
843-762-4342  
Mechanical, Plumbing & Electrical

Structural Consultant:  
**Weatherly**  
144 New Southfield Blvd., Suite 100, North Charleston, SC 29405  
COPYRIGHT 2018 ALL RIGHTS RESERVED  
PRINTED OR ELECTRONIC DRAWINGS AND DOCUMENTATION MAY NOT BE REPRODUCED IN ANY FORM WITHOUT WRITTEN PERMISSION FROM WEATHERLY ENGINEERING.

Irrigation Consultant:



MEMBERS OF THE AMERICAN INSTITUTE OF ARCHITECTS  
COPYRIGHT 2018. ALL RIGHTS RESERVED  
PRINTED OR ELECTRONIC DRAWINGS AND DOCUMENTATION MAY NOT BE REPRODUCED IN ANY FORM WITHOUT WRITTEN PERMISSION FROM SGA ARCHITECTURE

Job Number: 15017 (WE 18-126)  
Date: 03/14/18  
Drawn by: CMW  
Checked by: DWS

Notes:  
**BIDDING DOCUMENTS**

Revisions:

Foundation Sections & Details

S300










**REBAR LAP SPLICES IN REINFORCED MASONRY**

BAR SIZE	REQUIRED LAP
#4 BAR	24" LAP
#5 BAR	30" LAP
#6 BAR	48" LAP
#7 BAR	60" LAP
#8 BAR	90" LAP

**MINIMUM CONCRETE COVER**

CONCRETE CASE AGAINST EARTH	COVER
A. CONCRETE CASE AGAINST EARTH	3" COVER
B. CONCRETE EXPOSED TO EARTH OR WEATHER	2" COVER
C. CONCRETE NOT EXPOSED TO EARTH OR WEATHER	1-1/2" COVER

1. ALL BARS  
2. SLABS THROUGH #18 BARS  
3. BARS SMALLER  
4. SLABS & WALLS #14 AND #18 BARS  
5. BEAMS & COLUMNS (ALL REINFORCEMENT)



**Table 3.1—Dowel size and spacing for round, square, and rectangular dowels (ACI Committee 325 1956)**

Slab depth, in. (mm)	Dowel dimensions <sup>a</sup> , in. (mm)			Dowel spacing center-to-center, in. (mm)		
	Round	Square	Rectangular <sup>b</sup>	Round	Square	Rectangular
5 to 6 (125 to 150)	3/4 x 14 (19 x 350)	3/4 x 14 (19 x 350)	3/8 x 2 x 12 (10 x 50 x 300)	12 (300)	14 (350)	19 (475)
7 to 8 (175 to 200)	1 x 16 (25 x 400)	1 x 16 (25 x 400)	1/2 x 2-1/2 x 12 (12 x 60 x 300)	12 (300)	14 (350)	18 (450)
9 to 11 (225 to 275)	1-1/4 x 18 (30 x 450)	1-1/4 x 18 (30 x 450)	3/4 x 2-1/2 x 12 (19 x 60 x 300)	12 (300)	12 (300)	18 (450)

<sup>a</sup>Total dowel length includes allowance made for joint opening and minor errors in positioning dowels.  
<sup>b</sup>Rectangular plates are typically used in construction joints.  
Notes: Table values based on a maximum joint opening of 0.20 in. (5 mm). Dowels must be carefully aligned and supported during concrete operations. Misaligned dowels cause cracking.

**Table 3.2—Dowel size and spacing for diamond-shaped load plates**

Slab depth, in. (mm)	Diamond load plate dimensions, in. (mm)	Diamond load plate spacing center-to-center, in. (mm)
5 to 6 (125 to 150)	1/4 x 4-1/2 x 4-1/2 (6 x 115 x 115)	18 (450)
7 to 8 (175 to 200)	3/8 x 4-1/2 x 4-1/2 (10 x 115 x 115)	18 (450)
9 to 11 (225 to 275)	3/4 x 4-1/2 x 4-1/2 (19 x 115 x 115)	20 (500)

Notes: Table values based on a maximum joint opening of 0.20 in. (5 mm). The construction tolerances required make it impractical to use diamond-shaped load plates in construction joints.