

PLUMBING FIXTURE SCHEDULE									
MARK	FIXTURE	BRANCH SIZES (IN.)	CW	HW	WASTE	VENT	TRIM	CATALOG NUMBER	NOTES
SS1	SERVICE SINK (TERRAZZO) 24" x 24" x 12" 6" DROP FRONT	3/4"	3/4"	3"	2"		STERN WILLIAMS	HL-1910-LB	CHROME PLATED FAUCET WITH INTEGRAL CHECK VALVES, HOSE, BRACKET AND MOP HANGER.
SS4	SERVICE SINK (TERRAZZO) 24" x 24" x 12" 6" DROP FRONT	3/4"	3/4"	3"	2"		STERN WILLIAMS	HL-1910-LB	CHROME PLATED FAUCET WITH INTEGRAL CHECK VALVES, HOSE, BRACKET AND MOP HANGER.
SS5	SERVICE SINK (TERRAZZO) 32" x 32" x 12" 8" DROP FRONT	3/4"	3/4"	3"	2"		STERN WILLIAMS	HL-1910-LB	CHROME PLATED FAUCET WITH INTEGRAL CHECK VALVES, HOSE, BRACKET, MOP HANGER, LINT BASKET, & S.S. CAP ON ALL SIDES.
SS10	ACORN/VAC MOP SINK (TERRAZZO) 36" x 24" x 14" 8" CORNER DROP FRONT			3"	2"		STERN WILLIAMS	HTS-3024	REDUCED HEIGHT SERIES FOR USE WITH ACORN/VAC PLUMBING SYSTEM.
SS31	SERVICE SINK (TERRAZZO) 24" x 24" x 12" 6" CORNER DROP FRONT	3/4"	3/4"	3"	2"		STERN WILLIAMS	SBC-1700-LB	CHROME PLATED FAUCET WITH INTEGRAL CHECK VALVES, HOSE, BRACKET AND MOP HANGER.
SS32	SERVICE SINK (TERRAZZO) 32" x 32" x 12" 8" CORNER DROP FRONT	3/4"	3/4"	3"	2"		STERN WILLIAMS	SBC-1725-LB	CHROME PLATED FAUCET WITH INTEGRAL CHECK VALVES, HOSE, BRACKET, MOP HANGER, LINT BASKET, & S.S. CAP ON ALL SIDES.
SS33	SERVICE SINK (TERRAZZO) 36" x 24" x 12" 8" CORNER DROP FRONT	3/4"	3/4"	3"	2"		STERN WILLIAMS	HL2100	CHROME PLATED FAUCET WITH INTEGRAL CHECK VALVES, HOSE, BRACKET, MOP HANGER, LINT BASKET, & S.S. CAP ON ALL SIDES.
SS34	SERVICE SINK CAST IRON W/ ENAMEL FINISH WALL MOUNT	3/4"	3/4"	3"	2"		AMERICAN STANDARD	7692.000	CHROME PLATED FAUCET WITH INTEGRAL CHECK VALVES, HOSE, BRACKET, MOP HANGER, LINT BASKET, & S.S. RIM GUARD.
SS35	SERVICE SINK FIBERGLASS FLOOR MOUNT						FAUCET: CHICAGO 891-EZCP		
S1	SINK (LOUNGE) 2-COMPARTMENT STAINLESS STEEL	1/2"	1/2"	2"	1 1/2"		ELKAY JUST	DL-ADA-1829-A-GR	DOUBLE BOWL, DROP-IN, 5 1/2" MAXIMUM DEPTH, 1-HOLE SINGLE HANDLE PULL-OUT FAUCET 2.2 GPM
S2	SINK (PHARMACY) 4-COMPARTMENT STAINLESS STEEL	1/2"	1/2"	2"	1 1/2"		DAYTON BY ELKAY	D-12521	4 HOLES, 2.2 GPM FLOW RESTRICTOR AND AERATOR
S3	SINK (LOUNGE) 2-COMPARTMENT STAINLESS STEEL	1/2"	1/2"	2"	1 1/2"		ELKAY	DL-ADA-1829-A-GR	3 HOLES, DROP IN STYLE, 2.2 GPM FLOW RESTRICTOR, AND AERATOR, 9 1/2" MAXIMUM DEPTH
S4	SINK 1-COMPARTMENT STAINLESS STEEL	1/2"	1/2"	2"	1 1/2"		DAYTON BY ELKAY	D-11719	3 HOLES, 2.2 GPM FLOW RESTRICTOR AND AERATOR
L40	LAVATORY (T)	1/2"	1/2"	1 1/2"	1 1/2"		AMERICAN STANDARD	K-2055	FAUCET: SPEAKMAN SC-3084 CENTERSET FAUCET, GRID STRAINER WITH TAILPIECE, P-TRAP WITH CLEANOUT, STOP VALVES, SS BRAIDED WATER SUPPLIES AND ESCUTCHEONS. PROVIDE THERMOSTATIC MIXING VALVE FOR L41.
L41	LAVATORY	1/2"	1/2"	1 1/2"	1 1/2"		AMERICAN STANDARD	K-2055	CARRIER: JOSAM 17100 (FLOOR MOUNT), WADE W-520 (FLOOR MOUNT) OR JOSAM 17120 (WALL MOUNT). LAVATORY ENCLOSURE: TRUEBRO LAV-SHIELD 2018 L41 ASSE 1070 THERMOSTATIC MIXING VALVE. ZURN ZH9370XL SET TO 105°F.
EW1	EYEWASH	1/2"	1/2"	1 1/2"	1 1/4"		BRADLEY	S19-220	WALL MOUNTED, GALVANIZED STEEL PIPE, CHROME PLATED BRASS VALVE, YELLOW PLASTIC BOWL WITH DUST COVER, 3/4" SS HANDLE. PROVIDE P-TRAP AND TAILPIECE WHERE APPLICABLE ON PLANS.
EW2	EYEWASH	1/2"	1/2"	1 1/2"	1 1/4"		BRADLEY	S19-224-ADA	WALL MOUNTED, GALVANIZED STEEL PIPE, CHROME PLATED BRASS VALVE, YELLOW PLASTIC BOWL WITH DUST COVER, 3/4" SS HANDLE. PROVIDE P-TRAP AND TAILPIECE WHERE APPLICABLE ON PLANS.
PV82	PRESSURE VACUUM BREAKER						WATTS	LF608PQGT	LEAD FREE (NON-HAZARDOUS AMT.) SPHON, ANTI-SPILL VACUUM BREAKER AND INLET AND OUTLET SHUT-OFF VALVES. CONFORM TO ASSE 1056
PV83	PRESSURE VACUUM BREAKER						WATTS	LFN36N1	LEAD FREE BRASS WATER SERVICE VACUUM RELIEF VALVE. OUTLET SHUT-OFF VALVES. CONFORM TO ASSE 1056
PRV	WATER PRESSURE REGULATOR						WATTS	APOLLO 3T.F.262-01 (LF22)	LEAD FREE BRONZE BODY VALVE WITH SHUT-OFF VALVE UP TO 2 1/2". CAST IRON BODY FOR 1/2" OR 3/4". MAXIMUM OPERATING PRESSURE OF 200 PSI. CONFORM TO ASSE 1063
TMV	THERMOSTATIC MIXING VALVE	3/4"	3/4"				WILKINS 500L LAWLER	570	LEAD FREE HEAVY CAST BRONZE BODY VALVE. ROUGH BRONZE FINISH. BIMETAL THERMOSTAT OR THERMAL MOTOR. INTEGRAL CHECK VALVES. LIMIT STOP SET AT 85°F UNLESS NOTED OTHERWISE. MINIMUM FLOW: 1.5 GPM. CONFORM TO ASSE 1017/1070.
TMV2	THERMOSTATIC MIXING VALVE						LEONARD 370-LF LAWLER		LEAD FREE HEAVY CAST BRONZE BODY VALVE. ROUGH BRONZE FINISH. BIMETAL THERMOSTAT OR THERMAL MOTOR. INTEGRAL CHECK VALVES. LIMIT STOP SET AT 85°F UNLESS NOTED OTHERWISE. MINIMUM FLOW: 1.5 GPM. CONFORM TO ASSE 1017/1070.
ETMV	EMERGENCY THERMOSTATIC MIXING VALVE						LEONARD TM-186-5015-LF LAWLER		LEAD FREE HEAVY CAST BRONZE BODY VALVE. ROUGH BRONZE FINISH. BIMETAL THERMOSTAT OR THERMAL MOTOR. INTEGRAL CHECK VALVES. LIMIT STOP SET AT 85°F UNLESS NOTED OTHERWISE. MINIMUM FLOW: 1.0 GPM.
ETMV2	EMERGENCY THERMOSTATIC MIXING VALVE						LEONARD TM-300-POWERS ES150-LF LAWLER		LEAD FREE HEAVY CAST BRONZE BODY VALVE. ROUGH BRONZE FINISH. BIMETAL THERMOSTAT OR THERMAL MOTOR. INTEGRAL CHECK VALVES. LIMIT STOP SET AT 85°F UNLESS NOTED OTHERWISE. MINIMUM FLOW: 2.0 GPM.
HR1	HOSE REEL						REELCRAFT / COOPER	7890-DPL-50578 (800) 444-1134	SELF-RETRACTING OPEN REEL WITH 50' 1/2" ID YELLOW WATER HOSE.
IB8	ICE MAKER BOX						GLY GRAY-IPS	AS9700 SERIES	WHITE PLASTIC BOX AND FACEPLATE. LEAD FREE BOTTOM INLET WATER SUPPLY AND 1/2" x 1/4" COMPRESSION ANGLE STOP VALVE. PROVIDE FIRE RATED BOX WHEN INSTALLED IN FIRE RATED WALL.

TOILET PLUMBING FIXTURE SCHEDULE									
MARK	FIXTURE	BRANCH SIZES (IN.)	CW	HW	WASTE	VENT	TRIM	CATALOG NUMBER	NOTES
WC1	WATER CLOSET (FLOOR MOUNT)	1 1/4"		4"	2"		TOTO	CT705EN ST-2026-A	FLUSH VALVE: TOTO TETL432QCP-WR - 1.28 GPF SENSOR OPERATED SELF GENERATING POWER SYSTEM WITH MANUAL OVERRIDE AND VANDAL RESISTANT SET SCREW ESCUTCHEON AND STOP CAP. ELONGATED SEAT: BEM5 1055SSC, MANLINE ML 1055SC. CAST IRON FLOOR FLANGE: ZURN ZB-294-C14, TYLER 2-25T52, WITH "NO SLEEP" WAX RING AND BRASS ANCHOR BOLTS.
WC2	WATER CLOSET HANDICAPPED (FLOOR MOUNT)	1 1/4"		4"	2"		TOTO	CT706ELN ST-2029-A	FLUSH VALVE: TOTO TETL432QCP-WR - 1.28 GPF SENSOR OPERATED SELF GENERATING POWER SYSTEM WITH MANUAL OVERRIDE AND VANDAL RESISTANT SET SCREW ESCUTCHEON AND STOP CAP. ELONGATED SEAT: BEM5 1055SSC, MANLINE ML 1055SC.
WC3	WATER CLOSET (WALL MOUNT)	1 1/4"		4"	2"		TOTO	CT708E ST-2028-A	FLUSH VALVE: TOTO TETL432QCP-WR - 1.28 GPF SENSOR OPERATED SELF GENERATING POWER SYSTEM WITH MANUAL OVERRIDE AND VANDAL RESISTANT SET SCREW ESCUTCHEON AND STOP CAP. ELONGATED SEAT: BEM5 1055SSC, MANLINE ML 1055SC.
WC4	WATER CLOSET HANDICAPPED (WALL MOUNT)	1 1/4"		4"	2"		TOTO	CT708EA ST-2028-A	FLUSH VALVE: TOTO TETL432QCP-WR - 1.28 GPF SENSOR OPERATED SELF GENERATING POWER SYSTEM WITH MANUAL OVERRIDE AND VANDAL RESISTANT SET SCREW ESCUTCHEON AND STOP CAP. ELONGATED SEAT: BEM5 1055SSC, MANLINE ML 1055SC.
WC30	WATER CLOSET	1/2"		4"	2"		TOTO	CS7744E	1.28 GPF FLUSH TANK W/ LOCKING COVER. ELONGATED SEAT: BEM5 1055SSC, MANLINE ML 1055SC. CAST IRON FLOOR FLANGE: JONESPEC OF 2004-C14, TYLER 2-25T52, WITH "NO SLEEP" WAX RING AND BRASS ANCHOR BOLTS. SUPPLY LINE: STAINLESS STEEL BRAIDED HOSE.
WC31	WATER CLOSET HANDICAPPED	1/2"		4"	2"		TOTO	CS7744EL	1.28 GPF FLUSH TANK W/ LOCKING COVER. ELONGATED SEAT: BEM5 1055SSC, MANLINE ML 1055SC. CAST IRON FLOOR FLANGE: JONESPEC OF 2004-C14, TYLER 2-25T52, WITH "NO SLEEP" WAX RING AND BRASS ANCHOR BOLTS. SUPPLY LINE: STAINLESS STEEL BRAIDED HOSE.
CC1	WATER CLOSET CARRIER DOUBLE HORIZONTAL			4"	2"		JOSAM WADE	1264 1310ND	14 TURN BALL VALVE STOP. ADJUSTABLE COATED CAST IRON SHORT BARREL 4" NO HUB FITTING WITH 2" NO HUB VENT. ABS EXTENSION WITH TEST CAP. CHROME PLATED HARDWARE, NEOPRENE FITTING AND FIXTURE GASKETS, AND HUSKY SD4000 COUPLINGS.
CC1H	CC1 CARRIER WITH HANDICAP HEIGHT OPTION AS INDICATED BY THE FOLLOWING SUFFIXES: JOSAM -35			4"	2"		JOSAM WADE	1264 1310ND	14 TURN BALL VALVE STOP. ADJUSTABLE COATED CAST IRON SHORT BARREL 4" NO HUB FITTING WITH 2" NO HUB VENT. FACTORY-FAPPE 2" NO HUB URINAL CONNECTION, ABS EXTENSION WITH TEST CAP, CHROME PLATED HARDWARE, NEOPRENE FITTING AND FIXTURE GASKETS, AND HUSKY SD4000 COUPLINGS. FLOW DIRECTION (RIGHT OR LEFT) IS FROM SEATED FUTURE USER'S POINT OF REFERENCE.
CC2	WATER CLOSET CARRIER SINGLE HORIZONTAL			4"	2"		JOSAM WADE	1264 1310N-LA	ADJUSTABLE COATED CAST IRON SHORT BARREL 4" NO HUB FITTING WITH 2" NO HUB VENT. FACTORY-FAPPE 2" NO HUB URINAL CONNECTION, ABS EXTENSION WITH TEST CAP, CHROME PLATED HARDWARE, NEOPRENE FITTING AND FIXTURE GASKETS, AND HUSKY SD4000 COUPLINGS. FLOW DIRECTION (RIGHT OR LEFT) IS FROM SEATED FUTURE USER'S POINT OF REFERENCE.
CC2H	CC2 CARRIER WITH HANDICAP HEIGHT OPTION AS INDICATED BY THE FOLLOWING SUFFIXES: JOSAM -35			4"	2"		JOSAM WADE	1264 1310N-LA	ADJUSTABLE COATED CAST IRON SHORT BARREL 4" NO HUB FITTING WITH 2" NO HUB VENT. FACTORY-FAPPE 2" NO HUB URINAL CONNECTION, ABS EXTENSION WITH TEST CAP, CHROME PLATED HARDWARE, NEOPRENE FITTING AND FIXTURE GASKETS, AND HUSKY SD4000 COUPLINGS. FLOW DIRECTION (RIGHT OR LEFT) IS FROM SEATED FUTURE USER'S POINT OF REFERENCE.
CC3	WATER CLOSET CARRIER SINGLE HORIZONTAL			4"	2"		JOSAM WADE	1264 1310N-LA	ADJUSTABLE COATED CAST IRON SHORT BARREL 4" NO HUB FITTING WITH 2" NO HUB VENT. FACTORY-FAPPE 2" NO HUB URINAL CONNECTION, ABS EXTENSION WITH TEST CAP, CHROME PLATED HARDWARE, NEOPRENE FITTING AND FIXTURE GASKETS, AND HUSKY SD4000 COUPLINGS. FLOW DIRECTION (RIGHT OR LEFT) IS FROM SEATED FUTURE USER'S POINT OF REFERENCE.
CC3H	CC3 CARRIER WITH HANDICAP HEIGHT OPTION AS INDICATED BY THE FOLLOWING SUFFIXES: JOSAM -35			4"	2"		JOSAM WADE	1264 1310N-LA	ADJUSTABLE COATED CAST IRON SHORT BARREL 4" NO HUB FITTING WITH 2" NO HUB VENT. FACTORY-FAPPE 2" NO HUB URINAL CONNECTION, ABS EXTENSION WITH TEST CAP, CHROME PLATED HARDWARE, NEOPRENE FITTING AND FIXTURE GASKETS, AND HUSKY SD4000 COUPLINGS. FLOW DIRECTION (RIGHT OR LEFT) IS FROM SEATED FUTURE USER'S POINT OF REFERENCE.
UR1	URINAL	3/4"		2"	1 1/2"		ZURN	Z5728 6590.525	HIGH EFFICIENCY URINAL (HEU) SYSTEM: CHINA URINAL AND 0.125 GPF TURBINE OR BATTERY POWERED, WALL MOUNTED SENSOR OPERATED FLUSH VALVE WITH MANUAL OVERRIDE AND VANDAL RESISTANT SET SCREW ESCUTCHEON AND STOP CAP.
UR2	URINAL HANDICAPPED	3/4"		2"	1 1/2"		TOTO	UT105UJ TEL1UA12MCP	HIGH EFFICIENCY URINAL (HEU) SYSTEM: CHINA URINAL AND 0.125 GPF TURBINE OR BATTERY POWERED, WALL MOUNTED SENSOR OPERATED FLUSH VALVE WITH MANUAL OVERRIDE AND VANDAL RESISTANT SET SCREW ESCUTCHEON AND STOP CAP.
UC1	URINAL CARRIER						JOSAM WADE	17966-UR 430-AM11	FLOOR MOUNTED WITH HANGER AND BEARING PLATES, WELDED FEET, ADJUSTABLE SUPPORTING RODS, STRUCTURAL UPRIGHTS, AND CHROME PLATED TRIM.
L1	LAVATORY	1/2"	1/2"	1 1/2"	1 1/2"		KOHLER AMERICAN STANDARD	K-2055 0355.012	FAUCET: TOTO TETL432QCP-WR - 0.5 GPM SENSOR OPERATED SELF-GENERATING POWER SYSTEM, STANDARD SPOUT, 4" COVER PLATE, GRID STRAINER WITH TAILPIECE, P-TRAP WITH CLEANOUT, STOP VALVES, SS BRAIDED WATER SUPPLIES AND ESCUTCHEONS. PROVIDE THERMOSTATIC MIXING VALVE FOR L41. LAVATORY ENCLOSURE: TRUEBRO LAV-SHIELD 2018 L41 ASSE 1070 THERMOSTATIC MIXING VALVE. ZURN ZH9370XL SET TO 105°F.
L2	LAVATORY	1/2"	1/2"	1 1/2"	1 1/2"		KOHLER AMERICAN STANDARD	K-2055 0355.012	FAUCET: TOTO TETL432QCP-WR - 0.5 GPM SENSOR OPERATED SELF-GENERATING POWER SYSTEM, STANDARD SPOUT, 4" COVER PLATE, GRID STRAINER WITH TAILPIECE, P-TRAP WITH CLEANOUT, STOP VALVES, SS BRAIDED WATER SUPPLIES AND ESCUTCHEONS. PROVIDE THERMOSTATIC MIXING VALVE FOR L41. LAVATORY ENCLOSURE: TRUEBRO LAV-SHIELD 2018 L41 ASSE 1070 THERMOSTATIC MIXING VALVE. ZURN ZH9370XL SET TO 105°F.
L18	LAVATORY DECK 3-STATION RIGHT TRASH	1/2"	1/2"	1 1/2"	1 1/2"		LEVANTINA	Q3303RT	LEVANTINA: WALL MOUNTED, ONCE QUARTZIA DECK. DECK COLOR: SNOWFALL. BOWL: CHINA SHELL CH-6300 UNIVERSAL MOUNT 18"x13" CHINA BOWLS. BOWL: 400-200-224-4-295-228 (1) STOP VALVE, (1) 3/8"x12" BRASS WATER SUPPLY PER FAUCET, TMV NOT REQUIRED.
L19	LAVATORY DECK 3-STATION LEFT TRASH	1/2"	1/2"	1 1/2"	1 1/2"		LEVANTINA	Q3303LT	LEVANTINA: WALL MOUNTED, ONCE QUARTZIA DECK. DECK COLOR: SNOWFALL. BOWL: CHINA SHELL CH-6300 UNIVERSAL MOUNT 18"x13" CHINA BOWLS. BOWL: 400-200-224-4-295-228 (1) STOP VALVE, (1) 3/8"x12" BRASS WATER SUPPLY PER FAUCET, TMV NOT REQUIRED.
L20	LAVATORY DECK 3-STATION RIGHT TRASH	1/2"	1/2"	1 1/2"	1 1/2"		LEVANTINA	Q3303RT	LEVANTINA: WALL MOUNTED, ONCE QUARTZIA DECK. DECK COLOR: SNOWFALL. BOWL: CHINA SHELL CH-6300 UNIVERSAL MOUNT 18"x13" CHINA BOWLS. BOWL: 400-200-224-4-295-228 (1) STOP VALVE, (1) 3/8"x12" BRASS WATER SUPPLY PER FAUCET, TMV NOT REQUIRED.
L21	LAVATORY DECK 3-STATION LEFT TRASH	1/2"	1/2"	1 1/2"	1 1/2"		LEVANTINA	Q3303LT	LEVANTINA: WALL MOUNTED, ONCE QUARTZIA DECK. DECK COLOR: SNOWFALL. BOWL: CHINA SHELL CH-6300 UNIVERSAL MOUNT 18"x13" CHINA BOWLS. BOWL: 400-200-224-4-295-228 (1) STOP VALVE, (1) 3/8"x12" BRASS WATER SUPPLY PER FAUCET, TMV NOT REQUIRED.
L22	LAVATORY DECK 3-STATION LEFT TRASH	1/2"	1/2"	1 1/2"	1 1/2"		LEVANTINA	Q3303LT	LEVANTINA: WALL MOUNTED, ONCE QUARTZIA DECK. DECK COLOR: SNOWFALL. BOWL: CHINA SHELL CH-6300 UNIVERSAL MOUNT 18"x13" CHINA BOWLS. BOWL: 400-200-224-4-295-228 (1) STOP VALVE, (1) 3/8"x12" BRASS WATER SUPPLY PER FAUCET, TMV NOT REQUIRED.
L23	LAVATORY DECK 3-STATION LEFT TRASH	1/2"	1/2"	1 1/2"	1 1/2"		LEVANTINA	Q3303LT	LEVANTINA: WALL MOUNTED, ONCE QUARTZIA DECK. DECK COLOR: SNOWFALL. BOWL: CHINA SHELL CH-6300 UNIVERSAL MOUNT 18"x13" CHINA BOWLS. BOWL: 400-200-224-4-295-228 (1) STOP VALVE, (1) 3/8"x12" BRASS WATER SUPPLY PER FAUCET, TMV NOT REQUIRED.
L24	LAVATORY DECK 2-STATION	1/2"	1/2"	1 1/2"	1 1/2"		LEVANTINA	Q3302	LEVANTINA: WALL MOUNTED, ONCE QUARTZIA DECK. DECK COLOR: SNOWFALL. BOWL: CHINA SHELL CH-6300 UNIVERSAL MOUNT 18"x13" CHINA BOWLS. BOWL: 400-200-224-4-295-228 (1) STOP VALVE, (1) 3/8"x12" BRASS WATER SUPPLY PER FAUCET, TMV NOT REQUIRED.
L25	LAVATORY DECK 2-STATION	1/2"	1/2"	1 1/2"	1 1/2"		LEVANTINA	Q3302	LEVANTINA: WALL MOUNTED, ONCE QUARTZIA DECK. DECK COLOR: SNOWFALL. BOWL: CHINA SHELL CH-6300 UNIVERSAL MOUNT 18"x13" CHINA BOWLS. BOWL: 400-200-224-4-295-228 (1) STOP VALVE, (1) 3/8"x12" BRASS WATER SUPPLY PER FAUCET, TMV NOT REQUIRED.
L26	LAVATORY DECK 2-STATION	1/2"	1/2"	1 1/2"	1 1/2"		LEVANTINA	Q3302T	LEVANTINA: WALL MOUNTED, ONCE QUARTZIA DECK. DECK COLOR: SNOWFALL. BOWL: CHINA SHELL CH-6300 UNIVERSAL MOUNT 18"x13" CHINA BOWLS. BOWL: 400-200-224-4-295-228 (1) STOP VALVE, (1) 3/8"x12" BRASS WATER SUPPLY PER FAUCET, TMV NOT REQUIRED.
L27	LAVATORY DECK 2-STATION	1/2"	1/2"	1 1/2"	1 1/2"		LEVANTINA	Q3302T	LEVANTINA: WALL MOUNTED, ONCE QUARTZIA DECK. DECK COLOR: SNOWFALL. BOWL: CHINA SHELL CH-6300 UNIVERSAL MOUNT 18"x13" CHINA BOWLS. BOWL: 400-200-224-4-295-228 (1) STOP VALVE, (1) 3/8"x12" BRASS WATER SUPPLY PER FAUCET, TMV NOT REQUIRED.
L28	LAVATORY DECK 2-STATION	1/2"	1/2"	1 1/2"	1 1/2"		LEVANTINA	Q3301	LEVANTINA: WALL MOUNTED, ONCE QUARTZIA DECK. DECK COLOR: SNOWFALL. BOWL: CHINA SHELL CH-6300 UNIVERSAL MOUNT 18"x13" CHINA BOWLS. BOWL: 400-200-224-4-295-228 (1) STOP VALVE, (1) 3/8"x12" BRASS WATER SUPPLY PER FAUCET, TMV NOT REQUIRED.
L29	LAVATORY DECK 2-STATION	1/2"	1/2"	1 1/2"	1 1/2"		LEVANTINA	Q3301	LEVANTINA: WALL MOUNTED, ONCE QUARTZIA DECK. DECK COLOR: SNOWFALL. BOWL: CHINA SHELL CH-6300 UNIVERSAL MOUNT 18"x13" CHINA BOWLS. BOWL: 400-200-224-4-295-228 (1) STOP VALVE, (1) 3/8"x12" BRASS WATER SUPPLY PER FAUCET, TMV NOT REQUIRED.
L38	LAVATORY (ADA)	1/2"	1/2"	1 1/2"	1 1/2"		AMERICAN STANDARD	Q321.075	FAUCET: TOTO TETL432QCP-WR - 0.5 GPM SENSOR OPERATED SELF-GENERATING POWER SYSTEM, STANDARD SPOUT, 4" COVER PLATE, GRID STRAINER WITH TAILPIECE, P-TRAP WITH CLEANOUT, STOP VALVES, SS BRAIDED WATER SUPPLIES AND ESCUTCHEONS. PROVIDE THERMOSTATIC MIXING VALVE FOR L38. LAVATORY ENCLOSURE: TRUEBRO LAV-SHIELD 2018 L38 ASSE 1070 THERMOSTATIC MIXING VALVE. ZURN ZH9370XL SET TO 105°F.
L39	LAVATORY (ADA)	1/2"	1/2"	1 1/2"	1 1/2"		AMERICAN STANDARD	Q321.075	FAUCET: TOTO TETL432QCP-WR - 0.5 GPM SENSOR OPERATED SELF-GENERATING POWER SYSTEM, STANDARD SPOUT, 4" COVER PLATE, GRID STRAINER WITH TAILPIECE, P-TRAP WITH CLEANOUT, STOP VALVES, SS BRAIDED WATER SUPPLIES AND ESCUTCHEONS. PROVIDE THERMOSTATIC MIXING VALVE FOR L39. LAVATORY ENCLOSURE: TRUEBRO LAV-SHIELD 2018 L39 ASSE 1070 THERMOSTATIC MIXING VALVE. ZURN ZH9370XL SET TO 105°F.
EW1C1	ELECTRIC WATER COOLER (SINGLE)	1/2"		1 1/2"	1 1/4"		OASIS HALSEY TAYLOR	PG6AC HACBP-Q-ADA	STAINLESS STEEL TOP AND CABINET. FRONT AND SIDE PUSH BARS, LEAD FREE, WATER SAVER BUBBLER WITH FLEXIBLE BUBBLER GUARD (FOR HALSEY TAYLOR - SMARTFLOW BUBBLER KIT), STOP VALVE, 3/8"x1/2" SS BRAIDED WATER SUPPLY, P-TRAP WITH CLEANOUT AND ESCUTCHEON CARRIER. JOSAM 17966-WC, WADE 400-AM11.
EW1C2	ELECTRIC WATER COOLER (SPLIT-LEVEL)	1/2"		1 1/2"	1 1/4"		OASIS HALSEY TAYLOR	PG6ACSL HACBP-SBL-Q-ADA	STAINLESS STEEL TOP AND CABINET. FRONT AND SIDE PUSH BARS, MATCHING UPPER LINT APRON, LEAD FREE, WATER SAVER BUBBLER WITH FLEXIBLE BUBBLER GUARD (FOR HALSEY TAYLOR - SMARTFLOW BUBBLER KIT), STOP VALVE, 3/8"x1/2" SS BRAIDED WATER SUPPLY, P-TRAP WITH CLEANOUT AND ESCUTCHEON CARRIER. JOSAM 17966-WC, WADE 400-AM11.
HB6	HOSE BIBB (FLUSH MOUNTED WALL BOX)	3/4"					ACORN WOODFORD BRADLEY	8151 824 7910	POLISHED FINISH WITH STAINLESS STEEL OR CHROME HUNG BOX, INTEGRAL VACUUM BREAKER, AND LOOSE TEE KEY.

GENERAL INFORMATION (ALL FIXTURES):

- THIS SCHEDULE IS COMPREHENSIVE. ALL MARKS MAY OR MAY NOT BE USED ON THE PLANS.
- SUBSTITUTIONS NOT PERMITTED. REF SPECIFICATIONS FOR APPROVED MANUFACTURERS OF THE FOLLOWING TRIM AND ACCESSORIES:
  - P-TRAP WITH CLEANOUT PUG AND SINK CONTINUOUS WASTES. POLISHED CHROME-PLATED TUBULAR BRASS, 17 GAUGE, WITH BRASS NUTS AND SLIP INSERTS.
  - SS BRAIDED WATER SUPPLY. FLEXIBLE BRAIDED STAINLESS STEEL (SS) OUTER SHEATHING WITH REINFORCED PVC INNER TUBING.
  - STOP VALVES: CHROME PLATED BRASS, QUARTER TURN ANGLE STOP VALVES.

NOTES:


- INSTALL FURNISHED 1/2" X 3/4" STAINLESS STEEL SIMPSON WEDGE-ALL WEDGE ANCHORS FOR ALL FIXTURE CARRIERS.
- INSTALL FURNISHED THERMOSTATIC MIXING VALVE.
- REFERENCE ARCHITECTURAL DRAWINGS FOR EW22 ORIENTATION.
- COORDINATE WATER ROUGH-IN HEIGHT FROM MANUFACTURER'S INSTALLATION INSTRUCTIONS WITH GRAB BAR LOCATION. REF ARCH.
- USE SAME MANUFACTURER FOR UR1 AND UR2.

GENERAL INFORMATION (ALL FIXTURES):

- THIS SCHEDULE IS COMPREHENSIVE. ALL MARKS MAY OR MAY NOT BE USED ON THE PLANS.
- SUBSTITUTIONS NOT PERMITTED. REF SPECIFICATIONS FOR APPROVED MANUFACTURERS OF THE FOLLOWING TRIM AND ACCESSORIES:
  - P-TRAP WITH CLEANOUT PUG AND SINK CONTINUOUS WASTES. POLISHED CHROME-PLATED TUBULAR BRASS, 17 GAUGE, WITH BRASS NUTS AND SLIP INSERTS.
  - SS BRAIDED WATER SUPPLY. FLEXIBLE BRAIDED STAINLESS STEEL (SS) OUTER SHEATHING WITH REINFORCED PVC INNER TUBING.
  - STOP VALVES: CHROME PLATED BRASS, QUARTER TURN ANGLE STOP VALVES.

NOTES:

- INSTALL FURNISHED 3/8" AFF TO TOP OF HEAD SPRAY.
- INSTALL MOP SINK FAUCET AT 32" AFF AND LOCATE TWO MOP HANGER BRACKETS SIDE BY SIDE NEAR MOP SINK.
- INSTALL FURNISHED TMV UNLESS REVISED WITH TEMPERED WATER OR NOTED OTHERWISE ON PLUMBING DRAWINGS. SET AT 120° F.
- TRIM WITH OFFSET TAILPIECE, 58" ARMAFLEX INSULATION ON EXPOSED HOT WATER AND DRAIN LINES. HOLD ALL EXPOSED PIPING HIGH AS POSSIBLE.
- REFER TO OWNER PROVIDED EQUIPMENT INFORMATION FOR ACTUAL ROUGH-IN HEIGHT REQUIREMENTS.
- INSTALL FURNISHED THERMOSTATIC MIXING VALVE.
- INSTALL FURNISHED 1/2" X 2 1/2" STAINLESS STEEL SIMPSON WEDGE-ALL ANCHORS FOR ALL FIXTURES.
- CONTRACTOR TO COORDINATE THE REQUIRED CARRIER PRIOR TO ORDERING.



RETAIL DESIGN COLLABORATIVE

143 SISKIYOU

1101 SISKIYOU BLVD  
SUITE 100  
GORDONSVILLE, VA 22983  
TEL: 800-833-3333  
WWW.R2DESIGN.COM

STIPULATION FOR THE CONSULTANTS: THE CONSULTANTS SHALL NOT BE RESPONSIBLE FOR THE ACCURACY OF THE INFORMATION PROVIDED BY THE CLIENT OR FOR THE ACCURACY OF THE INFORMATION PROVIDED BY THE CLIENT'S REPRESENTATIVES. THE CONSULTANTS SHALL NOT BE RESPONSIBLE FOR THE ACCURACY OF THE INFORMATION PROVIDED BY THE CLIENT'S REPRESENTATIVES. THE CONSULTANTS SHALL NOT BE RESPONSIBLE FOR THE ACCURACY OF THE INFORMATION PROVIDED BY THE CLIENT'S REPRESENTATIVES.

CONSULTANTS: **R**