




FEATURES & SPECIFICATIONS

INTERLOCK CASE - Available for one replacement conventional and fluorescent high bay systems. Applications include...
CONSTRUCTION - Epoxy resin encapsulation from skin designed to prevent moisture migration...
OPTICS - 100% clear polycarbonate lenses available to meet both horizontal and vertical light requirements...
ELECTRICAL - 1-10, 20, 40, 80, 160, 320, 640, 1280, 2560, 5120, 10240, 20480, 40960, 81920 lumens...
WIRELESS NETWORKING - 3500m² Wireless technology creates a mesh network to create...
INSTALLATION - Suitable for suspension by rods, cable, surface-mounting brackets...
LED9000S - CRI > 90 and CRI > 95 available...
Dimming - DALI, 0-10V, 1-10V, 0-100% dimming...
WARRANTY - 5-year limited warranty...
Notes: Actual performance may differ as a result of real-world environment and installation. All values are based on typical values... Specifications subject to change without notice.

Length	Width	Height
120"	48"	12"
120"	48"	18"
120"	48"	24"
120"	48"	30"
120"	48"	36"
120"	48"	42"
120"	48"	48"
120"	48"	54"
120"	48"	60"
120"	48"	66"
120"	48"	72"
120"	48"	78"
120"	48"	84"
120"	48"	90"
120"	48"	96"
120"	48"	102"
120"	48"	108"
120"	48"	114"
120"	48"	120"

IBL LED High Bay

FIXTURE "B"



Series	Length	Width	Height	Operating mode	Beam Spread	Beam Diameter	Beam Angle	Beam Diameter @ 10m	Beam Diameter @ 20m	Beam Diameter @ 30m	Beam Diameter @ 40m	Beam Diameter @ 50m	Beam Diameter @ 60m	Beam Diameter @ 70m	Beam Diameter @ 80m	Beam Diameter @ 90m	Beam Diameter @ 100m
120"	120"	48"	12"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	18"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	24"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	30"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	36"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	42"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	48"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	54"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	60"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	66"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	72"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	78"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	84"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	90"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	96"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	102"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	108"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	114"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	120"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"

IBL LED High Bay

FIXTURE "B"

Lead times will vary depending on options selected. Consult with your sales representative. Example: IBL 150 WD 120 2700

Series	Length	Width	Height	Operating mode	Beam Spread	Beam Diameter	Beam Angle	Beam Diameter @ 10m	Beam Diameter @ 20m	Beam Diameter @ 30m	Beam Diameter @ 40m	Beam Diameter @ 50m	Beam Diameter @ 60m	Beam Diameter @ 70m	Beam Diameter @ 80m	Beam Diameter @ 90m	Beam Diameter @ 100m
120"	120"	48"	12"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	18"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	24"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	30"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	36"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	42"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	48"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	54"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	60"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	66"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	72"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	78"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	84"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	90"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	96"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	102"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	108"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	114"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	120"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"

Series	Length	Width	Height	Operating mode	Beam Spread	Beam Diameter	Beam Angle	Beam Diameter @ 10m	Beam Diameter @ 20m	Beam Diameter @ 30m	Beam Diameter @ 40m	Beam Diameter @ 50m	Beam Diameter @ 60m	Beam Diameter @ 70m	Beam Diameter @ 80m	Beam Diameter @ 90m	Beam Diameter @ 100m
120"	120"	48"	12"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	18"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	24"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	30"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	36"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	42"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	48"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	54"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	60"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	66"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	72"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	78"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	84"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	90"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	96"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	102"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	108"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	114"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	120"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"

Series	Length	Width	Height	Operating mode	Beam Spread	Beam Diameter	Beam Angle	Beam Diameter @ 10m	Beam Diameter @ 20m	Beam Diameter @ 30m	Beam Diameter @ 40m	Beam Diameter @ 50m	Beam Diameter @ 60m	Beam Diameter @ 70m	Beam Diameter @ 80m	Beam Diameter @ 90m	Beam Diameter @ 100m
120"	120"	48"	12"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	18"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	24"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	30"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	36"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	42"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	48"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	54"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	60"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	66"	100%	120°	120"	120°	120"	240"	360"	480"	600"	720"	840"	960"	1080"	1200"
120"	120"	48"	72"	100%	120°	120"	120°	12									