IMP - Integrated Modular Plug

- The integrated modular plug (IMP) option allows the installer to plug and play a multitude of accessories.
- Load sets connect quickly to any fixture with IMP option.
- IMP accessories include occupancy sensors, photocells, 3- point mixes.

IMP receptacle sensors	
CSYIMSMP	Straight plug, 120V
CSUIMSMP	Twist-lock, 120V
CSYIMHMP	Straight plug, 277V
CSYIMHRP	Twist-lock, 277V
CSDIMHMP	Twist-lock, 347V
CSDIMHRP	6003 SERIES photocontrol, twist-lock
CSDTMHMP	Twist-lock, 480V

IMP receptacle cover	
MSIMNP	Hole cover
MSIS600IMP	360° sensor



Notes
1 Cord set is rated for fixture operation, 40 pounds per load, or less.

RRL - RELOC®-Ready Luminaire

- RRL connectors can be used with Quick-Flex®, Modern-Tech and OneFlex® systems.
- Load side of connector factory installed to luminaire.
- 4-pole-stacking connector with push-in terminations allows for simple installation.
- Twist-lock design on both halves meets UL/CSA requirements.
- Tapping contact design allows safe disconnect under load.



Ordering Information Lead times will vary depending on options selected. Consult with your sales representative. **Example:** IBL4

Model	Primary configurations			
IBL	RELOC®-ready luminaire	A	Hot conductor wired to position #1 (phase A)	A1	Hot conductor wired to position #1 (phase A), hot conductor #2 wired to position #2 (phase B)*
		B	Hot conductor wired to position #2 (phase B)	A1R	Hot conductor wired to position #1 (phase A), hot conductor #2 wired to position #2 (phase B), inverter conductor wired to position #3 (phase C)**
		C	Hot conductor wired to position #3 (phase C)*	C12S	Hot conductor in position #1 (phase A), low voltage conductor #1 in position #2 low voltage conductor #2 in position #3 **
		XR	Unfiltered hot conductor wired to position #4 (phase A), filtered hot conductor wired to position #7 (phase B)		

Compatible RELOC® Cables for Industrial Luminaires (shipped and ordered separately)



Notes
1 C, RRL, and C12S options are not used with Quick-Flex OCS, OCU, OPT, and OD.
2 RRL and RRC-connected fixtures should disconnect from power before unplugging the OD, or fixture will go into discharge mode.
3 C12S option is used with the Quick-Flex OCS, OCU, PT, and DC to 3-PIN SMALL applications.

OPTIONS AND ACCESSORIES

The I-BEAM LED fixture offers numerous options for almost every industrial and spatial component, including a long list of field-installable accessories.



REFLECTORS
Wide distribution is fanned with 99% reflective white paint. Narrow distribution is fanned with Alanod® 5080®.



INTEGRATED ELECTRICAL OPTIONS
Channel sized to accept emergency components, surge protector, fusing and redundant sensors.



WIRE GUARD (external)
Field- or factory-installed. Protects light engine from impact. Mounting hardware included.

Factory-installed option:
WGE

Field-installed options:
WGBL
WGBL-66



DIFFUSER
Field- or factory-installed. Available in semi-diffuse acrylic. Mounting hardware included

Factory-installed options:
DFUSR
DFUSR-SDTOPS

Field-installed options:
DFUSRL-SDTOPS
DFUSRL-66-SDTOPS



EMBEDDED OCCUPANCY SENSOR
Factory-installed Sensor Switch® SBT-SDT-10 (MOS.10) or SBT-SDT-360 (MOS.360) pictured in the channel. Lower velocity models are thin risk of sensor damage compared to non-embedded sensors. Recommended mounting height for MOS.360 is over 15' and MOS.10 is under 15'.

Factory-installed options:
SBT-SDT-10
SBT-SDT-360



PENDANT MONOPOINT BRACKET
Accepts ¾" rigid conduit for single-point mounting. The bracket can be adjusted to help counterbalance fixture to offset weight customer has or need to add.

Order as:
IBLPMP
IBLPMPWB
IBLPMPBA
IBLPMPWBBA



SURFACE MOUNT BRACKET
Rapidly attaches I-BEAM LED to a hard ceiling. Can be placed anywhere along fixture.

Order as:
IBLSM Look for use in ambient temperatures exceeding 35°F (35°C), or on the 40L or 60L.



HANGERS
Several lengths of wrought-cross and chains available, even or adjust V-hooks.

Order as:
IBLHC12FT4LCS
IBLHMP
For others, see accessories on page 1.



CORD SETS
Available in several lengths with or without molded plug. White is standard.

For available options, see ordering information on page 1.



INTEGRATED MODULAR PLUG (IMP)
Must be factory-installed and allows for field installation of various modular accessories including motions, inverse sensors, photocells and [illegible] 3-point™ relays. Fixture must be ordered [illegible] option. Requires IMP power cord to operate fully.

FEATURES & SPECIFICATIONS

INTENDED USE — The 6" Wafer-Thin LED recessed downlight with remote driver box combines high quality light output and efficiency while eliminating the pot light housing for cost-conscious affordability. This innovative wafer-slim Type IC design allows easy installation for new construction or remodel from below the ceiling, without the requirement of a pot light housing. The LED module maintains at least 70% light output for 35,000 hours. These LED Wafer downlights are intended for closets, attics, hallways, bathrooms, kitchens, basements, soffits, entryways, porches, garages, stairwells, corridors, nursing/retirement homes, condos, dormitories, apartments, and any other small areas.

CONSTRUCTION — Ideal for shallow ceiling plenum since a pot light housing is NOT required. IC rated driver and fixture - approved for direct contact with insulation. Aluminum die-cast outer frame. Durable, powder coat paint to prevent rust. Round fixture with integral edge-lit LEDs. Steel spring clip for easy installation. Fixtures rated cable connector to connect from module to remote driver box. Insulated driver integrated inside steel remote box with four 7/8" knockouts with slots for support. Suitable for pulling wires with the 12 cable-tech wiring compartment to accommodate up to (6) 14 gauge insulated conductors, or (6) 12 gauge insulated conductors, making the Wafer LED Downlights much easier to wire in a 2in2 (not splice ground) daisy chain applications and connector friendly.

PATENT PENDING.

INSTALLATION — Ideal for shallow ceiling plenums, no housing required. Steel spring clip for easy installation. 6" cut-out template is provided to ensure a correct sized hole to cut into ceiling for proper installation of the trim. Size of hole should not exceed 6 1/4 inches for this product. Suitable for installation in t-grid and drop-ceiling applications. 2" plenum space required for installation of the remote-driver box.

OPTICS — Wafer-Thin downlight edge-lit LED technology uses light guided plate to distribute light. Polycarbonate lens provides even illumination throughout the space. Utilized 2700K, 3000K, 3500K, 4000K, and 5000K color temperature LEDs.

ELECTRICAL — Connect directly to 120V power supply via provided UL recognized driver. High efficient driver with power factor > 0.9, Ambient operating temperature -40°F(-40°C) to +104°F (+40°C). Dimming down to 10% (See page 2 for recommended dimmers). Standard input wattage is 13W, 19 lumens per watt. Replaces 35W incandescent for 800 lumens and 100W incandescent for 1520 lumens.

LISTINGS — CSA certified to US and Canadian safety standards. ENERGY STAR® certified product. Wet location. Air Tight certified in accordance with ASTM E283-2004. IC Rated.

WARRANTY — 5-year limited warranty. Complete warranty terms located at: www.acuitybrands.com/CustomerResources/Terms_and_conditions.asp

Note: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

Wafer LED Recessed Downlight

WF6

6" LED Module

IC/Non-IC

New Construction/Remodel



Matte White | Brushed Nickel | Oil-rubbed Bronze



All dimensions are inches (centimeters) unless otherwise indicated.

Ordering Information Fee sources: lead times, configure product using **standard options (shown in bold).** **Example:** WF6 LED 30K MVW

WF6				
Series	Lamp	CCT/CRI/90 Luminaire		Finish
WF6 6" wafer-thin LED downlight	LED LED	27K*	2700K/80CRI/15,898*/100LM	MVW Matte white
		30K	3000K/80CRI/19,067/120LM	MB Matte black
		35K*	3500K/80CRI/18,488*/110LM	BN Brushed nickel
		40K	4000K/80CRI/23,698/120LM	ORB Oil-rubbed bronze
		50K*	5000K/80CRI/14,698*/120LM	
	LL LED Low Lumen LED	27K	2700K/80CRI/12,750*/90LM	
		30K	3000K/80CRI/12,698/88LM	
		35K*	3500K/80CRI/12,698/90LM	
		40K	4000K/80CRI/12,698/85LM	
		50K*	5000K/80CRI/12,698/90LM	

Accessories: Order as separate catalog number.	
WF6 FAN RO12	6" new construction pan, retail pack of 12
WF6 IC	Remodel Joist Bar
WF6EXC10	10' FT4 cable
WF6EXC20	20' FT4 cable

WF6_Pan

Remodel Joist Bar

Extension Cable

Notes
1 Cable is required for fixture operation.
2 Only remodel joist bar for drywall applications.

PHOTOMETRICS

Distribution Curve	Distribution Data	Output Data	Coefficient of Utilization	Illuminance Data at 30" Above Floor for a Single Luminaire

WF6 LED27K, 2700 K LEDs, input watts: 13.7, delivered lumens: 1069, LM/W=78, test no. ISF 30021



| Axial Candlepower | | | |