FIXTURE TYPE "W"

LITHONIA LIGHTING

FEATURES & SPECIFICATIONS

INTENDED USE — LBL provides a digital lighting platform to deliver general ambient lighting for surface-mount applications. Light engine delivers long life and excellent color performance, providing quality, low-maintenance light installation.

CONSTRUCTION — Metal parts are die formed from cold-rolled steel. Prismatic diffuser is 3003H alloy, with specially welded luminous ends. Continuous side flanges on fixture body provide light trap and continuous diffuser support to prevent differential sagging and simplify maintenance.

Finish: Five-stage zinc phosphate pretreatment ensures superior paint adhesion and rust resistance.

Painted parts finished with high-gloss, high-reflectivity baked white polyester enamel (min 80% RGL).

OPTICS — Formed prismatic diffuser with linear side prisms and highly transmissive overlay maximizes lamp image and provides high-angle brightness control. Luminous end plates soften appearance for improved aesthetics.

ELECTRICAL — Long-life LEDs, coupled with high-efficiency drivers, provide extended service life. LBL is rated to deliver L70 performance at 36,000 hours.

LISTINGS — cULus certified to U.S. and Canadian standards. Damp listed.

DesignLights Consortium® (DLC) qualified product. Not all versions of this product may be DLC qualified. Please check the DLC Qualified Products List at www.designlights.org/QPL to confirm which versions are qualified.

WARRANTY — 5-year limited warranty. Complete warranty terms located at www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx

Note: Specifications subject to change without notice.

Order:

Type:

Contractor Select

LED Wraparound

2' and 4'

LED

DLC

Specifications

Length: 24-9/16 (624) / 48-7/16 (1230)

Width: 10-3/8 (264)

Depth: 2-3/4 (70)



All dimensions are inches (centimeters) unless otherwise indicated.

MOUNTING DATA

For most or new installation, surface or stem mounting. Stem mounting not available on 1LB unit.

Individual installation —

Two single stems hangers required.

Row installation —

One hanger per fixture plus one row required.



Catalog Number	UPC	Description	Lumens	Color Temperature	Color Type	Voltage	Mounting	Pallet	Standard carton qty
LBL2 L835	793572472664	2' LED Wraparound	2,000	3500K	Patterned 612 acrylic	120-277	36	112	1
LBL2 L840	793572472695	2' LED Wraparound	2,000	4000K	Patterned 612 acrylic	120-277	36	112	1
LBL2 L850	793572472701	2' LED Wraparound	2,000	5000K	Patterned 612 acrylic	120-277	36	112	1
LBL4 L835	793572472732	4' LED Wraparound	4,000	3500K	Patterned 612 acrylic	120-277	16	56	1
LBL4 L840	793572472763	4' LED Wraparound	4,000	4000K	Patterned 612 acrylic	120-277	16	56	1
LBL4 L850	793572472794	4' LED Wraparound	4,000	5000K	Patterned 612 acrylic	120-277	16	56	1

Notes:
1. MCP option not available.
2. Non-standard pallet and overhanging box boxes apply. Map drawn to confirm or call for LTL.

CONSTRUCTION DETAILS / LED

LED-WRAPWP0807

FIXTURE TYPE "W"

LBL LED Wraparound

PHOTOMETRICS

LBL2 LP835, 2010.5 delivered lumens, test no. LTL22712, tested in accordance to IESNA LM-79.



CP Summary

	0°	90°
0°	796	796
5°	791	796
15°	758	763
25°	676	685
35°	555	557
45°	395	406
55°	240	276
65°	123	186
75°	57	138
85°	23	92
90	3	74

Coefficients of Utilization

rcr	pf	80%	70%	50%
	pw	70%50%30%	50%30%10%	50%30%10%
RCR	1	116 116 116	112 112 112	105 105 105
	2	106 102 98	98 95 91	92 89 86
	3	97 90 83	87 81 76	82 77 73
	4	90 80 72	77 70 65	73 67 62
	5	83 71 63	69 62 56	65 59 54
	6	76 64 56	63 55 49	59 53 47
	7	71 58 50	57 49 43	54 47 42
	8	66 53 45	52 44 39	49 43 38
	9	62 49 41	48 40 35	46 39 34
	10	58 45 37	44 37 32	42 35 31

Zonal Lumen Summary

Zone	Lumens	% Lamp	% Fixture
0° - 30°	661	29.9	29.9
0° - 40°	947	42.1	42.1
0° - 60°	1472	73.2	73.2
0° - 90°	1773	88.2	88.2
90° - 120°	120	6.0	6.0
90° - 130°	156	7.8	7.8
90° - 150°	211	10.5	10.5
90° - 180°	236	11.8	11.8
0° - 180°	2010	100.0	100.0

LBL4 LP835, 4056.9 delivered lumens, test no. LTL23675, tested in accordance to IESNA LM-79.



CP Summary

	0°	90°
0°	1620	1620
5°	1606	1606
15°	1541	1535
25°	1389	1384
35°	1132	1128
45°	811	818
55°	509	544
65°	295	358
75°	155	262
85°	51	174
90	8	140

Coefficients of Utilization

rcr	pf	80%	70%	50%
	pw	70%50%30%	50%30%10%	50%30%10%
RCR	1	119 119 119	112 112 112	105 105 105
	2	107 102 98	99 95 92	92 89 87
	3	98 90 84	87 81 77	82 77 73
	4	90 80 72	78 71 65	73 67 62
	5	83 72 64	70 62 56	66 59 54
	6	77 65 56	63 55 49	60 53 48
	7	71 59 50	57 49 44	54 47 42
	8	66 53 45	52 44 39	50 43 38
	9	62 49 41	48 40 35	46 39 34
	10	58 45 37	44 37 32	42 38 31

Zonal Lumen Summary

Zone	Lumens	% Lamp	% Fixture
0° - 30°	1223	30.2	30.2
0° - 40°	1928	47.6	47.6
0° - 60°	2995	73.9	73.9
0° - 90°	3695	91.7	91.7
90° - 120°	235	5.8	5.8
90° - 130°	303	7.5	7.5
90° - 150°	401	9.9	9.9
90° - 180°	456	11.3	11.3
0° - 180°	4051	100.0	100.0

LITHONIA LIGHTING

Architectural Products Company

LBL Wraparound

1000 Lithonia Way Conyers, GA 30012 Phone: 800-705-7700 Fax: 770-929-5000 www.lithonia.com © 2015-2016 Acuity Brands Lighting, Inc. All rights reserved. Rev. 12/08/16

FIXTURE TYPE "W"

Verizon 87%

Home / Lighting & Ceiling Fans / Commercial Lighting / Wraparound Lights

Model # LBL 4 Internet #203638087 Store SKU # 1000611886



Lithonia Lighting

4 ft. 41-Watt White Integrated LED Low Profile Wraparound Flushmount

★★★★ (336) Write a Review Questions & Answers (130)

- Integrated LEDs produce 4000 lumens of light
- Bright white (4000K) color temperature
- Provides 50,000 hours of maintenance-free operation

$109.00 /each

Choose Your Options

Product Depth (in.)

48

Actual Color Temperature (K)

4000

Package Quantity

1

Add to Cart Print

FIXTURE TYPE "P"

Verizon

Sea Gull Painted Shade Pendants LED Antique

Today $112.60

Details & Specs Customer Reviews Q & A Tips & Inspiration Shipping & Returns

ITEM#: 18106855

The Sea Gull Lighting Painted Shade Pendants light indoor pendant in antique brushed copper enhances the beauty of your home with ample light and style to match today's trends. This Painted Shade pendant collection by Sea Gull Lighting features steel construction and is available in seven outer colors including Blacksmith, Painted Brushed Stainless, Emerald Green, Red Painted Antique Brushed Copper any all with a White interior. Inspired by classic farmhouse light, they use globe shades and bulbs to increase light output and a finish look. 54-inch cut cord is included for customizing the installation. All of these pendants easily convert to LED by purchasing replacement lamps sold separately.

- Lighting Type: Pendant
- Product Features: UL Listed
- Material: Steel
- Lighting Style: Transitional
- Dimensions: 15.75inches in diameter,8.25 inches high

Seagull lighting- painted shade Pendant, led 6519 with metal downrods.

Feature: English (English)

Style	Transitional
Material	Metal, Steel
Type	Globe
Finish	Antique
Light Bulb Type	LED
Lighting Style	Transitional
Lighting Type	Pendant Lighting
Product Features	UL Listed
Dimensions	15 3/4 inches in diameter,8 1/4 inches high
Warranty	5 year Limited Manufacturer
Model Number	6519913-63
Country of Origin	China

Verizon 8:00 AM 100%

acuitybrandslighting.com

LITHONIA LIGHTING

Catalog

FIXTURE TYPE "UC"

Hard wired, at closets provide 24 " with door switch

Type

Indoor General Purpose

UCEL LED Linkable Cabinet Light

Linkable



FEATURES & SPECIFICATIONS

INTENDED USE

Provides task or accent lighting in commercial, retail, hospitality and residential applications. Ideal for use under and over cabinets, display cases, task lighting, office lighting, coves and utility/work areas.

CONSTRUCTION

Low profile design, with on/off rocker switch. Can be direct wired or powered by 5' cord and plug (not included, see accessories). Connect up to 334 watts of fixtures with 15" connector cord or 7/8" lead row connector (included).

Rugged post-painted low-profile steel housing with white finish. Acrylic white diffuser provides soft widespread illumination with zip-lock design for easy installation, cleaning, and superior retention.

ELECTRICAL

Long-life LEDs, coupled with a high-efficiency driver, provide extended service life. Fixture is rated to deliver L70 performance at 50,000 hours and operates at 120 volts, 60Hz. Minimum starting temp -20F. Can direct-wire through rear access plate/knockout by utilizing the included Romex connector, or by utilizing the optional UCD JB Junction/Splice box (sold separately).

Works with most standard incandescent dimmers (see list of approved dimmers).

INSTALLATION

All mounting hardware included.

LISTINGS

UL listed to US and Canadian safety standards. ENERGY STAR® certified product (3000K and 4000K only) and Title 24 qualified. Listed for damp locations.

WARRANTY

5-year limited warranty. Complete warranty terms located at: www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx

NOTE: Actual performance may differ as a result of end-user environment and application.
All values are design or typical values, measured under laboratory conditions at 25 °C.
Specifications subject to change without notice.

SPECIFICATIONS	1	2	3	4
Lumens (3000K):	368	742	1162	1603
Watts (3000K):	5.8	10.2	14.8	19.5
Lumens per watt:	67	73	79	82
Length:	12 (30.5)	24 (61)	36 (91.4)	48 (121.9)

Order Plans @ WWW.LDIline.com

ARCHITECT'S STAMP

STATE OF GEORGIA · GORDON M. SMITH · 7575 · REGISTERED ARCHITECT

SIGNATURE REQUIRED

SMITH DESIGN GROUP, INC.
200 WEST DALTON STREET
LA GRANGE GEORGIA 30240
706-882-5511 www.SDGarch.net

REVISIONS

	DATE	DESCRIPTION

PROJECT:

VERNON ROAD FIRE STATION

VERNON ROAD
LAGRANGE GEORGIA

TITLE:

LIGHTING FIXTURE CUT-SHEETS

MODIFIED DATE:

ISSUED DATE: FOR BID AND PERMIT
07 MAY 2018

JOB NO:
1731

SHEET:
E-15