SECTION 1 — GENERAL CONDITIONS AND STATEMENTS

A. THESE NOTES SHALL APPLY UNLESS OTHERWISE INDICATED BY DRAWINGS OR SPECIFICATIONS.

B. STRUCTURAL DRAWINGS INDICATE TYPICAL AND CERTAIN SPECIFIC CONDITIONS ONLY. SHOP DRAWINGS SHALL DETAIL ALL CONDITIONS IN ACCORDANCE WITH SPECIFIED STANDARDS AND THE SPECIFIC REQUIREMENTS OF THIS PROJECT AS INDICATED ON THE DRAWINGS.

C. THE USE OR REPRODUCTIONS OF THESE CONTRACT DRAWINGS BY ANY CONTRACTOR, SUBCONTRACTOR, ERECTOR, FABRICATOR, OR MATERIAL SUPPLIER IN LIEU OF PREPARATION OF SHOP DRAWINGS SIGNIFIES HIS ACCEPTANCE OF ALL INFORMATION SHOWN HEREON AS CORRECT, AND OBLIGATES HIMSELF TO ANY JOB EXPENSE, REAL OR IMPLIED, ARISING DUE TO ANY ERRORS THAT MAY OCCUR HEREON.

D. THE STRUCTURE SHOWN ON THESE DRAWINGS IS STRUCTURALLY SOUND ONLY IN ITS COMPLETED FORM. THE CONTRACTOR SHALL TEMPORARILY BRACE ALL EARTH, FORMS, CONCRETE, STEEL, WOOD, MASONRY, TO RESIST GRAVITY, EARTH, WIND, SEISMIC AND CONSTRUCTION LOADS DURING CONSTRUCTION.

E. WHERE A DETAIL, TYPICAL DETAIL, SECTION, TYPICAL SECTION OR AS NOTED IS SHOWN FOR ONE CONDITION, IT SHALL APPLY FOR ALL LIKE OR SIMILAR CONDITIONS UNLESS OTHERWISE NOTED. IF THERE ARE QUESTIONS REGARDING THE APPLICABILITY OF A DETAIL, TYPICAL DETAIL, SECTION, TYPICAL SECTION, OR AN AS NOTED NOTE, CONTACT THE ARCHITECT IN WRITING REQUESTING A CLARIFICATION. THE CONTRACTOR SHALL NOT BE RELIEVED OF THE RESPONSIBILITY OF SUPPLYING AND INSTALLING REQUIRED ITEMS OR PERFORMING OTHER REQUIRED WORK DUE TO NOT UNDERSTANDING THE REQUIRED SCOPE OF WORK OR DUE TO ANY OTHER MISINTERPRETATION OF THE PROJECT DRAWINGS.

F. THESE STRUCTURAL DRAWINGS HAVE BEEN PREPARED IN ACCORDANCE WITH THE 2012 INTERNATIONAL BUILDING CODE, WITH CURRENT GEORGIA AMENDMENTS.

G. DESIGN LOADS:

DESIGN LIVE LOADS:	DESIGN COLLATERAL DEAD LOAD:
ROOF: 20 PSF (REDUCIBLE BASED ON TRIBUTARY AREA PER IBC)	ROOF: 7.0 PSF (METAL BUILDING) PLUS STRUCTURE WEIGHT
	ENTRY ROOF: 20 PSF (TOTAL)
FLOOR: 40 PSF+10 PSF PARTITION	FLOOR: 25 PSF

SNOW LOADS:

GROUND SNOW LOAD:	Pg =5 PSF
IMPORTANCE FACTOR:	I =1.20
THERMAL FACTOR:	Ct =1.0
EXPOSURE FACTOR:	Ce =1.0

H. WIND LOADS:

BASE WIND SPEED: Vult=120 MPH Vasd=93 MPH
MEAN ROOF HEIGHT: 22'-0"

EXPOSURE CATEGORY: B
OCCUPANCY CATEGORY: IV
REFER TO PEMB DRAWINGS FOR ADDTIONAL INFORMATION

J. SEISMIC LOAD:

OCCUPANCY CATEGORY = IV
IMPORTANCE FACTOR I = 1.50
SEISMIC RESPONSE ACCELERATION, Sds = 0.160; Sd1 = 0.129
SITE CLASS = D
SEISMIC DESIGN CATEGORY = C
RESPONSE MODIFICATION COEFFICIENT, R = 3

STRUCTURAL STEEL SYSTEM NOT SPECIFICALLY DESIGNED FOR SEISMIC RESISTANCE
EQUIVALENT LATERAL FORCE PROCEDURE

BUILDING SEISMIC BASE SHEAR V=(0.08W)=27.1^{k}

K. DO NOT SCALE FOR DIMENSIONS NOT SHOWN ON DRAWINGS. SEND WRITTEN REQUEST FOR INFORMATION TO THE ARCHITECT FOR DIMENSIONS NOT PROVIDED.

L. THE CONTRACTOR SHALL COMPARE STRUCTURAL SECTIONS WITH ARCHITECTURAL SECTIONS AND REPORT ANY DISCREPANCY TO THE ARCHITECT PRIOR TO FABRICATION OR INSTALLING STRUCTURAL MEMBERS.

M. EXISTING CONDITIONS:

1. CONTRACTOR IS RESPONSIBLE FOR LOCATING ALL UNDERGROUND UTILITIES IN THE AREA OF CONSTRUCTION THAT MIGHT BE AFFECTED BY OR OTHERWISE INTERFERE WITH INSTALLATION OF NEW WORK. THIS INCLUDES THOSE THAT MIGHT BE DAMAGED BY NEW FOUNDATIONS OR OTHER WORK, AND THOSE WHOSE PRESENCE MIGHT LEAD DAMAGE TO THE NEW WORK (SUCH AS DIFFERENTIAL SETTLEMENT, ETC.).

SECTION 2 — SOILS AND SUBSURFACE CONDITION

A. DESIGN SOIL BEARING CAPACITY FOR SPREAD FOOTINGS = 1500 PSF.

B. A REGISTERED GEOTECHNICAL SOILS ENGINEER SHALL VERIFY ALLOWABLE DESIGN SOIL BEARING CAPACITY, SUBGRADE, FILL, AND BACKFILL DESIGN VALUES PRIOR TO CONSTRUCTION OF FOUNDATIONS, SLABS, ETC. IF, AFTER EXCAVATION, THE CONDITION OF THE SOIL INDICATES A SAFE BEARING CAPACITY LESS THAN DESIGN SOIL BEARING CAPACITY OR IF SOIL CONDITIONS VARY, THE STRUCTURAL ENGINEER OF RECORD SHALL BE NOTIFIED AND THE FOOTINGS REVISED IF NECESSARY. ALL FOOTINGS SHALL BEAR ON ORIGINAL UNDISTURBED SOIL OR CONTROLLED FILL. FILL SHALL BE COMPACTED TO AT LEAST 95 PERCENT OF THE STANDARD PROCTOR VALUE (98 PERCENT IN TOP 12 INCHES). COLUMN FOOTINGS AND WALL FOOTINGS SHALL BE POURED MONOLITHIC WITH TOPS OF ADJACENT FOOTINGS AT THE SAME ELEVATION. REFER TO GEOTECHNICAL REPORT BY GEOTECHNICAL & ENVIRONMENTAL CONSULTANTS, INC. DATED MARCH 23, 2018 FOR ADDITIONAL INFORMATION.

C. BACKFILLING OF WALLS AND PIERS SHALL BE PLACED SUCH THAT SYMMETRICAL LOADING SHALL BE MAINTAINED ON BOTH SIDES WHERE DESIGN CONDITIONS REQUIRE BACKFILLING EACH SIDE TO UNEQUAL HEIGHTS, THEN WALLS OR PIERS SHALL BE FIRMLY SUPPORTED IN POSITION, AND SHORES SHALL REMAIN UNTIL FLOORS OR OTHER PERMANENT BRACING ELEMENTS ARE PLACED AND PROPERLY SET TO PROVIDE FULL SUPPORT.

D. PROVIDE POSITIVE DRAINAGE AWAY FROM THE BUILDING AREA, BOTH DURING CONSTRUCTION AND PERMANENTLY.

E. DO NOT ALLOW STORED EXCAVATION MATERIAL TO DISRUPT PROPER DRAINAGE OF AREA.

F. MAINTAIN STABILITY OF EXCAVATIONS UNTIL PROPERLY BACKFILLED. KEEP EXCAVATION FREE OF ANY LOOSE MATERIAL. DEWATER EXCAVATIONS AND REMOVE ANY WET MATERIAL PRIOR TO THE PLACING OF CONCRETE WORK.

SECTION 2 — (CONTINUED)

G. HEAVY EQUIPMENT FOR SPREADING AND COMPACTING BACKFILL SHALL NOT BE OPERATED CLOSER TO WALL, GRADE BEAM, ETC., THAN A DISTANCE EQUAL TO THE HEIGHT OF BACKFILL ABOVE TOP OF WALL FOOTING & BOTTOM OF GRADE BEAM, ETC. THE AREA REMAINING HALL BE COMPACTED BY HAND TAMPERS.

H. USE EXCAVATED MATERIAL AS BACKFILL IF ACCEPTABLE TO TESTING AGENCY. IF EXCAVATED BACKFILL MATERIAL IS NOT AVAILABLE, USE SELECT FILL MATERIAL ACCEPTABLE TO TESTING AGENCY.

I. GRADE SHALL BE SUCH THAT THICKNESS OF FOUNDATION, SLAB ON GRADE, ETC., IS NOT REDUCED BY MORE THAN 5% OF THAT SHOWN ON DRAWINGS.

J. POUR A 3" TO 4" MUD MAT OF LEAN CONCRETE IN THE BOTTOM OF A FOOTING EXCAVATIONS THAT WILL BE EXPOSED TO RAIN OR REMAIN OPEN OVERNIGHT.

SECTION 3 — CONCRETE

A. MIX DESIGNS FOR EACH TYPE OF CONCRETE SPECIFIED SHALL BE SUBMITTED FOR APPROVAL. SUBMIT HISTORICAL DATA PER ACI REQUIREMENTS FOR EACH MIX DESIGN. ADMIXTURES, CURING COMPOUNDS AND HARDENERS WHICH ARE INTENDED FOR USE ARE TO BE SUBMITTED FOR APPROVAL. USE OF ADMIXTURES CONTAINING CHLORIDES SHALL NOT BE PERMITTED. ALL CONCRETE PERMANENTLY EXPOSED TO FREEZING WEATHER SHALL BE AIR-ENTRAINED (5%± AIR CONTENT).

B. CONCRETE SHALL HAVE THE FOLLOWING 28-DAY COMPRESSIVE STRENGTH:

NORMAL WEIGHT CONCRETE (145-150 LB/CF, WITH 3"-5" SLUMP):	
BUILDING FOOTINGS	3,000 PSI
BUILDING FLOOR SLABS ON GRADE	3,000 PSI

C. TESTING LABORATORY SHALL SAMPLE AND TEST CONCRETE AS FOLLOWS:

1. SAMPLING:
   a. GENERAL: IN ACCORDANCE WITH ASTM C172 AND ASTM C31.
   b. NO.: (4) CYLINDERS FOR EACH 75 CUBIC YARDS, 5000 SQUARE FEET OF SURFACE AREA, OR EACH PLACEMENT OF EACH MIX DESIGN OF CONCRETE PLACED IN ANY ONE DAY.
   c. DESIGNATION: LABEL EACH CYLINDER IN EACH SET OF (4) CYLINDERS WITH AN ALPHA-NUMERIC DESIGNATION, E.G., THE FIRST SET SHALL BE NUMBERED 1A, 1B, 1C, AND 1D.
2. TESTING:
   a. SLUMP: IN ACCORDANCE WITH ASTM C 143, TO BE TAKEN WHEN EACH SET OF CYLINDERS IS PREPARED.
   b. AIR CONTENT: TEST EACH TIME A SET OF CYLINDERS IS PREPARED, IN ACCORDANCE WITH ASTM C231 OR ASTM C173.
   c. COMPRESSIVE STRENGTH: IN ACCORDANCE WITH ASTM C31 AND ASTM C39, BREAK ONE CYLINDER AT (7) DAYS, (2) AT (28) DAYS, AND HOLD (1) IN RESERVE. EACH PAIR OF BREAKS FROM EACH SET OF CYLINDERS WILL BE CONSIDERED ONE TEST.
3. TEST REPORTS SHALL BE AVAILABLE AT JOBSITE. ONE COPY SHALL BE SENT DIRECTLY TO THE STRUCTURAL ENGINEER AT THE ADDRESS SHOWN ON THIS SHEET.

D. CONCRETE WORK SHALL CONFORM TO ACI 318 (STRUCTURAL CONCRETE) AND THE FOLLOWING:

1. DETAILS AND DETAILING OF CONCRETE REINFORCEMENT SHALL COMPLY WITH ACI 315 AND THE CRSI "MANUAL OF STANDARD PRACTICE". ALL CONCRETE WORK SHALL CONFORM TO ACI 301, "SPECIFICATIONS FOR STRUCTURAL CONCRETE FOR BUILDINGS", UNLESS MORE STRINGENT CRITERIA ARE APPLIED IN THESE DOCUMENTS. CONCRETE SHALL BE MIXED IN ACCORDANCE WITH ASTM C94. CEMENT SHALL COMPLY WITH ASTM C150. AGGREGATES SHALL COMPLY WITH ASTM C33. CONCRETE FOR INTERIOR SLABS SHALL HAVE COARSE AGGREGATES GRADED SUCH THAT NOT MORE THAN 18% NOR LESS THAN 8% OF THE TOTAL AGGREGATE IS RETAINED ON THE 3", 1½", ⅜", AND #4 SIEVES. AGGREGATE USED IN FLOOR SLABS 8" OR GREATER IN THICKNESS SHALL BE #467 STONE, LIMESTONE, OR GRANITE. SHEET MATERIALS FOR CURING CONCRETE SHALL COMPLY WITH ASTM C171, AND LIQUID MEMBRANE-FORMING COMPOUNDS FOR CURING CONCRETE SHALL COMPLY WITH ASTM C309. CONCRETE CURING SHALL BE IN ACCORDANCE WITH ACI-302. MEMBRANE CURING SHALL BE COMPATIBLE WITH FINAL SEALER OR FLOOR FINISH. AIR ENTRAINING ADMIXTURES FOR CONCRETE SHALL COMPLY WITH ASTM C260. CHEMICAL ADMIXTURES SHALL COMPLY WITH ASTM C494. FLY ASH, MAY BE USED TO REPLACE UP TO 25% OF CEMENT. APPLY FINAL SEALER OR FLOOR FINISH AFTER THOROUGH CLEANING.
2. CONSTRUCTION TOLERANCES SHALL BE IN ACCORDANCE WITH ACI 301.

E. CONSTRUCTION AND/OR CONTROL JOINTS SHALL BE PROVIDED IN SLABS ON GRADE AS SHOWN ON THE DRAWINGS. ASPECT RATIO (LONGSIDE TO SHORTSIDE OF CONCRETE AREA) SHALL NOT EXCEED 1.5. NO EMBEDDED ANGLES OR OTHER FIXED METAL ITEMS SHALL EXTEND THROUGH JOINTS UNLESS OTHERWISE NOTED. EMBEDDED ANGLES AND OTHER FIXED METAL ITEMS SHALL BE CONTINUOUS BETWEEN CONTROL JOINTS UNLESS OTHERWISE NOTED. CONTROL JOINTS IN WALLS SHALL MATCH CONTROL JOINTS IN SLABS ON GRADE. SAWN JOINTS SHALL BE CUT USING THE SOFF-CUT METHOD.

F. HORIZONTAL CONSTRUCTION JOINTS SHALL NOT BE PERMITTED UNLESS SPECIFICALLY DETAILED ON STRUCTURAL DRAWINGS.

G. REFER TO ARCHITECTURAL, MECHANICAL, ELECTRICAL, AND VENDOR'S DRAWINGS FOR SLEEVES, EMBEDDED ITEMS, ACCESORIES, ETC. THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING AND PLACING ALL SLEEVES, EMBEDDED ITEMS, ACCESORIES, ETC.

H. UNLESS SHOWN ON STRUCTURAL DRAWINGS NO OPENINGS IN SLABS OR WALLS LARGER THAN 12"x12" SHALL NOT BE CONSTRUCTED UNLESS SPECIFICALLY NOTED ON STRUCTURAL DRAWINGS. DO NOT PLACE PIPES OR SLEEVES THROUGH FOOTINGS UNLESS SPECIFICALLY NOTED ON STRUCTURAL DRAWINGS. PIPES, DUCTS, AND SLEEVES SHALL NOT EXCEED 1/3 SLAB OR WALL THICKNESS UNLESS SPECIFICALLY NOTED ON STRUCTURAL DRAWINGS. APPROVALS MUST BE OBTAINED FROM THE STRUCTURAL ENGINEER PRIOR TO FABRICATION OF STEEL AND PLACEMENT OF CONCRETE.

I. REFER ARCHITECTURAL DRAWINGS CHAMFERS, REVEALS, FINISHES, AND LOCATIONS OF SLAB DEPRESSIONS.

J. REINFORCING BARS SHALL CONFORM WITH ASTM A615 — GRADE 60, UNLESS NOTED OTHERWISE. REINFORCEMENT TO BE WELDED SHALL CONFORM WITH ASTM A706.

K. WELDED WIRE FABRIC SHALL CONFORM TO ASTM A-185 AND SHALL BE SUPPLIED IN SHEETS (NOT ROLLS). MINIMUM LAP LENGTH AT ENDS AND SIDES SHALL BE 8".

L. DEFORMED BAR ANCHORS (D.B.A'S.) SHALL CONFORM TO ASTM A496. D.B.A'S. SHALL BE AUTOMATICALLY END WELDED USING MANUFACTURER'S RECOMMENDED PROCEDURES, EQUIPMENT, FLUX, AND FERRULES, U.N.O. D.B.A'S. SHALL BE NELSON FLUXED D.B.A'S. OR APPROVED ALTERNATE.

SECTION 3 — (CONTINUED)

M. ALL REINFORCEMENT AND EMBEDS SHALL BE SECURELY PLACED PRIOR TO PLACEMENT OF CONCRETE. CHAIRS, BOLSTERS, AND OTHER PREFABRICATED ACCESSORIES SHALL COMPLY WITH CRSI "MANUAL OF STANDARD PRACTICE", CLASS 1 AT EXPOSED SURFACES, AND CLASS 2 AT UNEXPOSED. LEGS OF ALL ACCESSORIES USED IN EXPOSED CONCRETE SHALL BE SOLID PLASTIC OR PLASTIC COATED.

N. REINFORCING STEEL COVERAGE SHALL BE AS FOLLOWS:

CAST IN PLACE CONCRETE	— NON PRESTRESSED
PIERS	— 2" TO TIES
WALLS	— 2" NOT EXPOSED TO EARTH AND WEATHER*
FOOTINGS	— 3" SIDES AND BOTTOM, 2" TOP

* IF WALLS OR SLABS, ARE EXPOSED TO WEATHER OR IN CONTACT WITH GROUND, PROVIDE 2" COVER TO REINFORCING BARS. IF CONCRETE IS CAST AGAINST AND PERMANENTLY EXPOSED TO EARTH PROVIDE 3" COVER TO REINFORCING BARS.

O. CONTINUOUS BARS LOCATED IN TURNED DOWN SLABS, THICKENED SLABS, AND CONTINUOUS STRIP FOOTINGS SHALL HAVE 42 BAR DIAMETER LAP SPLICES. SPLICES IN REINFORCEMENT SHALL BE MADE ONLY AS PERMITTED ON DESIGN DRAWINGS, SPECIFICATIONS, OR AS AUTHORIZED BY THE ENGINEER. PROVIDE CORNER BARS AT ALL WALLS, FOOTINGS, AND GRADE BEAMS. BARS SHALL BE THE SAME SIZE AND SPACING AS THE HORIZONTAL REINFORCING. INTERSECTING WALLS OR GRADE BEAMS SHALL BE DOWELED TOGETHER IN THE SAME MANNER. PROVIDE TWO NO. 4 TOP DIAGONAL BARS 4'-0" LONG AT ALL REENTRANT CORNERS IN ALL SLABS ON GRADE.

P. SUBMIT COMPLETE SHOP DRAWINGS OF ALL MATERIALS PROVIDED UNDER THIS SECTION. REINFORCING SHOP DRAWINGS SHALL INCLUDE SECTIONS AND ELEVATIONS (WRITTEN DESCRIPTION IS NOT ACCEPTABLE). STEEL PRODUCER'S CERTIFICATES OF MILL ANALYSIS, TENSILE, AND BEND TESTS FOR REINFORCING STEEL SHALL ACCOMPANY THE SHOP DRAWINGS.

Q. CONCRETE FINISHES:

1. FLOORS: HARD SMOOTH STEEL TROWEL.
2. SIDEWALKS: BROOM FINISH, PERPENDICULAR TO TRAFFIC

R. FLOOR FLATNESS AND LEVELNESS.

1. SPECIFIED OVERALL VALUE:
   a. FLATNESS: Ff = 20
   b. LEVELNESS: FL = 20
2. MINIMUM LOCAL VALUE:
   a. FLATNESS: Ff = 15
   b. LEVELNESS: FL = 15
3. NO POINT ON THE FLOOR SHALL BE MORE THAN ¾" FROM SPECIFIED ELEVATION.
4. ANY SECTION OF FLOOR (BOUNDED BY CONTROL OR CONSTRUCTION JOINTS) NOT MEETING THESE REQUIREMENTS SHALL BE REPLACED.

S. TAKE PRECAUTIONS TO PREVENT HIGH TEMPERATURES IN FRESH CONCRETE DURING HOT WEATHER PER ACI-305. COLD WEATHER PLACEMENT SHALL BE PER ACI-306.

SECTION 4 — MASONRY

A. U.N.O. HOLLOW LOAD BEARING MASONRY UNITS SHALL CONFORM TO ASTM C90, LIGHTWEIGHT, WITH A MINIMUM COMPRESSIVE STRENGTH OF 1900 PSI (f'm = 1500 PSI) ON THE NET AREA, SUBMIT RESULTS OF TESTS CONDUCTED IN ACCORDANCE WITH ASTM C140 FOR APPROVAL FOR THE CMU TO BE USED.

B. MORTAR SHALL CONFORM TO ASTM C270 — CEMENT-LIME TYPE M OR S.

C. COURSE MASONRY GROUT SHALL CONFORM TO ASTM C476 WITH MAXIMUM AGGREGATE SIZE OF 3/8". MINIMUM COMPRESSIVE STRENGTH SHALL BE 2000 PSI AT 28 DAYS U.N.O. PROVIDE CLEAN OUT OPENINGS WHERE GROUT LIFT EXCEEDS 4'-0".

D. CONCRETE MASONRY QUALITY CONTROL:

1. WORK IN PROGRESS SHALL BE INSPECTED FORCONFORMANCE WITH SPECIFIED MATERIALS AND THAT WORKMANSHIP AND CONSTRUCTION IS IN COMPLIANCE WITH PLANS, SPECIFICATIONS AND INDUSTRY STANDARDS.
2. WORK SHALL BE SAMPLED AND TESTED.
   MORTAR: 2x4 CYLINDERS OR 2" CUBES PER ASTM C780.
   a. (1) TEST OF (3) CYLINDERS OR CUBES PRIOR TO CONSTRUCTION, (1) TEST OF (3) CYLINDERS OR CUBES ON EACH OF THE FIRST (3) DAYS OF CONSTRUCTION AND
      (1) TEST OF (3) CYLINDERS OR CUBES FOR EACH 5000 SQ. FT. OF WALL AREA OR PER WEEK WHICHEVER OCCURS FIRST.
   b. GROUT: TEST SAMPLE CUBE CAST BETWEEN BLOCK UNITS (SEE ASTM C1019) CAP PER ASTM C617 AND TEST PER ASTM C39. TAKE (2) SPECIMENS PER TEST EACH (30) CUBIC YARDS OF GROUT OR FRACTION THEREOF PLACED EACH DAY AND WHEN MIX PROPORTIONS ARE CHANGED.

E. REINFORCEMENT IN MASONRY WALLS SHALL HAVE THE FOLLOWING LAP SPLICES, U.N.O:

#4 BAR VERTICAL REINFORCING IN 8" CMU WALLS — 36"
#5 BAR VERTICAL REINFORCING IN 8" CMU WALLS — 45"
#6 BAR VERTICAL REINFORCING IN 8" CMU WALLS — 54"

CONTINUOUS REINFORCING IN BOND BEAMS — (78) BAR DIA.

F. PROVIDE 8 GA. GALVANIZED LADDER TYPE HORIZONTAL JOINT REINFORCEMENTAT 16" o.c. VERTICALLY FOR FULL WALL HEIGHT, TYPICAL, U.N.O. LAP 6" MINIMUM AND PROVIDE PREFAB CORNERS AND TEES. SEE ARCHITECTURAL FOR BRICK TIES FABRICATED INTEGRAL WITH JOINT REINFORCING, IF REQUIRED.

G. PROVIDE HORIZONTAL 8" DEEP, U.N.O., CMU BOND BEAM WITH (2) #5 CONT. GROUTED SOLID AT THE TOP OF ALL CMU WALLS. PROVIDE (2) #5 CORNER BARS WITH 3'-6" LEGS LAPPED WITH CONT. REINF. AT CORNERS AND TEES. SEE PLAN AND SECTIONS FOR ADDITIONAL REQUIREMENTS.

H. WALL CONSTRUCTION JOINTS SHALL BE SPACED 24'-0" o.c. MAX. WITH TYPICAL VERTICAL REINF. AT EACH SIDE OF JOINT. HORIZONTAL JOINT REINF. SHALL TERMINATE 2" FROM EACH SIDE OF JOINT. BOND BEAM REINFORCEMENT SHALL BE CONTINUOUS THROUGH WALL C.J. DO NOT PROVIDE JOINTS THROUGH SPAN OF LINTEL.

I. ALL MASONRY SHALL BE LAID IN RUNNING BOND.

J. AT ALL CMU WALLS IN ADDITION TO TYPICAL REINFORCING BARS NOTED ON PLANS, PROVIDE (1) REINFORCING BAR IN EACH OF FIRST TWO CELLS ((2) BARS TOTAL), GROUTED SOLID, AT ENDS OF WALLS, CORNERS, TEES, EACH SIDE OF WALL CONTROL JOINTS AND EXPANSION JOINTS, AND AT EACH SIDE OF OPENINGS U.N.O. REINFORCED CELL SHALL BE FULL HEIGHT OF WALL. SEE PLANS FOR SPECIFIC REINFORCING BAR SIZES AND TYPICAL BAR SPACING FOR AT INDIVIDUAL WALLS.

K. PROVIDE HB-200A/DA-213 ADJUSTABLE VENEER ANCHORS, AS MANUFACTURED BY HOHMANN AND BARNARD INC., OR APPROVED ALTERNATE, AT 16"o.c. VERTICALLY AND HORIZONTALLY.

(GENERAL NOTES CONTINUE ON SHEET S0-2

ABBREVIATIONS

A.B.	ANCHOR BOLT	LB. OR #	POUND
ADJ.	ADJACENT	LG.	LONG
AL.	ALUMINUM	LLH	LONG LEG HORIZONTAL
ALT.	ALTERNATE	LLV.	LONG LEG VERTICAL
&	AND	LIN.	LINEAR OR LINEAL
APPROX.	APPROXIMATE	L.P.	LOW POINT
APPVD.	APPROVED	LGTH.	LENGTH
ASPH.	ASPHALT	LIN. FT.	LINEAR FEET
@	AT		
AVG.	AVERAGE	MAX.	MAXIMUM
		MB	METAL BUILDING
BLDG.	BUILDING	M.H.	MANHOLE
B. OR BOT	BOTTOM	MACH. RM.	MACHINE ROOM
B/	BOTTOM OF	MSRY. OPNG.	MASONRY OPENING
B/S	BOTTOM OF STEEL	MET.	METAL
BRG.	BEARING	MEZZ.	MEZZANINE
BLK.	BLOCK	MK.	MARK
BM.	BEAM	MFGR.	MANUFACTURER
B.M.	BENCH MARK	MIN.	MINIMUM
BRIDG.	BRIDGING	MISC.	MISCELLANEOUS
BTW. OR BETW.	BETWEEN		
		N.I.C.	NOT IN CONTRACT
C.G.	CENTER OF GRAVITY (PT TENDONS)	N.S. OR NS	NEAR SIDE
C.I.	CAST IRON	N.T.S. OR NTS	NOT TO SCALE
C.L.	CENTER LINE	NOM.	NOMINAL
CHG.	CHANGE	NO.	NUMBER
CIR.	CIRCLE, CIRCULAR	#	NUMBER (REBAR SIZE)
CL. OR CLR.	CLEAR OR CLEARANCE		
CONN.	CONNECTION	O.H.	OPPOSITE HAND
C.M.U. OR CMU	CONCRETE MASONRY UNIT	o.c.	ON CENTER
CONST.	CONSTRUCTION	O.D.	OUTSIDE DIAM.
CONT.	CONTINUOUS, CONTINUED	O.F.	OUTSIDE FACE
C.J.	CONSTRUCTION JOINT	OPNG.	OPENING
	CONTROL JOINT	OPP.	OPPOSITE
CONC.	CONCRETE		
COL.	COLUMN	PAF	POWDER ACTUATED FASTENERS
CSK.	COUNTERSINK	P.L.F. OR PLF	POUNDS PER LINEAR FOOT
CTR.	CENTERS	P.C.F. OR PCF	POUNDS PER CUBIC FOOT
		P.C.I. OR PCI	POUNDS PER CUBIC INCH
D.B.C.	DIAMETER BOLT CIRCLE	P.J.F.	PREMOLDED JOINT FILLER
DEG. OR °	DEGREE	P.S.F. OR PSF	POUNDS PER SQUARE FOOT
DET.	DETAIL	P.S.I. OR PSI	POUNDS PER SQUARE INCH
DIAG.	DIAGONAL	P.T.	POST TENSIONED
dia. OR ø	DIAMETER	PART.	PARTITION
DN.	DOWN	PRES.	PRESSURE
DIM.	DIMENSION	PROJ.	PROJECTION
DWG.	DRAWING	PT.	POINT
DBL. OR DBLE.	DOUBLE	P.E.J. OR PEJ	PREMOLDED EXPANSION JOINT
D.H. OR DBA	DEFORMED BAR ANCHOR	PEMB	PREENGINEERED METAL BUILDING
DK.	DECK BEARING ELEVATIONS		
E.W. EE	EACH END	R OR RAD.	RADIUS
EA.	EACH	R.D.	ROOF DRAIN
E.F. OR EF	EACH FACE	REV.	REVISION
E.J.	EXPANSION JOINT	RM.	ROOM
E.S. OR ES	EACH SIDE	REF.	REFERENCE
E.W. OR EW	EACH WAY	REINF.	REINFORCING OR REINFORCEMENT
EL.	ELEVATION	REQ'D.	REQUIRED
ELEC.	ELECTRICAL	RECT.	RECTANGULAR
EMBED.	EMBEDMENT	R.O.	ROOM OPENING
= OR EQ.	EQUAL	SHT.	SHEET
EQUIP.	EQUIPMENT	SIM.	SIMILAR
EST.	ESTIMATE	SECT.	SECTION
EX. GR.	EXISTING GRADE	SCHED.	SCHEDULE
EXIST.	EXISTING	SLH	SHORT LEG HORIZONTAL
EXP.	EXPANSION	SLV	SHORT LEG VERTICAL
EXT.	EXTENDED	SLV.	SLEEVE
EXIST.	EXISTING	SPA.	SPACING OR SPACES
E.O.S.	EDGE OF SLAB	SPEC.	SPECIFICATION
F.D.	FLOOR DRAIN	SQ.	SQUARE
F.F.	FINISH FLOOR	SQ.FT. OR SF	SQUARE FOOT
F/	FACE OF	S.S.	STAINLESS STEEL
F TO F	FACE TO FACE	STD.	STANDARD
FIN.	FINISH	STIFF.	STIFFENER
FLR.	FLOOR	STL.	STEEL
FT. OR ()'	FEET OR FOOT	STRUCT.	STRUCTURAL
F.S.	FAR SIDE	SUSP.	SUSPENDED
FTG.	FOOTING	SYM.	SYMMETRICAL
FDN.	FOUNDATION		
FUT.	FUTURE	T/	TOP OF
Fy OR fy	YIELD STRENGTH	T/BM	TOP OF BEAM
f'c	28 DAY CONCRETE COMPRESSIVE STRENGTH	T/COL	TOP OF COLUMN
		T/FTG	TOP OF FOOTING
GA.	GAUGE OR GAGE	T/SLAB	TOP OF SLAB
GALV.	GALVANIZED	T/S	TOP OF STEEL
GEN.	GENERAL	T.R.C.	TOP OF ROUGH CONCRETE
GR.	GRADE	TAN.	TANGENT
H.P.	HIGH POINT	THD.	THREAD
H.S.	HEADED STUD ANCHOR	THK.	THICK
HGT.	HEIGHT	TRD.	TREAD
HK.	HOOK	T/WALL	TOP OF WALL
HORZ.	HORIZONTAL	T	TOP
		TEMP.	TEMPORARY
IN. OR ()"	INCH OR INCHES	THRU	THROUGH
INCL.	INCLUSIVE OR INCLUDING	TS	TUBE STEEL
I.D.	INSIDE DIAMETER	T.O.S.	TOP OF SLAB
INSUL.	INSULATION	TYP.	TYPICAL
INT.	INTERIOR		
INV.	INVERT	UNO OR U.N.O.	UNLESS NOTED OTHERWISE
		VERT.	VERTICAL
JST.	JOIST	VOL.	VOLUME
JT.	JOINT		
J.G.	JOIST GIRDER	WD.	WOOD
		WPFG.	WATERPROOFING OR WATERPROOF
K.	KIPS (1000 POUNDS)	WT.	WEIGHT
K.S.I. OR KSI	KIPS PER SQUARE INCH	W/O	WITHOUT
K.S.F. OR KSF	KIPS PER SQUARE FOOT	W/	WITH
		WWF	WELDED WIRE FABRIC

LEGEND

ITEM	SYMBOL	ITEM	SYMBOL
CONCRETE		TOP OF FOOTING ELEVATION	-1'-8
GROUT		SPOT ELEVATION TOP OF CONCRETE	+0'-0"
EARTH		STEP IN FTG. OR GRADE BM. TO CLG. PLUMB.	8"
CONCRETE BLOCK (CMU)		℄ BEAM SPLICE	
BRICK		AND	&
SECTION INDICATOR	1 / S3.1	PLATE	PL
DETAIL INDICATOR	2 / S3.4	CENTERLINE	℄
COLUMN TYPE , PIER TYPE FOOTING TYPE TOP OF FOOTING ELEVATION	C1 P1 F1 -2'-0	NUMBER (PRECEEDING)	#, NO.
		PLUS OR TENSION	+
		MINUS OR COMPRESSION	−
		POUNDS (FOLLOWING)	#
		STEP IN STRUCTURE OR DEPRESSED SLAB	OR 1"
		TOP OF STEEL ELEVATION	T/S EL. +20'-8" OR (+20'-0")

ORIGINAL PLANS @ WWW.LDline.com

ARCHITECT'S STAMP
STATE OF GEORGIA — GORDON M. SMITH, JR. — 7575 — REGISTERED ARCHITECT
SIGNATURE REQUIRED

SMITH DESIGN GROUP, INC.
210 WEST GAMBLSON STREET
LAGRANGE, GEORGIA 30240
706-882-5511 www.SDGarch.net

REVISIONS

△	DATE	DESCRIPTION

PROJECT:
VERNON ROAD FIRE STATION
VERNON ROAD
LAGRANGE GEORGIA

TITLE:
GENERAL NOTES, LEGEND, AND ABBREVIATIONS

MODIFIED DATE:

JOB NO: 1731

ISSUED DATE: FOR BID AND PERMIT
7 MAY 2018

SHEET: S0-1

SBFA JOB # 18034.01
STANLEY BRADY FAGAN ASSOCIATES, INC.
CONSULTING STRUCTURAL ENGINEERS
2337 PERIMETER PARK SUITE 215
ATLANTA GEORGIA 30341
PHONE: (770) 455-3404 FAX: (770) 451-1415
COPYRIGHT ©STANLEY BRADY FAGAN ASSOCIATES, INC. 2018