

Order Plans @ www.LDILine.com

LIGHTING SWITCH CIRCUIT NOTE: ALL SWITCHES CONTROLLING LIGHTING CIRCUITS SHALL BE PROVIDED WITH THE GROUNDING CONDUCTOR (NEUTRAL) FOR THE LIGHTING CIRCUIT IN ACCORDANCE WITH NFPA 70 (NEC) ARTICLE 404.2(C).

ELECTRICAL GENERAL NOTES

- ALL 120 VOLT CIRCUITS LONGER THAN 100 FEET IN LENGTH SHALL USE #10 AWG CONDUCTORS.
- ALL CIRCUITS SHALL HAVE A SEPARATE GROUNDING CONDUCTOR SIZED PER N.E.C. SECTION 250.122.
- ALL CONDUIT INSTALLED INDOORS SHALL BE ELECTRICAL METALLIC TUBING (EMT), MINIMUM 1/2" OR AS NOTED OTHERWISE. CONDUCTORS TO BE A MINIMUM OF #12 THAWN PPM, COPPER UNLESS NOTED OTHERWISE. BRANCH CIRCUIT RUNS WITH NO MARKS OR IDENTIFICATION ARE TO BE PROVIDED WITH ONE HOT, ONE NEUTRAL, AND ONE EQUIPMENT GROUNDING CONDUCTOR.
- ELECTRICAL CONTRACTOR SHALL PROVIDE CIRCUIT DIRECTORY WITH TYPED CIRCUIT DESIGNATION CARD UNDER PLASTIC COVER ON THE INSIDE OF EACH PANEL DOOR. ELECTRICAL CONTRACTOR SHALL ALSO FURNISH AND INSTALL NAMEPLATES ON ALL DISCONNECT SWITCHES, PANELBOARDS AND SWITCHBOARDS.
- ELECTRICAL CONTRACTOR SHALL FURNISH ALL LABOR, MATERIAL, TOOLS, EQUIPMENT AND PERFORM ALL WORK AND SERVICES NECESSARY FOR OR INCIDENTAL TO THE FURNISHING AND INSTALLATION COMPLETE OF ALL WIRING MATERIALS AND METHODS AS SHOWN ON THE DRAWINGS AND AS SPECIFIED, IN ACCORDANCE WITH PROVISIONS OF THE CONTRACT DOCUMENTS. COORDINATE WITH WORK OF ALL OTHER TRADES.
- FIELD COORDINATE ALL FURNITURE POWER FEED LOCATIONS PRIOR TO ROUGH-IN.
- ALL EMPTY CONDUITS SHALL BE PROVIDED WITH PULL STRIPS INSTALLED AND PLASTIC CROWFOOT.
- CONTRACTOR SHALL COORDINATE THE LOCATION OF ELECTRICAL PANELS PRIOR TO THE BEGINNING OF THE WORK.
- ELECTRICAL CONTRACTOR TO VERIFY EXACT PLACEMENT OF ALL DEVICES SHOWN ON THE ELECTRICAL CONSTRUCTION DOCUMENTS WITH MECHANICAL DRAWINGS PRIOR TO FINAL MEASUREMENT.
- CIRCUIT IDENTIFICATION SHALL BE PROVIDED FOR EACH HOMEWIRING DEVICE UNLESS NOTED OTHERWISE.
- ALL FIRE ALARM HORN AND SIREN DEVICES LOCATED IN THE SAME ROOM OR OPEN OFFICE AREA SHALL BE SEQUENCED TO FLASH AT THE SAME RATE PER LATEST FIRE ALARM CODE.

LIGHTING PLAN NOTES

- INSTALL KEYED CLEANING LIGHT SWITCH. REFERENCE THE "TYPICAL AUDITORIUM DAMPER SYSTEM DETAIL" FOR SWITCH TYPE AND WIRING INFORMATION.
- CONNECT TO THE EMERGENCY LIGHTING CIRCUIT SERVING THIS AUDITORIUM. REFERENCE THE PROJECTION LEVEL LIGHTING PLANS.
- CONNECT TO THE NORMAL LIGHTING CIRCUIT SERVING THIS AUDITORIUM. REFERENCE THE PROJECTION LEVEL LIGHTING PLANS.
- CONNECT THE TYPE "T1" LIGHT FIXTURES TO THE ECOSYSTEM BUS DESCRIBED ON THE PROJECTION LEVEL LIGHTING PLANS. THE FIXTURES SHALL CONNECT TO THE BUS BY EITHER DASH, CHAINING OR TAPPING. THE LOWER CASE LETTER ASSOCIATED WITH THE LIGHT FIXTURE INDICATES THE ZONE TO WHICH THE FIXTURE SHALL BE PROGRAMMED.
- PROVIDE "T1" TAPE LIGHT IN COVE ALONG ARCHITECTURAL CEILING CLOUD FOR CONTINUOUS ILLUMINATION. INSTALL TAPE LIGHTS PER ARCHITECTURAL DETAIL. PROVIDE ALL NECESSARY POWER SUPPLIES AND MULTIPLE CONNECTIONS TO TAPE LIGHTS AS REQUIRED PER MANUFACTURERS INSTRUCTIONS. CONNECT POWER SUPPLY TO PANEL P1 AND THROUGH LIGHT. REFERENCE THE RESPECTIVE SCHEDULES.
- CONNECT THE EMERGENCY LIGHT FIXTURE TO A CONTROL DEVICE EQUAL TO WATTS TOPPER WELCO TO ALLOW THE NON-EMERGENCY LIGHTING IN THE ROOM/AREA. INSTALL AND WIRE PER MANUFACTURERS INSTRUCTIONS. IF MULTIPLE EMERGENCY LIGHT FIXTURES ARE INSTALLED IN A SINGLE ROOM ONLY ONE ELOC DEVICE WILL BE REQUIRED.
- PROVIDE DUAL TECHNOLOGY (ULTRASONIC AND PASSIVE INFRARED) VACANCY SENSOR WALL SWITCH. DEVICE SHALL BE PROGRAMMED WITH MANUAL "ON" FUNCTION.
- PROVIDE DIGITAL SWITCH COMPATIBLE WITH LIGHTING CONTROL PANEL. REFERENCE THE DIGITAL SWITCH SCHEDULE FOR ADDITIONAL INFORMATION. PROVIDE ALL REQUIRED CONTROL WIRING. COORDINATE THE INSTALLATION WITH THE MANUFACTURERS INSTRUCTION.
- PROVIDE A DIMMER SWITCH EQUAL TO LEVITON RP1164-EZ.



ENGINEERING
 Gibson, Drake, Scott, Inc.
 9201 E. 63rd Street, Suite 100
 Raleigh, Missouri 64313
 Phone: (314) 258-1790
 Fax: (314) 258-2467
 www.gdseng.com
 C0626262-0000-0000-0000-0000


SHEET LEGEND

0000	GENERAL INFORMATION
1000	SCHEDULES
2000	SCHEMATIC DETAILS
3000	FLOOR PLANS & CEILING PLANS
4000	GENERAL & FINISH ELEVATIONS
5000	MECHANICAL
6000	ELECTRICAL
7000	PLUMBING
8000	MECHANICAL
9000	ELECTRICAL
9900	UNASSIGNED DETAILS
9999	CORRECTIONS & COMMENTS

MADISON YARDS 8
 AMC NEW BUILD
 905 MEMORIAL DRIVE SE
 ATLANTA, GA 30316



No.	Date	Description



SHEET TITLE:
 ENTRY LEVEL AREA-A LIGHTING PLAN

SHEET NUMBER:
 E201

THIS DRAWING IS A SEPARATE SET OF THE PROJECT DOCUMENTS. IT IS NOT TO BE USED IN ISOLATION. THE PROJECT DOCUMENTS SHALL BE PROVIDED TO THE CONTRACTOR AND SHALL BE THE BASIS FOR THE WORK. THE CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFYING THE ACCURACY OF THE INFORMATION SHOWN ON THIS DRAWING. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND APPROVALS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING THE WORK WITH ALL OTHER TRADES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROTECTING ALL EXISTING UTILITIES AND STRUCTURES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTAINING ACCESS TO ALL ADJACENT PROPERTIES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR RESTORING ALL AREAS TO ORIGINAL OR BETTER CONDITION. THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND APPROVALS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATING THE WORK WITH ALL OTHER TRADES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROTECTING ALL EXISTING UTILITIES AND STRUCTURES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR MAINTAINING ACCESS TO ALL ADJACENT PROPERTIES. THE CONTRACTOR SHALL BE RESPONSIBLE FOR RESTORING ALL AREAS TO ORIGINAL OR BETTER CONDITION.