

PART 1 - GENERAL

1.1 SECTION INCLUDES

1. Plaques

1.2 DEFINITIONS

A. Accessible/ADA: In accordance with U.S. Architectural & Transportation Barriers Compliance Board's Americans with Disabilities Act (ADA) Accessibility Guidelines for Buildings and Facilities.

1.3 COORDINATION

A. Coordinate all signage elements, including work schedule and installation with general contractor.

1.4 ACTION SUBMITTALS

A. Product Data: For each type of product.

B. Shop Drawings: For plaques.

1. Include fabrication and installation details and attachments to other work.

2. Show plaque mounting heights, locations of supplementary supports to be provided by others, and accessories.

3. Show message list, typestyles, graphic elements, and layout for each sign at least half size.

4. Submit electronic and hard copy files for approval.

5. Shop drawings shall be approved prior to fabrication.

6. All shop drawings and router files shall become property of the Owner.

C. Samples for Initial Selection: For each type of plaque, exposed component, and exposed finish.

1. Include representative Samples of available typestyles and graphic symbols.

D. Samples for Verification: For each type of plaque showing all components and with the required finishes, in manufacturer's standard size unless otherwise indicated and as follows:

1. Plaques: Full size Sample.

2. Exposed Accessories: Full size Sample of each accessory type.

E. Plaque Schedule: Use same designations specified on Drawings or in a plaque or sign schedule.

F. Mockups: One First Article prototype for viewing and revising by the Owner for each plaque type.

1.5 INFORMATIONAL SUBMITTALS

A. Qualification Data: Submit resume and work examples with bid.

1. Engineering services: Provide details of engineering capabilities.

2. Project Management: Provide proof of dedicated project manager.

B. Sample Warranty: For special warranty.

1.6 CLOSEOUT SUBMITTALS

A. Maintenance Data: For plaques to include in maintenance manuals.

B. As-built drawings: For final sign configurations and locations.

C. Router Files: For all plaques manufactured.

D. Photos: Provide for all installed work.

E. Project Closeout Book: Place all information in 3-ring binder labeled with project name. Provide 2 hard copies and additional digital copy.

1.7 QUALITY ASSURANCE

A. Signage Company Qualifications: An entity that employs installers and supervisors who are trained and competent in the signage industry.

1.8 FIELD CONDITIONS

A. Field Surveys to confirm actual field conditions for all interior work prior to fabrication.

1. Verify that as-built conditions match the design documents.

2. Any discrepancies in the drawings from field measurements shall be reported to the Owner and coordinated prior to fabrication.

1.9 WARRANTY

A. Special Warranty: Manufacturer agrees to repair or replace components of plaques that fail in materials or workmanship within specified warranty period.

1. Failures include, but are not limited to, the following:

a. Deterioration of finishes beyond normal weathering.

b. Deterioration of embedded graphic image.

2. The finished product will be free of defects in materials and workmanship.

3. Warranty Period: One year from date of Substantial Completion.

PART 2 - PRODUCTS

2.1 PLAQUES, GENERAL

A. Regional Materials: Plaques shall be manufactured within 500 miles (800 km) of Project site.

2.2 PERFORMANCE REQUIREMENTS

A. Accessibility Standard: Comply with applicable provisions in the U.S. Architectural & Transportation Barriers Compliance Board's ADA-ABA, Accessibility Guidelines for Buildings and Facilities and ICC A117.1 for signs.

2.3 PLAQUES

A. Acrylic Plaque: Plaque with background, border, and characters having uniform faces, sharp corners, and precisely formed lines and profiles; and as follows:

1. Manufacturers: Subject to compliance with requirements, available manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:

a. TBD by Architect/Owner

2. Plaque Material: Acrylic

4. Plaque Thickness: 0.25 inch (6.35 mm) or as shown on the drawings.

5. Finishes:

a. Integral Metal Finish: Not Used.

b. Integral Aluminum Finish: Not Used.

c. Baked Enamel or Powder-Coat Finish: Not Used.

d. Overcoat: Manufacturer's standard baked on clear coating.

6. Background: Non-gloss acrylic painted as indicated.

7. Mounting: Countersunk followed through fasteners.

8. Text and Typeface: Accessible raised characters and Braille, Futura Md BT Medium. Finish raised characters to contrast with background color, and finish Braille to match background color.

2.4 MATERIALS

A. Aluminum Castings: Not Used.

B. Aluminum Sheet and Plate: Not Used.

C. Aluminum Extrusions: Not Used.

D. Brass Castings: Not Used.

E. Brass Sheet (Yellow Brass): Not Used.

F. Bronze Castings: Not Used.

G. Bronze Plate: Not Used.

H. Copper Sheet: Not Used.

I. Stainless-Steel Sheet: Not Used.

J. Zinc Castings: Not Used.

K. Zinc Sheet: Not Used.

L. Acrylic Sheet: ASTM D 4802, category as standard with manufacturer for each sign, Type UVF (UV filtering).

M. Paints and Coatings for Sheet Materials: Inks, dyes, and paints that are recommended by manufacturer for optimum adherence to surface and are UV and water resistant for exterior exposure.

2.5 ACCESSORIES

A. Fasteners and Anchors: Manufacturer's standard as required for secure anchorage of plaques, noncorrosive and compatible with each material joined, and complying with the following:

1. Use concealed fasteners and anchors unless indicated to be exposed.

2. For exterior exposure, furnish nonferrous metal devices unless otherwise indicated.

3. Exposed Metal Fastener Components, General:

a. Fabricated from same basic metal and finish of fastened metal unless otherwise indicated.

4. Fastener Heads: For nonstructural connections, use oval countersunk screws and bolts with hex or round heads, unless otherwise indicated. For mounting brackets:

a. Concealed Studs: Concealed (blind), threaded studs welded or brazed to back of plaque, or screwed into plaque, or welded into plaque, or inserted integrally into back of plaque, unless otherwise indicated.

b. Through Fasteners: Exposed metal fasteners matching plaque finish, with type of head, material, and finish as indicated on drawings.

B. Adhesives: As recommended by plaque manufacturer and with a VOC content of 70 g/L or less for use on the weatherproofed system and applied on-site when calculated according to 40 CFR 59, Subpart D (EPA Method 24).

C. Adhesives: As recommended by plaque manufacturer and that comply with the testing and product requirements of the California Department of Pesticide Regulation's "Standard Practice for the Testing of Volatile Organic Emissions from Various Sources Using Small Scale Environmental Chambers."

D. Two-Face Tape: Manufacturer's standard high bond, foam-core tape, 0.045 inch (1.14 mm) thick, with adhesive on both sides.

E. Bimimous Paint: Not Used.

2.6 FABRICATION

A. General: Provide manufacturer's standard plaques according to requirements indicated.

1. Preassemble plaques in the shop to greatest extent possible. Components may only be necessary for shipping and handling limitations. Clearly mark units for reassembly and installation; apply markings in locations concealed from view after final assembly.

2. Mill joints to a tight, beveled, chamfered, or chamfered joint, as indicated on drawings.

3. Comply with AWS for recommended practices for welding and brazing. Provide tight connections behind finished surfaces without distorting or discoloring exposed side. Clean exposed welded and brazed connections of flux, and dress exposed and contact surfaces.

4. Conceal connections if possible. Conceal connections where they are unavoidable.

5. Provide rebates, lugs, and other necessary components and to attach to existing work. Drill and tap for required fasteners. Use concealed fasteners where possible; use exposed fasteners that match plaque finish.

6. Castings: Fabricate castings free of sand, dross, and other defects that impair appearance or strength. Grind, wire brush, sandblast, and buff castings to remove seams, gate marks, casting flash, and other casting marks before finishing.

B. Brackets: Fabricate brackets and hardware in accordance with brackets indicated on drawings and mounting conditions indicated. Modify manufacturer's standard brackets as required.

1. Aluminum Brackets: Finish brackets in baked enamel or powder-coat finish to match sign-background color unless otherwise indicated.

2. Stainless-Steel Brackets: Finish brackets in match sign background finish unless otherwise indicated.

2.7 MATERIAL FINISH REQUIREMENTS

A. Maintenance: Protect exposed surfaces from damage by applying a tripartite, temporary protective covering before shipping.

B. Application of Finishes: Allowable variations in same place are not acceptable. Variations in appearance of adjoining components are acceptable if they are within the range of approved Samples and are assembled or installed to minimize contrast.

C. Dimensional Finishes: Non-grain with long dimension of each piece and perpendicular to long dimension of finished trim or border surface unless otherwise indicated.

D. Organic, Anodic, and Chemically Produced Finishes: Apply to formed metal after fabrication but before applying contrasting polished finishes unless otherwise indicated.

PART 3 - EXECUTION

3.1 EXAMINATION

A. Examine substrates, areas, and conditions, with Installer present, for compliance with requirements for installation tolerances and other conditions affecting performance of plaque work.

B. Verify that plaque support surfaces are within tolerances to accommodate plaques without gaps or irregularities between backs of plaques and support surfaces unless otherwise indicated.

C. Proceed with installation only after unsatisfactory conditions have been corrected.

3.2 INSTALLATION

A. General: Install plaques using mounting methods indicated and according to manufacturer's written instructions.

1. Install plaques level, plumb, true to line, and at locations and heights indicated, with plaque surfaces free of distortion and other defects in appearance.

2. Install plaques so they do not protrude or obstruct according to the accessibility standard.

3. Before installation, verify that plaque surfaces are clean and free of materials or debris that would impair installation.

4. Corrosion Protection: Coat concealed surfaces of exterior aluminum in contact with grout, concrete, masonry, wood, or dissimilar metals, with a heavy coat of bimimous paint.

5. Responsible for all services, including all labor, materials and equipment for the complete fabrication and installation of the product to meet the schedule in the contract documents.

B. Plaque Uses for Room Identification and Other Accessible Plaques: Install in locations on walls according to accessibility standard.

C. Mounting Methods:

1. Concealed Studs: Using a template, drill holes in substrate aligning with studs on back of plaque. Remove loose debris from hole and substrate surface.

a. Masonry Substrates: Fill holes with adhesive. Leave recess space in hole for displaced adhesive. Place plaque in position and push until flush to surface, embedding studs in holes. Temporarily support plaque in position until adhesive fully sets.

b. Thin or Hollow Surfaces: Place plaque in position and flush to surface, install washers and nuts on studs projecting through opposite side of surface, and tighten.

2. Through Fasteners: Drill holes in substrate using predrilled holes in plaque as template. Countersink holes in plaque if required. Place plaque in position and flush to surface. Install through fasteners and tighten.

3. Brackets: Remove loose debris from substrate surface and install bracket supports in position so that plaque is correctly located and aligned.

4. Adhesive: Clean bond breaking materials from substrate surface and remove loose debris. Apply linear beads or spots of adhesive symmetrically to back of plaque and of suitable quantity to support weight of plaque after cure without slippage. Keep adhesive away from edges to prevent adhesive extrusion as plaque is applied and to prevent visibility of cured adhesive at plaque edges. Place plaque in position, and push to engage adhesive. Temporarily support plaque in position until adhesive fully sets.

5. Two-Face Tape: Clean bond breaking materials from substrate surface and remove loose debris. Apply tape strips symmetrically to back of plaque and of suitable quantity to support weight of plaque without slippage. Keep strips away from edges to prevent visibility at plaque edges. Place plaque in position, and push to engage tape adhesive.

6. Shim-Plate Mounting: Provide 1/8-inch (3.2mm) thick, concealed aluminum shim plates with predrilled and countersunk holes, at locations indicated, and where other direct mounting methods are impractical. Attach plate with fasteners and anchors suitable for secure attachment to substrate. Attach plaques to plate using method specified above.

3.3 ADJUSTING AND CLEANING

A. Remove and replace damaged or deteriorated plaques and plaques that do not comply with specified requirements. Replace plaques with damaged or deteriorated finishes or components that cannot be successfully repaired by finish touch-up or spot repair or repair processes.

B. Remove temporary protective coverings and stripable films as plaques are installed.

C. On completion of installation, clean exposed surfaces of plaques according to manufacturer's written instructions, and touch up minor nicks and abrasions in finish. Maintain plaques in a clean condition during construction and protect signage until acceptance by Owner.

3.4 CODE REQUIREMENTS

A. Responsible for all permit drawings as well as permit procurement fees or any variance processes required.

B. Responsible for ADA signage compliance as well as city code requirements.

END OF SECTION 10 14 16

SECTION 10 14 19 - DIMENSIONAL LETTER SIGNAGE

PART 1 - GENERAL

1.1 SECTION INCLUDES

1. Cutout dimensional characters.

2. Fabricated channel dimensional characters.

3. Illuminated, fabricated channel dimensional characters.

1.2 DEFINITIONS

A. Illuminated: Illuminated by lighting source integrally constructed as part of the sign unit.

1.3 COORDINATION

A. Furnish templates for placement of electrical service embedded in permanent construction by others.

B. Coordinate with general contractor on power requirements, electrical connections and locations for all signage elements.

C. Coordinate all signage elements, including work schedule and installation with general contractor.

1.4 ACTION SUBMITTALS

A. Product Data: For each type of product.

B. Shop Drawings: For dimensional letter signs.

1. Include fabrication and installation details and attachments to other work.

2. Show sign mounting heights, locations of supplementary supports to be provided by others, and accessories.

3. Show message list, typestyles, graphic elements, and layout for each sign at least half size.

4. Show locations of electrical service connections.

5. Include diagrams for electrical signal, and color coding.

6. Submit electronic and hard copy files for approval.

7. Shop drawings shall be approved prior to fabrication.

8. All shop drawings and router files shall become property of the Owner.

C. Samples for Initial Selection: For each type of plaque, exposed component, and exposed finish.

1. Include representative Samples of available typestyles and graphic symbols.

D. Samples for Verification: For each type of plaque showing all components and with the required finishes, in manufacturer's standard size unless otherwise indicated and as follows:

1. Dimensional Characters: Full size Sample of each type of dimensional character.

2. Exposed Accessories: Full size Sample of each accessory type.

E. Sign Schedule: Use same designations specified or indicated on Drawings or in a sign schedule.

F. Delegated Design Submittal: For all signs as required by local codes.

1. Include structural analysis calculations and drawings for signs indicated to comply with design loads; signed and sealed by the qualified professional engineer responsible for their preparation.

2. Mockups: One First Article prototype for viewing and revising by the Owner for each sign type. Mockup can be used for final installation if approved by owner.

1.5 INFORMATIONAL SUBMITTALS

A. Qualification Data: Submit resume and work examples with bid.

1. Engineering services: Provide details of engineering capabilities.

2. Project Management: Provide proof of dedicated project manager.

B. Sample Warranty: For special warranty.

1.6 CLOSEOUT SUBMITTALS

A. Maintenance Data: For signs to include in maintenance manuals.

B. As-built drawings: For final sign configurations and locations.

C. Router Files: For all signs manufactured.

D. Photos: Provide for all installed work.

E. Project Closeout Book: Place all information in 3-ring binder labeled with project name. Provide 2 hard copies and additional digital copy.

1.7 QUALITY ASSURANCE

A. Signage Company Qualifications: An entity that employs installers and supervisors who are trained and competent in the sign industry.

1.8 FIELD CONDITIONS

A. Field Measurements: Verify locations of electrical service embedded in permanent construction by other installers by field measurements before fabrication, and indicate measurements on Shop Drawings.

B. Field Surveys to confirm actual field conditions is required for all interior and exterior work prior to fabrication.

1. Verify that as-built conditions match design documents.

2. Any discrepancies in the drawings from field measurements shall be reported to the Owner and coordinated prior to fabrication.

1.9 WARRANTY

A. Special Warranty: Manufacturer agrees to repair or replace components of signs that fail in materials or workmanship within specified warranty period.

1. Failures include, but are not limited to, the following:

a. Deterioration of finishes beyond normal weathering.

b. Separation or delamination of sheet materials and components.

2. The finished product will be free of defects in materials and workmanship.

3. Warranty Period: One year from date of Substantial Completion.

PART 2 - PRODUCTS

2.1 DIMENSIONAL LETTER SIGNS, GENERAL

A. Regional Materials: Dimensional letter signs shall be manufactured within 500 miles (800 km) of Project site.

2.2 PERFORMANCE REQUIREMENTS

A. Delegated Design: Engage a qualified professional engineer, as defined in Section 014000 "Quality Requirements," to design sign structure and anchorage of dimensional character sign type(s) to withstand design loads as indicated on Drawings.

B. Thermal Movements: For exterior fabricated channel dimensional characters, allow for thermal movements from ambient and surface temperature changes.

1. Temperature Change: 120 deg F (67 deg C), incident; 180 deg F (100 deg C), material surfaces.

C. Electrical Components, Devices, and Accessories: Listed and labeled as defined in NFPA 70, by a qualified testing agency, and marked for intended location and application.

2.3 DIMENSIONAL CHARACTERS

A. Cutout Characters: Characters with uniform faces; square-cut, smooth edges; precisely formed lines and profiles; and as follows:

1. Manufacturers: Subject to compliance with requirements, available manufacturers offering products that may be incorporated into the Work include, but are not limited to, the following:

a. Retain "Basis-of-Design Product" Subparagraph and list of manufacturers below to identify a specific product or a comparable product from manufacturers listed. Retain option and delete insert note if manufacturer's name and model number are indicated on Drawings.

b. Basis of Design Product: Subject to compliance with requirements, provide list of out characters by Dimensional Innovations or comparable product by one of the following:

a. TBD by Architect/Owner

3. Character Material: Sheet Closed Cell PVC and/or acrylic as indicated in drawings.

4. Character Height: As indicated in the drawings.

5. Thickness: As indicated in the drawings.

6. Finishes:

a. Integral Metal Finish: Not Used.

b. Integral Aluminum Finish: Not Used.

c. Integral Stainless-Steel Finish: Not Used.

d. Integral Acrylic Color: As indicated by manufacturer's designation.

e. Baked Enamel or Powder-Coat Finish: Manufacturer's standard, in color as indicated.

f. Overcoat: Manufacturer's standard baked on clear coating.

g. Painted Edges: Paint edges of acrylic characters with laminated metal facing as recommended in writing by manufacturer.

h. Paint: Matthews Paint products shall be used where painting is required.

NOT FOR CONSTRUCTION  
DATE: 05/20/2018  
TIME: 05:09:00  
Dimensional Innovations  
3421 Mountain Creek Blvd, Suite 100  
Atlanta, GA 30328  
Phone: 770-249-2491 Fax: 770-249-1100  
www.dimensional.com

SHEET LEGEND

0001	GENERAL INFORMATION & NOTES
0002	GENERAL INFORMATION & NOTES
0003	GENERAL INFORMATION & NOTES
0004	GENERAL INFORMATION & NOTES
0005	GENERAL INFORMATION & NOTES
0006	GENERAL INFORMATION & NOTES
0007	GENERAL INFORMATION & NOTES
0008	GENERAL INFORMATION & NOTES
0009	GENERAL INFORMATION & NOTES
0010	GENERAL INFORMATION & NOTES
0011	GENERAL INFORMATION & NOTES
0012	GENERAL INFORMATION & NOTES
0013	GENERAL INFORMATION & NOTES
0014	GENERAL INFORMATION & NOTES
0015	GENERAL INFORMATION & NOTES
0016	GENERAL INFORMATION & NOTES
0017	GENERAL INFORMATION & NOTES
0018	GENERAL INFORMATION & NOTES
0019	GENERAL INFORMATION & NOTES
0020	GENERAL INFORMATION & NOTES

AMC MADISON YARDS 8  
AMC NEW BUILD  
905 MEMORIAL DRIVE SE  
ATLANTA, GA 30316

amc  
American Multi-Chem, Inc.  
One AMC Drive  
11500 Ash Street  
Lawrenceville, GA 30046  
Copyright 2018  
American Multi-Chem, Inc.