NOTE GENERAL NOTES SHOWN HERE SHALL GOVERN FOR ALL ELECTRICAL SHEETS.

## ELECTRICAL GENERAL NOTES:

READ THE SPECIFICATIONS AND REVIEW DRAWINGS OF ALL DIVISIONS OF WORK. COORDINATE THIS WORK WITH ALL OTHER DIVISIONS OF WORK AND ALL SUBCONTRACTORS. PROVIDE ALL SUBCONTRACTORS WITH A COMPLETE SET OF BID DOCUMENTS.

EXSTING CONDITIONS WERE TAKEN FROM ORIGINAL DRAWINGS AND SITE YEITS AND MAY IN REFLECT EACH TABULITY CONDITIONS. FIELD VERIEY ALL EXISTING CONDITIONS PRIOR TO SUMITY AND AND STATE OF THE PROPERTY OF THE MEDICAL PROPERTY AND DEMOLITION WITH ALL OTHER BRIGHLINES AND EXISTING CONDITION.

SECURE AND PAY FOR ALL PERMITS AND FEES NECESSARY FOR EXECUTION AND COMPLETION
OF ELECTRICAL WORK. FURNISH TO THE ARCHITECT A COPY OF INSPECTION REPORTS AND
APPROVAL CERTIFICATES FROM LOCAL AND STATE INSPECTIONS.

ELECTRICAL CONTRACTOR'S HALL REQUEST A SET OF ARCHITECTURAL PLANS FOR REFERENCE FROM THE GENERAL CONTRACTOR.

ALL WORK SHALL BE PERFORMED IN COMPLIANCE WITH AHJ ADOPTED CEC, BUILDING CODES, AND INDUSTRY STANDARDS.

AND INCOMES IN A PROGRAMM UPON COMMENTATION OF A PROGRAMM OF A PROGRAMM

 AFTER COMPLETION OF WORK UNDER THIS SECTION, CLEAN-UP ALL RESULTANT DEBRIS FROM THIS WORK AND REMOVE FROM THE SITE. 10 VERRIYY LOCATIONS FOR ALL WINNO DEVCES AND ELECTRICAL EQUIPMENT WITH ABOUTECTURAL DAMWINGS FOR INTEROOD ET BLASS AND PARSH. IN CENTERNO DUTLETS AND EMBRET AND THE PROPERTY OF THE PROPERTY OF THE PROPERTY OF AN ARE PLASTED, WINNOW AND DOOR TEM, PARELING, CELLING AND ASSOCIATED CONDITIONS, AND DORRECT ANY INACCURACY RESULTING FOR ALLIES TO SWITCH THE PROPERTY OF THE PROPERTY OF

CONTRACTOR SHALL BE RESPONSIBLE TO COORDINATE WITH ALL REFERENCES ON ARCHITECTURAL DRAWINGS.

12. REFER TO ONE-LINE DIAGRAM FOR ADDITIONAL TELECOMMUN REQUIREMENTS.

EXPOSED CONDUT SHALL BE INSTALLED IN STRAIGHT LINES, PARALLEL WITH OR AT RIGHT ANGLES TO THE BULDING STRUCTURE. DO NOT LOOP EXCESS FLEXIBLE CONDUIT IN CEILING SPACE.

22. FLEXIBLE CONDUIT IS NOT PERMITTED WITHIN DEMISING WALLS AND IS ONLY ALLOWED FOR SHORT FINAL CONNECTIONS OF 8'-0" OR LESS TO VIBRATING EQUIPMENT AND RECESSED LIGHT FORTURES. DO NOT LOOP EXCESS FLEXIBLE CONDUIT IN CEILLING SPACE.

HORIZONTAL OR CROSS RUNS OF CONDUIT AND WIRING IN WALLS AND PARTITIONS IS NOT PERMITTED.

24. PASS RACEWAYS OVER WATER AND OTHER PIPING WHEN PULL BOXES ARE NOT REQUIRED. NO RACEWAY WITHIN 3" OF HOT WATER PIPES, OR APPLIANCES, EXCEPT CROSSING WHERE RACEWAY SHALL BE AT LEAST 1" FROM PIPE COVER.

SECURE ALL SUPPORTS TO BUILDING STRUCTURE AS REQUIRED. SUPPORT HORIZONTAL AND VERTICAL RUNS OF METALLIC RACEWAYS PER THE ELECTRICAL CODE.

28. COORDINATE FINAL CONNECTION LOCATIONS, TYPES, AND REQUIREMENTS FOR DIVISION 15 EQUIPMENT WITH DIVISION 15 CONTRACTOR PRIOR TO ROUGHIN.

27. COORDINATE NEUTRAL CONDUCTOR REQUIREMENTS FOR DIVISION 15 EQUIRMENT WITH DIVISION 15 CONTRACTOR PROVIDE NEUTRAL CONDUCTOR AS REQUIRED FOR MULTI-PHASE LOADS.

28. PROVIDE NYLON BUSHINGS FOR ALL CONDUITSTUB-UP LOCATIONS TERMINATED WITHOUT A JUNCTION BOX UNLESS NOTED OTHERWISE.

29. ALL JUNCTION BOXES SHALL BE RIGIDLY ATTACHED TO STRUCTURE OR MILLWORK.

30. ELECTRICAL CONTRACTOR SHALL MAKE ALL FINAL BLECTRICAL CONNECTIONS TO MLLWORK. CONFIRM FINAL CONNECTION LOCATION AND REQUIREMENTS WITH MILLWORK CONTRACTOR PRIOR TO ROUGH-IN.

31. PROVIDE ALL MISCELLANEOUS STEEL AS REQUIRED FOR THE PROPER INSTALLATION OF ELECTRICAL EQUIPMENT AND SYSTEMS.

32. ALL ELECTRICAL DEVICES AND COVER PLATES SHALL BE DECORATOR STYLE, UNLESS OTHERWISE NOTED, COORDINATE COVER PLATE STYLE WITH ARCHITECT.

33. CONFIRM WIRING DEVICE AND COVER PLATE FINISHES WITH ARCHITECT

34. COORDINATE FINAL LOCATION, MOUNTING HEIGHT, AND COLOR OF ALL LIGHT FIXTURES, WALL MOUNTED AND CELLIN MOUNTED DEVICES WITH ARCHITECT FROR TO ROUGH-IN. REFER TO ARCHITECTURAL, REFLECTED CELLING PLAN FROM EVENES AND LOCATIONS ALL CELLING MOUNTED DEVICES AND LOCATIONS ALL CELLING MOUNTED WEIGHT FIXTURES AND CENTRED IN CELLING THE WIFEN POSSIBLE.

36. LIGHT FIXTURE SCHEDULE ON SHEET E200 IS TO REFERENCE ELECTRICAL CHARACTERISTIC ONLY. REFER TO ARCHITECTURAL DRAWINGS FOR COMPLETE LIGHT FIXTURE SCHEDULE. COORDINATE FINAL LIGHT FIXTURE LOCATIONS WITH ARCHITECT PRIOR TO ROUGH-IN.

37. ALL ELECTRICAL DEVICES IN SHOW WINDOWS (FLOOR OR CEILING) MUST BE IN DISCRETE LOCATIONS, FLUSH WITH SURFACE, AND WITH FINISH COLOR AS PER ARCHITECT.

38. PROVIDE UN-SWITCHED HOT CONDUCTOR TO ALL EMERGENCY AND EXITS ISIN FIXTURES WITH BATTERY BACKUP BALLAST AND NISHT LIGHT FIXTURES. REFER TO LIGHT FIXTURE SCHEDULE FOR ADDITIONAL INFORMATION.

PROVIDE NEUTRAL CONDUCTOR TO ALL LINE VOLTAGE WALL LIGHT SWITCH LOCATIONS. IF NEUTRAL TERMINATION IS NOT REQUIRED, CAP CONDUCTOR AND TAG AS 'NEUTRAL FOR FUTURE USE'.

40. PROVIDE A DEDICATED NEUTRAL FOR ALL DIMMED LIGHTING CIRCUITS.

41. PROVIDE ALL REQUIRED MOUNTING AND SUPPORT HARDWARE FOR LIGHT FIXTURES TO MEET MOUNTING HEIGHTS INDICATED ON ELECTRICAL AND ARCHITECTURAL DRAWINGS.

PROVIDE A FACTORY-INSTALLED MAXMUM WATTAGE LABEL THAT CORRESPOND TO THE MAXMUM WATTAGE INDICATED IN THE LIGHT FIXTURE SCHEDULE ON ALL MEDIUM SCREW BASE LIGHT FXTURES.

44 ALL LOW VOLTAGE WIRES FOR CONTROLS, AUDONOSIAL, TELEPHONEUTITAN DESCRIPTION WIRES AND SECRET AND

INSTALL AND MAKE POWER CONNECTIONS TO ALL LOW-VOLTAGE LIGHT FIXTURES PER MANUFACTURERS INSTALLATION INSTRUCTIONS.

46. COORDINATE FLOORBOX AND POKETHRU COVER PLATE TYPES AND FINISHES WITH ARCHITECT PRIOR TO PURCHASE. PROVIDE SUBMITTAL INFORMATION FOR REVIEW.

47. MAINTAIN 3" CLEARANCE MINIMUM BETWEEN NON-IC RATED LIGHT FIXTURE HOUSINGS AND ALL DUCTWORK AND ENVELOPE INSULATION. 48. PROVIDE ALL REQUIRED MOUNTING AND SUPPORT HARDWARE FOR LIGHT FIXTURES TO MEET SPECIFIED MOUNTING HEIGHTS.

49. ALL LOW VOLTAGE CONDUITS SHALL BE 1"MINIMUM UNLESS NOTED OTHERWISE.

ELECTRICAL DEMOLITION GENERAL NOTES: COORDINATE DEMOLITION AND NEW WORK WITH ALL DISCIPLINES AND EXISTING CONDITIONS PRIOR TO CONSTRUCTION.

REFER TO ARCHITECTURAL DRAWNINGS FOR AREAS OF DEMOLITION. EXISTING LIGHTING FRY LURSE, BUT SIGNS, AND OTHER CELLING WOUNTED DRIVES TO BE REMOVED IN THESE PAREA SHALL BE DISCONNECTED FROM THEM THESE PAREA SHALL BE DISCONNECTED FROM THEM THE DO NAGEHTECTURAL DRAWNINGS WIRING AND CONDUT SHALL BE REMOVED BACK TO SOURCEPEND.

CALLISONRTKL

AUGUST ERO OWL

Client Address			
	V44th Street	<b>~</b> //	
New	York, NY 100	Bowlero	
Droin	ot Addrona	Down -	
3067	ct Address Washington I	au /	
Augu	sta, GA 3090	,	
Issue	Issue Drawing Log		
		ISSUE FOR PERMIT	
	2018.05.29	ISSUE FOR BID	
_			
_			
_			
_			
_			
_			
_			
_			

**ELECTRICAL LEGEND** & NOTES

E-000

DESTING CONDITIONS WERE TAKEN FROM ORIGINAL DRAWINGS & SITE VISIT AND MAY NOT REFLECT EVACT." AS-BUILL" CONDITIONS. RIELD VERIFY ALL EXISTING CONDITIONS PRIOR TO SUBMITTING RIVAL BIDS. CAREFULLY COORDINATE NEW WORK AND DEMOLITION WITH ALL OTHER DISCIPLINES AND DRISTING CONDITIONS.

THIS DOCUMENT IS RELEASED FOR THE PURPOSE OF PRELIMINARY SUBMITTAL IT IS NOT TO BE USED FOR CONSTRUCTION