



REFLECTED CEILING PLAN NOTES

- G1 REFERENCE PROJECT MANUAL FOR GENERAL NOTES, RESPONSIBILITIES, AND PROCEDURES EXECUTION OF CONSTRUCTION CONTRACT OR PERFORMING WORK ACCEPTS THE CONDITIONS AND PROVISIONS DOCUMENTED WITHIN THE PROJECT MANUAL AND CONSIDERS THE FOLLOWING NOTATION SUPPLEMENTAL TO THOSE CONDITIONS.
- G2 BUILDING MATERIALS / ELEMENTS TO BE NEW CONSTRUCTION U.N.O.
- G3 ALL ANGLES ARE TO BE 0, 45 OR 90 DEGREES U.N.O.
- G4 CENTER TILE / GRID OR LIGHT IN ROOM OR SPACE, UNLESS NOTED OR DIMENSIONED OTHERWISE.
- G5 PROVIDE LEVEL 5 FINISH AND PAINT AT GYP. BOARD CEILING, SOFFIT & BULKHEAD CONDITIONS.
- G6 GYPSUM BOARD SURFACE PREPARATION IN CONCEALED AREAS ABOVE CEILING SHALL BE LEVEL 2 U.N.O.
- G7 EGRESS ILLUMINATION SHALL COMPLY WITH 2000 IBC SIGNS SHALL COMPLY WITH IBC 1011, COORD. W/ ELEC. DWGS. PROVIDE MINIMUM 90 MIN. EMERGENCY POWER BATTERY BACKUP FOR ILLUMINATION & EXIT SIGNAGE.
- G8 GC TO COORDINATE DUCTWORK, STRUCTURAL MEMBERS, BRACES, CEILING HEIGHTS AND CEILING MOUNTED LIGHT FIXTURES PRIOR TO CONSTRUCTION.
- G9 LIGHTING AND MECHANICAL EQUIPMENT SHOWN FOR REFERENCE PURPOSES ONLY. REFER TO MECHANICAL & ELECTRICAL DRAWINGS FOR ASSOCIATED FIXTURES AND EQUIPMENT LOCATIONS & SPECS.
- G10 METERS AND OPENINGS IN CEILING FOR FIXTURES OR MECHANICAL SYSTEM PATHS AND SYSTEMS SHALL BE PRECISELY CUT FOR INSTALLED ITEMS WITH EDGES TO BE CONCEALED BY MOUNTING TRIM OR COVER. INSTALLATION OF TRIM AND COVERS SHALL BE FLUSH TO FINISH.
- G11 PROVIDE REQUIRED ACCESS PANELS IN CEILING FOR MECHANICAL, ELECTRICAL, AND PLUMBING SYSTEMS. LOCATION AND TYPE OF ACCESS PANEL SHALL BE VERIFIED WITH ARCHITECT PRIOR TO CONSTRUCTION.

REFLECTED CEILING PLAN KEYNOTES

- ITEMS LABELED WITH KEYED NOTE INDICATOR ARE FOR SPECIFIC LOCATIONS ON PLANS
- 1204 WALL-MTD. AIR COMPRESSOR PLATFORM ABOVE, PAINT P1, COORDINATE W/ MECH. & STRUCT. DWGS.
- 1209 BEGIN CEILING GRID HERE
- 1216 TRACK FIXTURES ABOVE DISPLAYS/ MAPS/ TOURS BOOKS. LENGTHS ARE DENOTED AT EACH FIXTURE. MOUNT 36" AWAY FROM WALL, UNO.
- 1217 GWB HEADER/BULKHEAD, PAINT P2. SEE DET. D11A-121. PAINT P2 FACE AND UNDERSIDE OF BULKHEAD.
- 1218 GWB HEADER, PAINT P1. SEE DET. D21A-121. PAINT P1 FACE AND UNDERSIDE OF BULKHEAD.
- 1219 TRANSITION OR TERMINATION POINT BETWEEN CURVED AND RADIAL BUILDING ELEMENTS. VERIFY/COORDINATE/ADJUST RADIAL ANGLES IN FIELD AS REQUIRED TO ENSURE PROPER TRANSITIONS BETWEEN CURVED BUILDING ELEMENTS AND INTERSECTING RADIAL BUILDING ELEMENTS.
- 1220 CEILING MOUNTED WALL WASHER. REFER TO ELECTRICAL DRAWINGS.
- 1221 GWB HEADER/BULKHEAD, PAINT P1. SEE DET. D31A-121. PAINT P1 FACE AND UNDERSIDE OF BULKHEAD.
- 1223 INFRARED TUBE HEATER. REFER TO MECHANICAL DRAWINGS FOR SPECIFICATION AND ADDITIONAL INFORMATION.
- 1225 ALIGN HEADER WITH EDGE OF WALL FACE.
- 1226 EIFS CORNICE ABOVE.
- 1227 CANVAS AWNING ON EXTRUDED ALUM. FRAME. (REF. MATERIALS KEY ON A-201 FOR COLORS/SPECS).
- 1228 WALL MOUNTED EXTERIOR LIGHT FIXTURE (TYP.) (REF. ELEC. DWGS.)
- 1229 WALL MOUNTED EXTERIOR EMERGENCY EGRESS LIGHT PACK (REF. ELEC. DWGS.)
- 1230 WALL MOUNTED EXTERIOR LIGHT FIXTURE W/ EMERGENCY BACKUP. (REF. ELEC. DWGS.)
- 1231 COORDINATE HEIGHT OF LIGHT FIXTURE WITH OVERHEAD DOOR VENDOR & EQUIPMENT PRIOR TO LIGHT INSTALL.

REFLECTED CEILING PLAN LEGEND

CEILING MATERIALS:
REFER TO FINISH SHEET FOR ADDITIONAL FINISH INFORMATION.

#-# CEILING HEIGHT INDICATOR
APC-1 APC-2, P1... CEILING FINISH INDICATOR

ACOUSTIC CEILING TILE & GRID 1
USG - (800-950-2639)
MARS CLIM PLUS
FINELINE 1/8 DXFF, 24" X 24", 9/16" METAL GRID

DRYWALL - PAINT - P1
SHERWIN WILLIAMS
DIVINE WHITE, SW 6105
CEILING: FLAT FINISH
WALLS: EGGSHELL FINISH

DRYWALL - PAINT - P2
SHERWIN WILLIAMS
FIREWORKS, SW 6867
CEILING: FLAT FINISH
WALLS: EGGSHELL FINISH

EXPOSED - PAINT - P1
PAINT STRUCTURE AND SYSTEMS ABOVE.
USE DRY PAINT FOR EXPOSED AREA.

CEILING COMPONENTS:
GRAPHIC SYMBOLS ARE FOR ILLUSTRATIVE PURPOSES ONLY.
REFER TO ENGINEERING DRAWINGS FOR FIXTURE SPECIFICATION.

	24" X 48" LED LIGHT FIXTURE		SURFACE MOUNTED LIGHT FIXTURE
	24" X 24" LED LIGHT FIXTURE		DOWNLIGHT FIXTURE (MULTIPLE TYPES ARE SUBSISTED)
	12" X 48" LED LIGHT FIXTURE		ARCHITECTURAL BOUNCE OR BUILDING LIGHT PACK
	LINEAR LIGHT FIXTURE		EXIT LIGHT
	48" CEILING MOUNTED LED LIGHT FIXTURE		EXIT LIGHT W/ DIRECTIONAL ARROW
	TRACK LIGHTING FIXTURE		WALL MOUNTED EXIT LIGHT
	18" X 48" LED LIGHT FIXTURE		SPRINKLER HEAD
	HVAC DIFFUSER REGISTER		CEILING DUPLEX OUTLET
	HVAC RETURN REGISTER		P.A. SPEAKERS
	HVAC SLOT DIFFUSER		CEILING - JUNCTION BOX ABOVE
	EXHAUST FAN		HOSE REEL

PROGRESSIVE
 THE AUTO CLUB GROUP
AAA - CAR CARE CENTER
TAMPA, FL 33607
 1701 NORTH WESTSHORE BLVD.

REFLECTED CEILING PLAN
A-121

6/22/2018 10:31:14 AM
 D:\Draws\Local\Plan\2018\99000000 - Westshore - CENTRAL - 2018 - 2018.rvt
 THIS DOCUMENT HAS BEEN PREPARED BY AEGE PC AS AN ELECTRONIC REFERENCE AND AEGE PC SHALL RETAIN ALL COMMON LAW, STATUTORY AND OTHER RESERVED RIGHTS, INCLUDING THE COPYRIGHT THEREIN.

ISSUANCE
 REVISIONS
 NO. DATE DESCRIPTION
 FILE NUMBER 79890009
 PROJECT MANAGER
 PROFESSIONAL
 DRAWN BY
 CHECKED BY