



- PLAN KEY NOTES**
- ROD SUPPORTED CANOPY. SEE 7/A1.53.
 - PROVIDE NEW STAGE CURTAIN. SEE SPECS.
 - NOT USED.
 - PROVIDE MARKER BOARD.
 - PROVIDE TACK BOARD.
 - PROVIDE INTERACTIVE WHITE BOARD.
 - PROVIDE NEW SECTION OF SOLED DISH TABLE BACK TO THE DISHWASHER. INCLUDE APRE-WASH SINK.
 - PROVIDE A 180° DIAGONAL MOTORIZED PROJECTION SCREEN IN THE COMMONS WITH OFF THE WALL HANGING BRACKETS.
 - PROVIDE A 90° DIAGONAL MOTORIZED PROJECTION SCREEN IN THE MEDIA CENTER.
 - PROVIDE FORWARD FOLDING BASKETBALL GOALS, ELECTRONICALLY OPERATED, PAINTED WHITE (SIX IN THE M.P. GYM AND TWO IN THE MAIN GYM).
 - PROVIDE PROJECTOR MOUNTED IN GELUNG.
 - NOT USED.
 - PROVIDE FOLDING PANEL PARTITION - SEE 7/A6.41.
 - PROVIDE ACOUSTICAL WALL PANELS IN THE STRINGS RM.
 - NOT USED.
 - RELOCATE PLAQUES, SALVAGED DURING DEMOLITION TO THE WALL.
 - NOT USED.
 - PROVIDE LOCKER ROOM BENCH, SEE DETAIL 4/A.
 - PROVIDE ACCESS LADDER TO ROOF HATCH. SEE 7/A1.53.
 - PROVIDE MOTORIZED TELESCOPING LADDERS-PROVIDE MIN. 415 SE.
 - PROVIDE METAL LOCKERS, TYPE A, 12"x12" DEEP, WITH 1" BASE AND SLOPED TOPS.
 - PROVIDE STORAGE SHELVING.
 - PROVIDE VOL. WALL COURT SLEEVES TWO IN MULTI-PURPOSE GYM.
 - PROVIDE DRINK DISPENSER IN COMMONS.
 - PROVIDE WIRE MESH PARTITION IN GYM GATE.
 - PROTECT EXISTING MOUNTAINERS IN COMMONS AND CORRIDOR SKYLIGHTS. DISPLACE SEE DETAIL 19/A1.41.
 - TOOTH-NAIL AS REQUIRED FOR NEW WORK, MATCH EXISTING SIZE OF CMU.
 - PROVIDE 1" THICK UNFACED SOUND ATTENUATION BLANKET INSULATION OVER THE SUSPENDED ACOUSTICAL PANEL CEILING IN DRAMA ROOM 305. REMOVE AND REINSTALL CEILING TILES REQUIRED FOR WORK.
 - PROVIDE SCOREBOARD. SEE SPECS.
 - NEW CMU INFILL TO MATCH EXISTING WALL THICKNESS.

PARTITION TYPE SCHEDULE

MARK	SYMBOL	ASSEMBLY	NOTES
4L	[Symbol]	4" CMU HEIGHT - 16" MIN. ABOVE CEILING	
5	[Symbol]	8" CMU HEIGHT - TO BOTTOM OF STRUCTURE AND/OR DECK	
5-1	[Symbol]	8" CMU - 1 HOUR HEIGHT - TO BOTTOM OF STRUCTURE AND/OR DECK	PROVIDE SIGNAGE WITH LETTERS A MIN. OF 2" HIGH AT 12" O.C. 1 HOUR FIRE BARRIER PROTECT ALL OPENINGS.
5L	[Symbol]	8" CMU HEIGHT - 16" MIN. ABOVE CEILING	
5-SP	[Symbol]	8" CMU SMOKE PARTITION HEIGHT - TO BOTTOM OF STRUCTURE AND/OR DECK	
5	[Symbol]	8" CMU HEIGHT - TO BOTTOM OF STRUCTURE AND/OR DECK	
5L	[Symbol]	8" CMU HEIGHT - 16" MIN. ABOVE CEILING	
5-SP	[Symbol]	8" CMU SMOKE PARTITION HEIGHT - TO BOTTOM OF STRUCTURE AND/OR DECK	
5-1	[Symbol]	8" CMU - 1 HOUR HEIGHT - TO BOTTOM OF STRUCTURE AND/OR DECK	PROVIDE SIGNAGE WITH LETTERS A MIN. OF 2" HIGH AT 12" O.C. 1 HOUR FIRE BARRIER PROTECT ALL OPENINGS.

PARTITION TYPE MODIFIERS

W WALL HEIGHT: TOP OF CMU IS 3'-4" AFF. PROVIDE CONTINUOUS BOND BEAM AT TOP COURSE WITH WOOD CAP AND TRIM.

- PLAN LEGEND**
- COLUMN GRID AND/OR WALL CENTER LINES
 - M.B., T.B. MARKER BOARD OR TACKBOARD
 - F.E. FIRE EXTINGUISHER CABINET & FIRE EXTINGUISHER
 - FE SURFACE MOUNTED FIRE EXTINGUISHER
 - DOOR NUMBER
 - WINDOW NUMBER
 - MILLWORK TYPE/BUILDING ELEVATION MARKER
 - C.J. CONTROL JOINT
 - CEILING MOUNTED PROJECTOR

- GENERAL NOTES**
- ALL INTERIOR WALLS ARE PARTITION TYPE "3" UNLESS INDICATED OTHERWISE.
 - 1 HR RATING FOR CMU IS EST. BY EQUIV. CONC. THICKNESS METHOD. PROVIDE WEB AND SHELL THICKNESS REQUIRED TO ACHIEVE 1 HR RATING. REFER TO IBC TABLE 722.1.1, 2012 EDITION.
 - MASONRY UNIT SHALL COMPLY WITH BLOCK CLASSIFICATION INDICATED IN UL DESIGN DESCRIPTION FOR 2 HR RATED PARTITIONS.
 - FOR PARTITIONS RATED 1 HOUR OR GREATER, PROVIDE FIRESTOPPING AT ALL PENETRATIONS, TERMINATIONS AND VOIDS. REFER TO SPECIFICATIONS FOR REQUIRED FIRESTOPPING.
 - FOR SMOKE PARTITION WALLS AND SMOKE BARRIER WALLS SEAL ALL PENETRATIONS, TERMINATIONS AND VOIDS TO PREVENT THE PASSAGE OF SMOKE. REFER TO SPECIFICATIONS FOR REQUIRED SMOKE STOPPING.
 - ALL C.M.U. WALLS ARE TO BE RUNNING BOND UNLESS INDICATED OTHERWISE.
 - ALL HALL WALLS TO BE PARTITION TYPE "5-SP" UNLESS INDICATED OTHERWISE.
 - ALL EXPOSED VERTICAL CORNERS OF CMU PARTITIONS AND CHASES SHALL BE CONSTRUCTED OF BULLNOSE CMU EXTEND BULLNOSE CMU TO 8" ABOVE CEILING.
 - SEE UL FIRE RESISTANCE DIRECTORY, VOLUME 1, LATEST EDITION, FOR FURTHER INFORMATION REGARDING REFERENCED UL DESIGNS.
 - WHERE A SECTION OR DETAIL IS SHOWN ON DRAWINGS IT IS ASSUMED TO BE REPRESENTATIVE OF ALL LIKE OR SIMILAR CONDITIONS.
 - SEE STRUCTURAL DRAWINGS FOR SHEARWALL AND BEARING WALL LOCATIONS.
 - SEE SHEET A4.13 FOR TYPICAL PARTITION TERMINATION DETAILS.
 - ONLY NEW ADDITION AREAS ARE TO RECEIVE NEW FIRE EXTINGUISHERS AS SHOWN ON THIS SHEET AND THE LIFE SAFETY PLAN SHEET.
 - PROVIDE EXTERIOR PAINT ON ALL METAL INCLUDING BUT NOT LIMITED TO: RAILINGS AND CANOPY STRUCTURES. SEE SPECS.
 - PROVIDE INTERIOR PAINT THROUGHOUT. SEE FINISH SCHEDULE AND SPECIFICATIONS.

REVISIONS/ISSUANCES

NO.	DATE	DESCRIPTION

KEY PLAN

Manley Spangler Smith Architects
A Professional Corporation

825 East Taylor St.
P.O. Box 950
Gresham, Georgia 30224
Office 770.227.5473
Fax 770.228.3442

PROJECT:
RENOVATIONS,
MODIFICATIONS, &
ADDITIONS TO HENRY
COUNTY SCHOOLS -
GROUP 10
WOODLAND HIGH SCHOOL
(ITEM C)

CLIENT:
HENRY COUNTY BOARD OF
EDUCATION

SHEET TITLE:
FLOOR PLAN - SECTOR
"AA"

DATE: 05.07.18
SCALE: AS NOTED
DRAWN BY: JS
CHECKED BY: RV

SHEET NO.:
A1.21AA

FLOOR PLAN - SECTOR "AA"
SCALE: 1/8" = 1'-0"

Order Plans @