

Ownership of Intellectual Property: All rights, title, and interest in the drawings, specifications, and other documents prepared by the Consultant shall remain the property of the Consultant. The Consultant shall retain all common law, statutory and other reserved rights, including, without limitation, the copyright therein. Other documents and instruments prepared by the Consultant shall remain the property of the Consultant. The Consultant shall retain all common law, statutory and other reserved rights, including, without limitation, the copyright therein.

Order Plans @

GENERAL NOTES

- A. BOLD-DASHED LINES ON NEW WORK PLANS INDICATE UNDERGROUND PLUMBING.
B. PIPING ROUTED TO COOLER OR FREEZER WALLS WILL NOT BE PERMITTED.
C. WATER PIPING IN AREAS SUBJECT TO FREEZING TEMPERATURES WILL NOT BE PERMITTED.
D. REFER TO ARCHITECTURAL CONCRETE PLACEMENT PLAN FOR REFRIGERATION PITS, TRENCHES.
E. TRENCH DRAINS TO BE OF SUFFICIENT LENGTH TO COVER DOOR OPENING AND/OR PROVIDE PROPER DRAINAGE FOR COOLER AND/OR FLOOR AREA. SEE PFD-34.
F. WHEN POSSIBLE, LOCATE CLEANOUTS, SO AS NOT TO FALL IN DOOR OPENINGS, UNDER PALLET RACKS, OR IN MAIN TRAFFIC AISLES.
G. ALL GAS, WATER, AND SPRINKLER LINES INSIDE BUILDING TO BE INSTALLED AS HIGH AS PRACTICAL.
H. MAKE FINAL CONNECTION TO KROGER SUPPLIED EQUIPMENT.
I. BRANCH ISOLATION VALVES TO BE MOUNTED AT 10'-0" A.F.F. UNLESS OTHERWISE NOTED. IF MOUNTING AT 10'-0" A.F.F. IS PHYSICALLY IMPOSSIBLE MOUNT AS CLOSE TO 10'-0" A.F.F. AS POSSIBLE. MAKE ACCESSIBLE, AND HIDDEN FROM PUBLIC VIEW.
J. WHEREVER POSSIBLE, NEW PIPING SHALL BE RUN CONCEALED. COORDINATE LOCATION OF ALL PIPING WITH TRAC AND ELECTRICAL SUBCONTRACTOR. COORDINATE CUTTING AND PATCHING WITH GENERAL CONTRACTOR.
K. WHEREVER FIXTURES REQUIRING PLUMBING CONNECTIONS ARE FURNISHED BY OWNER, PLUMBING SUBCONTRACTOR SHALL FURNISH AND INSTALL CARRIERS, "P" TRAP AND STOPS.
L. ALL PIPE DROPS IN SALES AREA FROM ROOF TO LOW WALLS OR EQUIPMENT SHOULD BE COORDINATED AND GROUP TOGETHER WITH OTHER MECHANICAL PIPES. ENSURE ALL PIPING DROPS ARE ARE SUPPORTED EVERY 10'. COORDINATE WITH GENERAL CONTRACTOR.
M. PIPING TO SERVICE AREAS SHALL BE INSTALLED IN FRAMED WALL ON WARM SIDE OF INSULATED WALL PANELS USED FOR PREP ROOMS. WALL RUN SHORTEST DISTANCE TO EQUIPMENT. GROUP INSULATED LINES TOGETHER WHERE EXPOSED IN SALES AREA FOR ALL LINES AT BOTTOM OF BAR JOISTS. PIPING IS NOT ALLOWED INSIDE COOLERS OR FREEZERS.
N. NO PIPE ROUTING ALLOWED TO RUN THROUGH ELEVATOR EQUIPMENT ROOMS.
O. DROP WATER DOWN IN WALL. ROUTE WATER THRU WALL TO SERVE MULTIPLE FIXTURES ON COMMON WALL. REFER TO FIXTURE CONNECTION SCHEDULE FOR EQUIPMENT REQUIREMENTS.
P. ALL MEP TRADES, INCLUDING SPRINKLER MUST COORDINATE WITH EACH OTHER PRIOR TO INSTALLATION.
Q. PROVIDE BACKFLOW PROTECTION ON ALL FIXTURES WITH THE POTENTIAL TO MIX. FOR EXAMPLE MOP SINK, FACET SUPPLY, 3 COMPARTMENT SINK, FACET SUPPLY, COFFEE MAKER, COFFEE MAKER, DRINKING MACHINE, ETC. REFER TO PLUMBING CONNECTION SCHEDULE.
R. NO SURFACE MOUNTED WATER OR VENT PIPING PERMITTED INSTALLED EXPOSED IN PREP ROOMS.
S. EXPOSED WATER, WASTE, SODA SYRUP LINES, AND CONDUCITS ON WALL, FLOOR, AND CEILING SURFACES ARE PROHIBITED.
T. ALL EQUIPMENT MUST MEET APPLICABLE ANSI STANDARDS FOR CONSTRUCTION AND INSTALLATION. ALL EQUIPMENT LISTED AS CUSTOM FABRICATED MUST MEET THE APPROPRIATE ANSI STANDARDS.

GENERAL PLUMBING DEMOLITION NOTES

- A. PLUMBING SYSTEMS SEVERING EXISTING TO REMAIN PLUMBING FIXTURES AS IDENTIFIED ON ARCHITECTURAL DEMOLITION SHEET SHALL REMAIN INTACT AND IN GOOD WORKING ORDER.
B. AT ALL LOCATIONS WHERE PLUMBING FIXTURES ARE TO BE REMOVED, PLUMBING SUBCONTRACTOR SHALL REMOVE PIPING, WATER, WASTE, VENTS TO A POINT BEYOND FINISH SURFACE AND CAP OFF. WHERE PIPING BEYOND EXISTING FIXTURE TO BE REMOVED ALSO SERVES FIXTURES THAT ARE TO REMAIN, PIPING SHALL BE REROUTED AND RECONNECTED AS REQUIRED TO ACCOMMODATE REMODELED AREAS AS REQUIRED.
C. WHERE EXISTING WALLS ARE TO BE REMOVED AND PIPING IS FOUND THAT MUST REMAIN, PLUMBING SUBCONTRACTOR SHALL REROUTED AND RECONNECT PIPING AS REQUIRED. DOMESTIC GAS, SOIL, WATER, AND ROOF LEAKS SHALL BE REROUTED AND RECONNECTED AS REQUIRED TO ACCOMMODATE REMODELED AREAS AS REQUIRED.
D. ALL REMOVED PIPING TO BE FOUND TO BE IN GOOD CONDITION PURPOSE SHALL BE MOVED AND CAPPED OFF BEYOND FINISH SURFACE.
E. COORDINATE ALL REMOVED PLUMBING FIXTURES WITH GENERAL RELOCATION OR FUTURE RELOCATION.

STANDARD PLUMBING ABBREVIATIONS

Table with 3 columns: Abbreviation, Description, and Unit/Notes. Includes entries like 1 COMP, 2 COMPARTMENT SINK, LAV, LITER, etc.


PLUMBING LEGEND

Table with 2 columns: SYMBOL and DESCRIPTION. Includes PLAN-VIEW LINE TYPES, PIPING LINE TYPES, PLUMBING ACCESSORIES, PIPE VALVES, and PLUMBING SYMBOLS.



1871 EAST BROOKFIELD PKWY, LOUISVILLE, KY 40223
TEL: 502-261-1111
WWW.STUDIOAARCHITECTS.COM

CONSULTANTS



1718 ALEXANDRIA PKWY, SUITE 111, LOUISVILLE, KY 40203
TEL: 502-261-1111
WWW.EKHLHENGINEERS.COM

KROGER L758

234 EAST BROOKFIELD PKWY, 1ST FLOOR, LOUISVILLE, KY

CLIENT



KROGER COMPANY

1600 Orendy Station Court, Louisville, Kentucky 40223

PLUMBING ABBREVIATIONS, SYMBOLS, AND GENERAL NOTES

Table with 3 columns: No., Description, Date. Includes a table for revision tracking.

BID ISSUE

DATE OF BID AWARD: 06/17/2016
REVISIONS TO BE MADE BY THE BIDDER SHALL BE INDICATED BY A REVISION SYMBOL AND NUMBER. THE BIDDER SHALL BE RESPONSIBLE FOR VERIFYING THE ACCURACY OF ALL INFORMATION.

P0.1

Project number: 20168
Date: 06/17/2016

2" REFERENCE LINE
ARS DS