

Disturbed Area Stabilization (With Mulching Only) Ds1

DEFINITION
This practice is applicable to areas that have been disturbed by construction activities and require stabilization. The practice involves the application of a mulch material to the soil surface to prevent erosion and promote vegetation growth.

PURPOSE
To prevent soil erosion and sediment transport.
To stabilize the soil surface.
To promote vegetation growth.

REQUIREMENT FOR REGULATORY COMPLIANCE
This practice is required for all areas that have been disturbed by construction activities and require stabilization.

CONSTRUCTION SPECIFICATIONS
The disturbed area shall be stabilized within 14 days of the completion of the construction activity. The mulch material shall be applied at a rate of 2.0 to 3.0 tons per acre. The mulch material shall be applied in a uniform layer over the entire disturbed area. The mulch material shall be watered in immediately after application. The mulch material shall be maintained in place for a minimum of 30 days. The mulch material shall be removed or replaced as needed during the construction process.

Disturbed Area Stabilization (With Temporary Seeding) Ds2

DEFINITION
This practice is applicable to areas that have been disturbed by construction activities and require stabilization. The practice involves the application of a temporary seed mix to the soil surface to prevent erosion and promote vegetation growth.

PURPOSE
To prevent soil erosion and sediment transport.
To stabilize the soil surface.
To promote vegetation growth.

REQUIREMENT FOR REGULATORY COMPLIANCE
This practice is required for all areas that have been disturbed by construction activities and require stabilization.

CONSTRUCTION SPECIFICATIONS
The disturbed area shall be stabilized within 14 days of the completion of the construction activity. The temporary seed mix shall be applied at a rate of 2.0 to 3.0 tons per acre. The seed mix shall be applied in a uniform layer over the entire disturbed area. The seed mix shall be watered in immediately after application. The seed mix shall be maintained in place for a minimum of 30 days. The seed mix shall be removed or replaced as needed during the construction process.

Disturbed Area Stabilization (With Permanent Seeding) Ds3

DEFINITION
This practice is applicable to areas that have been disturbed by construction activities and require stabilization. The practice involves the application of a permanent seed mix to the soil surface to prevent erosion and promote vegetation growth.

PURPOSE
To prevent soil erosion and sediment transport.
To stabilize the soil surface.
To promote vegetation growth.

REQUIREMENT FOR REGULATORY COMPLIANCE
This practice is required for all areas that have been disturbed by construction activities and require stabilization.

CONSTRUCTION SPECIFICATIONS
The disturbed area shall be stabilized within 14 days of the completion of the construction activity. The permanent seed mix shall be applied at a rate of 2.0 to 3.0 tons per acre. The seed mix shall be applied in a uniform layer over the entire disturbed area. The seed mix shall be watered in immediately after application. The seed mix shall be maintained in place for a minimum of 30 days. The seed mix shall be removed or replaced as needed during the construction process.

DUST CONTROL ON DISTURBED AREAS (NOT TO SCALE)

DEFINITION
This practice is applicable to areas that have been disturbed by construction activities and require dust control. The practice involves the application of a dust control agent to the soil surface to prevent dust from being blown or carried away by wind or water.

PURPOSE
To prevent dust from being blown or carried away by wind or water.
To stabilize the soil surface.
To promote vegetation growth.

REQUIREMENT FOR REGULATORY COMPLIANCE
This practice is required for all areas that have been disturbed by construction activities and require dust control.

CONSTRUCTION SPECIFICATIONS
The disturbed area shall be stabilized within 14 days of the completion of the construction activity. The dust control agent shall be applied at a rate of 2.0 to 3.0 tons per acre. The dust control agent shall be applied in a uniform layer over the entire disturbed area. The dust control agent shall be watered in immediately after application. The dust control agent shall be maintained in place for a minimum of 30 days. The dust control agent shall be removed or replaced as needed during the construction process.

DISTURBED AREA STABILIZATION (WITH MULCHING ONLY) Ds1

Material	Quantity	Notes
Mulch	2.0 to 3.0 tons per acre	Applied in a uniform layer over the entire disturbed area.
Water	As needed	Watered in immediately after application.

DISTURBED AREA STABILIZATION (WITH TEMPORARY SEEDING) Ds2

Material	Quantity	Notes
Temporary Seed Mix	2.0 to 3.0 tons per acre	Applied in a uniform layer over the entire disturbed area.
Water	As needed	Watered in immediately after application.

DISTURBED AREA STABILIZATION (WITH PERMANENT SEEDING) Ds3

Material	Quantity	Notes
Permanent Seed Mix	2.0 to 3.0 tons per acre	Applied in a uniform layer over the entire disturbed area.
Water	As needed	Watered in immediately after application.

DUST CONTROL ON DISTURBED AREAS (NOT TO SCALE)

Material	Quantity	Notes
Dust Control Agent	2.0 to 3.0 tons per acre	Applied in a uniform layer over the entire disturbed area.
Water	As needed	Watered in immediately after application.

DUST CONTROL ON DISTURBED AREAS (NOT TO SCALE)

DEFINITION
This practice is applicable to areas that have been disturbed by construction activities and require dust control. The practice involves the application of a dust control agent to the soil surface to prevent dust from being blown or carried away by wind or water.

PURPOSE
To prevent dust from being blown or carried away by wind or water.
To stabilize the soil surface.
To promote vegetation growth.

REQUIREMENT FOR REGULATORY COMPLIANCE
This practice is required for all areas that have been disturbed by construction activities and require dust control.

CONSTRUCTION SPECIFICATIONS
The disturbed area shall be stabilized within 14 days of the completion of the construction activity. The dust control agent shall be applied at a rate of 2.0 to 3.0 tons per acre. The dust control agent shall be applied in a uniform layer over the entire disturbed area. The dust control agent shall be watered in immediately after application. The dust control agent shall be maintained in place for a minimum of 30 days. The dust control agent shall be removed or replaced as needed during the construction process.

Order Plans @

CONSTRUCTION DETAILS

PAULDING COLLEGE & CAREER ACADEMY
4555 DALLAS ACWORTH HIGHWAY
DALLAS, GEORGIA 30132
FACILITY CODE NO. 710-1063

PAULDING COUNTY SCHOOLS

Date: AUG 8, 2018
Project Number: 17129
C5.5

HGA JOB No. 2018-186

HGA
HARRIS GIBSON & ASSOCIATES
CONSULTING ENGINEERS ARCHITECTS
1400 N. W. 10TH AVENUE, SUITE 100
LAUREL MOUNTAIN, GEORGIA 30046
TEL: 770-962-9100 FAX: 770-962-9100

BXA Associates
BROOK & ASSOCIATES
ARCHITECTS
5655 North East Gate East, Suite 200
Alpharetta, GA 30005 | (678) 595-4508

8/8/18

