



**MEZZANINE NOTES**

- 1 TOP OF FLOOR = 12'-4". TOP OF JOISTS = 10'-7". SEE SECTIONS FOR TOP OF STEEL BEAMS ELEVATIONS.
- 2 MEZZANINE TO BE 3" NORMAL WEIGHT CONCRETE SLAB (2000 PSI) WITH 6# W/ 4# W/ 4 WWS ON 8"16" FORMDECK (26 GAUGE, TYPE "C") WELDED AT SUPPORTS WITH WELDED WBSHES IN 3/4" PATTERN USE (2) #3 TEK SCREWS PER SPAN AT SOLEPLATS. DECK TO BE IN LENGTH TO SPAN FOR MORE SUPPORTS.
- 3 JOISTS AND DECKING WILL BE PROVIDED BY PUBLIX. STEEL FABRICATOR MUST CONTACT WULFRAFT TO RECEIVE A SET OF APPROVED SHOP DRAWINGS FOR COORDINATION. SEE SPEC 050700 FOR WULFRAFT CONTACT INFORMATION.
- 4 WHEN BRIDGING REBAR INTERFERE WITH MECH DUCTWORK, PROVIDE "X" BRIDGING ON EACH SIDE OF JOIST BAY WHERE BRIDGING WAS REMOVED. NOTE: ALL JOISTS MUST HAVE CONT' BRIDGING OR "X" BRIDGING ON ONE SIDE.
- 5 APPROVAL MUST BE OBTAINED FROM ENGINEER OF RECORD FOR ALL SLAB OPENINGS OTHER THAN THOSE SHOWN ON THE MEZZANINE SLAB PLAN.
- 6 THE FLOOR FRAMING HAS BEEN DESIGNED BASED ON THE FOLLOWING LOADS:  
**DECK LOAD:** 15 PSF (INCLUDES 10 PSF PARTITION LOAD)  
**LIVE LOAD:** 100 PSF (NO REDUCTIONS)
- 7 SEE WALL ELEVATIONS ON S3.1 AND S3.2 FOR MORE INFORMATION.

**PLOT DATE:**  
August 21 2018

No.	Description	Date

STORE NUMBER  
**1687**  
**Tattersall Park**  
US 280 & Highway 19  
Hoover  
Shelby Co., AL  
**48.10**  
V1814.2018  
SIENNA LITE

**MEZZANINE FRAMING AND SOFFIT PLAN**

As indicated  
**S1.3**

Order Plans