

1 Foundation Plan
SCALE: 1/8" = 1'-0"

STRUCTURAL KEY NOTES:

1 DRILL & EPOXY (S) IS DOWELS FROM RETAIL FTG. TO PUBLX FTG. W/ A MIN. OF 4" DISBURSEMENT OR POUR MONOLITHICALLY. MATCH TOP OF PUBLX FTG.	5 PUBLX STRUCTURE, REF. PUBLX PLANS
2 EXPANSION JOINT REF. ARCH. FOR ADDITIONAL INFORMATION.	6 REF. PUBLX FOUNDATION PLANS FOR ADDITIONAL INFORMATION.
3 REF. PUBLX FOUNDATION PLANS FOR ADDITIONAL FOOTING AND COLUMN INFORMATION.	7 REFER TO RETAIL FTG. MONOLITHICALLY. MATCH TOP OF PUBLX FTG.
4 MATCH PUBLX TOP OF FTG. TYP. AT PUBLX WALL.	8 G.C. TO BE USED IN LIEU OF FOOTING FOOTINGS INDICATED ON PLAN.

GENERAL NOTES:

- INTERIOR FOOTINGS HEREIN ARE RELATIVE TO FINISHED FLOOR ELEVATION OF 100'-0". THE TOP OF ALL EXTERIOR FOOTINGS SHALL BE THIS 30'-0" TYP. U.O.N.
- EXTERIOR FOOTINGS HEREIN ARE RELATIVE TO FINISHED FLOOR ELEVATION OF 100'-0". THE TOP OF ALL EXTERIOR FOOTINGS SHALL BE THIS 30'-0" TYP. U.O.N.
- REFERENCE ARCHITECTURAL DRAWINGS FOR LOCATIONS AND CONSTRUCTION OF NON-LOAD BEARING MTL. STUD WALLS, FIXTURES, AND OTHER ITEMS NOT PRESENTED HEREIN.
- 4" CONCRETE SLAB W/ 3000 PSI CONC. W/ EXXKING 1X2.1 W.W.F. OVER 10 M.L. MIN. VAPOR RETARDER. REFER TO GEOTECHNICAL FOR SUBGRADE REQUIREMENTS.
- C.J. CONTROL JOINT CONSTRUCTION JOINT. TO BE COORDINATED (REF. SUBMITTAL SECTION OF GENERAL NOTES). CONTROL JOINTS SHALL BE 1" DEEP SAW CUTS TO BE MADE WITHIN 24 HRS. OF POUR.
- REF. ARCH./PLUMBING DRAWINGS FOR DRAIN SLOPES, ELEVATIONS AND SLAB RECESSES.
- CONTROL JOINTS (C.J.) SHALL BE LOCATED AT 12'-0" O.C. MAX. U.O.N. WITH LENGTH TO WIDTH RATIO NOT TO EXCEED 1.5:1
- OPENING RE-ENTRANT CORNER, TYP. PROVIDE (2) #4 X 4'-0" LONG BARS @ MID-HEIGHT OF SLAB.

Structural Foundation Schedule

Mark	Length	Width	Foundation Thickness	Top Reinf.	Bottom Reinf.
FS	5'-0"	6'-0"	1'-0"	#5 @ 12" O.C. E.W.	#5 @ 12" O.C. E.W.
FS	6'-0"	7'-0"	1'-0"	#5 @ 12" O.C. E.W.	#5 @ 12" O.C. E.W.
FS	7'-0"	8'-0"	1'-0"	#5 @ 12" O.C. E.W.	#5 @ 12" O.C. E.W.

Structural Column Base Plate Schedule

Mark	Length	Width	Thickness	Masonry	Anchor Bolts
BP1	12'-0"	12'-0"	4" ASB STL	(4) 3/4" THREADED HEADED STUDS (ASTM F1554 GR. 55 S1)	(4) 3/4" THREADED HEADED STUDS (ASTM F1554 GR. 55 S1)
BP2	12'-0"	12'-0"	4" ASB STL	(4) 3/4" THREADED HEADED STUDS (ASTM F1554 GR. 55 S1)	(4) 3/4" THREADED HEADED STUDS (ASTM F1554 GR. 55 S1)

Structural Wall Foundation Schedule

Mark	Width	Foundation Thickness	Top Reinf.	Bottom Reinf.
WF2	2'-0"	1'-0"	N/A	(3) #5 CONT.

Structural Masonry Plaster Schedule

Mark	Size	Vert Reinf.	Notes
MPS1B	8" x 16"	(2) #5 EACH CELL	EDGE SPACING REF. GEN. CMU NFD.
MPS1B	8" x 24"	(2) #5 EACH CELL	EDGE SPACING REF. GEN. CMU NFD.

1925 Prospect Ave.
Orlando, FL 32814
P (407) 661-9100
F (407) 661-9101

White Development Company
1801 South Keene Rd.
Clearwater, FL 33756

White Development Company
1801 South Keene Rd.
Clearwater, FL 33756

Retail @ Tattersall Park
US Highway 280 & Highway 119
Hoover, AL



Revision Schedule

No.	Description	Date
A	100% Public Submission	06/07/18
B	Issued for Bid & Permit	7/26/18

Checked: EDW
Date: 07/26/18