

MIRADA WALL SCONCE (XWM)



KEY LIGHTING FACTS

Department of Energy has verified representative product test data and results in accordance with its Lighting Facts Program. Visit www.lightingfacts.com for specific testing details.

Light Output - Lumens	Wattage	Life
1000	10W	50,000
2000	20W	50,000
3000	30W	50,000
4000	40W	50,000
5000	50W	50,000

LED fixture as indicated in the product name.

LED - Available with 3000K, 4000K or 5000K color temperatures. Choose from Type 2, Type 1 or Type FT.

ENERGY SAVING CONTROL OPTIONS - DIM - 0-10 volt dimming enabled with loadable by others. Available with integrated LED controller module. **OPTIONAL INTEGRAL MOTION SENSOR** - Passive infrared sensor activates automatic dimming or complete light levels. High level light is activated when someone enters target zone and increased to full bright in 1-2 seconds. Low light level (30% of maximum drive current) is activated when target zone is absent of motion activity for 5 minutes and is gradually lowered down (10 seconds) to low level. Sensor detection range: 110' horizontal x 40' vertical x 10' motion detection distance.

EXPECTED LIFE - Minimum 60,000 hours to 100,000 hours depending upon the ambient temperature of the installation. See LSA web site for specific guidance.

LEDS - Available with 3000K, 4000K or 5000K color temperatures. Choose from Type 2, Type 1 or Type FT.

OPTICS/CONSTRAINTS - Max high efficiency reflector provides three distribution. Choose from Type 2, Type 1 or Type FT.

MOUNTING - One-piece die-cast aluminum housing is installable on most wall surfaces. Mounting hardware is sold separately. Mounting hardware is sold separately. Mounting hardware is sold separately.

WALL MOUNTING - Galvanized steel mounting plate easily installs directly to 1/2" drywall or masonry surface. See EPDM gasket for installation between mounting plate and fixture. See EPDM gasket for installation between mounting plate and fixture.

ELECTRICAL - Two-stage surge protector (backlash) provides surge protection. See EPDM gasket for installation between mounting plate and fixture.

EMERGENCY OPTIONS - Optional integral emergency battery-back-up options are available. See EPDM gasket for installation between mounting plate and fixture.

OPERATING TEMPERATURE - -40°F to +120°F (-40°C to +120°C).

FINISH - Fixture is finished with 1.5% DuPont™ polyester powder coat. See EPDM gasket for installation between mounting plate and fixture.

WARRANTY - 5-yr LED fixture warranty. See EPDM gasket for installation between mounting plate and fixture.

PHOTOMETRICS - Please visit our website at www.designlights.com for detailed photometric data.

SHIPPING WEIGHT (per fixture) - 30 lbs (13.6kg).

LISTING - ETL listed to ANSI, IESNA, UL, and other U.S. and international safety standards. See EPDM gasket for installation between mounting plate and fixture.

ANCHOR BOLT DETAIL BASE DIAGRAM - See detail 3/SP2.

ANCHOR BOLT DETAIL BASE DIAGRAM - See detail 3/SP2.

ANCHOR BOLT DETAIL BASE DIAGRAM - See detail 3/SP2.

ANCHOR BOLT DETAIL BASE DIAGRAM - See detail 3/SP2.

ANCHOR BOLT DETAIL BASE DIAGRAM - See detail 3/SP2.

ANCHOR BOLT DETAIL BASE DIAGRAM - See detail 3/SP2.

ANCHOR BOLT DETAIL BASE DIAGRAM - See detail 3/SP2.

ANCHOR BOLT DETAIL BASE DIAGRAM - See detail 3/SP2.

ANCHOR BOLT DETAIL BASE DIAGRAM - See detail 3/SP2.

ANCHOR BOLT DETAIL BASE DIAGRAM - See detail 3/SP2.

ANCHOR BOLT DETAIL BASE DIAGRAM - See detail 3/SP2.











ANCHOR BOLT DETAIL BASE DIAGRAM - See detail 3/SP2.

MIRADA WALL SCONCE (XWM)

Part	Quantity	Part Name	Part Number	Notes
1	1	LED Module	1000-LED-3000K	See EPDM gasket for installation between mounting plate and fixture.
2	1	Mounting Plate	MP-1000	See EPDM gasket for installation between mounting plate and fixture.
3	1	Anchor Bolt	AB-1/2-13	See EPDM gasket for installation between mounting plate and fixture.
4	1	Hex Nut	HN-1/2-13	See EPDM gasket for installation between mounting plate and fixture.
5	1	Washer	W-1/2-13	See EPDM gasket for installation between mounting plate and fixture.

Part	Quantity	Part Name	Part Number	Notes
1	1	LED Module	1000-LED-4000K	See EPDM gasket for installation between mounting plate and fixture.
2	1	Mounting Plate	MP-1000	See EPDM gasket for installation between mounting plate and fixture.
3	1	Anchor Bolt	AB-1/2-13	See EPDM gasket for installation between mounting plate and fixture.
4	1	Hex Nut	HN-1/2-13	See EPDM gasket for installation between mounting plate and fixture.
5	1	Washer	W-1/2-13	See EPDM gasket for installation between mounting plate and fixture.

Part	Quantity	Part Name	Part Number	Notes
1	1	LED Module	1000-LED-5000K	See EPDM gasket for installation between mounting plate and fixture.
2	1	Mounting Plate	MP-1000	See EPDM gasket for installation between mounting plate and fixture.
3	1	Anchor Bolt	AB-1/2-13	See EPDM gasket for installation between mounting plate and fixture.
4	1	Hex Nut	HN-1/2-13	See EPDM gasket for installation between mounting plate and fixture.
5	1	Washer	W-1/2-13	See EPDM gasket for installation between mounting plate and fixture.



LED AREA LIGHTS - LSI MIRADA (XALM)



KEY LIGHTING FACTS

Department of Energy has verified representative product test data and results in accordance with its Lighting Facts Program. Visit www.lightingfacts.com for specific testing details.

Light Output - Lumens	Wattage	Life
1000	10W	50,000
2000	20W	50,000
3000	30W	50,000
4000	40W	50,000
5000	50W	50,000

LED fixture as indicated in the product name.

LED - Available with 3000K, 4000K or 5000K color temperatures. Choose from Type 2, Type 1 or Type FT.

ENERGY SAVING CONTROL OPTIONS - DIM - 0-10 volt dimming enabled with loadable by others. Available with integrated LED controller module.

EXPECTED LIFE - Minimum 60,000 hours to 100,000 hours depending upon the ambient temperature of the installation. See LSA web site for specific guidance.

LEDS - Available with 3000K, 4000K or 5000K color temperatures. Choose from Type 2, Type 1 or Type FT.

OPTICS/CONSTRAINTS - Max high efficiency reflector provides three distribution. Choose from Type 2, Type 1 or Type FT.

MOUNTING - Suspend from ceiling using adjustable mounting hardware. Mounting hardware is sold separately.

ELECTRICAL - Two-stage surge protector (backlash) provides surge protection. See EPDM gasket for installation between mounting plate and fixture.

EMERGENCY OPTIONS - Optional integral emergency battery-back-up options are available. See EPDM gasket for installation between mounting plate and fixture.

OPERATING TEMPERATURE - -40°F to +120°F (-40°C to +120°C).

FINISH - Fixture is finished with 1.5% DuPont™ polyester powder coat. See EPDM gasket for installation between mounting plate and fixture.

WARRANTY - 5-yr LED fixture warranty. See EPDM gasket for installation between mounting plate and fixture.

PHOTOMETRICS - Please visit our website at www.designlights.com for detailed photometric data.

SHIPPING WEIGHT (per fixture) - 30 lbs (13.6kg).

LISTING - ETL listed to ANSI, IESNA, UL, and other U.S. and international safety standards. See EPDM gasket for installation between mounting plate and fixture.

ANCHOR BOLT DETAIL BASE DIAGRAM - See detail 3/SP2.

ANCHOR BOLT DETAIL BASE DIAGRAM - See detail 3/SP2.

ANCHOR BOLT DETAIL BASE DIAGRAM - See detail 3/SP2.

ANCHOR BOLT DETAIL BASE DIAGRAM - See detail 3/SP2.

ANCHOR BOLT DETAIL BASE DIAGRAM - See detail 3/SP2.

ANCHOR BOLT DETAIL BASE DIAGRAM - See detail 3/SP2.








ANCHOR BOLT DETAIL BASE DIAGRAM - See detail 3/SP2.

LED AREA LIGHTS - LSI MIRADA (XALM)

Part	Quantity	Part Name	Part Number	Notes
1	1	LED Module	1000-LED-3000K	See EPDM gasket for installation between mounting plate and fixture.
2	1	Mounting Plate	MP-1000	See EPDM gasket for installation between mounting plate and fixture.
3	1	Anchor Bolt	AB-1/2-13	See EPDM gasket for installation between mounting plate and fixture.
4	1	Hex Nut	HN-1/2-13	See EPDM gasket for installation between mounting plate and fixture.
5	1	Washer	W-1/2-13	See EPDM gasket for installation between mounting plate and fixture.

Part	Quantity	Part Name	Part Number	Notes
1	1	LED Module	1000-LED-4000K	See EPDM gasket for installation between mounting plate and fixture.
2	1	Mounting Plate	MP-1000	See EPDM gasket for installation between mounting plate and fixture.
3	1	Anchor Bolt	AB-1/2-13	See EPDM gasket for installation between mounting plate and fixture.
4	1	Hex Nut	HN-1/2-13	See EPDM gasket for installation between mounting plate and fixture.
5	1	Washer	W-1/2-13	See EPDM gasket for installation between mounting plate and fixture.

Part	Quantity	Part Name	Part Number	Notes
1	1	LED Module	1000-LED-5000K	See EPDM gasket for installation between mounting plate and fixture.
2	1	Mounting Plate	MP-1000	See EPDM gasket for installation between mounting plate and fixture.
3	1	Anchor Bolt	AB-1/2-13	See EPDM gasket for installation between mounting plate and fixture.
4	1	Hex Nut	HN-1/2-13	See EPDM gasket for installation between mounting plate and fixture.
5	1	Washer	W-1/2-13	See EPDM gasket for installation between mounting plate and fixture.








LED AREA LIGHTS - LSI MIRADA (XALM)

Part	Quantity	Part Name	Part Number	Notes
1	1	LED Module	1000-LED-3000K	See EPDM gasket for installation between mounting plate and fixture.
2	1	Mounting Plate	MP-1000	See EPDM gasket for installation between mounting plate and fixture.
3	1	Anchor Bolt	AB-1/2-13	See EPDM gasket for installation between mounting plate and fixture.
4	1	Hex Nut	HN-1/2-13	See EPDM gasket for installation between mounting plate and fixture.
5	1	Washer	W-1/2-13	See EPDM gasket for installation between mounting plate and fixture.

Part	Quantity	Part Name	Part Number	Notes
1	1	LED Module	1000-LED-4000K	See EPDM gasket for installation between mounting plate and fixture.
2	1	Mounting Plate	MP-1000	See EPDM gasket for installation between mounting plate and fixture.
3	1	Anchor Bolt	AB-1/2-13	See EPDM gasket for installation between mounting plate and fixture.
4	1	Hex Nut	HN-1/2-13	See EPDM gasket for installation between mounting plate and fixture.
5	1	Washer	W-1/2-13	See EPDM gasket for installation between mounting plate and fixture.

Part	Quantity	Part Name	Part Number	Notes
1	1	LED Module	1000-LED-5000K	See EPDM gasket for installation between mounting plate and fixture.
2	1	Mounting Plate	MP-1000	See EPDM gasket for installation between mounting plate and fixture.
3	1	Anchor Bolt	AB-1/2-13	See EPDM gasket for installation between mounting plate and fixture.
4	1	Hex Nut	HN-1/2-13	See EPDM gasket for installation between mounting plate and fixture.
5	1	Washer	W-1/2-13	See EPDM gasket for installation between mounting plate and fixture.



Order Plans

@

W

W

W

W

Carl K. Collins, P.E. 417-662-8558
11111 Westport Rd., Suite 1000
Springfield, Missouri 65804
417-662-3265
www.collins.com
417-662-1000
Manning Finkbeiner & Collins, Inc.
11111 Westport Rd., Suite 1000
Springfield, Missouri 65804

CRAIG A. SCHNEIDER, AIA
ARCHITECT
1736 East Sunshine, Suite 417
Springfield, Missouri 65804
e-mail: architect@esterycheider.com

PROJECT:
NEW O'REILLY AUTO PARTS STORE
NC STATE HWY 211
SEVEN LAKES, NC
SITE LIGHTING DETAILS

O'Reilly AUTO PARTS
CORPORATE OFFICES
233 SOUTH PATTERSON
SPRINGFIELD, MISSOURI 65802
(417) 862-2674 TELEPHONE

COMM # 4155
DATE: 3-23-18
REVISION
DATE: