Protestion Hit Trices on Structural Hemburs In. | Particulation | Particulatio Abbreato (Sestructing -- tipocomposito wide of the some type fitted above may be used provided allowable isoding is obtained on the laids of percomposite design: incliners **APPLIES** ^(C) when optional item 12 or 13 are used over 3-1/4 in Apictoségat concrete teapon (a) 1-672, 2 and 7 building, 24 or 35 in. wide, 22 MSG Rated and 26728 MSG activity with other space and track that 9 ft. 6 in. (b) 2 and 3 m, where, 29 or 35 in, wide, 30 MSS fluted error 33/20 MSS salishe with them game network than 10 ft, 6 in. Minimum Ory Minimum Ory Unrestrained
Thickness Thickness Book Book
mile non Size Rating Hr ISOLATER INTERNATIONAL — Typs Barsyffin W8 3 and Typs W9 3, Investigated for lateriar General Purpose. Typs Systy Pilon W5 4 am. Egypt W6 3, Investigation on Interior General Purpose. Typs Systy Pilon W6 4 and Typs W94, investigated for Esperior Ups with top took as discribed in town. NEWKEM PRODUCTS CORP — Type Wils 3. Januardigates for Jackerion General Purpose, Type Wils 4. Tanastig Volume General Purpose, Type Wils, Tenedigates for Extender this with top cost as described in John St. Minimum Oninoum Steel Poor Unicestroloid Ory Ory Unice Roam Thickness only Com Roam Rathing Nr. - Streen begins change coming of 1 by 1 by 6,325 in. Herbin shool diagray, the trickings of spray-applied fire resistive should shall be increased by 1,4 km, as the bodden changed only. TIONAL -- Type 5-QF, RF, Type II. Type ISS or Type X adhesive which may also be used as a Unrestrained Protection Triking on WilkZ6, In.

Beam Rating Wisen book Is When Occk Is Bland the AB Forted or AB Entition + + - When bettom inheres conset of 1 sy 1 by 0.125 in. thick's control of the local and the 10 control of Callular Concrete - Coar Togolog Mostore* - Concentrate inseed with water and Portland seminit per inserusionaries excitations. Also discinned or Zois, as inserumed to the loss surface of the structural contracts or borned greater (Orien 3) of 1566 offers used. Cost dry designs and 25 day into cooppressive strengts of 159 days as design-included in 257 days. CELCORE ENC -- Type Colonia with cost day amonds of 20 (a or - 2.0) put of Type Colonia RF with cost day density of 20 (a or - 5.0) pcf. C. Dislair Concrete Roof Topolog Nation? - Toom concretence mixed with valors, Pintford consists of IC Considers Windowski Agencycle are consolication opticallies featurations. Dod by absoly of 32 (4 or m 2 pcf and 38 bay concreted in a fact that are concreted in specificial with 361% CVPH-55.

AGRIC INDUSTRIESS — No. K S BLASTICCUL IDER OF AMERICA - 1/1/20 d. 6% At all cost dry density 39 (4 or -) 3.0 pcf, 46; 92 of oser dry density 40 (4 or -) 3.0 pcf, 46; 92 of oser dry density 47 (4 or -) 3.0 pcf, 46; 92 of oser dry density 47 (4 or -) 3.0 pcf, 46; 92 of oser dry density 47 (4 or -) 3.0 pcf, 46; 92 of oser dry density 47 (4 or -) 3.0 pcf, 46; 92 of oser dry density 47 (4 or -) 3.0 pcf, 46; 92 of oser dry density 47 (4 or -) 3.0 pcf, 46; 92 of oser dry density 40 (4 or -) Pertial Concrets: - a cult of Pertial Aggregated to 94 to or Pertiana Concret and 1-1/2 pt or antraining aport. No disconser 2 in. as measured to the top surface of structural concrets or facebre placed. (New 19th when it is used.) See Faceted frame: "yelloting category in dual-right hadorist threatony or Foarest frame." yelloting category in dual-right hadorist threatony or Foarest frame." (CDVR) Cloegory in dual-right hadorist blockery for list of Cloedford companies. 556. Financial Plantic* — (No. Store) — For use or with ophidar or positio conside. Section 24 by 42 inc. adjustment formed doctor contributes record revising devices of 1.0 () or 1.0,13 mt, encountered within contribute contributes or sections. The contributes of the contrib See Prented Medich (BRMX) category in Britishing Meteriate Directory or Prented Medich (CCMA) category in Fire Recolatory Directory for list of Categorian conspenses.

VERCO DECKING INC - & INSCOR CO → 24, 30 or 36 to what Types FL8, FL8CO, 5, 9(D. 54; 24 or 36 in, inde Types FL9CO, 90, 90(D. 54; 24 or 36 in, inde Types FL9CO, 90, 90(D. 54; 24 or 36 in, inde Types FL9CO, 90, 90(D. 54; 34 or 36 in, inde Types FL9CO, 90(D. 50(D. 54); 34 or 36 in, inde Types FL9CO, 90(D. 54); 34 or 36 in,

VILCRAFT, DOV OF NICOR CORF. — 24, 30 or 36 m. m/si, 15pp 3.5 NJ, 3.59U, 3.59U, 3.59U, 5.50 ftm, w/si, 15pp 3.5 U, 3.50 J, 3.5

ducry core insulating materials $^{\circ}$ manufacturing 6.1. c - Type 500, Type 2008s, Type 500s, of Type 58.

Restrained Assembly Rating Hr

"Indicates such products shall been the UL or cUL Carbification Mark for jurisdictions employing the UL or cUL Carbification (such as Canada), respectively. This approximate of a company's some or product in this distribution dozer not at itself income that arrelates as identified have been associated under 60% between the foreign. Dury frame conducts product product. Dury frame conducts product to 60%, these aboves be continued to 60% Contified and covered under 60% in Followillip Sortices, Adaptive 60% for the fraction on the product. 2010/4365Y-01-0005 - Joint Gystema (B) CHLINE CERTIFICATIONS BIRECTORY System No. HW-D-0045 XHBN.HW-D-0045 Joint Systems XHBN - Joint Systems Nominal Joint Width - 974 fo. (B) (IA) (3B) souther influent hadiges place to approximate the cooled of Challeged gain sheef class souther influent hadiges place to approximately seek states (from 20). National certain real solutions approximate to influent and influent dates dates and secured to realize seek sections or inside seeked into 25 to, (650 pm); DC.

8. Peritty Consiste — Mai applies of 5.2 vs & Peritty Aggregate* to 84 for of Portland opportunity and 1-172 of all enforcing agent. Compressive strength 50 and min.

ABU BRUNE (B) System No. HW-D-0022 XHBN.HW-D-0022 Joint Systems XHBN - Joint Systems XHBN7 - Joint Systems Certified for Canada System No. HW-D-0022 A1, Syray Applied Fire Resistrice Material? — (Optional, doct books). — Proc or the imposition of the Special Material and Pic, And or Carly Material (forms M. 38), the peri-form solds may be served with a min of 16 m., (A min) this best to man (USS) or (C7 cms). Bulletings of the existing resistant. WIR GRACE NICO - CONN - Type 695-6051 menty construction features.

2. Sized Nasof Decis — 1847, 2 /r. (35 min) decis pain (steel three) and decis.

8. Roof Transferen — (1986 Series — No. 3, Vin. (35 min) this grows insurating consists.

2. Series and from No. 100 docs do the fiber tells. C. Read trasslation — Mineral and Filter Grands" — (fr. 79) Scroot — Mo. 2/4 In. (19 con): drick (scotor applied in time or more layers directly even steel on over appears board seeathing larg step steel and look. 5. Joint System — Max separation between bottom of flour and top of wall is 1 in. (25 pm). The joint system is designed to accommodate a max 18 percent compression or actessor from its installed width. The part spector consider, in a forming mathematical act of outcode, is closely excluded. As Exempling Medication and 5 of individuals, 5s follows:

A. Exempling Medication — More 3 of its District Dis 16480-CHV-12-CC22 - Jord Systems 166 MDNWOOL C.L.C - Manufact 1200 Stating ARCHITECTS SUSSENBACH When the U. Lose Rock is on the product, or when the word "tentrement" is included in the O. Mark, places scent the <u>Ol Tentrement descripe</u> for indicates information regarding this product's perforables. The appearance if it comments there or product in the interiors does not in little flower deep medical as identified there been manufactured under tiff in Fellowing Bennic Christians places to the Indian state of the Confidence of the Confidence of the Confidence of the Indian (ICC) Fellowings Service, Plays, Service for the Service of the america. LANIER ASSEMBLIES 09/17/18 HAPMAN A-1.15

CGLS ARCHITECTS SHIE OF GEODA GDOE PRELIMINARY SUBMITTAL / DESIGN DEVELOPME 50% CONSTRUCTIO RFP NO. 411-19