VIPER L
SERIES
STRIKE
LARGE AREA LUMINAIRE

Cat.#	Type
Job	LF02-4B

BEACON
Approvals

SPECIFICATIONS

Intended Use:
The Beacon Viper luminaire is available in two sizes with a wide choice of delivered LED wattage/lumen options and optical distributions designed for medium mounting up to 1000W MH + HPS. Luminaires are rated for wet locations.

Construction:
- Attractive cast aluminum housing with die cast aluminum cover and a polycarbonate acrylic lens meets ASTM D5207 exposure and wet test requirements.
- Fasteners on exterior are corrosion resistant.
- Zero uplight optical cartridge system maximizes on site LED engine, LED board, optics, gasket and stainless steel cover.
- Cartridge is held together with internal torsion mounting system so the cover is held in place, but can be replaced as a one piece optical system.
- Tempered glass lens and molded polycarbonate Fresnel optic ensure a weather and wear resistant watertight optical cavity.

Electrical:
- Luminaire accepts 120V through 277V (50-60 Hz) or 347V, 480V or 277/480V input.
- Power factor is .90 or full load.
- Driver is 0-10V dimming standard. Must be ordered factory installed when specified for operation on external dimming controls.
- Components in each unit wired with the luminaire only, only to meet 90% of open wire warning specified by UL for unit to operate at 90°C or higher.
- Fuse (board mounted) provided on UL for use on 480 VAC, 10A or higher. Fuse rating applies to primary only 5 KA rating.
- Photocell or occupancy sensor shall not be affected by ambient lighting conditions.
- Components in each unit wired with the luminaire only, only to meet 90% of open wire warning specified by UL for unit to operate at 90°C or higher.
- Fuse (board mounted) provided on UL for use on 480 VAC, 10A or higher. 5 KA rating applies to primary only 5 KA rating.
- Photocell or occupancy sensor shall not be affected by ambient lighting conditions.

Construction/Options:
- Available with an optional passive infrared (PIR) motion sensor capable of dimming a matrix 360° around the luminaire. When no motion is detected by the PIR sensor, the luminaire will dim to the wattage and lumen level chosen in the configurator. When motion is detected by the PIR sensor, the luminaire returns to the wattage and lumen level chosen in the configurator. Other motion sensor configurations are also available.
- Available with integral 0-10V wireless dimming, timed dimming with multiple areas or zones formed by master and multiple area luminaires (consult Beacon Products if unsure).
- Available with integral 0-10V wireless dimming, timed dimming with multiple areas or zones formed by master and multiple area luminaires (consult Beacon Products if unsure).
- In addition, your can be specified with **SiteSync™** wireless control system for occupancy, timed dimming and multi-zoning, while achieving high quality LED. For more information, see SiteSync™ data sheet or visit beaconproducts.com/sitesync.

Installation:
- Mounting options for horizontal arm, vertical arm or trunnion arm mounting available. Mounting hardware included.

Finish:
- Electrostatic powder-coat applied to fully pretreated and thoroughly cured. Finish is available in a variety of standard colors and high-performance colors. Super durable TGIC polyester powder coat finish is applied to a minimum thickness of 2.5 mils.
- The finish passes the ASTM B117 salt spray resistance test for 5000 hours. Available in standard colors and custom colors. Consult factory for standard and custom color availability.

Certifications/Ratings:
- Designed to meet ANSI C136.31 3G vibration standard for bridge and overpass mounting. Compatible with ANSI C136.31 mounting arm and tenon diameters.
- Certified to UL 1598, UL 8750 and CSA C22.2 #250.0 for Wet Locations.
- Certified for Wet Locations per ANSI C136.25 corrosion requirements and Near Fumaces.
- IDA approved.
- The products are approved by the Florida Fish and Wildlife Conservation Commission. Products also available as

Warranty:
Five year limited warranty. For complete details, visit beaconproducts.com/warranty.

Commercial/Industrial:
- Available with an optional passive infrared (PIR) motion sensor capable of dimming a matrix 360° around the luminaire. When no motion is detected by the PIR sensor, the luminaire returns to the wattage and lumen level chosen in the configurator. When motion is detected by the PIR sensor, the luminaire returns to the wattage and lumen level chosen in the configurator. Other motion sensor configurations are also available.
- Available with integral 0-10V wireless dimming, timed dimming with multiple areas or zones formed by master and multiple area luminaires (consult Beacon Products if unsure).
- In addition, your can be specified with **SiteSync™** wireless control system for occupancy, timed dimming and multi-zoning, while achieving high quality LED. For more information, see SiteSync™ data sheet or visit beaconproducts.com/sitesync.

Installation:
- Mounting options for horizontal arm, vertical arm or trunnion arm mounting available. Mounting hardware included.

Finish:
- Electrostatic powder-coat applied to fully pretreated and thoroughly cured. Finish is available in a variety of standard colors and high-performance colors. Super durable TGIC polyester powder coat finish is applied to a minimum thickness of 2.5 mils.
- The finish passes the ASTM B117 salt spray resistance test for 5000 hours. Available in standard colors and custom colors. Consult factory for standard and custom color availability.

Certifications/Ratings:
- Designed to meet ANSI C136.31 3G vibration standard for bridge and overpass mounting. Compatible with ANSI C136.31 mounting arm and tenon diameters.
- Certified to UL 1598, UL 8750 and CSA C22.2 #250.0 for Wet Locations.
- Certified for Wet Locations per ANSI C136.25 corrosion requirements and Near Fumaces.
- IDA approved.
- The products are approved by the Florida Fish and Wildlife Conservation Commission. Products also available as

Warranty:
Five year limited warranty. For complete details, visit beaconproducts.com/warranty.

PRODUCT IMAGE(S)



DIMENSIONS

A	B	C	D	Weight	EPA
29.9"	24.19"	14.25"	4.19"	25.0 lbs	1.2 ft²
(741 mm)	(614 mm)	(362 mm)	(106 mm)	(11.3 kg)	

MOUNTING OPTIONS



CERTIFICATIONS/LISTINGS:

SB · cULus · DLC

ORDERING INFORMATION

ORDERING EXAMPLE: VPL/96L-350/4AT/4W/UNV/A/DB/TPR-TL/4ESB-04/BC

VPL

SERIES	LED ENGINE	CCT/CRI	ROTATION	VOLTAGE	COLOR	OPTIONS
VPL Viper	64L-135 135W LED 4-pin	3KT 3000K, 70 CRI	Leave blank for no rotation	UNV 120-277V	BL Black Textured	P Fusing
80L-180 180W LED 4-pin	4KT 4000K, 70 CRI	L* Optic rotation left	120 120V	DB Dark Bronze Textured	DYS Light Gray Smooth	SSP Field Slotted
80L-220 220W LED 4-pin	5KT 5000K, 70 CRI	R* Optic rotation right	208 208V	DYS Light Gray Smooth	PS Platinum Silver Smooth	BC Backlight control (limited to Type 4W only)
96L-280 280W LED 4-pin			240 240V	WH White Textured		
96L-315 315W LED 4-pin			277 277V	CC Custom Color		
96L-395 395W LED 4-pin			347 347V			
			480 480V			

DISTRIBUTION
FR Type I Forward Throw
2 Type 2
3 Type 3
4 Type 4
4W Type 4 Wide
5QM Type 5QM
5QW Type 5QW
SR Type IR Rectangular
5W Type 5W Round Wide

MOUNTING
A Rectangular Arm (Standard) RAI for square or round pole
MAP Round Arm (Internally 3/4"Ø) or 2-3/8" OD Horizontal arm
K Knuckle (Internally PKD) bolt to 3/4" Ø or 2-3/8" OD horizontal arm or vertical tenon
WB Wall Bracket
AD Universal Arm for square pole
RD3 Universal Arm for 2.4"-4.1" round pole
AD4 Universal Arm for 4.2"- 6.3" round pole
AD5 Universal Arm for 6.4"- 8.3" round pole
AD6 Universal Arm for 8.4"-9.9" round pole

CONTROL OPTIONS
7PR 7-Pin Receptacle w/shorting cap (photocontrol, or wireless control provided by others)
7PR-SC 7-Pin Receptacle w/Shorting Cap
7PR-TL 7-Pin Receptacle w/Twist Lock photocontrol
SCDT 3-Pin Programmable Accessory Sensor w/ Daylight Sensor (120/277 volts only)
GEN1-DC Gen1 DIM/ADIM
SWP1 SiteSync Pro-Controller
SWPM1 SiteSync Pro-Controller w/ Sensor

HOUSE-SIDE SHIELD ACCESSORIES:
HSS/EVP-L/90-FB/CCX 90° shield front or back
HSS/EVP-L/90-LR/CCX 90° shield left or right
HSS/EVP-L/270-FB/CCX 270° shield front or back
HSS/EVP-L/270-LR/CCX 270° shield left or right
HSS/EVP-L/360/CCX Full shield

Specify finish with an asterisk (*). Refer to page 3 for color chart. Not available in DYS finish.

MOUNTING ACCESSORIES
VPL-AD-RP2 2.4"-4.1" Round Pole Adapter for 90 arm
VPL-AD-RP3 4.2"-6.0" Round Pole Adapter for 90 arm
VPL-AD-RP4 6.0"-8.3" Round Pole Adapter for 90 arm
VPL-AD-RP5 8.0"-9.5" Round Pole Adapter for 90 arm

* Quality workmanship is our standard of excellence.
* Tenon mounted arm accepts 2.0" O.D. (or 2.375" O.D. with optional tenon adapter) tenons and secures luminaire.
* Tenon must be ordered separately.
* Shielding and control devices must be ordered separately and installed in the field. Refer to field installation instructions for proper installation.
* Refer to Beacon Products' Universal Arm Mounting Guide for proper selection of universal arm.
* Not available with SR mounting option.
* Not available with RD3 mounting option.
* Not available with RD3 and AD4 mounting options.
* Not available with AD4 and AD5 mounting options.
* Not available with AD5 and AD6 mounting options.
* Not available with AD6 mounting option.

PHOTOCONTROL OPTIONS ORDERED SEPARATELY: Specify finish. Shipped separately unless factory installed. Additional photocontrols may be required for some applications. Refer to Beacon Products' website for more information. Not available with 4W optic.

Consult factory for other photocontrol options.

Button Photocontrol
Twist-Lock Photocontrol

LEFT ROTATED OPTIC **RIGHT ROTATED OPTIC**

Accessories and Services (Ordered Separately)

Catalog Number	Description
SCP-ADVANCE	Remote Service for SCP. If active, Select at least one per project to program and control the accessory sensor
SWPM2SP	SiteSync Intermate software loaded to USB flash drive for use with owner supplied PC (Windows based only). Includes SiteSync license, software and USB code bridge node.
SWPM2P	Windows based site manager software. Includes latest web connected software, SiteSync license and USB code bridge node.
SWPM2U	SiteSync USB code bridge node only. Order if a replacement is required or if an extra bridge node is required.
SWPTPM	SiteSync 7-Pin to Adapt Hubbell Sensor (Twist-Lock) Tenon 105-4600BC

Other SiteSync Pro-Controller options may be required for some applications. Refer to Beacon Products' website for more information.

Hubbell Control Solutions - Accessories sold separately:

Catalog Number	Description	NOS System
NXPSE-1010-1BW	Pro-Series Keypad (3-gang, 6x7.09 x 1Bw, Daylight Sensor with Hubbell Flash-and-Learn Bluetooth Radio, 120-480VAC	NX Distributed Intelligence™
NXP-RSE-L	10A Relay Module (1-gang or 3-gang, 6x7.09 x 1.0in, Daylight Sensor with wireless Radio,	wiSCALE™ Lighting Control

For additional information, please visit beaconproducts.com/hubbell-control-solutions

SiteSync 7-Pin Module

- Works with SiteSync Products in a new way
- Available as an accessory for new construction or retrofit applications, with existing 7-Pin receptacle
- Available on all products that have a 7-Pin receptacle

SWPM

PERFORMANCE DATA

# LED's	DRIVE CURRENT (MILLIAMPS)	SYSTEM WATTS	5K (5000K nominal, 70 CRI) DISTRIBUTION TYPE	LUMENS	LPW	B	U	G	4K (4000K nominal, 70 CRI) LUMENS	LPW	B	U	G	3K (3000K nominal, 70 CRI) LUMENS	LPW	B	U	G
84	525 mA	135W	2	17235	128	2	1	2	17082	126	2	1	2	16422	122	2	1	2
			3	17235	128	2	1	2	17082	126	2	1	2	16422	122	2	1	2
			4	16945	126	2	1	2	16794	124	2	1	2	16142	120	2	1	2
			5W	17235	128	4	1	2	17082	126	4	1	2	16422	122	4	1	2
			5QM	17235	128	3	1	2	17082	126	3	1	2	16422	122	3	1	2
			5QW	17235	128	4	1	2	17082	126	4	1	2	16422	122	4	1	2
			FR	17235	128	2	1	2	17082	126	2	1	2	16422	122	2	1	2
80	700 mA	180W	2	23080	128	2	1	2	22880	127	2	1	2	21990	122	2	1	2
			3	23080	128	2	1	2	22880	127	2	1	2	21990	122	2	1	2
			4	22690	126	2	1	2	22493	125	2	1	2	21618	120	2	1	2
			5W	23080	128	4	1	2	22880	127	4	1	2	21990	122	4	1	2
			5QM	23080	128	3	1	2	22880	127	3	1	2	21990	122	3	1	2
			5QW	23080	128	4	1	2	22880	127	4	1	2	21990	122	4	1	2
			FR	23080	128	2	1	2	22880	127	2	1	2	21990	122	2	1	2
50	700 mA	220W	2	27270	124	2	1	2	27041	123	2	1	2	25992	118	2	1	2
			3	27270	124	2	1	2	27041	123	2	1	2	25992	118	2	1	2
			4	26810	122	2	1	2	26586	121	2	1	2	25549	116	2	1	2
			5W	27270	124	4	1	2	27041	123	4	1	2	25992	118	4	1	2
			5QM	27270	124	3	1	2	27041	123	3	1	2	25992	118	3	1	2
			5QW	27270	124	4	1	2	27041	123	4	1	2	25992	118	4	1	2
			FR	27270	124	2	1	2	27041	123	2	1	2	25992	118	2	1	2
96	700 mA	280W	2	34645	124	2	1	2	34353	123	2	1	2	33019	118	2	1	2
			3	34645	124	2	1	2	34353	123	2	1	2	33019	118	2	1	2
			4	34068	122	2	1	2	33788	121	2	1	2	32477	116	2	1	2
			5W	34645	124	4	1	2	34353	123	4	1	2	33019	118	4	1	2
			5QM	34645	124	3	1	2	34353	123	3	1	2	33019	118	3	1	2
			5QW	34645	124	4	1	2	34353	123	4	1	2	33019	118	4	1	2
			FR	34645	124	2	1	2	34353	123	2	1	2	33019	118	2	1	2
96	875 mA	350W	2	41218	118	2	1	2	40878	117	2	1	2	39297	112	2	1	2
			3	41218	118	2	1	2	40878	117	2	1	2	39297	112	2	1	2
			4	40539	116	2	1	2	40206	115	2	1	2	38652	110	2	1	2
			5W	41218	118	4	1	2	40878	117	4	1	2	39297	112	4	1	2
			5QM	41218	118	3	1	2	40878	117	3	1	2	39297	112	3	1	2
			5QW	41218	118	4	1	2	40878	117	4	1	2	39297	112	4	1	2
			FR	41218	118	2	1	2	40878	117	2	1	2	39297	112	2	1	2
96	1000mA	395W	2	47060	119	2	1	2	46671	118	2	1	2	44870	114	2	1	2
			3	47060	119	2	1	2	46671	118	2	1	2	44870	114	2	1	2
			4	46287	117	2	1	2	45904	116	2	1	2	44130	112	2	1	2
			5W	47060	119	4	1	2	46671	118	4	1	2	44870	114	4	1	2
			5QM	47060	119	3	1	2	46671	118	3	1	2	44870	114	3	1	2
			5QW	47060	119	4	1	2	46671	118	4	1	2	44870	114	4	1	2
			FR	47060	119	2	1	2	46671	118	2	1	2	44870	114	2	1	2
96	1220mA	395W	2	51969	131	2	1	2	51539	130	2	1	2	49552	125	2	1	2
			3	51969	131	2	1	2	51539	130	2	1	2	49552	125	2	1	2
			4	51109	129	2	1	2	50679	128	2	1	2	48737	123	2	1	2
			5W	51969	131	4	1	2	51539	130	4	1	2	49552	125	4	1	2
			5QM	51969	131	3	1	2	51539	130	3	1	2	49552	125	3	1	2
			5QW	51969	131	4	1	2	51539	130	4	1	2	49552	125	4	1	2
			FR	51969	131	2	1	2	51539	130	2	1	2	49552	125	2	1	2

* Total harmonic distortion is less than 20% at maximum dimming level.
* Power factor is .90 or greater at full load.
* Lumen maintenance at 50,000 hours is 70% of initial lumens per IESNA LM-80-08 and projected per IESNA TM-21-11.
* Actual performance may differ as a result of end-use application, operating conditions and manufacturing variances.
* Specifications subject to change without notice.

PROGRESS LIGHTING

Project:
Fixture Type: LF01
Location:
Comments:

CYLINDER
wall mounted • damp location rated PROGRESS LED

Specifications:

P5675-20/30K

Description:
The P5675 Series are ideal for a wide variety of interior and exterior applications including residential and commercial. Key attributes feature a 120V dimming current source and dimmable 0-10V constant current driver. This modular approach results in an energy efficient luminaire that offers performance, ease and supply benefits.

Construction:
Aluminum housing
Antique Bronze (-BA) powder coat
Die cast and extruded aluminum construction
Metal shade
Wide-bay dimming to 5% brightness with most 0-10V type dimmers (See Dimming Notes)
Aluminum cavity + tempered ½" hexagonal recessed outer lens
Mounting: Direct wire box mounted
6" of wire supplied
Wet location listed when used with 20W/30K/40K driver (LED engine only)

Performance:
Number of Sockets: 1
Input Power: 17.5W
Input Voltage: 120V
Input Frequency: 60Hz
Luminaire Lumens (Nominal): 1550 lm (3,000K, 90 CRI)
Luminaire CCT: 3000K
CRI: 90
Lifetime: 50,000 (L70) hours
Operating Temperature: 0°F to 120°F
Min. Start Temperature: -20°F
Warranty: 5 year warranty
Certifications: cULus, Wet Rated

Images:

Dimensions:
Width: 9"
Height: 11"
Depth: 6 7/8"
H/CTR: 5"

Catalog Number:

Base	Finish	Color Temp	CRI
P5675	20 - Antique Bronze	30K - 3000K	Blank - 90 CRI

For more information visit our website: www.progresslighting.com

Progress Lighting • 701 Millennium Boulevard • Greenville, SC 29607

PROGRESS LIGHTING

CYLINDER
wall mounted • damp location rated PROGRESS LED

Photometrics: P5675-20/30K

Test Report Date	20180116
Test Voltage	120
Input Frequency	60Hz
Input Current	0.15A
Input Power	17.5W
Power Factor	.9090
THD	12.6%
Ballast	ADC 20W-0T-Non-15-120v-K
Operating Temperature	-20°F to 77°F
Luminaire	Test

Photometrics available upon request

Polar Intensity Diagram



Test No. 16-0003
Tested at 25°C Ambient in Accordance to IESNA LM-79-2008

CANDELA DISTRIBUTION

DEG	CANDELA
0	473
5	466
15	458
25	441
35	395
45	298
55	189
65	89
75	37
85	9
90	0
95	4
105	10
115	14
125	12
135	7
145	3
155	1
165	0

ZONAL LUMEN SUMMARY

ZONE	LUMENS	%LUMINAIRE
0-30	1552	100%
0-40	1552	100%
0-60	1552	100%
0-90	1552	100%
90-120	0	0%
90-130	0	0%
90-150	0	0%
90-180	0	0%
0-180	1552	100%

COEFFICIENTS OF UTILIZATION

Zonal Cavity Method

Effective Ceiling Reflectance	80	70	50	30	10	0
Effective Wall Reflectance	50	50	50	30	10	0
Room Cavity Ratio	Coefficients of Utilization					
0	1.00	1.00	1.00	1.00	1.00	1.00
1	0.96	0.93	0.89	0.86	0.83	0.81
2	0.92	0.87	0.80	0.74	0.69	0.65
3	0.88	0.82	0.72	0.64	0.57	0.53
4	0.85	0.77	0.65	0.55	0.48	0.43
5	0.81	0.72	0.58	0.48	0.40	0.35
6	0.78	0.68	0.53	0.42	0.34	0.29
7	0.75	0.64	0.48	0.37	0.29	0.24
8	0.72	0.61	0.44	0.33	0.25	0.20
9	0.70	0.58	0.41	0.30	0.22	0.17
10	0.67	0.55	0.38	0.27	0.19	0.15

RULE JOY TRAMMELL + RUBIO, INC.
ARCHITECTURE | INTERIOR DESIGN
300 Galleria Parkway Suite 740 Atlanta, Georgia 30339
770-661-1492 (phone) 770-661-1493 (fax)
www.rjtdesign.com

THESE DRAWINGS ARE THE PROPERTY OF RULE JOY TRAMMELL + RUBIO, LLC AND NOT TO BE REPRODUCED WITHOUT WRITTEN CONSENT

PRINTED

DATE	ISSUE/REVISION
11/01/18	ISSUED FOR PERMIT

JB Electrical Design, P.C.
Electrical Consulting Engineers
8340 89th Ave N.
Minneapolis, MN 55445
763.486.0965
jeff@jbelectricaldesign.com
JBED Proj. No. 2018-065
©2018 by JB Electrical Design, PC

GEORGIA REGISTERED No. PROFESSIONAL ENGINEER JEFFREY A. BLAND
11/1/18

EXTENDED STAY AMERICA
POOLER, GA

LIGHT FIXTURE CUTSHEETS

COMMISSION NO: 18-120.00

DRAWING NO:
E112

Order Plans @ www.LDLine.com