

ROOM NO.	ROOM NAME	FLOOR	GROUT	BASE	GYP BD THICKNESS	SOUND ATTENUATION BATS	LPB THICKNESS	ROOM FINISH SCHEDULE:								REMARKS	ROOM NO.		
								TOP WALL		RIGHT WALL		BOTTOM WALL		LEFT WALL				CEILING	
								LOWER	UPPER	LOWER	UPPER	LOWER	UPPER	LOWER	UPPER			MAT.	FIN.
101	VESTIBULE	PORC-1	GR-2	VB-1	1/2"		3/4"	AL/GL	AL/GL	AL/GL	AL/GL	AL/GL	AL/GL	AL/GL	SAPC	--	9'-11"	101	
102	SALES	PORC-1	GR-2	VB-1/CPB/SSB	1/2" & 1/2" M.R. (A)		3/4"	LPB-1	GYP BD	AL/GL-L1	LPB-1	GYP BD	AL/GL	GYP BD	EXP	--	VARIES	102	
104	WOMENS	PORC-2	GR-2	SS-3	1/2" M.R. (B)	X		T-2/GR-1	GYP BD	T-2/GR-1	GYP BD	T-2/GR-1	GYP BD	T-2/GR-1	SAPC	--	9'-6"	104	
105	HALL	PORC-2	GR-2	VB-1	1/2"	X	3/4"	LPB-1	GYP BD	LPB-1	GYP BD	LPB-1	GYP BD	LPB-1	SAPC	--	9'-6"	105	
106	MENS	PORC-2	GR-2	SS-3	1/2" M.R. (B)	X		T-2/GR-1	GYP BD	T-2/GR-1	GYP BD	T-2/GR-1	GYP BD	T-2/GR-1	SAPC	--	9'-6"	106	
107	BREAKROOM	PORC-2	GR-2	VB-1/SS-3	1/2"	X		T-1/GR-5		GWB		GYP BD		T-5/GR-4	SAPC	--	10'-0"	107	
108	OFFICE	PORC-2	GR-2	VB-1	1/2" MLD. R. (C)	X		GYP BD		GYP BD		GYP BD		GYP BD	SAPC	--	10'-0"	108	
109	UTILITY AREA	CONC	--	CPB	1/2"			PLWD	GYP BD	PLWD	GYP BD	PLWD	GYP BD	PLWD	GYP BD	EXP-1	--	VARIES	109
110	BACK ROOM	CONC	--	CPB	1/2"			PLWD	GYP BD	PLWD	GYP BD	PLWD	GYP BD	PLWD	GYP BD	EXP-1	--	VARIES	110

FINISH NOTES:	
1	SEE REFLECTED CEILING PLAN FOR ALL CEILINGS AND SOFFITS.
2	REFER TO APPENDIX 'A' FOR ITEMS FURNISHED BY OWNER AND INSTALLED BY CONTRACTOR.
3	REFER TO APPENDIX 'B' FOR ITEMS PROVIDED BY OWNER.
4	DO NOT PAINT GALVANIZED DOOR THRESHOLDS.
5	USE SOLVENT TO REMOVE ALL MANUFACTURER WORDING ON EXPOSED PVC PIPING.
6	PAINT ALL EXPOSED PIPING TO MATCH ADJACENT CEILING/WALL COVERING.
7	SEE SPECIFICATION SECTION 099100 FOR PAINT SYSTEMS.
8	REFER TO PAINT FINISH SCHEDULES FOR TREATMENT AND COLOR OF WALL FINISHES.

GYP BD KEYNOTES:	
A	MR (MOISTURE RESISTANT) GYP BD TO EXTEND UP TO 2' ABOVE T.O. COOLER AND FREEZER. ALL PARTITIONS SURROUNDING COOLER AND FREEZER. MR GYP BD TO BE INSTALLED UP TO 8' AFF AT ALL WALLS SURROUNDING MULTIDECK UNITS AND ALONG ENTIRE LENGTH OF FIRST AISLE.
B	MR (MOISTURE RESISTANT) GYP BD TO EXTEND TO CEILING ALL WALLS.
C	USE MOLD RESISTANT (PAPERLESS) GYP BD ON WALLS ADJACENT TO FREEZER. APPLY VAPOR BARRIER BETWEEN GYP BD AND STUDS.

SOUND ATTENUATION BATS:	
1	PROVIDE SOUND BATS FOR FULL HEIGHT OF WALL ON ALL INTERIOR PARTITIONS SURROUNDING ROOMS WITH 'X' IN SCHEDULE ABOVE.

GYP BD NOTES:	
1	AT INTERIOR PARTITIONS. RUN WALL FRAMING AND GYP BD TO BOTTOM OF ROOF DECK.
2	AT EXTERIOR WALLS RUN GYP BD TO B.O. DECK.
3	SEE INTERIOR ELEVATIONS FOR LOCATIONS OF GYP BD SYSTEMS. SEE FINISH MATERIAL SCHEDULE AND PAINT COLOR SCHEDULE ON THIS PAGE FOR MORE INFORMATION.

FINISH MATERIAL SCHEDULE:		DESCRIPTION - COLOR		REMARKS
AL/GL	ALUMINUM & GLASS STOREFRONT	BY CONTRACTOR	CLEAR ANODIZED	SEE ELEVATIONS FOR GLAZING TYPES
CONC.	CONCRETE SLAB	BY CONTRACTOR		SEE PROJECT MANUAL - SECTION 033000
EXP	EXPOSED STRUCTURE	BY CONTRACTOR	PT-2 / CL-1: FLAT	SALES FLOOR - GC TO ENSURE ALL JOIST AND JOIST GIRDER TAGS ARE PROPERLY SECURED TO JOIST WEAVING AND CONCEALED FROM VIEW PRIOR TO PAINTING.
EXP-1	EXPOSED STRUCTURE	BY CONTRACTOR	NO PAINT	BACK ROOM/ABOVE CEILINGS
FRP	FIBER REINFORCED PLASTIC	BY CONTRACTOR	#151 LIGHT GRAY	SEE PROJECT MANUAL - SECTION 064400
GR-1	GROUT	MAPEI	#47 CHARCOAL	GROUT FOR T-2 AND T-3
GR-2	GROUT	TEC	POWER GROUT #941 RAVEN	GROUT FOR PORC-1 & PORC-2; PROVIDED BY OWNER
GR-3	GROUT	MAPEI	#00 WHITE	GROUT FOR T-4
GR-4	GROUT	MAPEI	#02 PEWTER	GROUT FOR T-5
GR-5	GROUT	MAPEI	#111 HICKORY	GROUT FOR T-1
GYP BD	GYP SUM WALL BOARD	BY CONTRACTOR		SEE PROJECT MANUAL - SECTION 092900
LPB-1	LAMINATED PARTICLE BOARD - WAINSCOT	FORMICA	#5883-58 PECAN WOODLINE	COORDINATE w/ MILLWORK VENDOR TO BE INSTALLED 1/2" AFF - REFER TO APPENDIX A.
LPB-2	LAMINATED PARTICLE BOARD - SACKING COUNTER, WINDOW SILLS AND CABINERY	FORMICA	#5884-58 CHESTNUT WOODLINE	COORDINATE w/ MILLWORK VENDOR. REFER TO APPENDIX A.
LPB-3	LAMINATED PARTICLE BOARD - COUNTER/TOPS OFFICE	FORMICA	#961-58 FOG	COORDINATE w/ MILLWORK VENDOR. REFER TO APPENDIX A.
LPB-4	NOT USED			
LPB-5	LAMINATED PARTICLE BOARD - COOLER AND FREEZER VALANCES	FORMICA	#2297-58 TERRILL	COORDINATE w/ MILLWORK VENDOR. REFER TO APPENDIX A.
PLWD	PLYWOOD - PAINTED	BY CONTRACTOR	PT-7 / CL-6: SEMIGLOSS	BACK ROOM; SEE PROJECT MANUAL - SECTION 061053 (RUB PLWD VERTICAL)
PORC-1	PORCELAIN TILE - THICK SET	ARGELITH	LIGHT GRAY R9, 12"x12" (RUNNING BOND W/ STRAIGHT LINES RUNNING IN THE SHORT DIMENSION OF THE SALES FLOOR)	TILE FURNISHED AND INSTALLED BY OWNER. SEE PROJECT MANUAL - SECTION 093000: GROUT: GR-2.
PORC-2	PORCELAIN TILE - THIN SET	ARGELITH	LIGHT GRAY R9, 12"x12" (RUNNING BOND W/ STRAIGHT LINES RUNNING IN THE SHORT DIMENSION OF THE SALES FLOOR)	TILE FURNISHED BY OWNER. INSTALLED BY GC. SEE PROJECT MANUAL - SECTION 093000: GROUT: GR-2.
SAPC	SUSPENDED ACOUSTIC PANEL CEILING	BY CONTRACTOR	WHITE	SEE PROJECT MANUAL - SECTION 095113
SS-1	SCHLUTER STRIP	SCHLUTER	SCHIENE E: STAINLESS STEEL FINISH	THIN SET PORCELAIN TILE TRANSITION EDGE - SIZE TO FIT TILE. INCLUDE ALL SPECIAL CORNER AND TRIM SHAPES (GC FURNISH AND INSTALL).
SS-2	SCHLUTER STRIP	SCHLUTER	ROHDEC: DB 14 A E; SATIN ANODIZED ALUMINUM FINISH	WALL TILE EDGE - SIZE TO FIT TILE. INCLUDE ALL SPECIAL CORNER AND TRIM SHAPES (GC FURNISH AND INSTALL).
SS-3	SCHLUTER STRIP	SCHLUTER	DILEX: AHK: ANODIZED ALUMINUM FINISH	WALL TILE BASE - SIZE TO FIT TILE. INCLUDE ALL SPECIAL CORNER AND TRIM SHAPES (GC FURNISH AND INSTALL).
SSM-1	SOLID SURFACE MATERIAL - COUNTER BREAKROOM	WILSONART	#9175 ML(3) AVALANCHE MELANGE	COORDINATE w/ MILLWORK VENDOR. REFER TO APPENDIX A.
T-1	GLAZED TILE	DALTILE	WILLOW BEND - DARK BROWN W803, 6"x6" (1/3 BOND)	SACKING COUNTER & BREAK ROOM W/ ACCENT TILE (GC FURNISH AND INSTALL) GROUT: GR-5
T-2	PORCELAIN TILE	DALTILE	UNITY COLORBODY ASHGREY P405, UNPOLISHED, 12"x24" (RUNNING BOND)	RESTROOM W/ ACCENT TILE (GC FURNISH AND INSTALL) GROUT: GR-1
T-3	PORCELAIN TILE	DALTILE	AVORIO P400 MODELLER, UNPOLISHED, 12"x24" (LINEAR BOND)	RESTROOM ACCENT TILE (GC FURNISH AND INSTALL) GROUT: GR-1
T-4	GLAZED TILE	DALTILE	RITTENHOUSE SQUARE WHITE 010, 6"x6" (RUNNING BOND)	SALES FLOOR WALL ACCENT TILE (GC FURNISH AND INSTALL) GROUT: GR-3
T-5	PORCELAIN TILE	DALTILE	RITTENHOUSE SQUARE - MESA DESERT GRAY X714, 3"x6" (RUNNING BOND)	BREAK ROOM BACKSPLASH TILE; BULLNOSE @ REFRIGERATOR END (GC FURNISH AND INSTALL) GROUT: GR-4
VB-1	VINYL BASE	ROPPE	193 BLACK - BROWN	SEE PROJECT MANUAL - SECTION 096513
WP-1	WOOD PANEL	ARCH SYSTEMS	INTERIOR OVEN ECO-PANELS - W/VEP017	FOR NATIONAL ACCOUNT ORDERING, CONTACT PACIFIC COOPER OF ARCH SYSTEMS VIA PHONE: 844-460-8222 OR EMAIL: RCOOPER@ARCHSYSTEMS.COM AND CC MRAMFELLIE@ARCHSYSTEMS.COM

WALL AND SURFACE PROTECTION SCHEDULE:		DESCRIPTION - COLOR		REMARKS
BG	BUMPER GUARD	MCCOY	STEEL	SEE PROJECT MANUAL - SECTION 102600
BR	BUMPER RAIL	MCCOY	CART STOP SSR	SEE PROJECT MANUAL - SECTION 102600
BR	BUMPER RAIL	MCCOY	CART STOP UG150 12"H. - 101 (GREY)	SEE PROJECT MANUAL - SECTION 102600
CG-A	CORNER GUARD	BY CONTRACTOR	CLEAR ANODIZED ALUMINUM	SEE PROJECT MANUAL - SECTION 102600
CG-ST	CORNER GUARD	BY CONTRACTOR	STEEL - PT-3 / CL-6: SEMIGLOSS	SEE PROJECT MANUAL - SECTION 055000
CPB	CONCRETE BUMPER	BY CONTRACTOR	PT-3 / CL-6: SEMIGLOSS (BACK ROOM, COOLER, FREEZER)	SEE DETAIL 7/A-601 FOR COLOR BREAK
CRTB	CART BUMPER	BY CONTRACTOR	CONC NATURAL - RUBBED FINISH	SEE DETAIL D1/S301
CT-PL	CART RAIL	BY CONTRACTOR	GALVANIZED	SEE PROJECT MANUAL - SECTION 055000
KICK PLATE	KICK PLATE	BY CONTRACTOR	STAINLESS STEEL	SEE PROJECT MANUAL - SECTION 087100
SSB	STAINLESS STEEL BUMPER RAIL	LAFOLLETTE CO	STAINLESS STEEL	
STB	STEEL TUBE BUMPER FLOOR MOUNTED	BY CONTRACTOR	PT-3 / CL-5: SEMIGLOSS	SEE PROJECT MANUAL - SECTION 055000

BOLLARD SCHEDULE:		DESCRIPTION - COLOR		REMARK
BLRD-1	NOT USED			
BLRD-2	10" Ø BOLLARD	BY CONTRACTOR	STEEL PIPE FILLED W/ GROUT PT-19 / CL-4: SEMIGLOSS	@ LOADING DOCK - SEE STRUCTURAL DWG.
BLRD-3	3" Ø BOLLARD	BY CONTRACTOR	GALV STEEL PIPE POST	@ CART CORRAL - CENTER WITHIN ROWS. ATTACH OWNER PROVIDED STARTER CHAINS FOR CART SYSTEM - COORD LAYOUT WITH ALDI CONSTRUCTION REPRESENTATIVE. SEE PROJECT MANUAL - SECTION 059000
BLRD-4	6" Ø STEEL PIPE BOLLARD W/ COVER	McCUE CORPORATION	316 STAINLESS STEEL POST COVER BRUSHED FINISH	FOR ORDERING, CONTACT JOHN ROMANO OF MCCUE CORP. 574-532-0221 / ROMKITG@AOL.COM

EQUIPMENT AND ACCESSORY SCHEDULE:		DESCRIPTION - COLOR		REMARK
AC-X	TOILET ROOM ACC.	BY CONTRACTOR		SEE PROJECT MANUAL - SECTION 102800
MDU	MULTIDECK UNITS W/ INTEGRAL FASCIA	HUSSMANN		BY OWNER
TR-1	TRASH RECEPTACLE	DAWN ENTERPRISES	MODEL # RP40S-ALDI-FACTORY FINISH	FOR ORDERING, CONTACT SARAH ANDERSON OF DAWN ENTERPRISES V. PHONE: 800-262-3211 X118 OR EMAIL: SARAH@DWN.COM
R-1	REFRIGERATOR	WHIRLPOOL	#WR178FZDM - STAINLESS STEEL	CONTRACTOR TO PROVIDE
DW-1	DISHWASHER	WHIRLPOOL	#WDF520S4FS - STAINLESS STEEL	CONTRACTOR TO PROVIDE
MW-1	MICROWAVE OVEN	WHIRLPOOL	#WMH32519HZ - STAINLESS STEEL	CONTRACTOR TO PROVIDE
TV-1	TELEVISION	VIZIO	#M50	CONTRACTOR TO PROVIDE, INCLUDING SOLID WALL MOUNTING AND COMPATIBLE FIXED MOUNTING BRACKET

CG-A SCHEDULE (I.N.C.)		REMARKS	
INSIDE CORNERS	1" x 1" x 1/16" x 80" LENGTHS	INSTALL AT LPB CORNER. OWNER FURNISHED CONTRACTOR INSTALLED	
OUTSIDE CORNERS	1/2" x 1/16" x 80" LENGTHS	INSTALL AT LPB ONLY. OWNER FURNISHED CONTRACTOR INSTALLED	
J CHANNEL	3/4" x 9/16" LENGTHS	INSTALL AT ALL LPB EDGES. LONG LEG ON THE BACK SIDE OF LPB AND SHORT LEG LEFT EXPOSED. OWNER FURNISHED CONTRACTOR INSTALLED	
ANGLE	1/2" REGLET 3/8"-50	INSTALL AT BOTTOM OF GYP. BD. ABOVE COOLER AND FREEZER DOORS. CONTRACTOR PROVIDED	

INTERIOR MTL. STUD SCHEDULE (I.N.O.):			
HEIGHT OF STUD	GAUGE	SPACING (I.N. O.C.)	
5'-0"	20	16	
15'-0"	18	16	
> 20'-0"	16	16	

ICC DEPTH INDICATED ON DRAWINGS

3. STRUCTURAL DRAWINGS & PROJECT SPECIFIC LIGHT GAUGE SHOP DRAWINGS SUPERSEDE THIS TABLE

THIS TABLE IS FOR GENERAL REFERENCE ONLY. STUD MANUFACTURER'S SPAN TABLES SHOULD SUPERSEDE THIS TABLE BASED ON STUD DESIGNATION SELECTED AND SPAN REQUIREMENTS.

ICC WORK REQUIREMENTS FOR G.C. (SOME ITEMS FOR RENOVATIONS ONLY):	
1	TILE VENDOR: 704-504-5544
2	STORE TO BE WATER TIGHT AND WIND PROOF.
3	A WATER SUPPLY IN A CONVENIENT LOCATION, PREFERABLY INSIDE THE BUILDING.
4	ALL AREAS, INCLUDING SMALL ROOMS, TO BE WELL LIT PRIOR TO THE START DATE.
5	ACCESS TO MULTIPLE STANDARD POWER SOCKETS INSIDE THE STORE.
6	THE 1ST VISIT WILL INVOLVE ICC INSTALLING ALL OF THE NEW TILE AREAS. PLEASE BOOK THIS DATE 8 WEEKS PRIOR TO THE START DATE.
7	THE 2ND VISIT WILL INVOLVE ICC MAKING ALL THE REPAIRS ON THE EXISTING FLOOR. THIS CREW WILL NOT BE ABLE TO INSTALL ANY NEW AREAS. PLEASE BOOK THIS DATE IN 4 WEEKS PRIOR TO THE START DATE. PLEASE PROVIDE AN ACCURATE COUNT OF THE TILES TO BE REPLACED AT THIS TIME.
8	GC TO SEND A PLAN AND PHOTOS SHOWING THE EXACT LOCATION OF ALL AREAS TO BE TILED. 4 WEEKS PRIOR TO THE ICC START DATE.
9	GC TO ORDER TILE DIRECTLY FROM ALDI. EACH PALLET IS 360SQFT. PLEASE ORDER 1 EXTRA PALLET FOR SPOT REPAIRS. GC TO UNLOAD TILE WHEN DELIVERED TO JOBSITE. TILE TO BE STORED ON THE SALES FLOOR. TILE WILL BE DELIVERED PRIOR TO INSTALLERS ARRIVING AT THE JOBSITE. DELIVERIES TO BE AGREED WITH ICC PM.
10	ICC TO HAVE ACCESS TO GC'S FORKLIFT.
11	ICC TO HAVE USE OF GC'S DUMPSTER.
12	GC TO COMPLETE AS MUCH OVERHEAD WORK AS POSSIBLE PRIOR TO ICC STARTING.
13	A DESIGNATED MIXING AND MATERIAL STORAGE AREA TO BE AVAILABLE CLOSE TO AN ENTRANCE TO THE SALES FLOOR. IF YOU NEED US TO START TILING AT THE FRONT OF THE STORE THEN THE MIXING STATION NEEDS TO BE AT THE REAR, AND VICE VERSA.
14	ANY CONNECTIONS TO EXISTING TILE ARE TO BE CUT CLEAN ALONG A GROUT JOINT. FOR THE LW AND SW PROJECTS A STRAIGHT AND CONSISTENT LINE ALONG THE EXISTING TILE IS TO BE PROVIDED, WHICH MEANS POTENTIALLY REMOVING UP TO 3 ROWS OF TILE.
15	A 2' MUDBED WILL BE MIXED AND PUMPED INTO THE STORE. THE TILE IS THEN LAID ON TOP AND VIBRATED INTO THE MUDBED. ALL MUDBED AREAS ARE TO BE READY AT THE SAME TIME.
16	ICC WILL BE WORKING A MINIMUM OF 12HR DAYS INCLUDING SATURDAYS AND SOME SUNDAYS. TYPICAL INSTALLATION TIME FOR THE SALES FLOOR, OFFICE, BATHROOMS, BREAKROOM AND HALLWAY IS 15 DAYS.
17	GC AND OTHER SUBCONTRACTORS NOT TO WALK ON NEW TILE AREAS FOR 3 DAYS AFTER INSTALLATION. AFTER SPEAKING TO ICC FOREMAN.
18	GC AND OTHER SUBCONTRACTORS NOT TO DRIVE ANY LIFTS OR HEAVY MACHINERY ON THE TILE FOR 10-14 DAYS AFTER INSTALLATION. ROLLING SCAFFOLDS CAN BE USED AFTER 3-5 DAYS. THE ICC FOREMAN WILL AGREE TO ACCESS DAYS/DATES WHILE ON THE JOBSITE.
19	GC WILL NEED TO WASH THE FLOOR PRIOR TO ALDI HAND-OVER. FILA DETERDIX OR A HIGH SPEC GROUT HAZE REMOVER IS RECOMMENDED (SEE SPEC SECTION 093000). PLEASE CALL ICC FOR FURTHER RECOMMENDATIONS.

PAINT COLOR SCHEDULE:				
MAT. KEY	KEY DESCRIPTION	MANUFACTURER	DESCRIPTION - COLOR	REMARKS
CL-1	PAINT COLOR	SHERWIN WILLIAMS	#7510 CHATEAU BROWN	
CL-2	PAINT COLOR	SHERWIN WILLIAMS	#6071 POPULAR GRAY	
CL-3	PAINT COLOR	SHERWIN WILLIAMS	#6073 PERFECT GREIGE	USED ABOVE PAINT BREAK LINE ONLY WITH SUSPENDED CEILING
CL-4	PAINT COLOR	SHERWIN WILLIAMS	SAFETY YELLOW	
CL-5	PAINT COLOR	SHERWIN WILLIAMS	#7504 KEYSTONE GRAY	
CL-6	PAINT COLOR	SHERWIN WILLIAMS	#7073 NETWORK GRAY	
CL-7	PAINT COLOR	SHERWIN WILLIAMS	#7015 REPOSE GRAY	
CL-8	PAINT COLOR	SHERWIN WILLIAMS	#7757 HIGH REFLECTIVE WHITE	
PT-X	PAINT SYSTEM	BY CONTRACTOR		SEE PAINT SYSTEM SCHEDULE ON THIS SHEET. REFER TO SPEC SECTION 099100 FOR PRODUCT REQUIREMENTS.

NOTE: PAINT COLORS MUST BE PROVIDED BY MANUFACTURER INDICATED; NO SUBSTITUTIONS WILL BE ACCEPTED FOR COLOR

INTERIOR PAINT SYSTEM SCHEDULE					
PT #	SYSTEM	SUBSTRATE	SYSTEM	COLOR	REMARKS
PT-1	LATEX EGG SHELL	CONCRETE BLOCK	1C. PRIMER B25W25 1C. B31-2600 1C. B31-2600	CL-6	EXPOSED CMU IN BACK ROOM WHEN APPLICABLE
PT-2	DRY-FALL	EXPOSED STEEL WOOD, DUCTS, CONDUIT & SCRM	1C. PRIMER B66-1560 1C. B66-1560	CL-1	CEILING OVERHEAD @ SALES FLOOR. COLLECTOR AND DUCTWORK - CAULK ALL JUNCTIONS PRIOR TO PAINT AND PAINT
PT-3	LATEX SEMI-GLOSS	STEEL & CONC.	1C. PRIMER B66-310 1C. B66-650 1C. B66-650	CL-5 @ DOORS AND FRAMES CONC. PALLET BUMPER CL-5 @ SALES FLOOR ROOM - SEE DETAIL 7/A-601 CL-6 @ COLUMNS AND G IN BACK ROOM	
PT-4	LATEX FLAT	GALVANIZED METAL GRILLES	1C. PRIMER B66-310 1C. B66-650 1C. B66-650	CL-2 @ SALES FLOOR CL-6 @ BACK ROOM	
PT-5	LATEX EGG SHELL	GYP SUM BOARD	1C. PRIMER B25W25 1C. B20-2600 1C. B20-2600	CL-1 @ RESTROOMS, OFFICE, BREAK ROOM @ BACK ROOM UPPER WALLS	
PT-6	LATEX FLAT	GYP SUM BOARD	1C. PRIMER B25W25 1C. B20-2600 1C. B20-2600	SALES UPPER WALLS	
PT-7	LATEX SEMI-GLOSS	PLYWOOD AND TRIM	1C. PRIMER B25W25 1C. B31 1C. B31	VESTIBULE AND HALL CL-8 @ CEILINGS	
PT-8	WATER-BORNE URETHANE	STEEL	1C. PRIMER B66-100 1C. B65-720 1C. B65-720	CL-4 @ LOADING DOCK	EDGE OF OVERHEAD DOOR OPENING AND TRACK GUARDS
PT-9	WATER-BORNE EPOXY	CONCRETE	1C. PRIMER 3460 WBE 1C. 3460 WBE/S150-15 1C. 4408	CL-6	OPTIONAL FLOOR OF COOLER ONLY WHEN REQUIRED BY CONSTRUCTION MANAGER
PT-10	WATER-BORNE EPOXY	CONCRETE	1C. PRIMER 8100 1C. 8100 1C. 8100	CL-4	WARNING STRIPING @ BACK ROOM 109 @ FLAP DOORS, EGRESS DOOR, MANAGER'S DESK, AND POWER EQUIPMENT. STRIPING TO BE 4" WIDE W/ 12" SPACING IN-BETWEEN

EXTERIOR PAINT SYSTEM SCHEDULE					
PT #	SYSTEM	SUBSTRATE	SYSTEM	COLOR	REMARKS
PT-15	LATEX SATIN	CAST CONCRETE	1C. PRIMER A24W8300 1C. K43 1C. K43	AS SELECTED BY OWNER	EXPOSED FOUNDATION WALLS WHERE NOTED
PT-16	URETHANE GLOSS	CONCRETE BLOCK	1C. PRIMER A2W200 1C. 446-100 1C. B45-720	AS SELECTED BY OWNER	DUMPSTER INTERIOR ENCLOSURE WALLS ONLY WHEN SHOWN OR REQUIRED BY CONSTRUCTION MANAGER
PT-17	LATEX SATIN	EXISTING EIFS /STUCCO	1C. PRIMER B28W2600 1C. B20-2600 1C. B20-2600	AS SELECTED BY OWNER	ONLY WHEN SHOWN OR REQUIRED BY CONSTRUCTION MANAGER
PT-18	LATEX SATIN	P.T. WOOD	1C. PRIMER B24W804 1C. K43 1C. K43	AS SELECTED BY OWNER	DUMPSTER ENCLOSURE ROOF FRAMING WHERE SHOWN OR REQUIRED BY CONSTRUCTION MANAGER
PT-19	LATEX GLOSS	STEEL	1C. PRIMER 646-100 1C. B65-720 1C. B65-720	CL-5 OR AS SELECTED BY OWNER	UNTELS, RAILINGS, GATE FRAMES, CART GUIDES, BOLLARDS, OVERHEAD DOOR FRAMES, MISC. EXPOSED STEEL
PT-20	LATEX OVER PRIMER SYSTEM	CMU	1C. PRIMER A24W200 1C. K43 1C. K43	AS SELECTED BY OWNER	EXPOSED CMU

NOTE: ALL PAINTS ARE FROM SHERWIN-WILLIAMS NATIONAL ACCT. CONTACT: TODD MCMARTIN @ 813-817-1714 / TODD.R.MCMARTIN@SHERWIN.COM

THERMAL INSULATION SCHEDULE				
LOCATION	MIN. R VALUE	INSULATION TYPE	DESIGN STANDARD	REMARKS
UNDER SLABS	30	TYPE IV EXTRUDED-POLYSTYRENE BOARD INSULATION		PROVIDE UNDER FREEZER SLAB
PERIMETER WALL INSULATION (SUPPORTING BACKFILL)	10	EXTRUDED POLYSTYRENE FOAM BOARD INSULATION	DOW STYROFOAM CAVITYMATE	PROVIDE AT FOUNDATION PERIMETER AS SHOWN ON DRAWINGS
CONTINUOUS WALL INSULATION	10.1	FOIL-FACED POLYSOCYANURATE BOARD INSULATION	DOW THERMAX XARMOR (CI) EXTERIOR INSULATION	PROVIDE AT EXTERIOR STUD FACE OF EXTERIOR PERIMETER WALLS AS SHOWN ON DRAWINGS
CONCEALED BUILDING INSULATION	14.8 3.7/INCH	OPEN-CELL SPRAY POLYURETHANE FOAM	ICYNENE CLASSIC (LD-C-50)	PROVIDE AT PERIMETER WALL STUDS AS SHOWN ON DRAWINGS - THERMAL BARRIER OF EITHER FULL HEIGHT 1/2" GYP. BD. OR INTUMESCENT COATING REQUIRED; SEE SPECIFICATIONS; GC TO PROVIDE BASED ON COST ANALYSIS
METAL STUDS & GYP BD PARTITIONS	N/A	SOUND ATTENUATION BLENKETS		PROVIDE PER ROOM FINISH SCHEDULE
CONCEALED SPACES	3.7/INCH	OPEN-CELL SPRAY POLYURETHANE FOAM	ICYNENE CLASSIC (LD-C-50)	
ROOF INSULATION	5.71/INCH TOTAL: 24	POLYSOCYANURATE BOARD INSULATION	CLOSE-CELL FOAM CORE FIBER-REINFORCED ORGANIC FELT FACING	CONFIRM REQUIRED INSULATION THICKNESS TO OBTAIN DESIGN R-VALUE WITH MANUFACTURER

INSULATION NOTES:
1. MINIMUM 'R' VALUE BASED ON (LTR) LONG-TERM THERMAL RESISTANCE VALUE PER ASTM C1289.



American Institute of Architects

310 MILLS AVE. GREENVILLE, SC 29605
864.242.9881
plans@narramore.net