


submission	Date
OWNER REVIEW	11/01/2018
BID SET	11/01/2018
PERMIT SET	11/01/2018

#	Description	Date
---	-------------	------



SECTION 09 90 00 - PAINTING

1. GENERAL

1.1 SUMMARY

- A. SURFACE PREPARATION AND PRIMING IN ADDITION TO SHOP-PRIMING AND SURFACE TREATMENT SPECIFIED UNDER OTHER SECTIONS
- B. PAINTING AND FINISHING OF EXPOSED INTERIOR ITEMS AND SURFACES
- C. PAINTING AND FINISHING OF EXPOSED EXTERIOR ITEMS AND SURFACES

1.2 SUBMITTALS

- A. SUBMIT PRODUCT DATA AND SAMPLES FOR EACH PRODUCT

1.3 QUALITY ASSURANCE

- A. SINGLE-SOURCE RESPONSIBILITY: PROVIDE PRIMERS AND UNDERCOAT PAINT PRODUCED BY THE SAME MANUFACTURER AS THE FINISH COATS

1.4 ENVIRONMENTAL REQUIREMENTS

- A. FOR INTERIOR APPLICATIONS USE PAINTS AND COATINGS THAT COMPLY WITH THE FOLLOWING LIMITS FOR VOC CONTENT WHEN CALCULATED ACCORDING TO 40 CFR 59, SUBPART D (EPA METHOD 24) OR ASTM D 3960 FOR THE FOLLOWING STANDARDS:
 - GREEN SEAL STANDARD GS-11, PS A1E/D11/T1/S10, 1N, MAY 20, 1993
 - FLAT PAINTS AND COATINGS: VOC CONTENT NOT MORE THAN 50 g/L
 - NON-FLAT PAINTS AND COATINGS: VOC CONTENT NOT MORE THAN 150 g/L
 - GREEN SEAL STANDARD GS-03, ANTI-CORROSION (IDEVDE IPT/ADONT, SJA, N24/ARY 7, 1997
 - ANTI-CORROSION COATINGS: VOC CONTENT NOT MORE THAN 250 g/L
 - SCAQMD RULE 1113, ARCHITECTURAL COATINGS, RULES IN EFFECT, JANUARY 1, 2004
 - VARNISHES AND SANDING SEALERS: VOC CONTENT NOT MORE THAN 350 g/L
 - STAINS: VOC CONTENT NOT MORE THAN 250 g/L
- AROMATIC COMPOUNDS: PAINTS AND COATINGS SHALL NOT CONTAIN MORE THAN 1.0 PERCENT BY WEIGHT TOTAL AROMATIC COMPOUNDS (HYDROCARBON COMPOUNDS CONTAINING ONE OR MORE BENZENE RINGS)

2. PRODUCTS

2.1 MANUFACTURER

- A. REFER TO FINISH LEGEND LOCATED ON THE CONTRACT DRAWINGS FOR ACCEPTABLE MANUFACTURERS
- 1. NO SUBSTITUTIONS

2.2 MATERIALS

- A. MATERIAL COMPATIBILITY: PROVIDE BLOCK FILLERS, PRIMERS, FINISH COAT MATERIALS, AND RELATED MATERIALS THAT ARE COMPATIBLE WITH ONE ANOTHER AND THE SUBSTRATES INDICATED UNDER CONDITIONS OF SERVICE AND APPLICATION, AS DEMONSTRATED BY THE MANUFACTURER BASED ON TESTING AND FIELD EXPERIENCE
- B. PROVIDE COLORS AND FINISHES AS INDICATED ON CONTRACT DRAWINGS. COLORS MUST BE PURE, NON-FADING, APPLICABLE TYPES TO SUIT SUBSTRATES AND SERVICE INDICATED.

3. EXECUTION

3.1 EXAMINATION

- A. EXAMINE SUBSTRATES, AREAS, AND CONDITIONS, WITH THE APPLICATOR PRESENT, UNDER WHICH PAINTING WILL BE PERFORMED FOR COMPLIANCE WITH PAINT APPLICATION REQUIREMENTS
- B. DO NOT BEGIN TO APPLY PAINT UNTIL SATISFACTORY CONDITIONS HAVE BEEN CORRECTED AND SURFACES RECEIVING PAINT ARE THOROUGHLY DRY
- C. START OF PAINTING WILL BE CONSTRUED AS THE APPLICATOR'S ACCEPTANCE OF SURFACES AND CONDITIONS WITHIN A PARTICULAR AREA

3.2 PREPARATION

- A. GENERAL: REMOVE HARDWARE AND HARDWARE ACCESSORIES, PLATES, MACHINED SURFACES, LIGHTING FIXTURES, AND SIMILAR ITEMS ALREADY INSTALLED THAT ARE NOT TO BE PAINTED. IF REMOVAL IS IMPRACTICAL OR IMPOSSIBLE BECAUSE OF THE SIZE OR WEIGHT OF THE ITEM, PROVIDE SURFACE-APPLIED PROTECTION BEFORE SURFACE PREPARATION AND PAINTING.
 - AFTER COMPLETING PAINTING OPERATIONS IN EACH SPACE OR AREA, REINSTALL ITEMS REMOVED USING WORKERS SKILLED IN THE TRADES INVOLVED
- SURFACE PREPARATION: CLEAN AND PREPARE SURFACES TO BE PAINTED ACCORDING TO MANUFACTURER'S WRITTEN INSTRUCTIONS FOR EACH PARTICULAR SUBSTRATE CONDITION AND AS SPECIFIED
 - SCHEDULE CLEANING AND PAINTING SO DUST AND OTHER CONTAMINANTS FROM THE CLEANING PROCESS WILL NOT FALL ON WET, NEWLY PAINTED SURFACES
 - FERROUS METALS: CLEAN STEEL SURFACES IN ACCORDANCE WITH SSPC-SP6/NACE NO. 3 COMMERCIAL BLAST CLEANING
 - GALVANIZED STEEL: CLEAN
- MATERIALS PREPARATION: MIX AND PREPARE PAINT MATERIALS ACCORDING TO MANUFACTURER'S WRITTEN INSTRUCTIONS
- TINTING: TINT EACH UNDERCOAT A LIGHTER SHADE TO SIMPLY IDENTIFICATION OF EACH COAT WHEN MULTIPLE COATS OF THE SAME MATERIAL ARE APPLIED. TINT UNDERCOATS TO MATCH THE COLOR OF THE FINISH COAT, BUT PROVIDE SUFFICIENT DIFFERENCES IN SHADE OF UNDERCOAT TO DISTINGUISH EACH SEPARATE COAT.

3.3 APPLICATION

- A. GENERAL: APPLY PAINT ACCORDING TO MANUFACTURER'S WRITTEN INSTRUCTIONS. USE APPLICATORS AND TECHNIQUES BEST SUITED FOR SUBSTRATE AND TYPE OF MATERIAL BEING APPLIED.
 - PAINT COLORS, SURFACE TREATMENTS, AND FINISHES ARE INDICATED IN THE SCHEDULES
 - APPLY ADDITIONAL COATS IF UNDERCOATS, STAINS, OR OTHER CONDITIONS SHOW THROUGH FINAL COAT OF PAINT UNTIL PAINT FILM IS OF UNIFORM FINISH, COLOR, AND APPEARANCE. GIVE SPECIAL ATTENTION TO ENSURE THAT SURFACES, INCLUDING EDGES, CORNERS, CREVICES, WELDS, AND EXPOSED FASTENERS, RECEIVE A DRY FILM THICKNESS EQUIVALENT TO THAT OF FLAT SURFACES
 - APPLY MATERIALS UNIFORMLY, SHOWING NO RUNS, SAGS, "CRAWLS," "HOLIDAYS," OR OTHER DEFECTS
 - THE TERM "EXPOSED SURFACES" INCLUDES AREAS VISIBLE WHEN PERMANENT OR BUILT-IN FIXTURES, CONNECTOR COVERS, COVERS FOR FINNED-TUBE RADIATION, GRILLES, AND SIMILAR COMPONENTS ARE IN PLACE. EXTEND COATINGS IN THESE AREAS, AS REQUIRED, TO MAINTAIN THE SYSTEM INTEGRITY AND PROVIDE DESIRED PROTECTION
 - FINISH EXTERIOR DOORS ON TOPS, BOTTOMS, AND SIDE EDGES THE SAME AS EXTERIOR FACES AS INDICATED ON CONTRACT DRAWINGS
- SCHEDULING PAINTING: APPLY FIRST COAT TO SURFACES THAT HAVE BEEN CLEANED, PRETREATED, OR OTHERWISE PREPARED FOR PAINTING AS SOON AS PRACTICABLE AFTER PREPARATION AND BEFORE SUBSEQUENT SURFACE DETERIORATION
 - DO NOT APPLY SUCCEEDING COATS UNTIL THE PREVIOUS COAT HAS CURED AS RECOMMENDED BY THE MANUFACTURER
 - OMIT PRIMER ON METAL SURFACES THAT HAVE BEEN SHOP PRIMED AND TOUCHUP PAINTED
 - IF UNDERCOATS, STAINS, OR OTHER CONDITIONS SHOW THROUGH FINAL COAT OF PAINT, APPLY ADDITIONAL COATS UNTIL PAINT FILM IS OF UNIFORM FINISH, COLOR, AND APPEARANCE. GIVE SPECIAL ATTENTION TO ENSURE EDGES, CORNERS, CREVICES, WELDS, AND EXPOSED FASTENERS RECEIVE A DRY FILM THICKNESS EQUIVALENT TO THAT OF FLAT SURFACES
 - HEATED ITEMS: PIPES CONTAINING HEAT SHALL NOT BE PAINTED UNTIL SYSTEM IS COLD AND REMAINS COLD UNTIL AFTER FINAL COAT HAS DRIED
- APPLICATION PROCEDURES: APPLY PAINTS AND COATINGS BY BRUSH, ROLLER, OR OTHER APPLICATORS ACCORDING TO MANUFACTURER'S WRITTEN INSTRUCTIONS
 - IF SPRAY EQUIPMENT IS TO BE USED, USE AIRLESS SPRAY EQUIPMENT WITH ORIFICE SIZE AS RECOMMENDED BY THE MANUFACTURER FOR THE MATERIAL AND TYPE OF SURFACE BEING PAINTED
- RECOAT PRIMED AND SEALED SURFACES WHERE THERE IS EVIDENCE OF SURFACE SPOTS OR UNSEALED AREAS IN FIRST COAT TO ASSURE A FINISH COAT WITH NO BURN-THROUGH (PAINT HOLES) OR OTHER DEFECTS DUE TO INSUFFICIENT SEALING
- BLOCK FILLERS: APPLY BLOCK FILLERS TO CONCENTRATE MASONRY BLOCK AT A RATE TO ENSURE COMPLETE COVERAGE WITH PORES FILLED
- PRIME COATS: BEFORE APPLYING FINISH COATS, APPLY A PRIME COAT OF MATERIAL AS RECOMMENDED BY THE MANUFACTURER. TO MATERIAL THAT IS REQUIRED TO BE PAINTED OR FINISHED AND THAT HAS NOT BEEN PRIME COATED BY OTHERS. RECOAT PRIMED AND SEALED SURFACES WHERE EVIDENCE OF SURFACE SPOTS OR UNSEALED AREAS IN FIRST COAT APPEARS, TO ENSURE A FINISH COAT WITH NO BURN-THROUGH OR OTHER DEFECTS DUE TO INSUFFICIENT SEALING
- PIGMENTED (OPAQUE) FINISHES: COMPLETELY COVER SURFACES AS NECESSARY TO PROVIDE A SMOOTH, OPAQUE SURFACE OF UNIFORM FINISH. COLOR APPEARANCE AND COVERAGE, CLOUDINESS, SPOTTING, HOLIDAYS, LAPS, BRUSH MARKS, REPELAGES, RUNS, SAGS, OR OTHER SURFACE IMPERFECTIONS WILL NOT BE ACCEPTABLE
- STIPPLE ENAMEL FINISHES: MIX AND RECONSTITUTE PAINT TO AN EVEN AND FINE TEXTURE. LEAVE NO EVIDENCE OF ROLLING, SPLICING, LAPS, OR IRREGULARITY IN TEXTURE. SKID MARKS, OR OTHER SURFACE IMPERFECTIONS
- COMPLETED WORK: MATCH ACCEPTED SAMPLES FOR COLOR, TEXTURE, AND COVERAGE. REMOVE, REFINISH, OR REPAINT WORK NOT COMPLYING WITH REQUIREMENTS

3.4 CLEANING

- A. CLEANUP: AT THE END OF EACH WORKDAY, REMOVE EMPTY CANS, RAGS, RUBBISH, AND OTHER DISCARDED PAINT MATERIALS FROM THE SITE
- B. AFTER COMPLETING PAINTING, CLEAN GLASS AND PAINT-SPATTERED SURFACES. REMOVE SPATTERED PAINT BY WASHING AND SCRAPPING. BE CAREFUL NOT TO SCRATCH OR DAMAGE ADJACENT FINISHED SURFACES.

3.4 CLEANING

- A. CLEANUP: AT THE END OF EACH WORKDAY, REMOVE EMPTY CANS, RAGS, RUBBISH, AND OTHER DISCARDED PAINT MATERIALS FROM THE SITE
- B. AFTER COMPLETING PAINTING, CLEAN GLASS AND PAINT-SPATTERED SURFACES. REMOVE SPATTERED PAINT BY WASHING AND SCRAPPING. BE CAREFUL NOT TO SCRATCH OR DAMAGE ADJACENT FINISHED SURFACES.

3.5 PROTECTION

- A. PROTECT WORK OF OTHER TRADES, WHETHER BEING PAINTED OR NOT, AGAINST DAMAGE BY PAINTING. CORRECT DAMAGE BY CLEANING, REPAIRING OR REPLACING, AND REPAINTING
- B. PROVIDE "WET PAINT" SIGNS TO PROTECT NEWLY PAINTED FINISHES. REMOVE TEMPORARY PROTECTIVE WRAPPINGS PROVIDED BY OTHERS TO PROTECT THEIR WORK AFTER COMPLETING PAINTING OPERATIONS
- C. AT COMPLETION OF CONSTRUCTION ACTIVITIES OF OTHER TRADES, TOUCH UP AND RESTORE DAMAGED OR DEFACED PAINTED SURFACES

3.6 PAINT SCHEDULE

- A. EXTERIOR WORK: PROVIDE THE FOLLOWING PAINTING SYSTEMS IN THE COLORS AND SHEENS AS INDICATED ON THE CONTRACT DRAWINGS
 - CONCRETE, STUCCO, AND MASONRY:
 - FLAT OR LOW-LUSTER ACRYLIC, TWO COATS OVER PRIMER
 - SEMI-GLOSS OR FULL-GLOSS ACRYLIC ENAMEL, TWO COATS OVER PRIMER
 - CONCRETE MASONRY UNITS:
 - FLAT OR LOW-LUSTER ACRYLIC, TWO COATS OVER BLOCK FILLER AND PRIMER
 - SEMI-GLOSS OR FULL-GLOSS ACRYLIC ENAMEL, TWO COATS OVER BLOCK FILLER AND PRIMER
 - FERROUS METAL:
 - FLAT, SEMI-GLOSS OR FULL-GLOSS ACRYLIC ENAMEL, TWO COATS OVER RUST-INHIBITING PRIMER
 - LOW LUSTER ACRYLIC, TWO COATS OVER RUST-INHIBITING PRIMER
 - FULL-GLOSS OR DEEP-COLOR FULL-GLOSS ALKYD ENAMEL, TWO COATS OVER RUST-INHIBITING PRIMER
 - ZINC-COATED METAL:
 - LOW LUSTER, TWO COATS OVER GALVANIZED METAL PRIMER
 - SEMI-GLOSS OR FULL-GLOSS ACRYLIC ENAMEL, TWO COATS OVER GALVANIZED METAL PRIMER
 - FULL-GLOSS ALKYD ENAMEL, TWO COATS OVER PRIME
- INTERIOR WORK: PROVIDE THE FOLLOWING PAINTING SYSTEMS IN THE COLORS AND SHEENS AS INDICATED ON THE CONTRACT DRAWINGS
 - GYPSON BOARD:
 - FLAT ACRYLIC, TWO COATS OVER PRIMER
 - LOW-LUSTER, SEMI-GLOSS, OR FULL-GLOSS ACRYLIC ENAMEL, TWO COATS OVER PRIMER
 - SEMI-GLOSS OR FULL-GLOSS ALKYD ENAMEL, TWO COATS OVER PRIMER
 - WOODWORK AND HARDBOARD:
 - LOW LUSTER OR SEMI-GLOSS ACRYLIC ENAMEL, TWO COATS OVER WOOD UNDERCOAT
 - SEMI-GLOSS OR FULL-GLOSS ACRYLIC ENAMEL, TWO COATS OVER WOOD UNDERCOAT
 - FULL-GLOSS ALKYD ENAMEL, TWO COATS OVER WOOD UNDERCOAT
 - STAINED WOODWORK:
 - ALKYD-BASE, SATIN VARNISH, TWO COATS CLEAR-SATIN VARNISH OVER SEALER AND WOOD STAIN
 - WATERBORNE, SATIN VARNISH, TWO COATS CLEAR-SATIN VARNISH OVER SEALER AND WOOD STAIN
 - WATER-BASED STAIN, FULL GLOSS, VARNISH, TWO COATS FULL-GLOSS VARNISH OVER SEALER AND WOOD STAIN
 - ALKYD-BASED STAIN, WAX POLISHED FINISH, THREE COATS PASTE WAX OVER SEALER AND WOOD STAIN
 - NATURAL FINISH WOODWORK:
 - ALKYD-BASED, SATIN VARNISH, TWO COATS CLEAR-SATIN VARNISH OVER SEALER
 - WATERBORNE, SATIN VARNISH, TWO COATS CLEAR-SATIN VARNISH OVER SEALER
 - WATER-BASED, FULL-GLOSS, VARNISH, TWO COATS FULL-GLOSS VARNISH OVER SEALER
 - WAX-POLISHED FINISH, THREE COATS PASTE WAX OVER SEALER
 - FERROUS METAL:
 - FLAT ACRYLIC, TWO COATS OVER PRIMER
 - LOW-LUSTER OR FULL-GLOSS ACRYLIC ENAMEL, TWO COATS OVER PRIMER
 - SEMI-GLOSS ACRYLIC ENAMEL, ONE COAT OVER UNDERCOAT AND PRIMER
 - SEMI-GLOSS ALKYD ENAMEL, ONE COAT OVER UNDERCOAT AND PRIMER
 - FULL-GLOSS, ALKYD ENAMEL, TWO COATS OVER PRIMER

DIVISION 10: SPECIALTIES

SECTION 101400 - SIGNAGE

1. GENERAL

1.1 SUMMARY

- A. PROVIDE BUILDING SIGNAGE TO COMPLY WITH CODE AND ACCESSIBILITY REQUIREMENTS
- B. EXTERIOR BUILDING IDENTIFICATION SIGNAGE SHALL BE PROVIDED BY OWNER'S SERVICE PROVIDER

1.2 SUBMITTALS:

- A. SUBMIT PRODUCT DATA, SAMPLES.

2. PRODUCTS:

- A. PRODUCTS: MATCH OWNER'S STANDARD
- B. COPY BASED TEXT, BRALLE, AND ENGLISH
- C. ACCESSORIES: FOAM ADHESIVE TAPES

3. EXECUTION

3.1 INSTALLATION:

- A. INSTALL IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS AND APPROVED SUBMITTALS.

SECTION 102800 - TOILET ACCESSORIES

1. GENERAL

1.1 SUMMARY:

- A. PROVIDE TOILET AND BATH ACCESSORIES AND METAL FRAMED MIRRORS.

1.2 SUBMITTALS:

- A. SUBMIT PRODUCT DATA, SAMPLES, SHOP DRAWINGS

1.3 QUALITY ASSURANCE:

- A. COMPLY WITH ADA AND LOCAL ACCESSIBILITY REQUIREMENTS.

2. PRODUCTS

2.1 MATERIALS

- A. TOILET COMPARTMENT MATERIALS:
 - SOLID PHENOLIC COMPARTMENTS: HIGH PRESSURE MELAMNE SURFACE FUSED TO SOLID PHENOLIC CORE
- TYPE AND MOUNTING:
 - COMPARTMENTS: CEILING HUNG.
 - SCREENS: WALL HUNG.
 - STYLE: STANDARD PRIVACY.
- ACCESSORIES:
 - HARDWARE: BRACKETS, HINGES, AND LATCHES
 - ROBE HOOKS AND BUMPERS ON BACK OF COMPARTMENT DOORS.

3. EXECUTION

3.1 INSTALLATION

- A. INSTALL IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS AND APPROVED SUBMITTALS.

SECTION 102800 - TOILET ACCESSORIES

1. GENERAL

1.1 SUMMARY:

- A. PROVIDE TOILET AND BATH ACCESSORIES AND METAL FRAMED MIRRORS.

1.2 SUBMITTALS:

- A. SUBMIT PRODUCT DATA, SAMPLES.

2. PRODUCTS

1.1 MATERIALS:

- A. PRODUCTS: AS SELECTED BY ARCHITECT COMPLYING WITH DESIGNATIONS ON THE DRAWINGS.
- B. MIRRORS AND FRAMES:
 - GLAZING: MIRROR GLASS, 1/4 INCH THICK (6 MM), ASTM C 1036.
 - FRAMES: STAINLESS STEEL.
 - TYPE: STANDARD WALL UNIT.
- MATERIALS AND FINISHES:
 - MATERIAL AND FINISH: STAINLESS STEEL, NO. 4 FINISH
 - BAKED ENAMEL ON STEEL: FACTORY APPLIED FINISH FROM MANUFACTURERS FULL LINE OF COLORS.

3. EXECUTION

3.1 INSTALLATION:

- A. INSTALL IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS AND APPROVED SUBMITTALS.

SECTION 10 44 00 - FIRE EXTINGUISHERS AND ACCESSORIES

1. GENERAL

1.1 SUMMARY

- A. SECTION INCLUDES PERFORMANCE CRITERIA FOR FIRE EXTINGUISHERS, FIRE EXTINGUISHER CABINETS, AND FIRE EXTINGUISHER MOUNTING BRACKETS

1.2 SUBMITTALS

- A. SUBMIT PRODUCT DATA FOR EACH PRODUCT

1.3 QUALITY ASSURANCE

- A. NFPA COMPLIANCE: FIRE EXTINGUISHERS SHALL COMPLY WITH NFPA-10
- B. UL-LISTED PRODUCTS: FIRE EXTINGUISHERS SHALL BE UL LISTED WITH UL LISTING MARKING TYPE, RATING, AND CLASSIFICATION OF EXTINGUISHER
- C. FM-LISTED PRODUCTS: FIRE EXTINGUISHERS APPROVED BY FACTORY MUTUAL RESURANCE CORPORATION FOR TYPE, RATING, AND CLASSIFICATION OF EXTINGUISHER

2. PRODUCTS

2.1 MATERIALS

- A. FIRE EXTINGUISHERS: PROVIDE FIRE EXTINGUISHERS OR OPERATIONS AS INDICATED ON THE DRAWING SET AND AS MAYBE ADDITIONALLY REQUIRED BY AUTHORITY HAVING JURISDICTION. TYPES AS DESCRIBED BELOW:
 - MULTI-PURPOSE DRY CHEMICAL, TYPE 2-A, UL-299, RATED FOR CLASS-A FIRES
 - DRY CHEMICAL, TYPE -K, UL-299, RATED FOR CLASS-B FIRES IN VULNERABLE COOKING MEDIA
 - CARBON DIOXIDE, TYPE C, UL-154, RATED FOR CLASS-C FIRES. FIRE EXTINGUISHER SHALL CONTAIN AGENTS THAT ARE NON-CONDUCTIVE TO ELECTRICITY
 - FIRE EXTINGUISHER CABINETS: SIZE SUITABLE FOR HOUSEHOLD FIRE EXTINGUISHERS TO ENSURE FIT AND PROTECTION OF TYPES AND RATES INDICATED
- MOUNTING: RECESSED
 - MANUFACTURER'S INDUSTRIES OR APPROVED EQUAL
 - MOUNTING: RECESSED
- BASIS OF DESIGN:
 - AMBASSADOR SERIES 1015 S21 (W/ HANDLE)
 - FE LETTERS: WHITE, VERTICAL
 - TRIM: FLAT
 - SIZE: 10 1/2" W x 24" H x 6" D
 - MOUNTING BRACKETS: MANUFACTURER'S STANDARD GALVANIZED STEEL, DESIGNED TO SECURE FIRE EXTINGUISHER TO WALL OR STRUCTURE
- IDENTIFICATION: COMPLYING WITH AUTHORITIES HAVING JURISDICTION. IDENTIFY THE BRACKET MOUNT FIRE EXTINGUISHER WITH THE WORDS "FIRE EXTINGUISHER" USING LETTER DECALS APPLIED TO MOUNTING SURFACE

3. EXECUTION

3.1 INSTALLATION

- A. INSTALL PER MANUFACTURER'S WRITTEN INSTRUCTIONS
- B. INSTALL AT HEIGHTS INDICATED OR IF NOT INDICATED AT HEIGHTS TO COMPLY WITH APPLICABLE REGULATIONS OF GOVERNING AUTHORITIES

DIVISION 11: EQUIPMENT

- A. REFER TO FOOD SERVICE CONSULTANT

DIVISION 12: FURNISHINGS

SECTION 122400 - ROLLER SHADES

1. GENERAL:

1.1 SUMMARY:

- A. PROVIDE WINDOW TREATMENT.

1.2 SUBMITTALS:

- A. SUBMIT PRODUCT DATA, SAMPLES, WARRANTY.

2. PRODUCTS:

- A. BASIS OF DESIGN: SKYCO SHADING SYSTEMS; MANUAL TECH SHADES, R-SERIES.
- TYPE: ROLLER SHADES
- WINDOW SHADECLOTH: VINYL COATED POLYESTER, TRANSLUCENT.
 - PHIFER, SHEERWEAVE 4000 WITH DOW EQUILIBRIUM, ECO, COLOR V15 ASH.
 - OPENNESS: 5%.
- ACCESSORIES:
 - FASCIA (VALANCE AT HEADBOX)
 - MOUNTING.
 - OPERATION: MANUAL, CHAIN OPERATED.
 - FACTORY FINISH: BLACK ANODIZED.

3. INSTALLATION:

- A. INSTALL IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS AND APPROVED SUBMITTALS.

NOTES
 1. ALL FINISHES ARE LISTED IN THE "FINISH SCHEDULE"
 2. PROVIDE SHOP DRAWINGS, COLOR CHARTS, SPECIFICATIONS ON ALL ITEMS LISTED FOR ARCHITECTS REVIEW PRIOR TO ORDERING OR FABRICATION
 3. THIS SPECIFICATION IS PERFORMANCE BASED. REFER TO DRAWINGS FOR PRODUCT SPECIFIC DESIGNATIONS. MOST PRODUCT DESIGNATIONS DO NOT MEET THE REQUIREMENTS FOR AN APPROVED EQUAL. SUBSTITUTIONS DO NOT MEET THE REQUIREMENTS FOR AN APPROVED EQUAL.

