


VICINITY MAP
N.T.S.

- Paving and Paving Notes**
- All signs, pavement markings, and other traffic control devices shall conform to the FHWA manual on uniform traffic control devices and hand-drawn signing shall meet Tennessee disabled parking regulations.
 - All pavement markings shall be four inches wide solid white unless indicated otherwise on the drawings. All handicap parking stalls shall be blue stripes.
 - A minimum clearance of the sign shall be maintained between the face of curb and any part of a sign or light pole. HC sign on sidewalk shall have 3 min. clearance for HC accessibility.
 - Contractor shall furnish and install all pavement markings as shown on the plans.
 - Contractor shall coordinate installation of all signs, pavement markings, and other traffic control devices with other contractors on site.
 - Contractor shall saw-cut to provide smooth transitions at tie-ins to existing edges of pavement. Joints or score marks are to be sharp and clean without showing edges of jointing tool.
 - All concrete for curbs, sidewalks & pavement shall be class a 4000 p.s.i. Items on City/County row shall be 4000 p.s.i. unless otherwise noted.
 - Contractor shall saw-cut tie-ins at existing curbs as necessary to ensure smooth transitions. Contractor shall saw-cut and transition to meet existing pavement as necessary and as directed by inspector to insure positive drainage. (typical @ all intersections)
 - Contractor shall comply with all pertinent provisions of the 'Manual of Accident Prevention in Construction' issued by AGC of America, Inc., and the Safety and Health Regulations for Construction issued by the U.S. Department of Labor.
 - Contractor shall be responsible for cost of pavement replacement where utility lines are extended from existing lines to the building.
 - All ramps constructed are not to exceed a slope of 1:12.
 - Concrete dumpster pads to be flush with pavement unless otherwise noted.
 - All dimensions are to face of curb unless indicated otherwise.
 - All work shall comply with all applicable codes, regulations, and/or local standards imposed by local utility, county, and state.
 - Necessary barricades, sufficient lights, signs and other traffic control methods as may be necessary for the protection and safety of the public shall be provided and maintained throughout the construction of driveways connecting to all roadways.
 - These plans are not to be used for building layout. See Architectural Plans to layout building.

PLANS LEGEND:

	EXISTING ASPHALT
	STANDARD DUTY ASPHALT
	CONCRETE
	LANDSCAPE AREAS (SEE LANDSCAPE PLANS FOR DETAILS)
	CURB AND GUTTER
	EXTRUDED CURB
	PROPERTY LINE
	EXISTING EASEMENT
	LIGHT POLES

SITE PAVING PLAN



IT IS THE CONTRACTOR'S RESPONSIBILITY TO CONTACT UTILITY COMPANIES PRIOR TO CONSTRUCTION AS THE LOCATION OF UTILITIES SHOWN ON THIS PLAN ARE APPROXIMATE AND POSSIBLY INCOMPLETE. THEREFORE CERTIFICATION TO THE LOCATION OF ALL UNDERGROUND UTILITIES IS WITHHELD.



11721 Market Street, P.O. Box 4048
Chattanooga, TN 37405
v: 423.266.1216 f: 423.266.1216

In association with:

CIVIL ENGINEER:

MILLER MCCOY, INC.
CONSULTING ENGINEERS
913 CREEKSIDE ROAD CHATTANOOGA, TENNESSEE 37408
PHONE (423) 698-2681 FAX (423) 698-2684
© Copyright 2014 Miller-McCoy, Inc.

CCS Gym
Expansion+Spirit
Store
for
**CHATTANOOGA
CHRISTIAN SCHOOL**



3354 Charger Dr., Chattanooga, TN 37409

This drawing is the property of Franklin Associates Architects Inc. Any use, reuse, reproduction, display or sale of this drawing without the express written consent of the Architect is strictly prohibited.

Copyright © 2017 | franklin architects



Construction Documents

Revisions		
No.	Issue	Date

Sheet Information	
Date	11/26/18
Job No.	6774.3/6774.4
Title	CIVIL SITE PAVING PLAN

CIVIL SITE PAVING PLAN

ORIENTATION

Sheet
C-2.0