

DATE	SET
10.15.18	

STONE (TILE OR SLAB)

ST-01 Engineered Stone at Public Areas

Product: Zodiac® Quartz
 Color/Finish: Snow Flurry/Polished
 Dimensions: Thickness: 2 CM
 Refer to drawings for additional dimensions.

Notes: Refer to manufacturer's recommended installation instructions. Stone installation to meet all requirements per MIA standards. Sample must be submitted for approval in accordance with architect's specifications.

Reference ID drawings for locations.

Manufacturer: DuPont
 Address: 500 Production Ave, Suite 600
 Madison, AL 35758
 Phone: (601) 760-9972
 Fax: (800) 756-5474
 Contact: Kyra Schaub
 E-mail: kschaub@oldenkamp.com

TILE

T-01 Tile @ Lobby Field, Public RR, Vending

Product: Invecke
 Color/Finish: Copper Haze ID103
 Dimensions: 12"W x 24"L, Thickness 3/8"

Coeff Friction: DCOF Wet ≥ .42
 Grout: Laticrete SpectraLOCK; 24 Natural Grey, 3/16"

Notes: Installer to use specified grout, thin set and leveling system to ensure the proper installation of tiles. Cementitious grout must be sealed after installation.

Manufacturer: Daltile Corporation
 Phone: (901) 794-1891
 Contact: Dustin Carr
 E-mail: dustin.carr@daltile.com

T-03 Tile @ Lobby Inset

Product: Forest Park
 Color/Finish: Willow Grove FP98
 Dimensions: 9"W x 36"L, Thickness 3/8"

Coeff Friction: DCOF Wet ≥ .42
 Grout: Laticrete SpectraLOCK; 24 Natural Grey, 3/16"

Notes: Installer to use specified grout, thin set and leveling system to ensure the proper installation of tiles. Cementitious grout must be sealed after installation.

Manufacturer: Daltile Corporation
 Phone: (901) 794-1891
 Contact: Dustin Carr
 E-mail: dustin.carr@daltile.com

TILE

T-04 Tile @ Lobby Accent Walls

Product: Flash
 Color/Finish: Iron/Satin
 Dimensions: 3" x 12"

Coeff Friction: DCOF Wet ≥ .42
 Grout: Laticrete SpectraLOCK; 78 Sterling Silver, 3/16"

Notes: Thickness: 9.5 mm

Manufacturer: Garden State Tile
 Address: 2730 Ogeechee Rd
 Savannah, GA 31405
 Phone: (912) 235-5499
 Contact: Leslie Weinberg
 E-mail: lweinberg@gstile.com

T-05 Tile @ Public Restroom Walls

Product: Matte Wall Tile
 Color/Finish: White 0790
 Dimensions: 3"W x 6"L

Coeff Friction: DCOF Wet ≥ .42
 Grout: Laticrete SpectraLOCK; 44 Bright White, 3/16"

Notes: Installer to use specified grout, thin set and leveling system to ensure the proper installation of tiles. Cementitious grout must be sealed after installation.

Manufacturer: Daltile Corporation
 Phone: (901) 794-1891
 Contact: Dustin Carr
 E-mail: dustin.carr@daltile.com

T-06 Tile @ Guestroom Entry and Bathroom

Product: Kimona Silk
 Color/Finish: White Orchid P-320
 Dimensions: 12"W x 24"L, Thickness 3/8"

Coeff Friction: DCOF Wet ≥ .42
 Grout: Laticrete SpectraLOCK; 23 Antique White, 3/16"

Notes: Installer to use specified grout, thin set and leveling system to ensure the proper installation of tiles. Cementitious grout must be sealed after installation.

Manufacturer: Daltile Corporation
 Phone: (901) 794-1891
 Contact: Dustin Carr
 E-mail: dustin.carr@daltile.com

TILE

T-08 Tile @ Pool - Mosaic

Product: Random Keystone Mosaic Pattern
 Color/Finish: Artic White D617; Ocean Blue D159; Galaxy D023
 Dimensions: 1" x 1", Overall Height: 6"

Coeff Friction: Wet: 0.60; Dry: 0.80
 Grout: Hydromant; H177 Bright White, 3/16"

Notes: Mosaic Tile @ Side of Pool
 Installer to use specified grout, thin set and leveling system to ensure the proper installation of tiles. Cementitious grout must be sealed after installation.

Manufacturer: Daltile Corporation
 Phone: (901) 794-1891
 Contact: Dustin Carr
 E-mail: dustin.carr@daltile.com

T-09 Tile @ Pool - Depth Marker

Product: 6" Ceramic Tile
 Color/Finish: White with Black Numbers
 Dimensions: 6" x 6"

Coeff Friction: Wet: 0.65; Dry: 0.94
 Grout: Hydromant; H1177 Bright White, 3/16"

Notes: Metric or US Customary Unit depth markers as required.
 General Contractor is responsible for ordering proper depth markers per applicable codes.
 Markers to be installed flush with adjacent tiles.
 Installer to use specified grout, thin set and leveling system to ensure the proper installation of tiles. Cementitious grout must be sealed after installation.

Manufacturer: Inlays, Inc.
 Address: 3333 Commodory Lane
 Green Bay, WI 54304
 Phone: (800) 426-6873

T-10 Tile @ Pool

Product: Veranda
 Color/Finish: Leather P505
 Dimensions: 13"W x 13"L

Coeff Friction: DCOF Wet ≥ .42
 Grout: Laticrete SpectraLOCK; 59 Espresso, 3/16"

Notes: Installer to use specified grout, thin set and leveling system to ensure the proper installation of tiles. Cementitious grout must be sealed after installation.

Manufacturer: Daltile Corporation
 Phone: (901) 794-1891
 Contact: Dustin Carr
 E-mail: dustin.carr@daltile.com

TILE

T-11 NOT USED

T-12 Tile 2 @ Lobby Accent Walls

Product: Flash
 Color/Finish: Grey/Satin
 Dimensions: 3" x 12"

Coeff Friction: DCOF Wet ≥ .42
 Grout: Laticrete SpectraLOCK; 78 Sterling Silver, 3/16"

Notes: Thickness: 9.5 mm

Manufacturer: Garden State Tile
 Address: 2730 Ogeechee Rd
 Savannah, GA 31405
 Phone: (912) 235-5499
 Contact: Leslie Weinberg
 E-mail: lweinberg@gstile.com

TILE BASE

TB-01 Tile Base @ Lobby, Public RR, Vending

Product: Invecke S-44H9
 Color/Finish: Copper Haze ID103
 Dimensions: 4"W x 18"L, Thickness 3/8"

Notes: GROUT: Coefficient of Friction: DCOF Wet ≥ .42
 Product: Laticrete SpectraLOCK
 Color: 24 Natural Grey
 Recommended Joint Width: 3/16"
 Installer to use specified grout, thin set and leveling system to ensure the proper installation of tiles. Cementitious grout must be sealed after installation.

Manufacturer: Daltile Corporation
 Phone: (901) 794-1891
 Contact: Dustin Carr
 E-mail: dustin.carr@daltile.com

TILE BASE

TB-10 Tile Cove Base @ Pool

Product: Veranda
 Color/Finish: Leather P505
 Dimensions: 6"W x 13"L

Notes: Installer to use specified grout, thin set and leveling system to ensure the proper installation of tiles. Cementitious grout must be sealed after installation.

GROUT: Coefficient of Friction: DCOF Wet ≥ .42
 Product: Laticrete SpectraLOCK
 Grout Color: 59 Espresso
 Grout Size: 3/16"

Manufacturer: Daltile Corporation
 Phone: (901) 794-1891
 Contact: Dustin Carr
 E-mail: dustin.carr@daltile.com

VINYL COMPOSITION TILE

VCT-01 Tile @ Storage Room

Product: Armstrong Migrations BBT with Biostride
 Color/Finish: Bark Brown T3528
 Dimensions: 12" X 12"

Notes: Materials meets or exceeds ADAAG recommended value of .6 on James Machine

Manufacturer: Armstrong Flooring, Inc.
 Address: 2530 Columbia Avenue PO Box 3025
 Lancaster, PA 17603
 Phone: (717) 672-7530
 Fax: (717) 481-5170
 Contact: Carlos Santos
 E-mail: csantos@armstrongflooring.com

WALLCOVERING

WC-01 Wallcovering @ Guestroom - Accent

Product: T2-EE-01; Empire Edge; II
 Color/Finish: Sky-Grey-Per
 Dimensions: 52"
 Type: II
 Weight: 20 oz
 Backing: Osneburg

Flame Requirements: Class A - ASTM E-84, NFPA 101, NFPA 286

Notes: Reverse match - repeat 24" H x 52" W
 Use midew resistant adhesive.

Manufacturer: Eykon Wallcovering Source
 Address: 5675 E. Shelby Drive
 Memphis, TN 38141
 Phone: (901) 550-2026
 Fax: (901) 368-0447
 Contact: Kathy McFall
 E-mail: mcfall@eykon.net

Source: John Gurley
 Phone: (615) 509-0046
 E-mail: gurley@eykon.net

WC-02 Wallcovering @ Guest Bathrooms

Product: H2B-02-02; II
 Dimensions: 54"
 Type: II
 Weight: 20 oz
 Repeat: 3 0"V x 3.25"H
 Backing: Non-woven

Flame Requirements: ASTM E84 - Class A

Notes: Match: Non-Reverse Hang, Straight Across Match
 Use midew resistant adhesive.

Manufacturer: Eykon Wallcovering Source
 Address: 5675 E. Shelby Drive
 Memphis, TN 38141
 Phone: (901) 550-2026
 Fax: (901) 368-0447
 Contact: Kathy McFall
 E-mail: mcfall@eykon.net

Source: John Gurley
 Phone: (615) 509-0046
 E-mail: gurley@eykon.net

Order Plans @ WWW.IDIOnline.com