



KEY NOTES

FINISH LEGEND:

CP	CARPET BARE	SEE	REFER TO FLOOR
CP 01	CARPET	REF	TO FLOOR
TR	TILE	REF	TO FLOOR
WB	WOOD BARE	REF	TO FLOOR
RC	RESILIENT CONCRETE	REF	TO FLOOR
RB	RESILIENT BASE	REF	TO FLOOR
RF	RESILIENT FLOOR	REF	TO FLOOR
VCT	VINYL COMPOSITE	REF	TO FLOOR

SHEET NOTES

- A. INTERIOR FINISHES PROVIDED BY AK DESIGN GROUP ARE FOR REFERENCE ONLY. VERIFY ALL DIMENSIONS AND CONDITIONS.
- B. TO ENSURE PROPER APPEARANCE AND ADHESION, THE SUB FLOOR MUST BE HARD, SMOOTH, CLEAN, DRY AND FREE FROM OILS, GREASE, OR OTHER CONTAMINANTS. USE OF A SUITABLE LEVELING COMPOUND IS REQUIRED TO CORRECT ANY DEFECTS AND IN ACCORDANCE WITH THE MANUFACTURER'S INSTRUCTIONS WILL ENSURE THAT NO IRREGULARITIES OCCUR AT THE SURFACE OF THE FINISHED FLOOR.
- C. TRANSITIONS OF ALL FLOORING MATERIALS SHOULD OCCUR AT THE CENTERLINE OF THE DOOR OR CARVED OPENING, FLOAT FLOOR AS REQUIRED.
- D. ALLOW ALL ADHESIVE AND SUB FLOOR TO STABILIZE TO CONSTANT TEMPERATURE CONDITIONS OF 70 DEGREES FOR A PERIOD OF 24 HOURS BEFORE AND AFTER INSTALLATION. ENSURE THAT ADHESIVE HAS BEEN PROTECTED FROM FROST DURING STORAGE.
- E. FIT CARPET NEATLY AT WALLS, COLUMNS, ADJACENT FLOORINGS, ETC. INSTALL CARPET'S REDUCER STRIP OR TRANSITION STRIP WHERE SOLE OF CARPET IS EXPOSED AND WHERE CARPET MEETS OTHER MATERIAL.
- F. CARPET SHALL LAY THE SAME DIRECTION UNLESS SHOWN OTHERWISE. CARPET TO HAVE MINIMAL SEAMS. CROSS JOINTS ARE NOT PERMITTED. AVOID SEAMING NEAR CORNERS AND DOORS.
- G. ALL PORCELAIN TILE TO BE CLEANED AND SEALED PRIOR TO INSTALLATION.
- H. NO SUBSTITUTIONS OF GRADE, QUALITY, OR MANUFACTURER SHALL BE ALLOWED WITHOUT THE APPROVAL OF AK DESIGN GROUP.

AK DESIGN GROUP
 MEMPHIS OFFICE
 7975 Stage Hills
 Boulevard, Suite 111
 Memphis, TN 38133
 NASHVILLE OFFICE
 9000 Split Log Road
 Brentwood, TN 37027
 P: 901.384.9536
 F: 615.850.8790

INTERIOR DESIGN DRAWINGS FOR
HOME 2
 ASHEVILLE, NC

ISSUED: DATE

FIRST FLOOR - FLOOR FINISH PLAN
 FOR CONSTRUCTION

DATE	SET
9.20.18	
10.01.18	

Order Plans

FIRST FLOOR - FLOOR FINISH PLAN

1/8" = 1'-0"

TRIBECA PROTOTYPE SCHEME

1
 ID1.00

ID1.00