



KEY NOTES:

FINISH LEGEND:

CB CARPET BASE
 CP CARPET
 T TILE
 TB TILE BASE
 WC WOOD BASE
 RC REINFORCED CONCRETE
 RB REBELLION BOARD
 RF REBELLION FLOOR
 VCT VINYL COMPOSITION TILE

NOTE:
 SEE TO FINISH SCHEDULES
 MANUAL FOR FINISHES?
 SPECIFICALLY LISTED WITHIN
 THESE DRAWINGS
 THESE DRAWINGS WILL
 SHOW THROUGH TO THE SURFACE OF THE FINISHED FLOOR.

SHEET NOTES:

A. INTERIORS FINISHES BY AK DESIGN GROUP ARE FOR REFERENCE. VERIFY ALL DIMENSIONS AND CONDITIONS.

B. TO ENSURE GOOD QUALITY APPEARANCE AND ADHESION, THE FLOOR MUST BE HARD, SMOOTH, CLEAN, DRY AND FREE FROM DEBRIS. USE OF A SUITABLE LEVELING COMPOUND IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS WILL ENSURE THAT NO IRREGULARITIES SHOW THROUGH TO THE SURFACE OF THE FINISHED FLOOR.

C. TRANSITIONS OF ALL FLOORING MATERIALS SHOULD OCCUR AT THE CENTERLINE OF THE DOOR OR CABINET OPENING. FLOAT FLOORS AS REQUIRED.

D. ALLOW ALL ADHESIVE AND SUB FLOOR TO STABILIZE TO CONSTANT TEMPERATURE CONDITIONS OF 70-85 DEGREES FOR A PERIOD OF 24 HOURS BEFORE AND AFTER INSTALLATION. ENSURE THAT ADHESIVE HAS BEEN PROTECTED FROM FROST DURING STORAGE.

E. FIT CARPET NEATLY AT WALLS, COLUMNS, ADJACENT FLOORING, ETC. INSTALL CARPET REDUCER STRIP OR TRANSITION STRIP WHERE EDGE OF CARPET IS EXPOSED AND WHERE CARPET ADJUTS OTHER MATERIAL.

F. CARPET SHALL LAY THE SAME DIRECTION UNLESS SHOWN OTHERWISE. CARPET TO HAVE MINIMAL SEAMS. CROSS JOINTS ARE NOT PERMITTED. AVOID SEAMING NEAR CORNERS AND DOORS.

G. ALL PORCELAIN TILE TO BE CLEANED AND SEALED PRIOR TO INSTALLATION.

H. NO SUBSTITUTIONS OF GRADE, QUALITY, OR MANUFACTURER SHALL BE ALLOWED WITHOUT THE APPROVAL OF AK DESIGN STUDIO.

AKDGD
 AK DESIGN GROUP, LLC
 HOSPITALITY INTERIORS

MEMPHIS OFFICE
 7975 Stage Hills
 Boulevard, Suite 111
 Memphis, TN 38133

NASHVILLE OFFICE
 9000 Split Log Road
 Brentwood, TN 37027

P: 901.384.9536
 F: 615.850.8790

INTERIOR DESIGN DRAWINGS FOR
HOME 2
 ASHEVILLE, NC

ISSUED: _____ DATE _____

THIRD FLOOR - FLOOR FINISH PLAN
 FOR CONSTRUCTION

DATE SET

DATE	SET

Order Plans

THIRD FLOOR - FLOOR FINISH PLAN

1/8" = 1'-0"

TRIBECA PROTOTYPE SCHEME

1
 ID1.02

ID1.02