



PANDA RESTAURANT GROUP INC.
 1683 Walnut Grove Ave.
 Rosemead, California
 91770
 Telephone: 626.799.9898
 Facsimile: 626.372.8288

All ideas, designs, arrangement and plans indicated or represented by this drawing are the property of Panda Express Inc. and were created for use on this specific project. None of these ideas, designs, arrangements or plans may be used by or disclosed to any person, firm or corporation without the written permission of Panda Express Inc.

REVISIONS:

NO.	DESCRIPTION	DATE
1	ISSUED FOR BID & PERMIT	12-11-18
2	BID SET	01-30-19

ISSUE DATE:
 1 ISSUED FOR BID & PERMIT 12-11-18
 2 BID SET 01-30-19

DRAWN BY: JO
 PANDA PROJECT # S8-19-D6573
 ARCH PROJECT # P7336

gph
 G.P.H. Inc.
 500 West Fulton St.
 Sanford, FL 32771
 Ph: 407-322-8841
 Licenses:
 Eng. C.O.A. No. 2750-E
 Survey L.B. No. CA-909-S
 Arch. Lic. No. 2853-L2



JEFFREY FOSTER, AIA

PANDA EXPRESS
 WARM & WELCOME 2200
 ATLANTIC BLVD & MARKETPLACE DR
 JACKSONVILLE, FL 32225

A-403

ARCHITECTURAL
 DETAILS

<p>NEW ELECTRICAL PANEL 5/8" GYP. BD. FINISH AS SCHEDULED (W/F) VERIFY PRIOR TO CONSTRUCTION EXTERIOR WALL 20GA. 6" MTL STUD FURROUT W/ 5/8" GYP. BD. ON FINISH SIDE 3/4" FIRE-TREATED PLYWOOD 20GA. 3 5/8" MTL STUDS 20GA. 6" MTL STUD FURROUT W/ 5/8" GYP. BD. ON FINISH SIDE</p> <p>NOTE: VERIFY ALL WALL PLACEMENT DIMENSIONS W/ ELECTRICAL PANEL SIZE, SPACING & MOUNTING HEIGHT REQUIREMENTS PRIOR TO CONSTRUCTION.</p> <p>RATED WALLS: G.C. TO PROVIDE 3M PRODUCT CS-195 COMPOSITE SHEETS AND INSTALL PER MANUFACTURERS RECOMMENDATIONS OR FIRE BLANKETS APPROVED BY LOCAL AUTHORITIES TO MAINTAIN INTEGRITY OF FIRE RATED WALL.</p>	<p>TWO LAYERS OF 5/8" GREEN BD. 48" HIGH ON TOP OF TWO LAYERS OF 5/8" X 12" CEMENT BD. WALL FINISH WP3 SILICONE JOINT SEALANT SS FLASHING BEHIND SS WALL PANEL AT TOP OF Q.T. BASE LATICRETE 9235 WATERPROOFG MEMBRANE, 8" UP ON WALL & 24" ON FLOOR, BETWEEN CEMENT BD. & QUARRY TILE QUARRY TILE BASE SLOPE FOR POSITIVE DRAINAGE 1/4" IN 24" TYP. STUD WALL MTL STUD SCREW, TOP & BOTTOM @ 16" O.C. SEALANT, GE SILPRUF SCS 2000 20 GA. GALV. PLATE BETWEEN MTL STUD AND CEMENT BD. 8" UP & 1" ON FLOOR, 1" OVERLAP ON GALV. PLATE WATER PROOFING REQ. 8" UP WALL & 24" ON FLOOR, TYP.</p>	<p>COUNTER TOP PROVIDED BY PK, INSTALLED BY G.C. MTLER JOINT TILE PRE-FABRICATED WOOD FRAMES PROVIDED BY PK, INSTALLED BY G.C. WP1 OVER 5/8" WATER RESISTANT GYP. BD. BY G.C. WP1 OVER 12" X 5/8" DUROCK CEMENT BD. BY G.C. 5/8" GYP. BD. AS TILE BACKING INSTALL BY G.C. SCHLUTER COVE TRIM TREATED SILL PLATE SET IN BEAD OF SEALANT, TYP. REFER STRUCTURAL 20 GA. GALV. PLATE REFER 2/A-403 FOR WATER PROOFING DETAIL QUARRY COVED BASE TILES SLOPE FOR POSITIVE DRAINAGE 1/4" IN 24" TYP.</p>	<p>COUNTER TOP PROVIDED BY PK, INSTALLED BY G.C. MTLER JOINT TILE S.S. CASHIER COUNTER ELEC. J.BOX & ELEC. OUTLET, REFERENCE MEP PRE-FABRICATED WOOD FRAMES PROVIDED BY G.C. WP1 OVER 5/8" WATER RESISTANT GYP. BD. BY G.C. WP1 OVER 12" X 5/8" DUROCK CEMENT BD. BY G.C. LAMINATED PLYWOOD UNDER SIDE 5/8" GYP. BD. AS TILE BACKING INSTALL BY G.C. SCHLUTER COVE TRIM TREATED SILL PLATE SET IN BEAD OF SEALANT, TYP. REFER STRUCTURAL 20 GA. GALV. PLATE REFER 2/A-403 FOR WATER PROOFING DETAIL QUARRY COVED BASE TILES SLOPE FOR POSITIVE DRAINAGE 1/4" IN 24" TYP.</p>	<p>COUNTER TOP PROVIDED BY PK, INSTALLED BY G.C. MTLER JOINT OVERLAP 4" TILE WALL BEYOND CUSTOMER PLYWOOD UNDER SIDE SCHLUTER COVE TRIM SEALANT, GE SILPRUF SCS 2000 STAINLESS STEEL SERVICE TABLE MAKE JOINT TIGHT WITH CLEAR SEALANT BY G.C. THIS FACE OF PRE-FABRICATED LOW WALL SHALL BE ESTABLISHED RELATIVE TO DIMENSIONS PROVIDED ON A-103 WP1 OVER 5/8" WATER RESISTANT GYP. BD. BEYOND PRE-FABRICATED WOOD FRAMES PROVIDED BY OWNER, INSTALLED BY G.C. WP1 OVER 12" X 5/8" DUROCK CEMENT BD. BY G.C. 5/8" GYP. BD. AS TILE BACKING INSTALL BY G.C. TREATED SILL PLATE SET IN BEAD OF SEALANT, TYP. REFER STRUCTURAL QUARRY COVED BASE TILES SLOPE FOR POSITIVE DRAINAGE 1/4" IN 24" TYP. 20 GA. GALV. PLATE REFER 2/A-403 FOR WATER PROOFING DETAIL</p>
ELECTRIC PANELS DETAIL 19 Scale= 3/4" = 1'-0" A-403	WALL BASE @ COOKLINE 16 Scale= NTS A-403	CASHIER COUNTER PLAN & DETAIL 12 Scale= 1 1/2" = 1'-0" A-403	SERVICE COUNTER DETAIL 8 Scale= 1 1/2" = 1'-0" A-403	SERVICE COUNTER DETAIL 4 Scale= 1 1/2" = 1'-0" A-403

<p>NOT USED 15 Scale= x = 1'-0" A-403</p> <p>WALK-IN WALL PANEL WALK-IN CEILING PANEL METAL COVE BASE SUB-FLOOR PANEL VULKEM 116 TREMCO SEALANT COLOR: ALUMINUM SPREAD SLOW DRYING SPRAYING FOAM IN BETWEEN QUARRY TILE AND SUB-FLOOR PANEL LEVEL, SUB-FLOOR PANEL AFTER FOAM APPLICATION. NOTE: PROVIDE WALK-IN FREEZER MANUFACTURER FORM PLASTIC INSULATION COMPLIANCE LABEL PER SEC.2602 UBC 97</p>	<p>TYP. WALK-IN FREEZER SECTION 11 Scale= 1 1/2" = 1'-0" A-403</p> <p>8 A-403 12 A-403 WASHED LINES INDICATES EDGE OF STAINLESS STEEL EQUIPMENT COUNTER TOP PROVIDED BY PANDA, INSTALLED BY G.C. COLD PAN 1" S.S. COUNTER OVERLAP SCHLUTER EDGE STRIP SCHLUTER COVE TRIM B-END ELEVATION-NTS</p>
	SERVICE COUNTER PLAN AND ELEVATION 3 Scale= 3/4" = 1'-0" A-403

<p>NOT USED 18 Scale= x = 1'-0" A-403</p> <p>5/8" GYP. BD. OVER STUDS WALL BASE TILE FLOOR TILE TILE OVER THIN SET MORTAR SEALANT, GE SILPRUF SCS 2000 'CEMCO' METAL STUDS ICBO #3403P L.A.R.R. #29923T METAL STUD L.A.R.R. #22646 MTL STUD SCREW, TOP & BOTTOM @ 16" O.C. 20 GA. GALV. PLATE BETWEEN MTL STUD AND CEMENT BD. 8" UP & 1" ON FLOOR, 1" OVERLAP ON GALV. PLATE 'HILTY' POWER DRIVEN PINS @ 24" O.C. MAX. TYP. U.N.O. I.C.B.O. #1290 2X BLOCK @ 4" O.C. MAX. (TYP) 2-#10 SCREWS (TYP.)</p>	<p>WALL BASE @ DINING ROOM 14 Scale= 3" = 1'-0" A-403</p> <p>ADDITIONAL 5/8" TYPE 'X' GYP. BD., FULL LENGTH UNDER HOOD AND UP TO 10'-0" HIGH WOK RANGE 18 GA. METAL STRAP BACKING, REFER ELEVATION 9A-502 1 1/2" S.S. SCREW FOR SECURING EQUIPMENT TO WALL 24'-11" LENGTH OF EXHAUST HOOD STUD (WOOD OR METAL) @ 16" O.C. INSULATION IF REQUIRED 5/8" TYPE 'X' GYP. BD. OVER STUDS</p>	<p>METAL STUD CONNECTION 10 Scale= 1 1/2" = 1'-0" A-403</p> <p>5/8" MOISTURE RESISTANT GREEN BD. 48" HIGH ON TOP OF 5/8" X 12" CEMENT BD. BY DUROCK WALK-IN BOX WALL PANEL WALL FINISH WP1 FINISH FRP WITH J-MOLD ON TOP OF QUARRY TILE SILICONE JOINT SEALANT VULKEM 116 TREMCO SEALANT COLOR: ALUMINUM 'CEMCO' METAL STUDS ICBO #3403P L.A.R.R. #29923T LATICRETE 9235 WATERPROOFG MEMBRANE, 8" UP ON WALL & 24" ON FLOOR, BETWEEN CEMENT BD. & QUARRY TILE MTL STUD SCREW, TOP & BOTTOM @ 16" O.C. 20 GA. GALV. PLATE BETWEEN MTL STUD AND CEMENT BD. 8" UP & 1" ON FLOOR, 1" OVERLAP ON GALV. PLATE 'HILTY' POWER DRIVEN PINS @ 24" O.C. MAX. TYP. U.N.O. I.C.B.O. #1290 VULKEM 116 TREMCO SEALANT COLOR: ALUMINUM</p>	<p>WALL BASE @ WALK-IN & STUD WALL 6 Scale= 3" = 1'-0" A-403</p> <p>5/8" MOISTURE RESISTANT GREEN BD. 48" HIGH ON TOP OF 5/8" X 12" CEMENT BD. BY DUROCK WALL FINISH WP1 (SEE SCHEDULE) FINISH FRP WITH J-MOLD ON TOP OF QUARRY TILE SILICONE JOINT SEALANT LATICRETE 9235 WATERPROOFG MEMBRANE, 8" UP ON WALL & 24" ON FLOOR, BETWEEN CEMENT BD. & QUARRY TILE 'CEMCO' METAL STUDS ICBO #3403P L.A.R.R. #29923T METAL STUD L.A.R.R. #22646 MTL STUD SCREW, TOP & BOTTOM @ 16" O.C. 20 GA. GALV. PLATE BETWEEN MTL STUD AND CEMENT BD. 8" UP & 1" ON FLOOR, 1" OVERLAP ON GALV. PLATE 'HILTY' POWER DRIVEN PINS @ 24" O.C. MAX. TYP. U.N.O. I.C.B.O. #1290</p>	<p>WALL BASE @ KITCHEN 2 Scale= 3" = 1'-0" A-403</p> <p>5/8" GYP. BD. OVER STUDS WALL TILE & BASE (SEE ELEVATIONS) PROVIDE SCHLUTER COVE TRIM FLOOR TILE SLOPE FOR POSITIVE DRAINAGE 1/4" IN 24" TYP. TILE OVER THIN SET MORTAR SEALANT, GE SILPRUF SCS 2000 'CEMCO' METAL STUDS ICBO #3403P L.A.R.R. #29923T METAL STUD L.A.R.R. #22646 MTL STUD SCREW, TOP & BOTTOM @ 16" O.C. 20 GA. GALV. PLATE BETWEEN MTL STUD AND CEMENT BD. 8" UP & 1" ON FLOOR, 1" OVERLAP ON GALV. PLATE 'HILTY' POWER DRIVEN PINS @ 24" O.C. MAX. TYP. U.N.O. I.C.B.O. #1290</p>
		METAL STUD CONNECTION 10 Scale= 1 1/2" = 1'-0" A-403	WALL BASE @ WALK-IN & STUD WALL 6 Scale= 3" = 1'-0" A-403	WALL BASE @ KITCHEN 2 Scale= 3" = 1'-0" A-403

<p>NOT USED 17 Scale= 3" = 1'-0" A-403</p> <p>FINISH FRP ABOVE STAINLESS STEEL BACKSPLASH (UPTO 48" ABOVE MOP SINK) OVER 5/8" GYP. BRD. 2X BACKING CLR. SILICONE G.C. TO FURN & INSTALL S/S 'Z' BAR - 2 SIDES MTL STUD SCREW, TOP & BOTTOM @ 16" O.C. 20 GA. GALV. PLATE BETWEEN MTL STUD AND CEMENT BD. 8" UP & 1" ON FLOOR, 1" OVERLAP ON GALV. PLATE FINISH FRP BETWEEN MOP SINK & WALL WITH FOAM 24" HIGH MOP SINK - SEE A-101 CONTACT: G.S.W. - 1-800-897-5999 STAINLESS STEEL G.S.W. MOP SINK TO BE SUPPLIED BY G.C. & INSTALLED BY G.C. STAINLESS STEEL BACKSPLASH @ 48" ABOVE MOP SINK HEIGHT, ON ALL SIDES SET MOP SINK IN MORTAR BED WITH LIQUID NAILER</p>	<p>CEILING DETAIL 13 Scale= 3/4" = 1'-0" A-403</p> <p>STRUCTURE PROVIDE PERMISSIBLE SLOTS IN CONDUIT FALLS IN BETWEEN RUN WIRE THRU CENTER OF CONDUIT - CONNECT TO ROOF STRUCT. WITH EYE LAG SCREW WRAP WIRE THRU PREDRILLED SLOTS IN RUNNERS & AROUND BOTTOM OF CONDUIT 4-12 GA. SPRAY WIRES SEE 'SPLAY' PERIMETER WIRE AT EACH TERMINATION POINT FACE OF WALL C2 OR C1 CROSS RUNNER @ 2'-0" O.C. MAIN RUNNER @ 4'-0" O.C.</p> <p>NOTE: THIS DETAIL IS APPLICABLE IN SEISMIC ZONES OR WHERE REQUIRED BY LOCAL CODE.</p>	<p>GYP. BOARD BEHIND COOKLINE 9 Scale= NTS A-403</p> <p>NOTE: INSTALLER TO PROVIDE A WATER-TIGHT SEAL BETWEEN BOTTOM OF COOLER BOX WALL AND QUARRY TILE FLOOR COOLER WALL VULKEM 116 TREMCO SEALANT COLOR: ALUMINUM S.S. RIVET AT 12" O.C. 1" X 1" ANGLE 1 1/2" HILTY SHOT PIN AT 24" O.C. (ICBO 2388) QUARRY FLOOR TILE SLOPE FOR POSITIVE DRAINAGE 1/4" IN 24" TYP. VULKEM 116 TREMCO SEALANT COLOR: ALUMINUM</p>	<p>WALK-IN COOLER BASE 5 Scale= 1/4" = 1'-0" A-403</p> <p>5/8" GYP. BD. OVER STUDS WALL TILE & BASE (SEE ELEVATIONS) PROVIDE SCHLUTER COVE TRIM FLOOR TILE SLOPE FOR POSITIVE DRAINAGE 1/4" IN 24" TYP. TILE OVER THIN SET MORTAR SEALANT, GE SILPRUF SCS 2000 'CEMCO' METAL STUDS ICBO #3403P L.A.R.R. #29923T METAL STUD L.A.R.R. #22646 MTL STUD SCREW, TOP & BOTTOM @ 16" O.C. 20 GA. GALV. PLATE BETWEEN MTL STUD AND CEMENT BD. 8" UP & 1" ON FLOOR, 1" OVERLAP ON GALV. PLATE 'HILTY' POWER DRIVEN PINS @ 24" O.C. MAX. TYP. U.N.O. I.C.B.O. #1290</p>	<p>WALL BASE @ RESTROOM 1 Scale= 3" = 1'-0" A-403</p> <p>FINISH FRP ABOVE STAINLESS STEEL BACKSPLASH (UPTO 48" ABOVE MOP SINK) OVER 5/8" GYP. BRD. 2X BACKING CLR. SILICONE G.C. TO FURN & INSTALL S/S 'Z' BAR - 2 SIDES MTL STUD SCREW, TOP & BOTTOM @ 16" O.C. 20 GA. GALV. PLATE BETWEEN MTL STUD AND CEMENT BD. 8" UP & 1" ON FLOOR, 1" OVERLAP ON GALV. PLATE FINISH FRP BETWEEN MOP SINK & WALL WITH FOAM 24" HIGH MOP SINK - SEE A-101 CONTACT: G.S.W. - 1-800-897-5999 STAINLESS STEEL G.S.W. MOP SINK TO BE SUPPLIED BY G.C. & INSTALLED BY G.C. STAINLESS STEEL BACKSPLASH @ 48" ABOVE MOP SINK HEIGHT, ON ALL SIDES SET MOP SINK IN MORTAR BED WITH LIQUID NAILER</p>
		GYP. BOARD BEHIND COOKLINE 9 Scale= NTS A-403	WALK-IN COOLER BASE 5 Scale= 1/4" = 1'-0" A-403	WALL BASE @ RESTROOM 1 Scale= 3" = 1'-0" A-403

Order Plans