



ROOF PLAN NOTES

WALK-WAY PAD NOTES:

- PADS SHALL BE AS MANUFACTURED BY "DURO-LAST" STYLE IS "ROOF TRAK II" WHITE W/ YELLOW SAFETY TRIM. CONTACT W/ THE WEB: WWW.DURO-LAST.COM OR BY PHONE: 1-800-248-0280
- EXTEND ROOF WALK-WAY PADS TO ALL EQUIPMENT, ELECTRICAL, RECEPTACLES, EXHAUST FANS AND ROOF DRAINS. VERIFY LOCATIONS IN THE FIELD.
- WALK PADS ARE NOT TO CROSS ROOFING MEMBRANE SEAMS
- THE SUPPORTS FOR THE CONDENSATION, REFRIGERATION, AND GAS PIPING TO BE MOUNTED ON 12"X12" WALK PAD SECTIONS, FASTENED WITH AN APPROVED ADHESIVE.

GENERAL NOTES:

- SLOPED ROOF AREAS TO RECEIVE 40 MIL ICE & WATER SHIELD UNDERLAYMENT (ATA SHIELD OR APPR. EQ.)
- ALL LEAVES, FROM THE ROOF EDGE TO 6" UP ROOF SLOPE
- COORDINATE ALL PLUMBING PENETRATIONS WITH THE PLUMBING DRAWINGS.
- GC TO PLACE (3) LOOSE WALK-PAD IN TOWER FOR LOTTERY VENDOR
- COUNTER-SINK ALL SCREWS AT 1.0. PARAPET PLATE LOCATIONS TO PREVENT ROOF MEMBRANE DAMAGE AND TEAR.
- CONTRACTOR TO PROVIDE CRICKETS ON UPHILL SIDE OF ALL EQUIPMENT CURBS
- CONTRACTOR SHALL ENSURE THE USE OF TAPERED SHEETS OF INSULATION AT ALL CRICKETS. NO SQUARE EDGES WILL BE ACCEPTABLE
- ALL EQUIPMENT CURB CRICKETS SHALL BE BUILT UP TO ENSURE A 1/4" SLOPE FROM CENTER RIDGE TO OUTSIDE EDGE OF CURB. ALL CRICKETS SHALL EXTEND TO THE OUTSIDE EDGE OF THE CURB.
- ALL VALLEYS 3'-0" UP ON EACH SIDE OF THE VALLEY.
- ALL ROOF PENETRATIONS OR FEATURES THAT PENETRATE THE PANEL, APPLY AT 2'-0" PERIMETER AND FROM THERE DOWN TO THE EAVE.

4
Chahaci & Peterson
Architects Engineers Planners

1925 Prospect Ave.
Owensboro, KY 40360
(407) 668-1100
(407) 668-9101
www.c&p.com

PROJECT NAME: WAWA U45-FB1-VA-M v2017.01
STORE #6661-STO
Newtown Rd. & Stony Point St.
Norfolk, VA

DATE: 05-11-18
DRAWN: XX
CHECKED: SS

Revision Schedule

No.	Description	Date
1	PERMIT SET	05/11/2018
2	PRE-BID REVIEW SET	01/09/2019
3	BID SET	01/29/2019

PROJECT NO: 270577

A3