



GENERAL NOTES:

1. SEE SHEET P101 FOR ALL GENERAL NOTES.
2. DUCTWORK, CONDUIT AND PIPING SHALL BE INSTALLED BETWEEN TRUSSES OR THROUGH TRUSSES IN CEILING SHIPPING ROOM AS SHOWN WITH ALL ITEMS LOCATED ABOVE THE BOTTOM OF STRUCTURE UNLESS OTHERWISE NOTED ON PLAN.

CONSTRUCTION NOTES:

- ① P.C. SHALL INSTALL MIXING VALVE BELOW HANDBASE AT ACCESSIBLE LOCATION. SET MIXING VALVE AT 110" (MAX.) SEE DETAIL 15/P801.
- ② PROVIDE 1 1/2" RPZ BACKFLOW PREVENTER AT LOCATION SHOWN. SEE DETAIL 4/P801.
- ③ ELECTRIC GAS VALVE FURNISHED BY HOOD MANUFACTURER AND INSTALLED BY PLUMBING CONTRACTOR. ELECTRIC CONNECTIONS BY ELECTRICAL CONTRACTOR.
- ④ P.C. SHALL PROVIDE METAL BRAIDED SUPPLY LINE FROM WALL TO EQUIPMENT.
- ⑤ PROVIDE 1/2" TEMPERED WATER DOWN TO CHEMICAL FEED. PROVIDE (BFP-3 (RPZ)) ON CHEMICAL FEED LINE, IF NOT ALREADY PROVIDED. PROVIDE TWO HOSE CONNECTION TO CHEMICAL FEED.
- ⑥ P.C. SHALL INSTALL MIXING VALVE BELOW LAVATORY. SET MIXING VALVE AT 110" (MAX.). SEE DETAIL 14/P801.
- ⑦ ROUTE 3/4" CW TO WATER BOOSTER AND 3/4" CW TO FILTER. SEE DETAIL 1/P801 FOR PIPING SCHEMATIC.
- ⑧ NATURAL GAS PIPING DOWN TO MANFOLD. SUPPORT PIPING TO WALL AT 48" INTERVALS.
- ⑨ GAS PIPING DOWN THROUGH ROOF. SEE SHEET P401 FOR CONTINUATION. SEE DETAIL 6/P801.
- ⑩ PROVIDE 1/2" COLD WATER DOWN TO CHEMICAL FEED, PROVIDE (BFP-3 (RPZ)) ON CHEMICAL FEED LINE, IF NOT ALREADY PROVIDED. PROVIDE TWO HOSE CONNECTION TO CHEMICAL FEED.

REFER TO CIVIL FOR CONTINUATION

LMHT Project No. 18187
THIS DRAWING IS THE PROPERTY OF THE ARCHITECT AND MAY NOT BE REPRODUCED OR USED WITHOUT HIS WRITTEN PERMISSION.
LDI
 NATIONAL REGISTERED ARCHITECTS & ENGINEERS
 3005 Constitution Hill Blvd, Suite 150 Mariettaville, GA
 PH: 678 544 7251 FAX: 678 544 9399
 A Division of LMHT Associates



PROJECT: FIVE GUYS BURGERS & FRIES
 630 CRANE CREEK DRIVE
 AUGUSTA, GA, 30907
DRAWING: PLUMBING WATER PLAN

Revisions	
REVISION DATE	
PROJECT DATE	12.3.18
Drawn By	SCP
Checked By	SDS
Sheet No.	P301

1 WATER PLAN
P301 SCALE: 1/4" = 1'-0"

IF ANY DISCREPANCIES ARE FOUND ON THE PLANS, THE PLUMBING CONTRACTOR SHALL INSTALL THE MORE CONSERVATIVE SPECIFICATION AND CALL ENGINEER FOR CLARIFICATION.

PRIOR TO SUBMITTING BID, CONTRACTOR SHALL VISIT SITE TO EXAMINE SITE CONDITIONS. CONTRACTOR SHALL EXAMINE EXISTING CONDITIONS AND REUSE AND RECONNECT TO EXISTING SERVICE WHERE POSSIBLE. ALL REUSED PIPING AND EQUIPMENT MUST COMPLY WITH STATE AND LOCAL PLUMBING CODE.

WHILE EVERY ATTEMPT HAS BEEN MADE IN THE PREPARATION OF THIS PLAN TO AVOID MISTAKES, THE DESIGNER AND COMPANY CANNOT GUARANTEE AGAINST ERROR OR UNFORESEEN FIELD CONDITIONS. THE CONTRACTOR OR BUILDER MUST CHECK ALL DIMENSIONS, DETAILS AND REPORT ANY DISCREPANCIES.

Order Plans @