

REFERENCE DETAILS
 ASD-48, 49, 42, 8, 50, 1, 84, 8, 104-14
CONTROL JOINT NOTES:
 1. PROVIDE JOINTS AT 12'-0" TO 18'-0" IN EACH DIRECTION FOR INTERIOR TILE WORK EXPOSED TO DIRECT SUNLIGHT OR MOISTURE.
 2. PROVIDE JOINTS WHERE TILE MEET PERIMETER SURFACES SUCH AS PERIMETER WALLS, DISH/WALL FLOORS, CURBS, COLUMNS, PIPES, CEILING, AND WHERE CHANGES OCCUR IN BACKING MATERIALS.
 3. ALL EXPANSION, CONTRACTION, COLD AND HEATING JOINTS IN THE STRUCTURE SHOULD CONTINUE THROUGH THE TILE WORK INCLUDING SUCH JOINTS AT VERTICAL SURFACES.
 4. JOINTS THROUGH TILE WORK DIRECTLY OVER STRUCTURAL JOINTS MUST NEVER BE HANDMADE THROUGH THE STRUCTURAL JOINTS.
 5. PROVIDE CONTROL JOINTS IN GENERAL AT 8'-0" MAX IN EACH DIRECTION AND AT CORNERS OF COLUMNS AND CORNERS. SEE CONCRETE PLACEMENT PLAN FOR CONTROL JOINT LOCATIONS.

GENERAL FLOOR COVERING NOTES:

- SEE SPECIFICATIONS FOR ALL FINISH COVERS AND FINISHES AND FOR ADDITIONAL FINISH REQUIREMENTS THAT MAY NOT BE NOTED ON DRAWINGS.
- BEFORE INSTALLATION OF V.C.T. SUBCONTRACTOR TO VERIFY LAYOUT WITH EXISTING CONDITIONS AND DIMENSIONS. ANY DISCREPANCIES SHOULD BE BROUGHT TO THE ATTENTION OF KROGER PROJECT MANAGER.
- FLOOR COVERINGS SHALL NOT BE INSTALLED OVER TRENCHES AND PITS BEFORE CONSTRUCTION HAS GAINED.
- IF CUTTING V.C.T. IS NECESSARY, NO TILE SHALL BE LESS THAN 4" EXCEPT AT WALLS. ALL V.C.T. TILE BEHOLD TO RUN IN SINGLE DIRECTION UNLESS OTHERWISE NOTED.
- ALL FLOOR TILE INSTALLATION SHALL BE COORDINATED WITH KROGER PROJECT MANAGER TO ALLOW FOR MINIMUM HANDING WITH NO HAZARD TO THE COMPLETION OF THE INSTALLATION PRIOR TO DELIVERY & INSTALLATION OF KROGER REFRIGERATION EQUIPMENT. IF THE FLOOR CANNOT BE MAINTAINED IT IS THE RESPONSIBILITY OF THE GENERAL CONTRACTOR TO PROTECT THE TILE BY ANY MEANS DEEMED NECESSARY BY THE KROGER PROJECT MANAGER.
- ALL FLOOR TILE WORK IN EXISTING KROGER STORE TO BE DONE AT NIGHT. COORDINATE WITH STORE MANAGER AND KROGER PROJECT MANAGER.
- REPLACE ALL FLOOR FINISHES DAMAGED FROM DEMOLITION AND NEW CONSTRUCTION.
 A. ALL TILES TO BE 1/2" 1/2" UNLESS NOTED OTHERWISE.
 B. WHERE TWO TILE THICKNESS ADJON. PROVIDE TRANSITION AS REQUIRED TO PRODUCE SMOOTH FINISH.
- VERIFY ALL TILE ALIGNMENTS PER PLAN WITH FIXTURE LOCATIONS & DIMENSIONS PRIOR TO STARTING WORK.
 A. WRITE DIMENSIONS HAVE PRECEDENCE OVER SCALE.
 B. ANY DISCREPANCIES MUST BE CONTACTED KROGER PROJECT MANAGER BEFORE PROCEEDING.
- CONTRACTOR IS TO PROTECT ALL NEW TILE EDGES AGAINST TRAFFIC DAMAGE BY INSTALLING MIN. 2" WIDE EDGES OF SCRAP TILE UNTIL ADJ. NEW TILE IS LAD.
- GENERAL SALES FLOOR TILE TO GABRY UNDERBATH THE CAGES AND V.C.T. FLOORING CONTINUOUS TO PERIMETER INTERCLOSURES, WALLS, UNLESS OTHERWISE NOTED. VERIFY WITH STORE MANAGER.
- CONTRACTOR IS NOT TO SEAL V.C.T. FLOORING BY KROGER PROJECT MANAGER.
- FLOOR TILE SUBCONTRACTOR TO PROVIDE SURFACE FOR FLOOR TILE, FLOOR TILE SHALL BE INSTALLER TO PROVIDE SURFACE FOR FLOOR TILE BEING INSTALLED AND LEVEL. FLOORING MANUFACTURER OF THE FLOOR TILE BEING INSTALLED AND LEVEL. FLOORING MANUFACTURER OF THE FLOOR TILE BEING INSTALLED.
- USE A TRANSITION STRIP BETWEEN EXPOSED CONCRETE (OVER ASD-48 OR 49) S&H GET SLAB FOR INSTALLATION STIP. EXTEND 6" EAST WEST OF OPENING BY 6" W.
- BEFORE NOTING ANY OTHER FLOORING CONTRACTOR (OR SALES) THAT NEW FLOORING WILL BE INSTALLED.
- FLOOR TILE SHALL BE INSTALLED BEFORE OTHER FLOORING CONTRACTORS. PROVIDE METAL REDUCER BETWEEN FLOOR TILE BEING INSTALLED AND OTHER FLOORING CONTRACTORS.
- CONTRACTOR SHALL REMOVE EXISTING TILE UNTIL NEW TILE IS READY TO BE LAD. THE INTENT OF EXISTING FLOOR TILE IS TO REMAIN.
- INSTALL V.C.T. FLOORING ON V.C.T. PARTITIONS ADJACENT TO V.C.T. FLOORING OR SHEET METAL PARTITIONS ADJACENT TO V.C.T. FLOORING THAT WILL BE PERFORMED BY OTHER CONTRACTORS. (E.G., PARTITIONS, SHELVING, ETC.)
- REMOVE EXISTING V.C.T. FLOORING FROM ALL AREAS SIDE OF REAR-LOAD DAIRY COOLER.
- VERIFY ALL FLOOR FINISHES AND DIMENSIONS AGAINST TRAFFIC DAMAGE BY INSTALLING MIN. 2" WIDE EDGES OF SCRAP TILE UNTIL ADJ. NEW TILE IS LAD.
- FIELD DIMENSIONS ARE TO BE VERIFIED BY CONTRACTOR TO MATCH EXISTING FIELD DIMENSIONS. CONTRACTOR IS TO VERIFY AND BE RESPONSIBLE FOR ALL FIELD DIMENSIONS AND CONDITIONS INCLUDING, BUT NOT EXCLUSIVE TO: GAGE LOCATIONS, FLOOR CONDITIONS AND DIMENSIONS.
- FIELD LOCATION IS RELATIVE TO GAGE LOCATION AS SHOWN ON THE PLAN. IT IS THE RESPONSIBILITY OF THE TILE INSTALLER TO ADJUST THE PATTERN IN RELATION TO ACTUAL FIELD CONDITIONS.
- GENERAL CONTRACTOR TO REMOVE EXISTING V.C.T. FLOORING FROM SALES AREA VINYL CONCRETE TILE (V.C.T.) FLOORING TO REMAIN UNLESS NOTED OTHERWISE. GENERAL CONTRACTOR TO REMOVE DAMAGED V.C.T. AND REPLACE WITH MATCHING V.C.T. FLOOR COVERING SCHEDULE LIST V.C.T. FLOORING DESIGN BASIS FROM ASD-BUILT DOCUMENTATION FOR REFERENCE. IT IS THE RESPONSIBILITY OF THE TILE INSTALLER TO MATCH EXISTING COLORS AND FINISHES IN FIELD AND PROVIDE LIKE V.C.T. TO MATCH - COORDINATE WORK WITH KROGER PROJECT MANAGER.

KEYED FLOOR COVERING NOTES:


- EXTENTS OF RECESSED CONCRETE SLAB. REFERENCE DRAWING A12 FOR EXACT LOCATION OF EDGE OF RECESSED SLAB.
- NEW STAINLESS STEEL EDGE/RAMP TRANSITION @ EDGE OF CERAMIC RESTROOM TILE. REFER TO ASD-4C.
- NEW STAINLESS STEEL WATER STOP CASE FLASHING SHOWN AS A DASHED LINE. REFERENCE 8020-14.
- EXISTING TRENCH DRAIN TO REMAIN. REMOVE AND REPLACE TRENCH DRAIN COVER WITH NEW TO MATCH EXISTING. SEE PLUMBING DRAWINGS.
- INSTALL CONTROL, CONTRACTION JOINTS AND/OR ISOLATION JOINTS IN RECESSED FIELD AREAS SHOWN ON DRAWING. REMOVE AND REPLACE TRENCH DRAIN COVER WITH NEW TO MATCH EXISTING. REFER TO DETAIL A1A/B1.
- REMOVE A SECTION OF EXISTING DAMAGED CONCRETE. REPLACE WITH NEW CONCRETE TO MATCH EXISTING SIZE & PROFILE. - SEE ASD-B.
- REMOVE EXISTING FLOOR SLAB. SEE CONCRETE PLACEMENT PLAN FOR SURFACE FINISH AND COLOR.
 - ALTERNATE NO. 2 - NEW CONCRETE FLOOR SLAB. SEE CONCRETE PLACEMENT PLAN FOR SURFACE FINISH AND COLOR.
- REMOVE EXISTING QUARRY TILE & SETTING BED IN HATCHED AREA (SEE CONCRETE PLACEMENT NOTES). REMOVE EXISTING CONCRETE SLAB IN HATCHED AREA & REPLACE WITH NEW 4" (MIN) CONC. REFER TO CONCRETE PLACEMENT PLAN (SHEET A13) FOR SLAB ELEVATIONS AND SLOPES. REMOVE QUARRY TILE & SETTING BED TO THE NEAREST FULL TILE. AFTER SLAB CURING & SLOPE CORRECT. INSTALL NEW QUARRY TILE AND SETTING BED TO MATCH EXISTING COLOR AND SHAPE.
- REMOVE EXISTING QUARRY SLAB IN HATCHED AREA AND ADJACENT QUARRY TILE TO NEAREST FULL TILE AS REQUIRED FOR NEW CONSTRUCTION. REPLACE WITH NEW 4" (MIN) CONC. REFER TO CONCRETE PLACEMENT PLAN (SHEET A13) FOR SLAB ELEVATIONS AND SLOPES. INSTALL NEW QUARRY TILE AND SETTING BED TO MATCH EXISTING COLOR AND SHAPE. TILE TO FLUSH WITH EXISTING QUARRY TILE.
- EXISTING QUARRY TILE & SETTING BED OVER CONCRETE SLAB TO POWER HAZ & THROUGHOUT CLEAN QUARRY TILE AND GROUT THROUGHOUT PREP AREAS. TO PROVIDE PROTECTION TO TILE. ALL TILE SURFACES, REFER TO CONCRETE PLACEMENT PLAN FOR DAMAGE OR CONTAMINATION DURING CLEANING. WORK MAY REQUIRE TEMPORARILY FLOORING AND MOVING OF FLOORING AS NECESSARY TO PROTECT. REMOVE QUARRY TILE AND SETTING BED TO MATCH EXISTING. REFER TO DETAIL T-1, T-2, T-3, T-4 FOR TILE PATTERN AND V.C.T. TO MATCH EXISTING. REFER TO DETAIL T-1, T-2, T-3, T-4 FOR TILE PATTERN AND V.C.T. TO MATCH EXISTING. REFER TO DETAIL T-1, T-2, T-3, T-4 FOR TILE PATTERN AND V.C.T. TO MATCH EXISTING. REFER TO DETAIL T-1, T-2, T-3, T-4 FOR TILE PATTERN AND V.C.T. TO MATCH EXISTING. REFER TO DETAIL T-1, T-2, T-3, T-4 FOR TILE PATTERN AND V.C.T. TO MATCH EXISTING.
- REMOVE AND REPLACE DAMAGED OR UNEVEN QUARRY TILE & SETTING BED IN HATCHED AREA. QUARRY TILE TO REMAIN REMOVE TO THE NEAREST FULL TILE EXTENT OF TILE REMOVAL AND REPLACE WITH V.C.T. TO MATCH EXISTING. REFER TO DETAIL T-1, T-2, T-3, T-4 FOR TILE PATTERN AND V.C.T. TO MATCH EXISTING. REFER TO DETAIL T-1, T-2, T-3, T-4 FOR TILE PATTERN AND V.C.T. TO MATCH EXISTING. REFER TO DETAIL T-1, T-2, T-3, T-4 FOR TILE PATTERN AND V.C.T. TO MATCH EXISTING. REFER TO DETAIL T-1, T-2, T-3, T-4 FOR TILE PATTERN AND V.C.T. TO MATCH EXISTING.
- REMOVE EXISTING QUARRY TILE FROM EXISTING BASE AND REPLACE WITH NEW TO MATCH EXISTING. BASE TO REMAIN.
- REMOVE EXISTING QUARRY TILE FROM EXISTING BASE AND REPLACE WITH NEW TO MATCH EXISTING. BASE TO REMAIN.

FLOOR COVERING SCHEDULE

FLOOR TYPE	QTY.	MANIF.	PRODUCT/SIZE	COLOR	FURNISHED / UNINSTALLED
VINYL COMP. TILE	VI-20A	ATKOCK BY TARKETT	THRU-QUARTZ	103920	9.0 / 8.0
	VI-20B	ATKOCK BY TARKETT	THRU-QUARTZ	1023M	9.0 / 8.0
	VI-20C	ATKOCK BY TARKETT	CORTINA COLORS	V-18B	9.0 / 8.0
	VI-20D	ATKOCK BY TARKETT	VARIATIONS	SALSAH	9.0 / 8.0
	VI-20E	ATKOCK BY TARKETT	CORTINA COLORS	V-17A	9.0 / 8.0
	VI-20F	ATKOCK BY TARKETT	CORTINA COLORS	V-1071	9.0 / 8.0
	VI-20G	ATKOCK BY TARKETT	GRANITE SLIP	SK-156	9.0 / 8.0
	VI-20H	ATKOCK BY TARKETT	GRANITE SLIP	SK-158	9.0 / 8.0
	VI-20I	ATKOCK BY TARKETT	NATURAL CREATORS	CLASSICS LUXURY	9.0 / 8.0
	VI-20J	ATKOCK BY TARKETT	DUR-A-FLEX	SKA, STONHARD	9.0 / 8.0
GLAZED	GT-001	DALTILE	QUARRY TEXTURES	OTR, DIABLO	9.0 / 8.0
	GT-002	LAINGRE INTERNATIONAL	RECTIFIED PORCELAIN	TILE 24"x24"	9.0 / 8.0
	GT-003	LAINGRE INTERNATIONAL	SPECTRA LOCK PRO	TRV, MOGHA	9.0 / 8.0
	GT-004	LAINGRE INTERNATIONAL	REG ACCOGLOR EPK	REG ACCOGLOR EPK	9.0 / 8.0

LEGEND FOR FLOOR COVERING HATCH PATTERNS

- NEW GRANITE - SEE PLAN & SCHEDULE FOR TYPE AND MANUFACTURER.
- AREA OF NEW CONCRETE FLOOR SLAB - REFERENCE CONCRETE PLACEMENT PLAN FOR EXTENTS (A12).
- NEW QUARRY TILE TO MATCH EXISTING - SEE PLAN & SCHEDULE FOR TYPE AND MANUFACTURER.
- NEW VINYL COMPOSITION FLOOR TILE - MATCH EXISTING SALES AREA FIELD AND ACCENT TILE COLORS & TEXTURE.
- NEW EXISTING LUXURY VINYL TILE - NEW TILE TO MATCH EXISTING COLOR AND SIZE - SEE PLAN & SCHEDULE FOR TYPE AND MANUFACTURER.
- NEW CERAMIC FLOOR TILE - SEE PLAN & SCHEDULE FOR TYPE AND MANUFACTURER.
- NEW RESILIENT FLOORING - SEE PLAN & SCHEDULE FOR TYPE AND MANUFACTURER.



D&E DOLLARS ARCHITECTURE INC.

13600 Snellville Rd.
 Suite 1100
 Snellville, GA 30151
 (770) 875-7915
 Fax: (770) 875-7928



NO. REVISIONS

KROGER STORE #GA-483 SNELLVILLE
 1670 STATE HWY 124, SUITE 'F', SNELLVILLE, GEORGIA 30078

FLOOR COVERING PLAN, NOTES & DETAILS

COPYRIGHT

ALL RIGHTS RESERVED. NO PART OF THIS DOCUMENT IS TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT THE WRITTEN PERMISSION OF D&E ARCHITECTURE, INC.

COPYRIGHT

ISSUE DATE: MARCH 04, 2019

PROJECT NO: 219206

SHEET NUMBER: **A1.6**