



1 REFLECTED CEILING PLAN
A3 3/16" = 1'-0"
NORTH

SEE ELECTRICAL SHEETS FOR EMERGENCY LIGHTS LOCATIONS

SEE SHEET A3.1 FOR ADDITIONAL RCP SCHEDULES, NOTES AND DETAILS

RCP KEYED NOTES

- 1 LOCATION OF SECURITY CAMERA, TYP (10), SEE SHEET A3.1 FOR SCHEDULE, TYPE AND MOUNTING HEIGHT.
- 2 UNISTRUT MOUNTED.
- 3 DASHED LINE INDICATES OUTLINE OF LOW PARTITION BELOW.
- 4 SEE SHEETS A5.4 AND A5.5 FOR MOUNTING LOCATIONS OF WALL-MOUNTED LIGHT FIXTURES.
- 5 EXG 8x8 STEEL ANGLE STIFFENER TO REMAIN. PAINT TO MATCH SOFFIT. SEE STRUCTURAL SHEETS. FIELD VER EXACT LOCATIONS.
- 6 ILLUMINATED "LUCKY BRAND" DOUBLE-SIDED LOGO BLADE SIGNAGE AT TRELIS ABOVE FOR REFERENCE ONLY. SIGNAGE UNDER SEPARATE PERMIT. COORDINATE W/ LL & SIGN VENDOR.
- 7 LOCATION OF ILLUMINATED "LUCKY BRAND" STOREFRONT SIGNAGE. SIGNAGE UNDER SEPARATE PERMIT. COORD. W/ LL & SIGN VENDOR.
- 8 CENTER LIGHT FIXTURE IN FITTING ROOM, TYP UON.
- 9 GC TO PROVIDE CEILING GRID, SEE A3.1 & A6.1 FOR ADD'L INFO.
- 10 GC TO PROVIDE WHITE PAINTED UNISTRUT AND THREADED ROD @ 9'-0" AFF TO MOUNT PENDANT LIGHTS.
- 11 LOCATION OF WIRELESS ROUTER ACCESS POINT. SEE ELECTRICAL.
- 12 FIXTURE DESIGNATED AS EMERGENCY & NIGHT LIGHT. SEE ELEC. SHEETS.
- 13 NOT USED.
- 14 GC TO PROVIDE 5/8" GYP BD AT THE BACKSIDE OF THE MALL BULKHEAD TO DECK IF NOT ALREADY EXISTING. TAPE/SAND READY FOR FINISHES.
- 15 PROVIDE FIBERGLASS ACCESS PANEL AT INTERIOR FACE OF STOREFRONT BEHIND SIGNAGE. PAINT TO MATCH CEILING FINISH. COORD. EXACT LOCATION WITH TENANT PROJECT MANAGER. SEE DETAIL 5/A3.1. GC TO INCLUDE PRICING FOR TOTAL.
- 16 CEILING GRID, INSTALL/LOCATE ABOVE PLATFORM FIXTURE BELOW. WIRE MESH SIDE FACES CEILING. SEE STRUCTURAL SHEETS FOR ADD'L INFO. SEE 7/A3.1 FOR DETAILS.
- 17 MOUNT ON INTERIOR FACE OF GYP BD. SOFFIT, BOT @ 14'-6" AFF

CEILING TYPE SCHEDULE

SYMBOL	DESCRIPTION
CL1	5/8" GYP BD OVER 18 GA MTL STUDS @ 16" O.C. PREPARE FOR PAINT OR OTHER FINISHES AS NOTED. HEIGHT PER PLAN.
CL2	OPEN TO DECK ABOVE. ALL CONDUIT SHALL BE GANGED, PARALLEL, & PERPENDICULAR TO LEASE LINES. ALL PIPES, DUCTS & FIXTURES SHALL BE SUPPORTED FROM HANGRODS OR AIRCRAFT WIRE PER LATEST SMACNA STANDARDS. VERIFY FIRE PROOFING IS INTACT, IF APPLICABLE.
CL3	1/4" SMOOTH HARDIESOFFIT ON 1/2" EXTERIOR GRADE PLYWOOD OVER 18 GA MTL STUDS @ 16" O.C. HEIGHT PER PLAN. FINISH AS SCHEDULED. INCLUDE 3/4" HARDIE TRIM AT PERIMETER. SEE 7/A6.1 FOR DETAIL FL-APPROVAL #13265.

FIRE PROTECTION NOTES

1. FIRE SPRINKLER/ALARM DESIGN, IF REQUIRED, SHALL BE CONDUCTED BY A STATE CERTIFIED DESIGNER.
2. FIRE SPRINKLER/ALARM CONTRACTOR SHALL SUBMIT SHOP DRAWINGS TO LANDLORD AND ALL APPLICABLE CODE OFFICIALS AS REQ FOR APPROVAL/PERMITS.
3. FIRE SPRINKLER/ALARM CONTRACTOR SHALL USE THE CEILING PAN FOR LAYOUT TO COORDINATE SPRINKLER HEAD LOCATIONS AND ALTERATIONS OF EXISTING SYSTEM TO AVOID CONFLICTS WITH EXISTING CONDITIONS OR MECHANICAL AND ELECTRICAL SYSTEMS.
4. IT IS THE INTENT THAT SPRINKLER MAIN AND BRANCH LINES WILL NOT BE RELOCATED. SPRINKLER HEADS WILL NEED TO BE (RE)LOCATED AS REQUIRED BY CHANGES IN THE CEILING/STORE DESIGN FROM THE CURRENT LAYOUT PER NFPA STANDARDS.
5. WHERE NEW HEADS ARE REQUIRED:
 - PROVIDE CONCEALED/FULLY-RECESSED HEADS WITH WHITE CONCEALER CAPS AT ALL GYP BD AND ACT CEILING AREAS. CENTER IN ACT CEILING TILE.
 - PROVIDE UPTURNED HEADS AND EXTENSIONS AS NECESSARY AT CEILING LOCATIONS WHEN SPRINKLER MAIN AND BRANCH LINES ARE BELOW THE CEILING.
 - PROVIDE UPTURNED HEADS AND EXTENSIONS AS NECESSARY AT OPEN-TO-STRUCTURE CONDITIONS.

RCP GENERAL NOTES

1. VERIFY HEIGHTS AND LOCATIONS OF EXISTING OVERHEAD OBSTRUCTIONS. NOTIFY ARCHITECT AND TENANT IMMEDIATELY OF ANY SUCH OBSTRUCTIONS THAT MAY INTERFERE WITH STORE DESIGN.
2. PROVIDE CEILING ACCESS PANELS IN GYP BD CEILINGS AS REQUIRED BY ENGINEERS AND FOR ANY EXISTING LANDLORD EQUIPMENT. PAINT TO MATCH ADJACENT CEILING FINISH.
3. PROVIDE ADEQUATE CLEARANCES FOR DUCTS & RELATED APPURTENANT ITEMS NECESSARY TO MAINTAIN THE SPECIFIED HEIGHTS FOR CLG SYSTEMS & LIGHT FIXTURES ABOVE FINISHED FLOOR.
4. PROVIDE HANGER AND SAFETY WIRE FOR LIGHT FIXTURES, SPEAKERS, AND AIR SUPPLY/RETURN DIFFUSERS (AS REQUIRED PER LOCAL CODE).
5. ALL CEILING HEIGHTS INDICATED ON PLANS ARE FROM TOP OF FINISH FLOOR TO UNDERSIDE OF FINISH CEILING UNLESS OTHERWISE NOTED.
6. ARCHITECTURAL DRAWINGS DETERMINE LUMINAIRE LOCATION AND OTHER ARCHITECTURAL ITEMS AND SUPERSEDE ALL OTHER CEILING APPURTENANCES, SUCH AS DIFFUSER LOCATIONS.
7. GC TO COORDINATE EXACT LOCATION OF SPEAKERS WITH VENDOR.

PATRICK G. BLEES
architecture • planning • interior design

PATRICK G. BLEES ARCHITECT, PLLC
800 WASHINGTON AVE. N., SUITE 208
MINNEAPOLIS, MN 55401-1330
PHONE: (612) 547-1300
FAX: (612) 547-1301

CONTACT: ELYVY B. CLEARY
ecleary@cmarch.com

SEAL:

PATRICK G. BLEES, ARCHITECT

04/03/19
DATE ISSUED

AR93439
REG. NO.

LUCKY BRAND

DANIA POINTE

1763 POINTE BLVD
DANIA BEACH, FL
33004

SPACE #M115

SPECIALTY

SHEET TITLE:
REFLECTED CEILING
PLAN AND NOTES

REVISIONS:
ORIGINAL ISSUE: 01.17.19
NO: 1 DATE: 04/03/19 BY: BLDG

04.03.19	BLDG

PROJECT NO: 18028.008
DRAWN BY: MGM/EBC

A3