



**FLOOR PLAN**  
SCALE: 1/4" = 1'-0"

- OUTSIDE FACE OF FOUNDATION WALL BELOW.
- C. ALL ANGLED WALLS ARE AT 90° UNLESS NOTED OTHERWISE.
- D. FIRE EXTINGUISHERS, SHALL COMPLY WITH APPLICABLE BUILDING CODES AND LOCAL RESTRICTIONS. G.C. SHALL PROVIDE ONE (1) TYPE "ABC" EXTINGUISHER IN A SEMI-RECESSED, CLEAR ANODIZED ALUMINUM CABINET IN THE DINING ROOM AS LOCATED BY THE FIRE-MARSHAL AND ONE (1) TYPE "K" EXTINGUISHER WALL-MOUNTED ON A BRACKET IN THE KITCHEN. COORD. W/ FOOD SERVICE AND THE LOCAL FIRE MARSHAL.
- E. ELEVATION OF DRIVE-THROUGH LANE 2" (MAXIMUM) BELOW FINISH FLOOR ELEVATION. DRIVE-THROUGH LANE AT SAME ELEVATION AS FINISH FLOOR IS PREFERRED. REFERENCE DETAIL #5, SHEET A-1.1 FOR DOOR AND WINDOW TYPES, REFER TO SHEET A-1.1.
- F. AT THE KITCHEN THE GC IS TO PROVIDE STAINLESS STEEL OUTER CORNERS AT QUARRY TILE BASE IN LIEU OF QUARRY TILE CORNERS - SEE [HTTP://WWW.CENTURY-CORNERS.COM](http://www.century-corners.com)

**KEYED NOTES:**

- SELF-SERVE DRINKS AND CONDIMENT STAND. REFER TO SHEET EQ-1.
- STEEL BOLLARD - REFER TO SHEET S-1.
- ELECTRIC SERVICE - REFER TO ELECTRICAL DRAWINGS.
- SERVICE COUNTER PARTITION BY G.C. REFER TO WALLS ON SHEET E-4 FOR ADDITIONAL INFORMATION. PROVIDE COUNTER TOP/FINISHES INSTALLATION RESPONSIBILITY WITH THE SUPPLIER. MAXIMUM COUNTER HEIGHT = 32" F.F.
- CORNER GUARDS - REFER TO DETAIL #4, SHEET A-1.1.
- MENU BOARD BULKHEAD ABOVE RESTROOMS TO SHEET A-4.1
- INTERIOR WALK-IN COOLERS WITH FLOOR ON CONCRETE SLAB. VERIFY SIZE WITH MANUFACTURER.
- PROVIDE ADDITIONAL BRACKETS ON WALLS BEHIND URINAL SCREEN AND BEHIND PLUMBING FIXTURES FOR SUPPORT OF WATER LINES (TYPICAL).
- ALL WALLS AT EXPOSED TRUSSES TO BE FRAMED AND FINISHED TO THE ROOF DECK ABOVE.
- SUBSTRATE CREW:
  - RESTROOMS - 5/8" USG "DUROCK" PANELS AT FINISH FLOOR TO 24" A.F.F.
  - 5/8" WATER RESISTANT GYPSUM BOARD FROM 24" A.F.F. TO 6" ABOVE FINISHED CEILING.
  - PROVIDE ALTERNATE BID OF 5/8" USG "FIBEROCK" PANELS IN LIEU OF DUROCK.
  - DINING ROOM - CORRIDOR - 5/8" TYPE USG "SHEETROCK" TYPE "X" GYPSUM WALL BOARD.
  - FINISH - CORONADO PAINT - LIGHT ORANGE PEEL APPLIED WITH CORONADO AIR ASSIST TIP (Z-12KD) OR EQUAL.
- ELECTRICAL PANELS
  - OPTION #1: RECESS ELECTRICAL CONTACTOR PANEL AND PANELS "A", "B" AND "M" IN FURRED OUT WALL ADJACENT TO EXTERIOR FRAMING. G.C. TO VERIFY PANEL SIZES PRIOR TO FURR-OUT TO INSURE ADEQUATE SPACE.
  - OPTION #2: HILL PHOENIX INTEGRATED WALL UNIT INCLUDES PANELS "A", "B", "M" AND MASTER CONTRACTOR PANEL IN ONE CABINET. UNIT TO BE SURFACE MOUNTED ON A 4" HIGH CONCRETE CURB. REFERENCE SHEET E-5 FOR ADDITIONAL INFORMATION.
- PROVIDE 10"x10" FINISHED OPENING THROUGH WALL CENTERED AT 13" A.F.F. FOR ROUTING OF UTILITIES.
- CAN WASH - DUROCK SUBSTRATE ON ALL THREE SIDES, FLOOR TO CEILING.
- OFFICE WINDOW - REFERENCE SHEET A-10.
- 4" DEEP FURR-OUT ELEMENT, 18" FINISH WIDTH MINIMUM (U.N.O.). REFER TO WALL SECTIONS. PROVIDE 12" DEEP CONCRETE CURB (REF. FOUNDATION PLAN) AND FRAMING AS REQUIRED FOR FINISH DIMENSION REQUIREMENTS.
- TILE FLOOR (REFERENCE SPECIFICATIONS ON ID SHEETS).
- +++++ INDICATES 5/8" PLYWOOD BACKING ON WALLS FOR EQUIPMENT AS INDICATED ON PLAN OR SHELF SUPPORT FROM 48" A.F.F. TO 96" A.F.F., BEHIND 3-COMPARTMENT SINK AND PREP SINK AND ON BULKHEAD AT MENU BOARD WALL FROM 6'-8" A.F.F. TO BOTTOM OF ROOF TRUSSES.
- COUNTER TOP - REFERENCE DETAIL #5, A-1.1.
- USG 5/8" DUROCK (BOTH SIDES) ON 3"-5/8", 18 GAUGE CEE STUD FRAMING AT 16" O.C. BEHIND HOOD. WALL TO EXTEND 18" BEYOND EACH END OF HOOD.
- STAINLESS STEEL PANELS BELOW AND 18" WIDE AT EACH SIDE OF HOOD SUPPLIED BY HOOD MANUFACTURER AND INSTALLED BY G.C.
- 4" CONCRETE WALK BETWEEN DRIVE-THROUGH BUMP-OUTS. CONCRETE WALK IS NOT REQUIRED IF EXPEDITING DOORS ARE NOT USED.
- INDICATES 3"x12" SUBWAY TILE. REFER TO SHEET ID-1/AD-1.1.
- REMAINING BACK OF HOUSE WALLS TO BE FINISHED IN FIBERGLASS REINFORCED PANELS, FRP-1 (REFER TO APPLICABLE INTERIOR FINISH SCHEDULE).
- 8" STUD WALL. REFER TO INTERIOR FINISH SCHEDULE.
- PROVIDE TYPE ABC FIRE-EXTINGUISHER IN SIMI-RECESSED WALL-CABINET.
- PROVIDE TYPE X FIRE EXTINGUISHER AT KITCHEN - LOCATED ON WALL-MOUNTED HOOK WERE REQUIRED BY FIRE-MARSHAL.
- PROVIDE DRAFT-STOP - 2X4 FRAMING W/ TAPED AND SEALED GYP BETWEEN THE DECK AND THE TOP OF COOLER - ABOVE CEILING AT COOLER / FREEZER.
- WALLS AT RESTROOMS SHOWN W/ ADDITIONAL DIMENSION SPACE TO ALLOW FOR TILE WALL FINISHES; STUDS @ 5-1/2" & 6" WALLS ARE TO BE 2X4 (NOM) STUDS W/ FINISHES, ETC.
- BACK OF HOUSE FLOOR & BASE FINISHES TO BE THE FOLLOWING UNLESS NOTED OTHERWISE BY INTERIOR DECOR:
  - FLOOR - QUARRY TILE - 6X6 - DAL-TILE COLOR: -0042 "AIRD GRAY" W/ ADDED ABRASIVE GRAIN.
  - BASE - QUARRY TILE - 5X6 - DAL-TILE COLOR: Q-3565 "AIRD GRAY"
  - GROUT - LATICRETE - SPECTRALOCK 2000G - COLOR: #45 "RAVEN"
  - TRANSITION STRIPS (AS NEEDED) - SCHLUTER SYSTEM - SCHIENE AND / OR AE 1000 - R, SATIN ANODIZED ALUMINUM - 3/8" - 10MM
- OFFICE WINDOW - 1'-8"(W) X 2'-0" TALL CLEAR ANODIZED ALUM. STOREFRONT FRAMING W/ SINGLE PANEL, CLEAR, TEMPERED GLAZING SET 3'-0" (MIN.) A.F.F.

Order Plans @



PREMIER KINGS, INC.  
5529 CARMICHAEL ROAD  
MONTGOMERY, ALABAMA 36117  
P.O. BOX 1100  
LINES@BKCALABAMA.COM

2126 Morris Avenue  
Birmingham, AL 35203  
Phone: (205) 329-1751  
Fax: (205) 329-1752  
www.hpluhba.com

**James M. Huckestein**  
architect, AIA  
architecture • planning • interior design

