

SANITARY PLUMBING FLOOR PLAN
1/4" = 1'-0"

GENERAL NOTES	
A.	KEY NOTES WITH ELLIPTICAL SYMBOL AND NUMBER CORRESPOND TO KITCHEN EQUIPMENT SHOWN IN KITCHEN PLAN SHEETS. REFER TO KITCHEN PLANS FOR SUPPLEMENTAL INFORMATION.
B.	ALL EXPOSED PIPING IN PUBLIC AREAS SHALL BE INSTALLED AS TIGHT AS POSSIBLE TO THE WARM SIDE OF THE EXPOSED ROOF STRUCTURE.
C.	THE INSTALLATION OF THE PLUMBING SYSTEMS SHALL BE COORDINATED WITH ALL ELECTRICAL AND MECHANICAL EQUIPMENT, AND STRUCTURAL SLAB AND FRAMING.
D.	REFER TO PLUMBING SHEET P3.1 FOR PLUMBING FIXTURE AND EQUIPMENT SCHEDULES INCLUDING SPECIFICATIONS AND ROUGH-IN SIZES.
E.	REFER TO THE KITCHEN DRAWINGS PREPARED BY THE KITCHEN EQUIPMENT SUPPLIER FOR ADDITIONAL INFORMATION NOT SHOWN ON THIS SHEET.
F.	PLUMBING CONTRACTOR SHALL COORDINATE WITH THE KITCHEN EQUIPMENT SUPPLIER FOR THE COMPLETE INSTALLATION AND SERVICE CONNECTIONS OF ALL KITCHEN EQUIPMENT.
G.	PLUMBING CONTRACTOR SHALL BE RESPONSIBLE FOR THE COMPLETE INSTALLATION OF ALL DRAIN LINES FROM KITCHEN EQUIPMENT. REFER TO THE KITCHEN DRAWINGS FOR PROPOSED SIZES AND ROUTING. ALL INDIRECT DRAIN LINES SHALL BE INSTALLED WITH APPROVED AIR GAPS.
H.	REFER TO ARCHITECTURAL AND MILLWORK DRAWINGS FOR DETAILS OF COUNTERTOPS, CASEWORK, AND OTHER FIXTURES, SHOWING EXACT LOCATION OF OPENINGS FOR PLUMBING ITEMS BEING INSTALLED. COORDINATE THE COMPLETE INSTALLATION WITH THE GENERAL CONTRACTOR.
I.	THE PROPOSED ROUTING AND SIZES OF SODA SLEEVE LINES ARE SHOWN ON ARCHITECT DRAWINGS. THE PLUMBING CONTRACTOR SHALL BE RESPONSIBLE FOR THEIR COMPLETE INSTALLATION AND COORDINATION WITH OTHER DISCIPLINES.
J.	ALL WALL PIPING STUB-OUTS SHALL BE SECURELY TIED TO THE STRUCTURE WITH SUFFICIENT BACKING TO ELIMINATE MOVEMENT. FINAL CONNECTIONS TO KITCHEN SINKS SHALL BE HARD PIPED.
K.	PITCH ALL WASTE AND DRAIN LINES A MINIMUM OF 1/8" PER FOOT IN THE DIRECTION OF FLOW, OR AS SPECIFIED BY LOCAL CODES.
L.	ALL SINKS IN DWY SYSTEMS RESULTING FROM INSTALLATION ROUGH-IN SHALL BE PROTECTED WITH A TEST PLUG THAT IS SECURELY LOCKED IN PLACE UNTIL FINAL FINISHED CONNECTIONS ARE INSTALLED.
M.	PLUMBING CONTRACTOR TO ADVANCE AND PAY FOR ALL REQUIRED FEES, PERMITS, AND MISCELLANEOUS COSTS ASSOCIATED WITH THE PLUMBING WORK PER LOCAL PLUMBING CODES.
N.	ALL PENETRATIONS IN FIRE RATED WALL ASSEMBLIES SHALL BE SEALED WITH UL LISTED FIRE STOPPING MATERIAL.


KEYED NOTES	
①	ROUTE VENT UP TO VTR. COORDINATE ROOF PENETRATION LOCATION WITH OUTDOOR AIR INTAKE OF ROOFTOP EQUIPMENT. MAINTAIN A MINIMUM HORIZONTAL CLEARANCE OF 18'-0".
②	EXTEND 4" WASTE PIPING ON SITE. FIELD VERIFY EXACT SIZE, LOCATION AND INVERT ELEVATIONS OF CONNECTIONS AT THE EXISTING MAIN PRIOR TO START OF ANY WORK. SEE CIVIL DRAWINGS FOR CONTINUATION.
③	NEW WALK-IN COOLER/ FREEZER CONDENSATE DRAIN LINE IS AS HIGH AS POSSIBLE AND ALONG WALLS. INSULATE ALL CONDENSATE PIPING AND PITCH A MINIMUM OF 1/4" PER FOOT IN THE DIRECTION OF FLOW. SEAL ALL COOLER WALL PENETRATIONS WATER TIGHT AND COVER EACH WITH AN ESCUTCHEON PLATE. PROVIDE FULL SIZE TRAP AND EXTEND ABOVE FLOOR AND BEHIND EQUIPMENT FOR AN INDIRECT CONNECTION TO AN APPROVED RECEPTOR.
④	NEW CONDENSATE DRAIN LINE IN THE WALK-IN FREEZERS HEAT TRAPED TO PREVENT FREEZING. HEAT TRACE TAPE SHALL BE FURNISHED AND INSTALLED BY THE ELECTRICAL CONTRACTOR.
⑤	ANY DWY PIPING IN COOKLINE WALL WITH 1/2" OF TYPE 1 EXHAUST HOOD SHALL BE CAST IRON.
⑥	ROUTING OF SODA LINES ABOVE CEILING. PROVIDE 4" SLEEVES IN WALLS.
⑦	EXISTING 4" GREASE WASTE PIPING ON SITE. FIELD VERIFY EXACT SIZE AND LOCATION PRIOR TO START OF ANY WORK.
⑧	CONNECT TO EXISTING GREASE WASTE LINE. FIELD VERIFY EXACT SIZE & LOCATION PRIOR TO START OF ANY WORK.

PG TO FIELD VERIFY EXACT SIZE & LOCATION OF SAN, GW, & VENT LINES PRIOR TO START OF ANY WORK.

ALL FLOOR SINKS TO BE 1" ABOVE SLAB FLOOR.



LIP Architecture
2200 W Cleveland Boulevard #4
Akron, Ohio 44308
513.688.2343
www.liparchitecture.com



PROJECT NO.:	
DRAWN BY:	TBA
CHECKED BY:	TBA
ISSUED DATE:	05.07.19
ISSUED REVISIONS:	

3070 Highland Pte. Dr.
Owensboro, KY 42303
Rise and Shine Prototype
SANITARY PLUMBING FLOOR PLAN

