

TERMS & ABBREVIATIONS:

ACST	ALUMINUM CLAD STEEL
AL	ALUMINUM
ALIC	ALUMINUM INSULATED CORE
ANO	ANODIZED
ASD-BP	AUTOMATIC SLIDING DOOR (BIPARTING)
ASD-SS	AUTOMATIC SLIDING DOOR (SINGLE SLIDING)
BS-SL	BARN-STYLE SLIDING DOOR
DA-2SF	DOUBLE ACTING (2 SINGLE FLUSH)
F	FLUSH
F-G	FULL GLASS
F-PHC	FLUSH WITH PEEP HOLE AND COVER
F-VP-H	FLUSH VISION PANEL HALF-LITE
F-VP-N	FLUSH VISION PANEL NARROW-LITE
F-VP	FLUSH WITH PEEP HOLE AND COVER
HPCG	HOLLOW CORE PAINT GRADE
HM	HOLLOW METAL
HMIC	HOLLOW METAL INSULATED CORE
OH	OVERHEAD COLING
PG	PATIO / POOL GATE
PS	PAIR
PTD	PAINTED
SCPG	SOLID CORE PAINT GRADE
SCWD	SOLID CORE WOOD DOOR
SCWV	SOLID CORE WOOD VENEER
SL	SLIDING
SR-6P	STYLE AND RAIL 6 PANEL
SR-DS	STYLE AND RAIL DOUBLE GLASS
SR-FG	STYLE AND RAIL FULL GLASS
SS	STAINLESS STEEL
ST	STEEL
STN	STAIN
T	TEMPERED, SEE DOOR GENERAL NOTES 12-14.
TEG	TRASH ENCLOSURE GATE
TU	TILT UP

DOOR GENERAL NOTES:

- REFER TO SPECIFICATIONS FOR DOOR HARDWARE SETS AND INFORMATION. HAND-ACTIVATED DOOR OPENING HARDWARE SHALL BE CENTERED BETWEEN 34" AND 48" A.F.F. U.N.O.
- DOOR CLOSER SWEEP PERIOD SHALL BE ADJUSTED SO THAT FROM THE OPEN POSITION OF 70 DEGREES, THE DOOR WILL TAKE AT LEAST 3 SECONDS TO MOVE TO A POINT 3 INCHES FROM THE LATCH, MEASURED TO THE LEADING EDGE OF THE DOOR. THE MAXIMUM DOOR OPENING FORCE FOR PUSHING OR PULLING INTERIOR DOORS SHALL BE 5 POUNDS PER FOOT.
- ALL EXTERIOR DOORS ARE TO OPEN OUTWARD AND ARE TO BE SELF CLOSING. CLOSERS TO BE PARALLEL ARM STYLE WHERE APPLICABLE.
- DOOR FRAMES TO BE EQUIPPED W/ SILENCER BUTTONS UNLESS GASKETS ARE SPECIFIED.
- RATED FRELITE INT GLASS.
- ALL EXTERIOR H.M. DOORS AND FRAMES SHALL BE INSULATED.
- FILL ALL JOISTS IN THRESHOLDS W/ SEALANT TO MATCH GROUT.
- SEE FIRE ITEMS FOR SPECIALTY DOORS.
- WHERE COAT HOOKS ARE INDICATED IN RESTROOMS AND BATHROOMS, LOCATE COAT HOOK CENTERED ON DOOR ON THE RESTROOMS AND BATHROOMS SIDE OF DOORS. IF APPLICABLE, GLASS IN 1 HOUR RATED DOORS AND SIDE LITES TO BE 45 MIN. RATED FRELITE INT GLASS.
- ALL GLASS IN NON-RATED INTERIOR DOORS AND SIDELITES ARE TO BE G4 TEMPERED OR LAMINATED SAFETY GLASS.
- ALL EXTERIOR GLASS IN 1 HOUR RATED DOORS AND SIDE LITES TO BE TEMPERED OR LAMINATED SAFETY GLASS.
- EXTERIOR FLUSH DOORS ARE TO BE INSULATED HOLLOW METAL DOORS.

DOOR OPENING FINISHES SCHEDULE:

- ALL INTERIOR DOOR ARE TO BE SOLID CORE WOOD DOORS FINISHED ON ALL SIDES.
- ALL INTERIOR HOLLOW METAL DOORS AND FRAMES ARE TO BE PAINTED FINISHED.
- ALL EXTERIOR SOLID CORE WOOD DOORS AND FRAMES ARE TO BE PAINTED FINISH.
- ALL ALUMINUM DOORS AND FRAMES ARE TO BE CLEAR ANODIZED ALUMINUM FINISHED.

DOOR SCHEDULE

NO.	ROOM NAME	DOOR INFORMATION				FRAME INFORMATION				RATINGS			HARDWARE		SIGNAGE		COMMENTS						
		WIDTH	HEIGHT	THICKNESS	UNDER CUT	MATERIAL	FINISH	DOOR TYPE	MATERIAL	FINISH	FRAME TYPE	FRAME DEPTH	HEAD	JAMB	THRESHOLD	FIRE LABEL		STC RATING	HARDWARE SET	PANIC HARDWARE PROVIDED	PROVIDE ROOM NO.	TACTILE EXIT SIGN REQ'D	
01	GUESTROOMS																						
GR-01	ENTRY	3'-0"	7'-0"	0'-1 3/4"		SCWD	-	FWP	HM	-	F1	7"	S2-A	S2-B	S2-C	20 MIN	30-35	HW-019	No	Y	N	PROVIDE CARD READER	
GR-01A	ENTRY	3'-0"	7'-0"	0'-1 3/4"		SCWD	-	FWP	HM	-	F1	7"	S2-A	S2-B	S2-C	20 MIN	30-35	HW-020	No	Y	N	PROVIDE CARD READER	
GR-02	BATH POCKET	3'-0"	6'-8"	0'-1 3/4"	1"	SCWD	-	FP	WD	-	F1	5 7/8"	S2-1A	S2-1B	S2-1C	-	-	HW-022A	No	N	N		
GR-03	CONNECTING	3'-0"	6'-8"	0'-1 3/4"		SCWD	-	DA-2SF	HM	-	F1	1'-2 7/8"	M2-A	M2-B	M2-C	45 MIN	30-35	HW-021	No	N	N		
GR-04A	BATH SWING	3'-0"	6'-8"	0'-1 3/4"	1"	SCWD	-	F	HM	-	F1	9 3/8"	S2-A	S2-B	S2-C	-	-	HW-022	No	N	N		
GR-04B	BATH SWING	3'-0"	6'-8"	0'-1 3/4"	1"	SCWD	-	F	HM	-	F1	9 3/8"	S2-A	S2-B	S2-C	-	-	HW-022	No	N	N		
GR-04C	BATH SWING	3'-0"	6'-8"	0'-1 3/4"	1"	SCWD	-	F	HM	-	F1	8 1/4"	S2-A	S2-B	S2-C	-	-	HW-022	No	N	N		
GR-04D	BATH SWING	3'-0"	6'-8"	0'-1 3/4"	1"	SCWD	-	F	HM	-	F1	8 1/4"	S2-A	S2-B	S2-C	-	-	HW-022	No	N	N		
GR-05	BEDROOM	3'-0"	6'-8"	0'-1 3/4"		SCWD	-	F	HM	-	F1	9 3/8"	S2-A	S2-B	S2-C	-	-	HW-023	No	N	N		
GR-06	BATH POCKET ADA	3'-0"	6'-8"	0'-1 3/4"	1"	SCWD	-	FP	WD	-	F1	5 7/8"	S2-1A	S2-1B	S2-1C	-	-	HW-022A	No	N	N		
02	STAIRS																						
156	STAR	3'-0"	7'-0"	0'-1 3/4"		HM	-	F-VP-N	HM	-	F3	5 7/8"	M1-A	M1-B	M1-C	90 MIN	-	HW-008	No	Y	N		
156A	STAR EXTERIOR	3'-0"	7'-0"	0'-1 3/4"		GALV HM	-	F	GALV HM	-	F3	5 7/8"	10/A.504	M1-B	M1-C	5/A.501	1-1/2 HR	-	HW-004	No	N	Y	PROVIDE CARD READER
158	STAR	3'-0"	7'-0"	0'-1 3/4"		HM	-	F-VP-N	HM	-	F3	5 7/8"	M1-A	M1-B	M1-C	90 MIN	-	HW-008	No	Y	N		
158A	STAR EXTERIOR	3'-0"	7'-0"	0'-1 3/4"		GALV HM	-	F	GALV HM	-	F3	5 7/8"	10/A.504	M1-B	M1-C	5/A.501	1-1/2 HR	-	HW-004	No	N	Y	PROVIDE CARD READER
234	STAR	3'-0"	7'-0"	0'-1 3/4"		HM	-	F-VP-N	HM	-	F3	5 7/8"	M1-A	M1-B	M1-C	90 MIN	-	HW-008	No	Y	Y		
236	STAR	3'-0"	7'-0"	0'-1 3/4"		HM	-	F-VP-N	HM	-	F3	5 7/8"	M1-A	M1-B	M1-C	90 MIN	-	HW-008	No	Y	Y		
334	STAR	3'-0"	7'-0"	0'-1 3/4"		HM	-	F-VP-N	HM	-	F3	5 7/8"	M1-A	M1-B	M1-C	90 MIN	-	HW-008	No	Y	Y		
336	STAR	3'-0"	7'-0"	0'-1 3/4"		HM	-	F-VP-N	HM	-	F3	5 7/8"	M1-A	M1-B	M1-C	90 MIN	-	HW-008	No	Y	Y		
434	STAR	3'-0"	7'-0"	0'-1 3/4"		HM	-	F-VP-N	HM	-	F3	5 7/8"	M1-A	M1-B	M1-C	90 MIN	-	HW-008	No	Y	Y		
436	STAR	3'-0"	7'-0"	0'-1 3/4"		HM	-	F-VP-N	HM	-	F3	5 7/8"	M1-A	M1-B	M1-C	90 MIN	-	HW-008	No	Y	Y		
03	FIRST FLOOR																						
110A	CORRIDOR	3'-0"	7'-2"	0'-1 3/4"		ALUM	-	SR-FG	ALUM	-	F3	4 1/2"	4/A.505	S2-B	S2-C	4/A.501	-	-	HW-005	No	N	Y	PROVIDE CARD READER
110B	CORRIDOR	3'-0"	7'-0"	0'-1 3/4"		ALUM	-	SR-FG	ALUM	-	F1	4 1/2"	4/A.505	S2-B	S2-C	4/A.501	45 MIN	-	HW-007	No	Y	Y	
112	CORRIDOR	3'-0"	7'-0"	0'-1 3/4"		ALUM	-	SR-FG	ALUM	-	F1	4 1/2"	4/A.505	S2-B	S2-C	4/A.501	45 MIN	-	HW-007	Yes	N	N	
113	MENS	3'-0"	7'-0"	0'-1 3/4"	1"	SCWD	-	F	HM	-	F1	5 7/8"	S2-A	S2-B	S2-C	-	-	HW-014	No	Y	N		
114A	LAUNDRY DISCHARGE	3'-6"	7'-0"	0'-1 3/4"		SCWD	-	F	HM	-	F1	7 1/8"	S2-A	S2-B	S2-C	1-1/2 HR	-	HW-015	No	Y	N	PROVIDE CARD READER	
114B	LAUNDRY DISCHARGE	3'-0"	7'-0"	0'-1 3/4"		SCWD	-	F	HM	-	F1	7 1/8"	S2-A	S2-B	S2-C	1-1/2 HR	-	HW-015	No	Y	N		
115	WOMENS	3'-0"	7'-0"	0'-1 3/4"	1"	SCWD	-	F	HM	-	F1	5 7/8"	S2-A	S2-B	S2-C	-	-	HW-014	No	Y	N		
117	ENGINEER OFFICE	3'-0"	7'-0"	0'-1 3/4"		SCWD	-	F	HM	-	F1	5 7/8"	S2-A	S2-B	S2-C	45 MIN	-	HW-015	No	Y	N		
118	STORAGE	3'-0"	7'-0"	0'-1 3/4"		SCWD	-	F	HM	-	F1	5 7/8"	S2-A	S2-B	S2-C	45 MIN	-	HW-015A	No	Y	N		
121	FITNESS	3'-0"	7'-0"	0'-1 3/4"		ALUM	-	SR-FG	ALUM	-	F1	4 1/2"	S2-A	S2-B	S2-C	45 MIN	-	HW-022	No	Y	N		
122	FOLDING	5'-0"	7'-0"	0'-1 3/4"	3/4"	SCWD	-	F (PR-U)	HM	-	F2	5 7/8"	S2-A	S2-B	S2-C	45 MIN	-	HW-013	No	Y	N	PROVIDE CARD READER	
123	MANAGERS OFFICE	3'-0"	7'-0"	0'-1 3/4"		SCWD	-	F	HM	-	F1	5 7/8"	S2-A	S2-B	S2-C	45 MIN	-	HW-011	No	Y	N		
126	CLOSET	2'-6"	7'-0"	0'-1 3/4"		SCWD	-	F	HM	-	F1	5 7/8"	S2-A	S2-B	S2-C	-	-	HW-034	No	Y	N		
127	LAUNDRY	3'-0"	7'-0"	0'-1 3/4"		SCWD	-	F	HM	-	F1	5 7/8"	S2-A	S2-B	S2-C	-	-	HW-016A	No	N	N	PROVIDE CARD READER	
128	EMPLOYEE BREAK	3'-0"	7'-0"	0'-1 3/4"		SCWD	-	F-VP-N	HM	-	F1	5 7/8"	S2-A	S2-B	S2-C	45 MIN	-	HW-033	No	Y	N		
130A	VESTIBULE	10'-0"	7'-8"			ALUM	-	ASD-DS	ALUM	-	-	4 1/2"	ASD-A	ASD-B	ASD-C	-	-	HW-001	No	N	Y		
130B	VESTIBULE	10'-0"	7'-8"			ALUM	-	ASD-DS	ALUM	-	-	4 1/2"	ASD-A	ASD-B	ASD-C	-	-	HW-002	No	N	Y		
131	RISER ROOM	3'-0"	7'-0"	0'-1 3/4"		SCWD	-	F	HM	-	F1	5 7/8"	S2-A	S2-B	S2-C	-	-	HW-018	No	Y	N		
134	POOL EQUIPMENT	3'-0"	7'-0"	0'-1 3/4"		GALV HM	-	F	GALV HM	-	F3	5 1/2"	8/A.504	S2-B	S2-C	-	-	HW-018	No	Y	N		
135	CHEM.	3'-0"	7'-0"	0'-1 3/4"	1"	SCWD	-	F-L	HM	-	F1	5 7/8"	S2-A	S2-B	S2-C	-	-	HW-018A	No	Y	N		
136A	FOOD PREP	3'-0"	7'-0"	0'-1 3/4"	1"	SCWD	-	F	HM	-	F1	5 7/8"	S2-A	S2-B	S2-C	-	-	HW-010	No	Y	N	PROVIDE CARD READER	
136B	FOOD PREP	3'-0"	7'-0"	0'-1 3/4"	1"	SCWD	-	F	HM	-	F1	5 7/8"	S2-A	S2-B	S2-C	-	-	HW-009	No	Y	N	PROVIDE CARD READER	
140	CORRIDOR	3'-0"	7'-0"	0'-1 3/4"		SCWD	-	F	HM	-	F1	5 7/8"	S2-A	S2-B	S2-C	45 MIN	-	HW-011	No	Y	N	PROVIDE CARD READER	
141	SALES	3'-0"	7'-0"	0'-1 3/4"		SCWD	-	F	HM	-	F1	5 7/8"	S2-A	S2-B	S2-C	-	-	HW-011A	No	Y	N		
142	OFFICE	3'-0"	7'-0"	0'-1 3/4"		SCWD	-	F	HM	-	F1	5 7/8"	S2-A	S2-B	S2-C	-	-	HW-011A	No	Y	N		
143	STORAGE	3'-0"	7'-0"	0'-1 3/4"		SCWD	-	F	HM	-	F1	5 7/8"	S2-A	S2-B	S2-C	45 MIN	-	HW-016A	No	Y	N		
144	MEETING ROOM	3'-0"	7'-0"	0'-1 3/4"		SCWD	-	F	HM	-	F1	5 7/8"	S2-A	S2-B	S2-C	-	-	HW-029	No	Y	N		
144A	STORAGE	6'-0"	7'-0"	0'-1 3/4"		SCWD	-	F-L02 (PR)	HM	-	F2	5 7/8"	S2-A	S2-B	S2-C	45 MIN	-	HW-030	No	Y	N	FUSIBLE LINK LOUVER REQ'D	
145	MEETING ROOM	3'-0"	7'-0"	0'-1 3/4"		SCWD	-	F	HM	-	F1	7"	S3	S3B	S3C	-	-	HW-029	No	Y	N		
145A	STORAGE	6'-0"	7'-0"	0'-1 3/4"		SCWD	-	F-L02 (PR)	HM	-	F2	5 7/8"	S2-A	S2-B	S2-C	45 MIN	-	HW-030	No	Y	N	FUSIBLE LINK LOUVER REQ'D	
147	MEETING ROOM STORAGE	5'-0"	7'-0"	0'-1 3/4"		SCWD	-	F (PR-U)	HM	-	F2	5 7/8"	S2-A	S2-B	S2-C	45 MIN	-	HW-013	No	Y	N		
148	CORRIDOR	5'-0"	7'-0"	0'-1 3/4"		SCWD	-	F (PR-U)	HM	-	F2	5 7/8"	S2-A	S2-B	S2-C	45 MIN	-	HW-035	No	Y	N		
148A	ELECTRICAL	3'-0"	7'-0"	0'-1 3/4"	3/4"	SCWD	-	F	HM	-	F1	5 7/8"	S2-A	S2-B									