

LIGHT FIXTURE SCHEDULE:

- A3 RECESSED TWO FOOT BY FOUR FOOT LED, 277 VOLT, 90 CRI, 0-10V DIMMING CONTROLS, 4000K COLOR TEMP, 4000 LUMEN OUTPUT. CREZ ZR24 SERIES.
- A3E RECESSED TWO FOOT BY FOUR FOOT LED, 277 VOLT, 90 CRI, 0-10V DIMMING CONTROLS, 90 MINUTE EMERGENCY BATTERY PACK, 4000K COLOR TEMP, 4000 LUMEN OUTPUT. CREZ ZR24 SERIES.
- A4 RECESSED TWO FOOT BY FOUR FOOT LED, 277 VOLT, 90 CRI, 0-10V DIMMING CONTROLS, 4000K COLOR TEMP, 5000 LUMEN OUTPUT. CREZ ZR24 SERIES.
- A4E RECESSED TWO FOOT BY FOUR FOOT LED, 277 VOLT, 90 CRI, 0-10V DIMMING CONTROLS, 90 MINUTE EMERGENCY BATTERY PACK, 4000K COLOR TEMP, 5000 LUMEN OUTPUT. CREZ ZR24 SERIES.
- B4 RECESSED 4" LINEAR RECESSED FOUR FOOT LED, 120/277 VOLT, 90 CRI, 3000 LUMENS, OPAL FLUSH LENS, 34 INPUT WATTS, 0-10V DIMMING CONTROLS, 4000K COLOR TEMP, ZUMTOBEL SPOT LIGHT II LED SERIES.
- B4E RECESSED 4" LINEAR RECESSED FOUR FOOT LED, 120/277 VOLT, 90 CRI, 90 MINUTE EMERGENCY BATTERY PACK, 3000 LUMENS, OPAL FLUSH LENS, 34 INPUT WATTS, 0-10V DIMMING CONTROLS, 4000K COLOR TEMP, ZUMTOBEL SPOT LIGHT II LED SERIES.
- B8 RECESSED 4" LINEAR RECESSED EIGHT FOOT LED, 120/277 VOLT, 90 CRI, 6800 LUMENS, OPAL FLUSH LENS, 82 INPUT WATTS, 0-10V DIMMING CONTROLS, 4000K COLOR TEMP, ZUMTOBEL SPOT LIGHT II LED SERIES.
- B8E RECESSED 4" LINEAR RECESSED EIGHT FOOT LED, 120/277 VOLT, 90 CRI, 90 MINUTE EMERGENCY BATTERY PACK, 6800 LUMENS, OPAL FLUSH LENS, 82 INPUT WATTS, 0-10V DIMMING CONTROLS, 4000K COLOR TEMP, ZUMTOBEL SPOT LIGHT II LED SERIES.
- C SURFACE MOUNTED FOUR FOOT LED, 120 VOLT, 90 CRI, 4000K COLOR TEMP, 4000 LUMEN OUTPUT, VISCOLUM48-LED-8 SERIES OR PRIOR APPROVED EQUAL.
- D SIX INCH RECESSED LED DOWNLIGHT, 15W, ANODIZED ALUMINUM REFLECTOR, 4000K COLOR TEMP, 120/277 VOLT, 1156 LUMEN. CREZ SOL6 SERIES OR PRIOR APPROVED EQUAL.
- DE SIX INCH RECESSED LED DOWNLIGHT, 15W, ANODIZED ALUMINUM REFLECTOR, 90 MINUTE EMERGENCY BATTERY PACK, 4000K COLOR TEMP, 120/277 VOLT, 1156 LUMEN. CREZ SOL6 SERIES OR PRIOR APPROVED EQUAL.
- D12 WET LOCATION SHOWER LIGHT, SIX INCH RECESSED LED DOWNLIGHT, ANODIZED ALUMINUM REFLECTOR, 13W, 4000K COLOR TEMP, 0-10V DIMMING CONTROLS, 1060 LUMEN, 0-10V DIMMING CONTROLS, ZUMTOBEL PANOS-D-N-150-R-H-13W-840-CS-W (PANOS-D-N-150-R-H-13W-DA) SERIES OR PRIOR APPROVED EQUAL.
- EX NINETY MINUTE EMERGENCY BATTERY PACK WITH TWO LED HEADS, WHITE FINISH, 120 VOLT, EXITRONIX 277-52-60 SERIES OR PRIOR APPROVED EQUAL.
- FE 4" LINEAR BARNELL FIXTURE WITH INSTALLED OCCUPANCY SENSOR, 120/277 VOLT, 90 MINUTE EMERGENCY BATTERY PACK, 5000 LUMEN OUTPUT WITH 25° FLOOD LEVELS, VISIONEERING LELM48-LED SERIES. WALL MOUNT 4" ABOVE THE STAIR LANDING.
- G WALL GRAZE CONTINUOUS RECESSED LIGHT FIXTURE, WALL WASH, 277 VOLT, 90 CRI, 0-10V DIMMING CONTROLS, 4000K COLOR TEMP, STANDARD LUMEN OUTPUT, BIRCHWOOD JAK-LED-W6 SERIES.
- H SURFACE MOUNTED ENTRY FIXTURE, 277V.
- H2 SURFACE MOUNTED WALL PACK, LED, WET LOCATION, 277V.
- J WET LOCATION, 277 VOLT SIGN/LANDSCAPE LIGHT FIXTURE, CUSTOM COLOR AS SELECTED BY ARCHITECT, 12.5W LED, 50W OUTPUT, 60 DEGREE SPREAD, FURNISH AND INSTALL WITH KNUCKLE AND FLUSH LENS. VISION3 FL1A SERIES.
- KP PENDANT MOUNTED 4" LINEAR SURFACE EIGHT FOOT LED, 120/277 VOLT, 90 CRI, 6000 LUMENS, OPAL FLUSH LENS, 67 INPUT WATTS, 0-10V DIMMING CONTROLS, 4000K COLOR TEMP, 90 MINUTE EMERGENCY BATTERY PACK, CUSTOM LENGTH MOUNTED CABLE. CONTRACTOR SHALL COORDINATE THE EXACT MOUNTING HEIGHT OF PENDANT FIXTURE WITH ARCHITECT/ENGINEER PRIOR TO ROUGH-IN. CUSTOM COLOR AS SELECTED BY ARCHITECT. ZUMTOBEL SPOT LIGHT II LED SERIES.
- KPE PENDANT MOUNTED 4" LINEAR SURFACE EIGHT FOOT LED, 120/277 VOLT, 90 CRI, 6000 LUMENS, OPAL FLUSH LENS, 67 INPUT WATTS, 0-10V DIMMING CONTROLS, 4000K COLOR TEMP, 90 MINUTE EMERGENCY BATTERY PACK, CUSTOM LENGTH MOUNTED CABLE. CONTRACTOR SHALL COORDINATE THE EXACT MOUNTING HEIGHT OF PENDANT FIXTURE WITH ARCHITECT/ENGINEER PRIOR TO ROUGH-IN. CUSTOM COLOR AS SELECTED BY ARCHITECT. ZUMTOBEL SPOT LIGHT II LED SERIES.
- L SLM PROFILE COVE LUMINAIRE, 400K, 277, VOLT, CONTINUOUS LENGTHS AS SHOWN. TRAXON AC-DIM GI SERIES.
- M4 RECESSED 4" LINEAR RECESSED FOUR FOOT LED, 120/277 VOLT, 90 CRI, 3400 LUMENS, OPAL FLUSH LENS, 41 INPUT WATTS, 0-10V DIMMING CONTROLS, 4000K COLOR TEMP, ZUMTOBEL SPOT LIGHT II LED SERIES.
- M6 RECESSED 4" LINEAR RECESSED EIGHT FOOT LED, 120/277 VOLT, 90 CRI, 6800 LUMENS, OPAL FLUSH LENS, 82 INPUT WATTS, 0-10V DIMMING CONTROLS, 4000K COLOR TEMP, ZUMTOBEL SPOT LIGHT II LED SERIES.
- M6E RECESSED 4" LINEAR RECESSED EIGHT FOOT LED, 120/277 VOLT, 90 CRI, 90 MINUTE EMERGENCY BATTERY PACK, 6800 LUMENS, OPAL FLUSH LENS, 82 INPUT WATTS, 0-10V DIMMING CONTROLS, 4000K COLOR TEMP, ZUMTOBEL SPOT LIGHT II LED SERIES.
- X LED EXIT SIGN, SINGLE OR DOUBLE STENCIL FACE, WITH ARROWS AS INDICATED, 90 MINUTE BATTERY, CAST ALUMINUM BODY, AND RED LED LAMPS AND LETTERS, DIFFUSE FACE, MOUNT TO CEILING OR WALL, AS INDICATED, 120/277 VOLT. EXITRONIX 400E SERIES.

PNL NO.	TYPE	MELO	DESCRIPTION	QTY	UNIT	REMARKS
1	RECEPT	10000	120V 15A	1	RECEPT	
2	RECEPT	10000	120V 15A	1	RECEPT	
3	RECEPT	10000	120V 15A	1	RECEPT	
4	RECEPT	10000	120V 15A	1	RECEPT	
5	RECEPT	10000	120V 15A	1	RECEPT	
6	RECEPT	10000	120V 15A	1	RECEPT	
7	RECEPT	10000	120V 15A	1	RECEPT	
8	RECEPT	10000	120V 15A	1	RECEPT	
9	RECEPT	10000	120V 15A	1	RECEPT	
10	RECEPT	10000	120V 15A	1	RECEPT	
11	RECEPT	10000	120V 15A	1	RECEPT	
12	RECEPT	10000	120V 15A	1	RECEPT	
13	RECEPT	10000	120V 15A	1	RECEPT	
14	RECEPT	10000	120V 15A	1	RECEPT	
15	RECEPT	10000	120V 15A	1	RECEPT	
16	RECEPT	10000	120V 15A	1	RECEPT	
17	RECEPT	10000	120V 15A	1	RECEPT	
18	RECEPT	10000	120V 15A	1	RECEPT	
19	RECEPT	10000	120V 15A	1	RECEPT	
20	RECEPT	10000	120V 15A	1	RECEPT	
21	RECEPT	10000	120V 15A	1	RECEPT	
22	RECEPT	10000	120V 15A	1	RECEPT	
23	RECEPT	10000	120V 15A	1	RECEPT	
24	RECEPT	10000	120V 15A	1	RECEPT	
25	RECEPT	10000	120V 15A	1	RECEPT	
26	RECEPT	10000	120V 15A	1	RECEPT	
27	RECEPT	10000	120V 15A	1	RECEPT	
28	RECEPT	10000	120V 15A	1	RECEPT	
29	RECEPT	10000	120V 15A	1	RECEPT	
30	RECEPT	10000	120V 15A	1	RECEPT	
31	RECEPT	10000	120V 15A	1	RECEPT	
32	RECEPT	10000	120V 15A	1	RECEPT	
33	RECEPT	10000	120V 15A	1	RECEPT	
34	RECEPT	10000	120V 15A	1	RECEPT	
35	RECEPT	10000	120V 15A	1	RECEPT	
36	RECEPT	10000	120V 15A	1	RECEPT	
37	RECEPT	10000	120V 15A	1	RECEPT	
38	RECEPT	10000	120V 15A	1	RECEPT	
39	RECEPT	10000	120V 15A	1	RECEPT	
40	RECEPT	10000	120V 15A	1	RECEPT	
41	RECEPT	10000	120V 15A	1	RECEPT	
42	RECEPT	10000	120V 15A	1	RECEPT	
43	RECEPT	10000	120V 15A	1	RECEPT	
44	RECEPT	10000	120V 15A	1	RECEPT	
45	RECEPT	10000	120V 15A	1	RECEPT	
46	RECEPT	10000	120V 15A	1	RECEPT	
47	RECEPT	10000	120V 15A	1	RECEPT	
48	RECEPT	10000	120V 15A	1	RECEPT	
49	RECEPT	10000	120V 15A	1	RECEPT	
50	RECEPT	10000	120V 15A	1	RECEPT	
51	RECEPT	10000	120V 15A	1	RECEPT	
52	RECEPT	10000	120V 15A	1	RECEPT	
53	RECEPT	10000	120V 15A	1	RECEPT	
54	RECEPT	10000	120V 15A	1	RECEPT	
55	RECEPT	10000	120V 15A	1	RECEPT	
56	RECEPT	10000	120V 15A	1	RECEPT	
57	RECEPT	10000	120V 15A	1	RECEPT	
58	RECEPT	10000	120V 15A	1	RECEPT	
59	RECEPT	10000	120V 15A	1	RECEPT	
60	RECEPT	10000	120V 15A	1	RECEPT	
61	RECEPT	10000	120V 15A	1	RECEPT	
62	RECEPT	10000	120V 15A	1	RECEPT	
63	RECEPT	10000	120V 15A	1	RECEPT	
64	RECEPT	10000	120V 15A	1	RECEPT	
65	RECEPT	10000	120V 15A	1	RECEPT	
66	RECEPT	10000	120V 15A	1	RECEPT	
67	RECEPT	10000	120V 15A	1	RECEPT	
68	RECEPT	10000	120V 15A	1	RECEPT	
69	RECEPT	10000	120V 15A	1	RECEPT	
70	RECEPT	10000	120V 15A	1	RECEPT	
71	RECEPT	10000	120V 15A	1	RECEPT	
72	RECEPT	10000	120V 15A	1	RECEPT	
73	RECEPT	10000	120V 15A	1	RECEPT	
74	RECEPT	10000	120V 15A	1	RECEPT	
75	RECEPT	10000	120V 15A	1	RECEPT	
76	RECEPT	10000	120V 15A	1	RECEPT	
77	RECEPT	10000	120V 15A	1	RECEPT	
78	RECEPT	10000	120V 15A	1	RECEPT	
79	RECEPT	10000	120V 15A	1	RECEPT	
80	RECEPT	10000	120V 15A	1	RECEPT	
81	RECEPT	10000	120V 15A	1	RECEPT	
82	RECEPT	10000	120V 15A	1	RECEPT	
83	RECEPT	10000	120V 15A	1	RECEPT	
84	RECEPT	10000	120V 15A	1	RECEPT	
85	RECEPT	10000	120V 15A	1	RECEPT	
86	RECEPT	10000	120V 15A	1	RECEPT	
87	RECEPT	10000	120V 15A	1	RECEPT	
88	RECEPT	10000	120V 15A	1	RECEPT	
89	RECEPT	10000	120V 15A	1	RECEPT	
90	RECEPT	10000	120V 15A	1	RECEPT	
91	RECEPT	10000	120V 15A	1	RECEPT	
92	RECEPT	10000	120V 15A	1	RECEPT	
93	RECEPT	10000	120V 15A	1	RECEPT	
94	RECEPT	10000	120V 15A	1	RECEPT	
95	RECEPT	10000	120V 15A	1	RECEPT	
96	RECEPT	10000	120V 15A	1	RECEPT	
97	RECEPT	10000	120V 15A	1	RECEPT	
98	RECEPT	10000	120V 15A	1	RECEPT	
99	RECEPT	10000	120V 15A	1	RECEPT	
100	RECEPT	10000	120V 15A	1	RECEPT	

PNL NO.	TYPE	MELO	DESCRIPTION	QTY	UNIT	REMARKS
101	RECEPT	10000	120V 15A	1	RECEPT	
102	RECEPT	10000	120V 15A	1	RECEPT	
103	RECEPT	10000	120V 15A	1	RECEPT	
104	RECEPT	10000	120V 15A	1	RECEPT	
105	RECEPT	10000	120V 15A	1	RECEPT	
106	RECEPT	10000	120V 15A	1	RECEPT	
107	RECEPT	10000	120V 15A	1	RECEPT	
108	RECEPT	10000	120V 15A	1	RECEPT	
109	RECEPT	10000	120V 15A	1	RECEPT	
110	RECEPT	10000	120V 15A	1	RECEPT	
111	RECEPT	10000</				