HOLIDAY INN - CLARKSVILLE, TN — PANEL "J" — A.I.C. BREAKER MINIMUM 10,000

MAIN BRKR FRAME | MAIN BREAKER AMPS | MLO SIZE 400 | TYPE SQUARE "D" - NQ | BUS AL
VOLTAGE 120/208 | PHASE THREE | WIRE FOUR | MOUNTING SURFACE

DESCRIPTION	A	B	C	WIRE SIZE	NO. OF W'S	POLE	TRIP	CT. NO.	CT. NO.	TRIP	POLE	NO. OF W'S	WIRE SIZE	A	B	C	DESCRIPTION
REC DBL QUEEN	900			12	2	1	20	1	2	20	1	2	12	900			REC DBL QUEEN
REC DBL QUEEN		1080		12	2	1	20	3	4	20	1	2	12		1080		REC DBL QUEEN
REC DBL QUEEN			1000	12	2	1	20	5	6	20	1	2	12			1000	REC DBL QUEEN
DBL QUEEN PTAC	1615			10	2	2	20	7	8	20	2	2	10	1615			DBL QUEEN PTAC
----------		1615		10	-	-	-	9	10	-	-	-	10		1615		----------
REC DBL QUEEN			900	12	2	1	20	11	12	20	1	2	12			900	REC KING ADA
REC DBL QUEEN	1080			12	2	1	20	13	14	20	1	2	12	1080			REC KING ADA
REC DBL QUEEN		1000		12	2	1	20	15	16	20	1	2	12		1000		REC KING ADA
DBL QUEEN PTAC			1615	10	2	2	20	17	18	20	2	2	10			1615	KING ADA PTAC
----------	1615			10	-	-	-	19	20	-	-	-	10	1615			----------
REC DBL QUEEN ADA		900		12	2	1	20	21	22	20	1	2	12		900		REC KING ADA
REC DBL QUEEN ADA			1080	12	2	1	20	23	24	20	1	2	12			1080	REC KING ADA
REC DBL QUEEN ADA	1000			12	2	1	20	25	26	20	1	2	12	1000			REC KING ADA
DBL QUEEN PTAC		1615		10	2	2	20	27	28	20	2	2	10		1615		KING ADA PTAC
----------			1615	10	-	-	-	29	30	-	-	-	10			1615	----------
REC KING	900			12	2	1	20	31	32	20	1	2	12	900			REC KING
REC KING		1080		12	2	1	20	33	34	20	1	2	12		1080		REC KING
REC KING			1000	12	2	1	20	35	36	20	1	2	12			1000	REC KING
KING PTAC	1615			10	2	2	20	37	38	20	2	2	10	1615			KING PTAC
----------		1615		10	-	-	-	39	40	-	-	-	10		1615		----------
REC DBL QUEEN			900	12	2	1	20	41	42	20	1	2	12			900	REC KING
REC DBL QUEEN	1080			12	2	1	20	43	44	20	1	2	12	1080			REC KING
REC DBL QUEEN		1000		12	2	1	20	45	46	20	1	2	12		1000		REC KING
DBL QUEEN PTAC			1615	10	2	2	20	47	48	20	2	2	10			1615	KING PTAC
----------	1615			10	-	-	-	49	50	-	-	-	10	1615			----------
SPARE						1	20	51	52	20	1						SPARE
SPARE						1	20	53	54	20	1						SPARE
SECTION B																	
REC DBL QUEEN	900			12	2	1	20	55	56	20	1	2	12	900			REC KING
REC DBL QUEEN		1080		12	2	1	20	57	58	20	1	2	12		1080		REC KING
REC DBL QUEEN			1000	12	2	1	20	59	60	20	1	2	12			1000	REC KING
DBL QUEEN PTAC	1615			10	2	2	20	61	62	20	2	2	10	1615			KING PTAC
----------		1615		10	-	-	-	63	64	-	-	-	10		1615		----------
REC DBL QUEEN			900	12	2	1	20	65	66	20	1	2	12			900	REC KING
REC DBL QUEEN	1080			12	2	1	20	67	68	20	1	2	12	1080			REC KING
REC DBL QUEEN		1000		12	2	1	20	69	70	20	1	2	12		1000		REC KING
DBL QUEEN PTAC			1615	10	2	2	20	71	72	20	2	2	10			1615	KING PTAC
----------	1615			10	-	-	-	73	74	-	-	-	10	1615			----------
REC KING		900		12	2	1	20	75	76	20	1	2	12		900		REC KING
REC KING			1080	12	2	1	20	77	78	20	1	2	12			1080	REC KING
REC KING	1000			12	2	1	20	79	80	20	1	2	12	1000			REC KING
KING PTAC		1615		10	2	2	20	81	82	20	2	2	10		1615		KING PTAC
----------			1615	10	-	-	-	83	84	-	-	-	10			1615	----------
REC DBL QUEEN	900			12	2	1	20	85	86	20	1	2	12	900			REC KING
REC DBL QUEEN		1080		12	2	1	20	87	88	20	1	2	12		1080		REC KING
REC DBL QUEEN			1000	12	2	1	20	89	90	20	1	2	12			1000	REC KING
DBL QUEEN PTAC	1615			10	2	2	20	91	92	20	2	2	10	1615			KING PTAC
----------		1615		10	-	-	-	93	94	-	-	-	10		1615		----------
REC DBL QUEEN			900	12	2	1	20	95	96	20	1	2	12			560	LTS ELEVATOR
REC DBL QUEEN	1080			12	2	1	20	97	98	20	1	2	12	300			ELEVATOR CAB LIGHTS
REC DBL QUEEN		1000		10	2	2	30	99	100	30	2	2	10		300		ELEVATOR CAB LIGHTS
DBL QUEEN PTAC			1615	10	2	2	20	101	102	-	-	-	10			300	ELEVATOR CAB LIGHTS
----------	1615			10	-	-	-	103	104	20	1						SPARE
SPARE						1	20	105	106	20	1						SPARE
SPARE						1	20	107	108	20	1						SPARE

LIGHTS@125% = 1,825 VA	RECEPTACLES = 33,310 VA	HVAC@100% = 61,370 VA	OTHER EQUIP@ 100% = 0 VA
VA'S TOTAL = 96,505 VA	A PHASE = 43,285 VA	B PHASE = 38,920 VA	C PHASE = 37,245 VA
AMPS TOTAL = 268	A PHASE = 361	B PHASE = 324	C PHASE = 310

HOLIDAY INN - CLARKSVILLE, TN — PANEL "G" — A.I.C. BREAKER MINIMUM 10,000

MAIN BRKR FRAME | MAIN BREAKER AMPS | MLO SIZE 400 | TYPE SQUARE "D" - NQ | BUS AL
VOLTAGE 120/208 | PHASE THREE | WIRE FOUR | MOUNTING SURFACE

DESCRIPTION	A	B	C	WIRE SIZE	NO. OF W'S	POLE	TRIP	CT. NO.	CT. NO.	TRIP	POLE	NO. OF W'S	WIRE SIZE	A	B	C	DESCRIPTION
REC DBL QUEEN	900			12	2	1	20	1	2	20	1	2	12	900			REC DBL QUEEN
REC DBL QUEEN		1080		12	2	1	20	3	4	20	1	2	12		1080		REC DBL QUEEN
REC DBL QUEEN			1000	12	2	1	20	5	6	20	1	2	12			1000	REC DBL QUEEN
DBL QUEEN PTAC	1615			10	2	2	20	7	8	20	2	2	10	1615			DBL QUEEN PTAC
----------		1615		10	-	-	-	9	10	-	-	-	10		1615		----------
REC DBL QUEEN			900	12	2	1	20	11	12	20	1	2	12			900	REC KING ADA
REC DBL QUEEN	1080			12	2	1	20	13	14	20	1	2	12	1080			REC KING ADA
REC DBL QUEEN		1000		12	2	1	20	15	16	20	1	2	12		1000		REC KING ADA
DBL QUEEN PTAC			1615	10	2	2	20	17	18	20	2	2	10			1615	KING ADA PTAC
----------	1615			10	-	-	-	19	20	-	-	-	10	1615			----------
REC DBL QUEEN ADA		900		12	2	1	20	21	22	20	1	2	12		900		REC KING ADA
REC DBL QUEEN ADA			1080	12	2	1	20	23	24	20	1	2	12			1080	REC KING ADA
REC DBL QUEEN ADA	1000			12	2	1	20	25	26	20	1	2	12	1000			REC KING ADA
DBL QUEEN PTAC		1615		10	2	2	20	27	28	20	2	2	10		1615		KING ADA PTAC
----------			1615	10	-	-	-	29	30	-	-	-	10			1615	----------
REC KING	900			12	2	1	20	31	32	20	1	2	12	900			REC KING
REC KING		1080		12	2	1	20	33	34	20	1	2	12		1080		REC KING
REC KING			1000	12	2	1	20	35	36	20	1	2	12			1000	REC KING
KING PTAC	1615			10	2	2	20	37	38	20	2	2	10	1615			KING PTAC
----------		1615		10	-	-	-	39	40	-	-	-	10		1615		----------
REC DBL QUEEN			900	12	2	1	20	41	42	20	1	2	12			900	REC KING
REC DBL QUEEN	1080			12	2	1	20	43	44	20	1	2	12	1080			REC KING
REC DBL QUEEN		1000		12	2	1	20	45	46	20	1	2	12		1000		REC KING
DBL QUEEN PTAC			1615	10	2	2	20	47	48	20	2	2	10			1615	KING PTAC
----------	1615			10	-	-	-	49	50	-	-	-	10	1615			----------
SPARE						1	20	51	52	20	2	2	12		1500		EWH-3
SPARE						1	20	53	54	-	-	-	12			1500	----------
SECTION B																	
REC DBL QUEEN	900			12	2	1	20	55	56	20	1	2	12	900			REC KING
REC DBL QUEEN		1080		12	2	1	20	57	58	20	1	2	12		1080		REC KING
REC DBL QUEEN			1000	12	2	1	20	59	60	20	1	2	12			1000	REC KING
DBL QUEEN PTAC	1615			10	2	2	20	61	62	20	2	2	10	1615			KING PTAC
----------		1615		10	-	-	-	63	64	-	-	-	10		1615		----------
REC DBL QUEEN			900	12	2	1	20	65	66	20	1	2	12			900	REC KING
REC DBL QUEEN	1080			12	2	1	20	67	68	20	1	2	12	1080			REC KING
REC DBL QUEEN		1000		12	2	1	20	69	70	20	1	2	12		1000		REC KING
DBL QUEEN PTAC			1615	10	2	2	20	71	72	20	2	2	10			1615	KING PTAC
----------	1615			10	-	-	-	73	74	-	-	-	10	1615			----------
REC KING		900		12	2	1	20	75	76	20	1	2	12		900		REC KING
REC KING			1080	12	2	1	20	77	78	20	1	2	12			1080	REC KING
REC KING	1000			12	2	1	20	79	80	20	1	2	12	1000			REC KING
KING PTAC		1615		10	2	2	20	81	82	20	2	2	10		1615		KING PTAC
----------			1615	10	-	-	-	83	84	-	-	-	10			1615	----------
REC DBL QUEEN	900			12	2	1	20	85	86	20	1	2	12	900			REC KING
REC DBL QUEEN		1080		12	2	1	20	87	88	20	1	2	12		1080		REC KING
REC DBL QUEEN			1000	12	2	1	20	89	90	20	1	2	12			1000	REC KING
DBL QUEEN PTAC	1615			10	2	2	20	91	92	20	2	2	10	1615			KING PTAC
----------		1615		10	-	-	-	93	94	-	-	-	10		1615		----------
REC DBL QUEEN			900	12	2	1	20	95	96	20	1						SPARE
REC DBL QUEEN	1080			12	2	1	20	97	98	20	1						SPARE
REC DBL QUEEN		1000		10	2	2	30	99	100	20	1						SPARE
DBL QUEEN PTAC			1615	10	2	2	20	101	102	20	1						SPARE
----------	1615			10	-	-	-	103	104	20	1						SPARE
SPARE						1	20	105	106	20	1						SPARE
SPARE						1	20	107	108	20	1						SPARE

LIGHTS@125% = 0 VA	RECEPTACLES = 33,310 VA	HVAC@100% = 61,370 VA	OTHER EQUIP@ 100% = [illegible] VA
VA'S TOTAL = 97,680 VA	A PHASE = 42,985 VA	B PHASE = 40,12[illegible] VA	C PHASE = 37,885 VA
AMPS TOTAL = 271	A PHASE = 358	B PHASE = 334	C PHASE = 316

HOLIDAY INN - CLARKSVILLE, TN — PANEL "E" — A.I.C. BREAKER MINIMUM 10,000

MAIN BRKR FRAME | MAIN BREAKER AMPS | MLO SIZE 400 | TYPE SQUARE "D" - NQ | BUS AL
VOLTAGE 120/208 | PHASE THREE | WIRE FOUR | MOUNTING SURFACE

DESCRIPTION	A	B	C	WIRE SIZE	NO. OF W'S	POLE	TRIP	CT. NO.	CT. NO.	TRIP	POLE	NO. OF W'S	WIRE SIZE	A	B	C	DESCRIPTION
REC DBL QUEEN	900			12	2	1	20	1	2	20	1	2	12	900			REC DBL QUEEN
REC DBL QUEEN		1080		12	2	1	20	3	4	20	1	2	12		1080		REC DBL QUEEN
REC DBL QUEEN			1000	12	2	1	20	5	6	20	1	2	12			1000	REC DBL QUEEN
DBL QUEEN PTAC	1615			12	2	1	20	7	8	20	1	2	12	1615			DBL QUEEN PTAC
----------		1615		12	2	1	20	9	10	20	1	2	12		1615		----------
REC DBL QUEEN			900	12	2	1	20	11	12	20	1	2	12			900	REC DBL QUEEN
REC DBL QUEEN	1080			12	2	1	20	13	14	20	1	2	12	1080			REC DBL QUEEN
REC DBL QUEEN		1000		12	2	1	20	15	16	20	1	2	12		1000		REC DBL QUEEN
DBL QUEEN PTAC			1615	12	2	1	20	17	18	20	1	2	12			1615	DBL QUEEN PTAC
----------	1615			12	2	1	20	19	20	20	1	2	12	1615			----------
REC DBL QUEEN ADA		900		12	2	1	20	21	22	20	1	2	12		900		REC KING
REC DBL QUEEN ADA			1080	12	2	1	20	23	24	20	1	2	12			1080	REC KING
REC DBL QUEEN ADA	1000			12	2	1	20	25	26	20	1	2	12	1000			REC KING
DBL QUEEN PTAC		1615		12	2	1	20	27	28	20	1	2	12		1615		[illegible]TAC
----------			1615	12	2	1	20	29	30	20	1	2	12			[illegible]	----------
REC KING	900			12	2	1	20	31	32	20	1	2	12	900			REC KI[illegible]
REC KING		1080		12	2	1	20	33	34	20	1	2	12		[illegible]		REC KING
REC KING			1000	12	2	1	20	35	36	20	1	2	12			[illegible]	REC KING
KING PTAC	1615			12	2	1	20	37	38	20	1	2	12	[illegible]			[illegible] PTAC
----------		1615		12	2	1	20	39	40	20	1	2	12		1615		----------
REC DBL QUEEN			900	12	2	1	20	41	42	20	1	2	12			[illegible]	REC DBL QUEEN
REC DBL QUEEN	1080			12	2	1	20	43	44	20	1	[illegible]	12	1080			REC DBL QUEEN
REC DBL QUEEN		1000		12	2	1	20	45	46	20	[illegible]	[illegible]	12		[illegible]		REC DBL QUEEN
DBL QUEEN PTAC			1615	12	2	1	20	47	48	20	1	[illegible]	12			1615	DBL QUEEN PTAC
----------	1615			12	2	1	20	49	50	20	[illegible]	2	[illegible]	[illegible]			----------
SPARE				12	2	[illegible]	20	51	[illegible]	30	[illegible]	2	[illegible]		1500		SIGNAGE
SPARE				12	2	[illegible]	20	53	54	[illegible]	[illegible]	[illegible]	[illegible]			1500	----------
SECTION B																	
REC DBL QUEEN	900			12	2	1	[illegible]	55	56	20	[illegible]	2	12	900			REC DBL QUEEN
REC DBL QUEEN		1080		12	2	1	[illegible]	57	58	20	1	2	12		1080		REC DBL QUEEN
REC DBL QUEEN			[illegible]	12	2	1	20	[illegible]	[illegible]	20	1	2	12			1000	REC DBL QUEEN
DBL QUEEN PTAC	1615			12	2	1	20	[illegible]	62	20	1	2	12	1615			DBL QUEEN PTAC
----------		[illegible]		[illegible]	2	1	20	[illegible]	64	20	1	2	12		1615		----------
REC DBL QUEEN			900	[illegible]	2	1	[illegible]	[illegible]	66	20	1	2	12			900	REC KING
REC DBL QUEEN	1080			[illegible]	2	1	[illegible]	67	68	20	1	2	12	1080			REC KING
REC DBL QUEEN		1000		12	2	[illegible]	20	69	70	20	1	2	12		1000		REC KING
DBL QUEEN PTAC			1615	12	[illegible]	1	20	71	72	20	1	2	12			1615	KING PTAC
----------	[illegible]			12	[illegible]	1	20	73	74	20	1	2	12	1615			----------
REC DBL QUEEN		900		12	2	1	20	75	76	20	1	2	12		900		REC KING
REC DBL QUEEN			1080	12	2	1	20	77	78	20	1	2	12			1080	REC KING
REC DBL QUEEN	1000			12	2	1	20	79	80	20	1	2	12	1000			REC KING
DBL QUEEN PTAC		1615		12	2	1	20	81	82	20	1	2	12		1615		KING PTAC
----------			1615	12	2	1	20	83	84	20	1	2	12			1615	----------
REC DBL QUEEN	900			12	2	1	20	85	86	20	1						SPARE
REC DBL QUEEN		1080		12	2	1	20	87	88	20	1						SPARE
REC DBL QUEEN			1000	12	2	1	20	89	90	20	1						SPARE
DBL QUEEN PTAC	1615			12	2	1	20	91	92	20	1						SPARE
----------		1615		12	2	1	20	93	94	20	1						SPARE
SPARE						1	20	95	96	20	1						SPARE
SPARE						1	20	97	98	20	1						SPARE
SPARE						1	20	99	100	20	1						SPARE
SPARE						1	20	101	102	20	1						SPARE
SPARE						1	20	103	104	20	1						SPARE
SPARE						1	20	105	106	20	1						SPARE
SPARE						1	20	107	108	20	1						SPARE

LIGHTS@125% = 0 VA	RECEPTACLES = 30,330 VA	HVAC@100% = 54,910 VA	OTHER EQUIP@ 100% = 3,000 VA
VA'S TOTAL = 88,240 VA	A PHASE = 37,775 VA	B PHASE = 36,425 VA	C PHASE = 34,370 VA
AMPS TOTAL = 245	A PHASE = 315	B PHASE = 304	C PHASE = 286

HOLIDAY INN - CLARKSVILLE, TN — PANEL "K" — A.I.C. BREAKER MINIMUM 10,000

MAIN BRKR FRAME | MAIN BREAKER AMPS | MLO SIZE 225 | TYPE SQUARE "D" - NQ | BUS AL
VOLTAGE 120/208 | PHASE THREE | WIRE FOUR | MOUNTING SURFACE

DESCRIPTION	A	B	C	WIRE SIZE	NO. OF W'S	POLE	TRIP	CT. NO.	CT. NO.	TRIP	POLE	NO. OF W'S	WIRE SIZE	A	B	C	DESCRIPTION
HP-10	1500			10	2	2	30	1	2	60	3	3	6	4340			DOAS-1
----------		1500		10	-	-	-	3	4	-	-	-	6		4340		----------
HP-11			1500	10	2	2	30	5	6	-	-	-	6			4340	----------
----------	1500			10	-	-	-	7	8	70	3	3	4	5300			DOAS-2
HP-12		1790		10	3	3	30	9	10	-	-	-	4		5300		----------
----------			1790	10	-	-	-	11	12	-	-	-	4			5300	----------
----------	1790			10	-	-	-	13	14	35	3	3	8	2100			KSF-1
MSHP-3/MS-3		450		12	2	2	20	15	16	-	-	-	8		2100		----------
----------			450	12	-	-	-	17	18	-	-	-	8			2100	----------
MSHP-4/MS-4	450			12	2	2	20	19	20	20	1	2	12	500			EXHAUST FANS
----------		450		12	-	-	-	21	22	20	1	2	12		500		EXHAUST FANS
MSHP-5/MS-5			450	12	2	2	20	23	24	20	1	2	12			500	EXHAUST FANS
----------	450			12	-	-	-	25	26	20	1						SPARE
SPARE						1	20	27	28	20	1						SPARE
SPARE						1	20	29	30	20	1						SPARE

LIGHTS@125% = 0 VA	RECEPTACLES = 0 VA	HVAC@100% = 50,790 VA	OTHER EQUIP@ 100[illegible] 0 VA
VA'S TOTAL = 50,790 VA	A PHASE = 17,930 VA	B PHASE = 16,430 VA	C PHASE[illegible] 16,430 VA
AMPS TOTAL = 141	A PHASE = 149	B PHASE = 137	C PHASE = 137

HOLIDAY INN - CLARKSVILLE, TN — PANEL "H" — A.I.C. BREAKER MINIMUM 10,000

MAIN BRKR FRAME | MAIN BREAKER AMPS | MLO SIZE [illegible] | TYPE SQUARE "D" - NQ | BUS AL
VOLTAGE 120/208 | PHASE THREE | WIRE [illegible]OUR | MOUNTING SURFACE

DESCRIPTION	A	B	C	WIRE SIZE	NO. OF W'S	POLE	TRIP	CT. NO.	CT. NO.	TRIP	POLE	NO. OF W'S	WIRE SIZE	A	B	C	DESCRIPTION
REC KING	900			[illegible]	2	1	[illegible]	[illegible]	2	20	1	2	12	900			REC KING
REC KING		1080		[illegible]	2	[illegible]	[illegible]	[illegible]	4	20	1	2	12		1080		REC KING
REC KING			[illegible]00	[illegible]	2	[illegible]	20	[illegible]	6	20	1	2	12			1000	REC KING
KING PTAC	1615			[illegible]	[illegible]	2	20	[illegible]	8	20	2	2	10	1615			KING PTAC
----------		1615		10	[illegible]	-	-	9	10	-	-	-	10		1615		----------
REC KING			900	12	2	1	[illegible]	11	12	20	1	2	12			900	REC KING
REC KING	1080			[illegible]	2	1	20	13	14	20	1	2	12	1080			REC KING
REC KING		1000		12	2	1	20	15	16	20	1	2	12		1000		REC KING
KING PTAC			1615	10	2	2	20	17	18	20	2	2	10			1615	KING PTAC
----------	1615			10	-	-	-	19	20	-	-	-	10	1615			----------
REC DBL QU[illegible]		900		12	2	1	20	21	22	20	1	2	12		900		REC DBL QUEEN
REC DBL QU[illegible]			1080	12	2	1	20	23	24	20	1	2	12			1080	REC DBL QUEEN
[illegible] QUEEN	1000			12	2	1	20	25	26	20	1	2	12	1000			REC DBL QUEEN
[illegible] PTAC		1615		10	2	2	20	27	28	20	2	2	10		1615		DBL QUEEN PTAC
----------			1615	10	-	-	-	29	30	-	-	-	10			1615	----------
RE[illegible] QUEEN	900			12	2	1	20	31	32	20	1	2	12	900			REC DBL QUEEN
RE[illegible]		1080		12	2	1	20	33	34	20	1	2	12		1080		REC DBL QUEEN
RE[illegible]UEEN			1000	12	2	1	20	35	36	20	1	2	12			1000	REC DBL QUEEN
DBL [illegible]EN PTAC	1615			10	2	2	20	37	38	20	2	2	10	1615			DBL QUEEN PTAC
----------		1615		10	-	-	-	39	40	-	-	-	10		1615		----------
REC DBL QUEEN			900	12	2	1	20	41	42	20	1	2	12			900	REC KING
REC DBL QUEEN	1080			12	2	1	20	43	44	20	1	2	12	1080			REC KING
REC DBL QUEEN		1000		12	2	1	20	45	46	20	1	2	12		1000		REC KING
DBL QUEEN PTAC			1615	10	2	2	20	47	48	20	2	2	10			1615	KING PTAC
----------	1615			10	-	-	-	49	50	-	-	-	10	1615			----------
SPARE						1	20	51	52	20	1						SPARE
SPARE						1	20	53	54	20	1						SPARE
SECTION B																	
REC KING	900			12	2	1	20	55	56	20	1	2	12	900			REC DBL QUEEN
REC KING		1080		12	2	1	20	57	58	20	1	2	12		1080		REC DBL QUEEN
REC KING			1000	12	2	1	20	59	60	20	1	2	12			1000	REC DBL QUEEN
KING PTAC	1615			10	2	2	20	61	62	20	2	2	10	1615			DBL QUEEN PTAC
----------		1615		10	-	-	-	63	64	-	-	-	10		1615		----------
REC KING			900	12	2	1	20	65	66	20	1	2	12			900	REC DBL QUEEN
REC KING	1080			12	2	1	20	67	68	20	1	2	12	1080			REC DBL QUEEN
REC KING		1000		12	2	1	20	69	70	20	1	2	12		1000		REC DBL QUEEN
KING PTAC			1615	10	2	2	20	71	72	20	2	2	10			1615	DBL QUEEN PTAC
----------	1615			10	-	-	-	73	74	-	-	-	10	1615			----------
REC DBL QUEEN		900		12	2	1	20	75	76	20	1	2	12		900		REC KING
REC DBL QUEEN			1080	12	2	1	20	77	78	20	1	2	12			1080	REC KING
REC DBL QUEEN	1000			12	2	1	20	79	80	20	1	2	12	1000			REC KING
DBL QUEEN PTAC		1615		10	2	2	20	81	82	20	2	2	10		1615		KING PTAC
----------			1615	10	-	-	-	83	84	-	-	-	10			1615	----------
REC DBL QUEEN	900			12	2	1	20	85	86	20	1	2	12	900			REC KING
REC DBL QUEEN		1080		12	2	1	20	87	88	20	1	2	12		1080		REC KING
REC DBL QUEEN			1000	12	2	1	20	89	90	20	1	2	12			1000	REC KING
DBL QUEEN PTAC	1615			10	2	2	20	91	92	20	2	2	10	1615			KING PTAC
----------		1615		10	-	-	-	93	94	-	-	-	10		1615		----------
LTS CORRIDOR			1140	12	2	1	20	95	96	20	1	2	12			1000	REC TV EQUIP
REC CORRIDOR	1260			12	2	1	20	97	98	20	1	2	12	1000			REC TV EQUIP
LTS HOUSEKEEPING		610		10	2	2	30	99	100	20	1	2	12		500		REC TV EQUIP
LTS STORAGE			570	10	-	-	-	101	102	20	1						SPARE
ICEMAKER	1500			10	3	3	30	103	104	20	1						SPARE
AH-12		2665		10	-	-	-	105	106	20	1						SPARE
----------			2665	10	-	-	-	107	108	20	1						SPARE

LIGHTS@125% = 2,900 VA	RECEPTACLES = 34,450 VA	HVAC@100% = 63,470 VA	OTHER EQUIP@ 100% = 0 VA
VA'S TOTAL = 100,820 VA	A PHASE = 44,050 VA	B PHASE = 41,395 VA	C PHASE = 39,245 VA
AMPS TOTAL = 280	A PHASE = 367	B PHASE = 345	C PHASE = 327

HOLIDAY INN - CLARKSVILLE, TN — PANEL "F" — A.I.C. BREAKER MINIMUM 10,000

MAIN BRKR FRAME | MAIN BREAKER AMPS | MLO SIZE 400 | TYPE SQUARE "D" - NQ | BUS AL
VOLTAGE 120/208 | PHASE THREE | WIRE FOUR | MOUNTING SURFACE

DESCRIPTION	A	B	C	WIRE SIZE	NO. OF W'S	POLE	TRIP	CT. NO.	CT. NO.	TRIP	POLE	NO. OF W'S	WIRE SIZE	A	B	C	DESCRIPTION
REC KING	900			12	2	1	20	1	2	20	1	2	12	900			REC KING
REC KING		1080		12	2	1	20	3	4	20	1	2	12		1080		REC KING
REC KING			1000	12	2	1	20	5	6	20	1	2	12			1000	REC KING
KING PTAC	1615			10	2	2	20	7	8	20	2	2	10	1615			KING PTAC
----------		1615		10	-	-	-	9	10	-	-	-	10		1615		----------
REC KING			900	12	2	1	20	11	12	20	1	2	12			900	REC KING
REC KING	1080			12	2	1	20	13	14	20	1	2	12	1080			REC KING
REC KING		1000		12	2	1	20	15	16	20	1	2	12		1000		REC KING
KING PTAC			1615	10	2	2	20	17	18	20	2	2	10			1615	KING PTAC
----------	1615			10	-	-	-	19	20	-	-	-	10	1615			----------
REC DBL QUEEN		900		12	2	1	20	21	22	20	1	2	12		900		REC DBL QUEEN
REC DBL QUEEN			1080	12	2	1	20	23	24	20	1	2	12			1080	REC DBL QUEEN
REC DBL QUEEN	1000			12	2	1	20	25	26	20	1	2	12	1000			REC DBL QUEEN
DBL QUEEN PTAC		1615		10	2	2	20	27	28	20	2	2	10		1615		DBL QUEEN PTAC
----------			1615	10	-	-	-	29	30	-	-	-	10			1615	----------
REC DBL QUEEN	900			12	2	1	20	31	32	20	1	2	12	900			REC DBL QUEEN
REC DBL QUEEN		1080		12	2	1	20	33	34	20	1	2	12		1080		REC DBL QUEEN
REC DBL QUEEN			1000	12	2	1	20	35	36	20	1	2	12			1000	REC DBL QUEEN
DBL QUEEN PTAC	1615			10	2	2	20	37	38	20	2	2	10	1615			DBL QUEEN PTAC
----------		1615		10	-	-	-	39	40	-	-	-	10		1615		----------
REC DBL QUEEN			900	12	2	1	20	41	42	20	1	2	12			900	REC KING
REC DBL QUEEN	1080			12	2	1	20	43	44	20	1	2	12	1080			REC KING
REC DBL QUEEN		1000		12	2	1	20	45	46	20	1	2	12		1000		REC KING
DBL QUEEN PTAC			1615	10	2	2	20	47	48	20	2	2	10			1615	KING PTAC
----------	1615			10	-	-	-	49	50	-	-	-	10	1615			----------
SPARE						1	20	51	52	20	2	2	12		1500		EWH-4
SPARE						1	20	53	54	-	-	-	12			1500	----------
SECTION B																	
REC KING	900			12	2	1	20	55	56	20	1	2	12	900			REC DBL QUEEN
REC KING		1080		12	2	1	20	57	58	20	1	2	12		1080		REC DBL QUEEN
REC KING			1000	12	2	1	20	59	60	20	1	2	12			1000	REC DBL QUEEN
KING PTAC	1615			10	2	2	20	61	62	20	2	2	10	1615			DBL QUEEN PTAC
----------		1615		10	-	-	-	63	64	-	-	-	10		1615		----------
REC KING			900	12	2	1	20	65	66	20	1	2	12			900	REC DBL QUEEN
REC KING	1080			12	2	1	20	67	68	20	1	2	12	1080			REC DBL QUEEN
REC KING		1000		12	2	1	20	69	70	20	1	2	12		1000		REC DBL QUEEN
KING PTAC			1615	10	2	2	20	71	72	20	2	2	10			1615	DBL QUEEN PTAC
----------	1615			10	-	-	-	73	74	-	-	-	10	1615			----------
REC DBL QUEEN		900		12	2	1	20	75	76	20	1	2	12		900		REC KING
REC DBL QUEEN			1080	12	2	1	20	77	78	20	1	2	12			1080	REC KING
REC DBL QUEEN	1000			12	2	1	20	79	80	20	1	2	12	1000			REC KING
DBL QUEEN PTAC		1615		10	2	2	20	81	82	20	2	2	10		1615		KING PTAC
----------			1615	10	-	-	-	83	84	-	-	-	10			1615	----------
REC DBL QUEEN	900			12	2	1	20	85	86	20	1	2	12	900			REC KING
REC DBL QUEEN		1080		12	2	1	20	87	88	20	1	2	12		1080		REC KING
REC DBL QUEEN			1000	12	2	1	20	89	90	20	1	2	12			1000	REC KING
DBL QUEEN PTAC	1615			10	2	2	20	91	92	20	2	2	10	1615			KING PTAC
----------		1615		10	-	-	-	93	94	-	-	-	10		1615		----------
LTS CORRIDOR			1140	12	2	1	20	95	96	20	1	2	12			1000	REC TV EQUIP
REC CORRIDOR	1260			12	2	1	20	97	98	20	1	2	12	1000			REC TV EQUIP
LTS HOUSEKEEPING		610		10	2	2	30	99	100	20	1	2	12		500		REC TV EQUIP
LTS STORAGE			570	10	-	-	-	101	102	20	1						SPARE
ICEMAKER	1500			10	3	3	30	103	104	20	1						SPARE
AH-11		2665		10	-	-	-	105	106	20	1						SPARE
----------			2665	10	-	-	-	107	108	20	1						SPARE

LIGHTS@125% = 2,900 VA	RECEPTACLES = 34,450 VA	HVAC@100% = 63,470 VA	OTHER EQUIP@ 100% = 3,000 VA
VA'S TOTAL = 103,820 VA	A PHASE = 44,050 VA	B PHASE = 42,895 VA	C PHASE = 40,745 VA
AMPS TOTAL = 288	A PHASE = 367	B PHASE = 357	C PHASE = 340

Geary Engineering
5502 Walsh Lane Suite 102
Rogers, AR. 72758
Phone: (479) 464-8006
E-mail: tgeary@gearyeng.com
Web: www.gearyeng.com

THESE DRAWINGS ARE PRELIMINARY IN NATURE AND INTENDED FOR REVIEW AND PERMITTING. DRAWINGS ARE NOT TO BE USED FOR CONSTRUCTION WITHOUT ARCHITECT'S AND ENGINEER'S SIGNATURE AND THEIR DATE OF ISSUE FOR CONSTRUCTION.

JSA ARCHITECTS
9726 E. 42nd St. SUITE 153
TULSA, OK 74146
918.640.6800
JHNSANFORD@AOL.COM

Copyright 2019 John Sanford

JOHN SANFORD,
AIA, NCARB
TN LICENSE #106056

NOT VALID FOR CONSTRUCTION UNLESS SIGNED IN THIS BLOCK

PROPOSED HOLIDAY INN LI 9383
215 CRACKER BARREL DR., CLARKSVILLE, TN
MONTGOMERY COUNTY, TENNESSEE

PERMIT NO: -----

GE#18002

No.	Description	Date

SHEET

E802
ELECTRICAL PANEL SCHEDULES

Order Plans @ www.LDIILine.com