LIGHT FIXTURE SCHEDULE

TYPE	DESCRIPTION	MANUFACTURER AND CATALOG NO.	VOLTAGE	LAMPS	REMARKS
A1	RECESSED 2X2 ARCHITECTURAL LED TROFFER WITH STEEL HOUSING, ROUND RIBBED FROSTED ACRYLIC DIFFUSER, 3300 LUMEN OUTPUT, 3500K COLOR TEMPERATURE, UNIVERSAL VOLTAGE 0-10V (10%) LED DIMMING DRIVER, AND WHITE FINISH.	LITHONIA # 2BLT2 33L ADP GZ10 LP835 OR APPROVED EQUAL	UNV	28W LED	
A2	RECESSED 2X4 ARCHITECTURAL LED TROFFER WITH STEEL HOUSING, ROUND RIBBED FROSTED ACRYLIC DIFFUSER, 4800 LUMEN OUTPUT, 3500K COLOR TEMPERATURE, UNIVERSAL VOLTAGE 0-10V (10%) LED DIMMING DRIVER, AND WHITE FINISH.	LITHONIA # 2BLT4 48L ADP GZ10 LP835 OR APPROVED EQUAL	UNV	39W LED	
A3	RECESSED 2X2 ARCHITECTURAL LED TROFFER WITH STEEL HOUSING, ROUND RIBBED FROSTED ACRYLIC DIFFUSER, 3300 LUMEN OUTPUT, 3500K COLOR TEMPERATURE, UNIVERSAL VOLTAGE 0-10V (DIM TO DARK) LED DIMMING DRIVER, AND WHITE FINISH.	LITHONIA # 2BLT2 33L ADP EZ6 LP835 MEZ10522 OR APPROVED EQUAL	UNV	28W LED	
A4	RECESSED 2X4 ARCHITECTURAL LED TROFFER WITH STEEL HOUSING, ROUND RIBBED FROSTED ACRYLIC DIFFUSER, 4800 LUMEN OUTPUT, 3500K COLOR TEMPERATURE, UNIVERSAL VOLTAGE 0-10V (DIM TO DARK) LED DIMMING DRIVER, AND WHITE FINISH.	LITHONIA # 2BLT4 48L ADP EZ6 LP835 MEZ10521 OR APPROVED EQUAL	UNV	39W LED	
A5	6'X9' GRAPHIC IMAGE PANEL WITH INTEGRAL LED LIGHTING, STEEL HOUSING, GRID MOUNTING, UNIVERSAL VOLTAGE 0-10V (10%) LED DIMMING DRIVER, AND WHITE ANTI-MICROBIAL POWDER COAT FINISH.	HEALTHCARE LIGHTING # HCV2-22-G-MVOLT-SP1-LED35-G9-____-GM-AM OR APPROVED EQUAL OR APPROVED EQUAL	UNV	351W LED	IMAGE TO BE SELECTED BY OWNER/INTERIOR DESIGNER
A6	6'X9' MIRI SAFE GRAPHIC IMAGE PANEL WITH INTEGRAL LED LIGHTING, ALUMINUM HOUSING, GRID MOUNTING, REMOTE UNIVERSAL VOLTAGE 0-10V (10%) LED DIMMING DRIVER, AND WHITE ANTI-MICROBIAL POWDER COAT FINISH.	HEALTHCARE LIGHTING # HCV223-G-MVOLT-SP1-G9-____-GWTR2-GWAM OR APPROVED EQUAL OR APPROVED EQUAL	UNV	351W LED	IMAGE TO BE SELECTED BY OWNER/INTERIOR DESIGNER
A7	DECORATIVE ARCHITECTURAL 2X2 TROFFER WITH STEEL HOUSING, 4" DROP FROSTED ACRYLIC LENS, 3500 LUMEN OUTPUT, 3500K COLOR TEMPERATURE, UNIVERSAL VOLTAGE 0-10V 10% DIMMING DRIVER AND WHITE FINISH.	FOCAL POINT # PRVL-22-ACA-3500L-35K-1C-UNV-LD1-G1-WH OR APPROVED EQUAL	UNV	44W LED	
B1	RECESSED 2X4 LENSED LED SURGICAL TROFFER WITH STEEL HOUSING, FLUSH ALUMINUM DOOR, DIFFUSED DR ACRYLIC LENS WITH ASYMMETRIC/SYMMETRIC OPTICS, 15,000 LUMEN OUTPUT, 4000K COLOR TEMPERATURE, 80CRI, 120V 0-10V LED DIMMING DRIVER, ANTI-MICROBIAL WHITE FINISH, AND INTEGRAL EMERGENCY BATTERY.	KENALL # M4SED-24-15DL-UD4-ARLSS-4IVOLT-GZ1-TRW OR APPROVED EQUAL OR APPROVED EQUAL	UNV	169W LED	
B2	COMBINATION GREEN/WHITE LIGHT RECESSED 2X4 LENSED LED SURGICAL TROFFER WITH STEEL HOUSING, FLUSH ALUMINUM DOOR, DIFFUSED DR ACRYLIC LENS WITH ASYMMETRIC/SYMMETRIC OPTICS, 2,700 LUMEN GREEN LIGHT AND 10,000 LUMEN WHITE LIGHT OUTPUT, 4000K COLOR TEMPERATURE, 80CRI, 120V 0-10V LED DIMMING DRIVER, ANTI-MICROBIAL WHITE FINISH, AND INTEGRAL EMERGENCY BATTERY.	KENALL # M4SED-24-4SG1030L-4DK9-DCC-120-2F-PAH-A3YM-LEL OR APPROVED EQUAL OR APPROVED EQUAL	120	162W LED	
B3	RECESSED 2X4 LENSED LED SEALED CLEANROOM TROFFER WITH POWDER COATED STEEL HOUSING, PAINTED STEEL DOOR, SYMMETRIC DIFFUSED ACRYLIC LENS, 3500K COLOR TEMPERATURE, 6500 LUMEN OUTPUT, UNIVERSAL VOLTAGE 0-10V DIMMING DRIVER, WHITE ANTIMICROBIAL FINISH, AND UL WET LOCATION LISTING	KENALL # CSED-24-8TL35K-DCC-120-2F-2H-SYM-AWF OR APPROVED EQUAL OR APPROVED EQUAL	UNV	87W LED	
B4	RECESSED 2X2 CORRECTIONAL GRADE LED TROFFER WITH 16 GAUGE STEEL HOUSING, 0.125" THICK PRISMATIC ACRYLIC INNER LENS, 0.5" CLEAR POLYCARBONATE OUTER LENS, 3475 LUMEN OUTPUT, 3500K COLOR TEMPERATURE, 120V 0-10V 10% LED DIMMING DRIVER, AND WHITE FINISH	KENALL # RMCD-2-FLCC-1-4SL35K-DCC-120-1U-I OR APPROVED EQUAL OR APPROVED EQUAL OR APPROVED EQUAL	UNV	45W LED	
B5	RECESSED 2X4 LENSED LED LIGHT PANEL WITH SEAMLESS ALUMINUM FRAME, SATIN WHITE ACRYLIC LENS, 4800 LUMEN OUTPUT, 3500K COLOR TEMPERATURE, UNIVERSAL VOLTAGE 0-10V 10% LED DIMMING DRIVER, AND WHITE FINISH.	LITHONIA # EPANEL-2X4-4800LM-80CRI-35K-MVOLT-SCP OR APPROVED EQUAL OR APPROVED EQUAL OR APPROVED EQUAL	UNV	39W LED	
D1	4" ROUND, RECESSED, LED DOWNLIGHT WITH STEEL HOUSING, CLEAR SEMI-SPECULAR REFLECTOR, 1000 LUMEN OUTPUT, 3500K COLOR TEMPERATURE, UNIVERSAL VOLTAGE 0-10V LED DIMMING DRIVER, AND WHITE PAINTED FLANGE.	LITHONIA # LDN4-35/10-L04-ARLSS-4IVOLT-GZ1-TRW OR APPROVED EQUAL OR APPROVED EQUAL OR APPROVED EQUAL	UNV	13W LED	
D1W	4" ROUND, RECESSED, WALL WASH, LED DOWNLIGHT WITH STEEL HOUSING, CLEAR SEMI-SPECULAR REFLECTOR, 1000 LUMEN OUTPUT, 3500K COLOR TEMPERATURE, UNIVERSAL VOLTAGE 0-10V LED DIMMING DRIVER, AND WHITE PAINTED FLANGE.	LITHONIA # LDN4-35/10-L04-ARLSS-4IVOLT-GZ1-TRW OR APPROVED EQUAL OR APPROVED EQUAL OR APPROVED EQUAL	UNV	13W LED	
D2	4" ROUND, RECESSED, LED DOWNLIGHT WITH STEEL HOUSING, CLEAR SEMI-SPECULAR REFLECTOR, 2000 LUMEN OUTPUT, 3500K COLOR TEMPERATURE, UNIVERSAL VOLTAGE 0-10V LED DIMMING DRIVER, AND WHITE PAINTED FLANGE	LITHONIA # LDN4-35/20-L04-ARLSS-4IVOLT-GZ1-TRW OR APPROVED EQUAL OR APPROVED EQUAL OR APPROVED EQUAL	UNV	23W LED	
D3	6" ROUND, RECESSED, SURGICAL GRADE LED DOWNLIGHT WITH STEEL HOUSING, CLEAR SEMI-SPECULAR REFLECTOR WITH MEDIUM DISTRIBUTION, FLUSH LENS, 1500 LUMEN OUTPUT, 4000K COLOR TEMPERATURE, 90 CRI, UNIVERSAL VOLTAGE 0-10V 1% LED DIMMING DRIVER, IP65 RATING, AND WHITE PAINTED FLANGE.	KENALL # M4DLS-IPF-35W-22L-40K9-MI-CSS-T-IW65-DV-GWH OR APPROVED EQUAL OR APPROVED EQUAL	UNV	22W LED	
D4	4" ROUND, RECESSED, LED DOWNLIGHT WITH STEEL HOUSING, CLEAR SEMI-SPECULAR REFLECTOR, 1000 LUMEN OUTPUT, 3500K COLOR TEMPERATURE, UNIVERSAL VOLTAGE 0-10V LED DIMMING DRIVER, WHITE PAINTED FLANGE, AND WET LOCATION LISTING.	LITHONIA # LDN4-35/10-L04-ARLSS-4IVOLT-GZ1-TRW-WL OR APPROVED EQUAL OR APPROVED EQUAL	UNV	13W LED	
D5	MRI SAFE 6" ROUND, RECESSED, LED DOWNLIGHT WITH NON-FERROUS HOUSING, CLEAR SEMI-SPECULAR REFLECTOR WITH MEDIUM WIDE DISTRIBUTION, RECESSED LENSED TRIM, 2030 LUMEN OUTPUT, 3500K COLOR TEMPERATURE, REMOTE UNIVERSAL VOLTAGE 0-10V 10% LED DIMMING DRIVER, AND WHITE FINISH.	GOTHAM LIGHTING FIXTURE # EVOMRI-35/20-4AR-MWD-LSS-TRW-EVDRD6-_____-2000LM-MVOLT-GZ10 OR APPROVED EQUAL	UNV	24W LED	PROVIDE SUFFICIENT REMOTE DRIVER CAPACITY TO ACCOMMODATE THE NUMBER OF FIXTURES WITHIN THE MRI PROCEDURE ROOM.
D6	4" SQUARE, RECESSED, LED DOWNLIGHT WITH STEEL HOUSING, CLEAR SEMI-SPECULAR REFLECTOR, 1030 LUMEN OUTPUT, 3500K COLOR TEMPERATURE, UNIVERSAL VOLTAGE 0-10V LED DIMMING DRIVER, AND WHITE PAINTED FLANGE.	LITHONIA # LDN4SQ-35/10-L04-ARLSS-MVOLT-GZ1-TRW OR APPROVED EQUAL OR APPROVED EQUAL	UNV	13W LED	
EX1	SINGLE FACE EDGE LIT LED EXIT SIGN WITH UNIVERSAL MOUNT EXTRUDED ALUMINUM HOUSING, CLEAR ACRYLIC FACE WITH GREEN LETTERING, FIELD APPLIED CHEVRONS, AC ONLY, UNIVERSAL VOLTAGE, AND WHITE FINISH.	LITHONIA # EDG-W-1-G OR APPROVED EQUAL	UNV	1W LED	REFER TO ARCHITECTURAL LIFE SAFETY PLAN FOR DIRECTIONAL ARROWS
EX2	DUAL FACE EDGE LIT LED EXIT SIGN WITH UNIVERSAL MOUNT EXTRUDED ALUMINUM HOUSING, MIRRORED ACRYLIC FACE WITH GREEN LETTERING, FIELD APPLIED CHEVRONS, AC ONLY, UNIVERSAL VOLTAGE, AND WHITE FINISH.	LITHONIA # EDG-W-1-GWR OR APPROVED EQUAL OR APPROVED EQUAL	UNV	1W LED	REFER TO ARCHITECTURAL LIFE SAFETY PLAN FOR DIRECTIONAL ARROWS PROVIDE WITH CUSTOM FACE AND LETTERING TO MATCH EXISTING BUILDING SIGNS
EX3	SINGLE FACE THERMOPLASTIC LED EXIT SIGN WITH UNIVERSAL MOUNTING, TAMPER RESISTANT HARDWARE, CLEAR POLYCARBONATE LENS, GREEN LETTERING, FIELD ADJUSTABLE CHEVRONS, LOW AMBIENT TEMPERATURE RATED (-4F), AC ONLY, UNIVERSAL VOLTAGE, WHITE FINISH, AND WET LOCATION LISTING.	LITHONIA # IRLTE-W-1-G-TP OR APPROVED EQUAL OR APPROVED EQUAL	LED	REFER TO ARCHITECTURAL LIFE SAFETY PLAN FOR DIRECTIONAL ARROWS	
EX4	DUAL FACE THERMOPLASTIC LED EXIT SIGN WITH UNIVERSAL MOUNTING, TAMPER RESISTANT HARDWARE, CLEAR POLYCARBONATE LENS, GREEN LETTERING, FIELD ADJUSTABLE CHEVRONS, LOW AMBIENT TEMPERATURE RATED (-4F), AC ONLY, UNIVERSAL VOLTAGE, WHITE FINISH, AND WET LOCATION LISTING.	LITHONIA # IRLTE-W-1-G-TP OR APPROVED EQUAL OR APPROVED EQUAL	UNV	REFER TO ARCHITECTURAL LIFE SAFETY PLAN FOR DIRECTIONAL ARROWS	
J1	4' LED STRIP FIXTURE WITH STEEL HOUSING, ROUND DIFFUSE ACRYLIC LENS WITH GENERAL DISTRIBUTION, 3500K COLOR TEMPERATURE, 5000 LUMEN OUTPUT, UNIVERSAL VOLTAGE 0-10V 10% LED DIMMING DRIVER, AND WHITE FINISH.	LITHONIA # CLX-L48-5000LM-SEF-ROL-MVOLT-GZ10-35K-80CRI-WH OR APPROVED EQUAL OR APPROVED EQUAL	UNV	39W LED	MOUNT FIXTURE AT 9'-0"AFF.
J1E	4' LED STRIP FIXTURE WITH STEEL HOUSING, ROUND DIFFUSE ACRYLIC LENS WITH GENERAL DISTRIBUTION, 3500K COLOR TEMPERATURE, 5000 LUMEN OUTPUT, UNIVERSAL VOLTAGE 0-10V 10% LED DIMMING DRIVER, WHITE FINISH, AND INTEGRAL EMERGENCY BATTERY.	LITHONIA # CLX-L48-5000LM-SEF-ROL-MVOLT-GZ10-35K-80CRI-EL-WH OR APPROVED EQUAL OR APPROVED EQUAL	UNV	39W LED	MOUNT FIXTURE AT 9'-0"AFF.
J2	4' LED VAPORLIME WITH FIBERGLASS HOUSING, LINEAL RIBBED FROSTED ACRYLIC LENS, MEDIUM DISTRIBUTION, 8000 LUMEN OUTPUT, 3500K COLOR TEMPERATURE, STAINLESS STEEL LATCHES, UNIVERSAL VOLTAGE LED NON-DIMMING DRIVER, AND WHITE FINISH.	LITHONIA # FBN-L48-8000LM-WAR-MVOLT-GZ10-35K-80CRI-SSTEL OR APPROVED EQUAL	UNV	80W LED	
K1	RECESSED 2X4 PATIENT ROOM MULTIFUNCTION TROFFER WITH STEEL HOUSING, EXTRUDED ALUMINUM HOUSING, .125" THICK HIGH IMPACT CLEAR ACRYLIC LENS, READING/AMBIENT/EXAM FUNCTIONS, 3500K COLOR TEMPERATURE, 10,700 LUMEN OUTPUT, UNIVERSAL VOLTAGE 0-10V LED DIMMING DRIVERS, INTEGRAL LOW VOLTAGE CONTROLLER, AND WHITE ANTIMICROBIAL FINISH.	KENALL # MPCAD6E24-G-4EL10L-35K-DCC-120-4C-AWF-VVCD-LEL OR APPROVED EQUAL	UNV	148W LED	READING AND AMBIENT FUNCTIONS SHALL BE CONTROLLED VIA THE NURSE CALL PILLOW SPEAKER.
L1	4" CONTINUOUS LINEAR SLOT FIXTURE WITH EXTRUDED ALUMINUM HOUSING, FLUSH SATIN ACRYLIC LENS, ASYMMETRIC DISTRIBUTION, GRID MOUNTING DISTRIBUTION SHOULD AIM TOWARDS THE CENTER OF THE CORRIDOR, LIT CORNERS, 500 LUMEN PER FOOT OUTPUT, 3500K COLOR TEMPERATURE, 120V 0-10V 10% LED DIMMING DRIVER, AND WHITE FINISH.	MARK ARCHITECTURAL LIGHTING # SL-4L-IOP-___-FT-MSLB-WTG-60CRI-___-835LMF-MW-MVN10-120-ZT OR APPROVED EQUAL	120	6WFT LED	PROVIDE LENGTH AS INDICATED ON THE FLOOR PLANS. PROVIDE SHOP DRAWINGS OF FINAL FIXTURE LAYOUT FROM FIXTURE MANUFACTURER DURING THE SUBMITTAL PROCESS FOR REVIEW AND APPROVAL BY THE ENGINEER.
L2	2" CONTINUOUS LINEAR SLOT FIXTURE WITH EXTRUDED ALUMINUM HOUSING, RECESSED SATIN ACRYLIC LENS, SYMMETRIC DISTRIBUTION, FLANGE MOUNTING, 400 LUMEN PER FOOT OUTPUT, 3500K COLOR TEMPERATURE, 120V 0-10V 10% LED DIMMING DRIVER, AND WHITE FINISH.	MARK ARCHITECTURAL LIGHTING # SWIN-MOD-4L-IOP-___-LIGHTING-60CRI-L-IOP-___-FT-_RLP-FL-60CRI-35K-835LMF-MW-MVN10-120-ZT OR APPROVED EQUAL	120	4WFT LED	PROVIDE LENGTH AS INDICATED ON THE FLOOR PLANS. PROVIDE SHOP DRAWINGS OF FINAL FIXTURE LAYOUT FROM FIXTURE MANUFACTURER DURING THE SUBMITTAL PROCESS FOR REVIEW AND APPROVAL BY THE ENGINEER.
L3	4" CONTINUOUS LINEAR SLOT FIXTURE WITH EXTRUDED ALUMINUM HOUSING, FLUSH SATIN ACRYLIC LENS, SYMMETRIC DISTRIBUTION, FLANGE MOUNTING, 600 LUMEN PER FOOT OUTPUT, 3500K COLOR TEMPERATURE, 120V 0-10V 10% LED DIMMING DRIVER, WHITE FINISH, AND WET LOCATION LISTING.	MARK ARCHITECTURAL LIGHTING # SWIN-MOD-4L-IOP-___-LIGHTING-60CRI-L-IOP-___-FT-_RLP-FL-60CRI-35K-835LMF-MW-MVN10-120-ZT-WL OR APPROVED EQUAL	120	6WFT LED	PROVIDE LENGTH AS INDICATED ON THE FLOOR PLANS. PROVIDE SHOP DRAWINGS OF FINAL FIXTURE LAYOUT FROM FIXTURE MANUFACTURER DURING THE SUBMITTAL PROCESS FOR REVIEW AND APPROVAL BY THE ENGINEER.
L4	4" CONTINUOUS LINEAR PERIMETER FIXTURE WITH EXTRUDED ALUMINUM HOUSING, RECESSED SATIN ACRYLIC LENS, GRID MOUNTING, 450 LUMEN PER FOOT OUTPUT, 3500K COLOR TEMPERATURE, 120V 0-10V 10% LED DIMMING DRIVER, AND WHITE FINISH.	MARK ARCHITECTURAL LIGHTING # SPRILED-Q-IOP-___-FT-_RLP-FL-P-09-60CRI-35K-835LMF-MVN1-120-ZT OR APPROVED EQUAL	120	4WFT LED	PROVIDE LENGTH AS INDICATED ON THE FLOOR PLANS. PROVIDE SHOP DRAWINGS OF FINAL FIXTURE LAYOUT FROM FIXTURE MANUFACTURER DURING THE SUBMITTAL PROCESS FOR REVIEW AND APPROVAL BY THE ENGINEER.
L5	4" CONTINUOUS LINEAR DIRECT/INDIRECT PENDANT FIXTURE WITH EXTRUDED ALUMINUM HOUSING, EDGE VIEW DIRECT SATIN ACRYLIC LENS WITH STANDARD LAMBERTIAN DISTRIBUTION, CLEAR ACRYLIC INDIRECT LENS WITH BATWING DISTRIBUTION, 400 LUMEN PER FOOT OUTPUT DIRECT, 600 LUMEN PER FOOT OUTPUT INDIRECT, 3500K COLOR TEMPERATURE, 120V 0-10V 1% LED DIMMING DRIVER, AND TEXTURED SILVER FINISH WITH SQUARE WHITE CANOPY AND WHITE POWER CORD.	MARK ARCHITECTURAL LIGHTING # S4UD-LOS-___-FT-MSLB-80CRI-35K-400LMF-I80CRI-I35K-600LMF-MW-MVN1-SCT-EGLD-120-SLVT-ET-P135A-SQCV-WHTCV-WCRD-DC OR APPROVED EQUAL	120	10WFT LED	PROVIDE LENGTH AS INDICATED ON THE FLOOR PLANS. MOUNT FIXTURE AT 18" BELOW FINISHED CEILING TO TOP OF FIXTURE
L6	2.5" LINEAR DIRECT/INDIRECT ACOUSTIC LED PENDANT WITH EXTRUDED ALUMINUM HOUSING, 8" TALL ACOUSTIC PANEL, RECESSED SATIN ACRYLIC DIRECT LENS, BATWING OPTIC CLEAR ACRYLIC INDIRECT LENS, 200 LUMEN PER FOOT DIRECT OUTPUT, 625 LUMEN PER FOOT INDIRECT OUTPUT, 3500K COLOR TEMPERATURE, UNIVERSAL VOLTAGE 0-10V 10% LED DIMMING DRIVER, WITH SILVER GRAY ACOUSTIC PANEL MATERIAL.	FOCAL POINT LIGHTING # ASM19SS-BWRL-8-3000K-625UP-35K-1C-UNV-LD1-X24_-_-FT-SLG OR APPROVED EQUAL OR APPROVED EQUAL	UNV	8.5WFT LED	PROVIDE LENGTH AS INDICATED ON THE FLOOR PLANS. MOUNT FIXTURE AT 18" BELOW FINISHED CEILING TO TOP OF FIXTURE
L6A	2.5" LINEAR ACOUSTIC PENDANT (NO LIGHT FIXTURE, WITH 8" TALL ACOUSTIC PANEL, AND SILVER GRAY FINISH.	FOCAL POINT LIGHTING # AUSM19-8-X24_-_-FT-SLG OR APPROVED EQUAL	N/A	N/A	PROVIDE LENGTH AS INDICATED ON THE FLOOR PLANS. MOUNT FIXTURE AT 18" BELOW FINISHED CEILING TO TOP OF FIXTURE
W1	STATIC WHITE LED TAPE LIGHT WITH 45 DEGREE ROUND MOUNTING CHANNEL AND FROSTED LENS, 375 LUMENS PER FOOT OUTPUT, 3500K COLOR TEMPERATURE REMOTE UNIVERSAL VOLTAGE TO 24VDC, 0-10V 10% LED DIMMING POWER SUPPLY AND SATIN ALUMINUM FINISH.	ILIAD LIGHTING # SLA12 20FT 35K 80CRI-SM5-48IN-FR-SA OR APPROVED EQUAL	UNV	4.4WFT LED	PROVIDE LENGTH AS INDICATED ON THE FLOOR PLANS.
W2	STATIC WHITE TAPE LIGHT WITH INTEGRATED MICRO OPTICS, 15 DEGREE OPTIC, 425 LUMENS PER FOOT OUTPUT, 3500K COLOR TEMPERATURE, REMOTE UNIVERSAL VOLTAGE 0-10V LED DIMMING DRIVER, AND ALUMINUM SURFACE MOUNTING CHANNEL	ILIAD LIGHTING # ICA16-15D-5FT-35K-80CRI-DLDP5-__3K-RPCZT-IOLP-5FT-SA OR APPROVED EQUAL	UNV	4.8WFT LED	PROVIDE LENGTH AS INDICATED ON THE FLOOR PLANS.
W3	STATIC WHITE LED TAPE LIGHT WITH 255 LUMENS PER FOOT OUTPUT, 3500K COLOR TEMPERATURE REMOTE UNIVERSAL VOLTAGE TO 24VDC LED POWER SUPPLY AND WET LOCATION LISTING.	ILIAD LIGHTING # SLW212 20FT 35K 80CRI-DLDP5__-W-RPCZT-SLWCLIP OR APPROVED EQUAL	UNV	2.2WFT LED	PROVIDE LENGTH AS INDICATED ON THE FLOOR PLANS.
W4	STATIC WHITE LED TAPE LIGHT WITH LOW PROFILE SURFACE MOUNTING CHANNEL AND FROSTED LENS, 375 LUMENS PER FOOT OUTPUT, 3500K COLOR TEMPERATURE REMOTE UNIVERSAL VOLTAGE TO 24VDC, 0-10V 10% LED DIMMING POWER SUPPLY AND SATIN ALUMINUM FINISH.	ILIAD LIGHTING # SLA12 20FT 35K 80CRI-SM14-48IN-FR-SA OR APPROVED EQUAL	UNV	4.4WFT LED	PROVIDE LENGTH AS INDICATED ON THE FLOOR PLANS.
P1	DECORATIVE METALLIC GEOMETRIC CHANDELIER WITH INTERCONNECTED GEOMETRIC SHAPES, WITH 28 MODULES FOR AN OVERALL WIDTH OF 120", INCLUDED LED LAMP, REMOTE 120VAC TO 24VDC CLASS 2 LED DIMMING DRIVER, WHITE EXTERIOR AND SATIN NICKEL INTERIOR FINISH.	GABRIEL SCOTT LIGHTING # WELLES-28X-EBSW12DC OR APPROVED EQUAL	120	84W LED	PROVIDE SHOP DRAWING WITH ALL PARTS AND PIECES FOR FINAL APPROVAL FROM ARCHITECTIEN GINEER.
P2A	36" DECORATIVE DIRECT/INDIRECT LED TRIANGLE PENDANT WITH EXTRUDED ALUMINUM HOUSING, FROSTED ACRYLIC LENS, STAINLESS STEEL SUSPENSION CABLES, 7500 LUMEN OUTPUT, 3500K COLOR TEMPERATURE, REMOTE UNIVERSAL VOLTAGE 0-10V 1% LED DIMMING DRIVER, AND METALLIC SILVER FINISH.	BETA CALCO # BB-4120-D35-N35-S1-MS OR APPROVED EQUAL	UNV	60W LED	REFER TO FLOOR PLANS FOR MOUNTING INFORMATION.
P2B	48" DECORATIVE DIRECT/INDIRECT LED TRIANGLE PENDANT WITH EXTRUDED ALUMINUM HOUSING, FROSTED ACRYLIC LENS, STAINLESS STEEL SUSPENSION CABLES, 10000 LUMEN OUTPUT, 3500K COLOR TEMPERATURE, REMOTE UNIVERSAL VOLTAGE 0-10V 1% LED DIMMING DRIVER, AND METALLIC SILVER FINISH.	BETA CALCO # BB-4150-D35-N35-S1-MS OR APPROVED EQUAL	UNV	80W LED	REFER TO FLOOR PLANS FOR MOUNTING INFORMATION.
P2C	60" DECORATIVE DIRECT/INDIRECT LED TRIANGLE PENDANT WITH EXTRUDED ALUMINUM HOUSING, FROSTED ACRYLIC LENS, STAINLESS STEEL SUSPENSION CABLES, 12000 LUMEN OUTPUT, 3500K COLOR TEMPERATURE, REMOTE UNIVERSAL VOLTAGE 0-10V 1% LED DIMMING DRIVER, AND METALLIC SILVER FINISH.	BETA CALCO # BB-4140-D35-N35-S1-MS OR APPROVED EQUAL	UNV	100W LED	REFER TO FLOOR PLANS FOR MOUNTING INFORMATION.
P2D	72" DECORATIVE DIRECT/INDIRECT LED TRIANGLE PENDANT WITH EXTRUDED ALUMINUM HOUSING, FROSTED ACRYLIC LENS, STAINLESS STEEL SUSPENSION CABLES, 15000 LUMEN OUTPUT, 3500K COLOR TEMPERATURE, REMOTE UNIVERSAL VOLTAGE 0-10V 1% LED DIMMING DRIVER, AND METALLIC SILVER FINISH.	BETA CALCO # BB-4150-D35-N35-S1-MS OR APPROVED EQUAL	UNV	120W LED	REFER TO FLOOR PLANS FOR MOUNTING INFORMATION.
P3A	36" DECORATIVE INDIRECT LED TRIANGLE PENDANT WITH EXTRUDED ALUMINUM HOUSING, FROSTED ACRYLIC LENS, STAINLESS STEEL SUSPENSION CABLES, 5000 LUMEN OUTPUT, 3500K COLOR TEMPERATURE, REMOTE UNIVERSAL VOLTAGE 0-10V 1% LED DIMMING DRIVER, AND METALLIC SILVER FINISH.	BETA CALCO # BB-4320-35-S1-MS OR APPROVED EQUAL	UNV	30W LED	REFER TO FLOOR PLANS FOR MOUNTING INFORMATION.
P3B	48" DECORATIVE INDIRECT LED TRIANGLE PENDANT WITH EXTRUDED ALUMINUM HOUSING, FROSTED ACRYLIC LENS, STAINLESS STEEL SUSPENSION CABLES, 10000 LUMEN OUTPUT, 3500K COLOR TEMPERATURE, REMOTE UNIVERSAL VOLTAGE 0-10V 1% LED DIMMING DRIVER, AND METALLIC SILVER FINISH.	BETA CALCO # BB-4330-35-S1-MS OR APPROVED EQUAL	UNV	40W LED	REFER TO FLOOR PLANS FOR MOUNTING INFORMATION.
P4	2" ROUND, LED CYLINDER PENDANT DOWNLIGHT WITH DIE CAST ALUMINUM HOUSING, CLEAR SEMI-SPECULAR REFLECTOR WITH 55 DEGREE CUTOFF, 1500 LUMEN OUTPUT, 3500K COLOR TEMPERATURE, UNIVERSAL VOLTAGE 0-10V 1% LED DIMMING DRIVER, AND BLACK FINISH.	GOTHAM # CO CYL-35/15-2AR-LSS-83D-MVOLT-UGZ-PAYR-OBL OR APPROVED EQUAL	UNV	22W LED	MOUNT SUCH THAT THE BOTTOM OF THE PENDANT IS FLUSH WITH THE BOTTOM OF THE SLAT CEILING.
P5	LARGE DECORATIVE PENDANT WITH SPUN METAL CONICAL SHADE, E26 MEDIUM BASE LAMP SOCKET, AND RUBBERIZED WHITE CORD WITH CANOPY FINISH.	TECH LIGHTING # 700-TD-SIGGP-WL OR APPROVED EQUAL	120	10W LED	CONTRACTOR SHALL PROVIDE FIXTURE WITH 800 LUMEN, 3500K COLOR TEMP A19 LED REPLACEMENT LAMP. COORDINATE MOUNTING HEIGHT WITH ARCHITECT.
P6	MEDIUM DECORATIVE PENDANT WITH SPUN METAL CONICAL SHADE, E26 MEDIUM BASE LAMP SOCKET, AND RUBBERIZED WHITE CORD WITH CANOPY FINISH.	TECH LIGHTING # 700-TD-SIG-WL OR APPROVED EQUAL	120	10W LED	CONTRACTOR SHALL PROVIDE FIXTURE WITH 800 LUMEN, 3500K COLOR TEMP A19 LED REPLACEMENT LAMP. COORDINATE MOUNTING HEIGHT WITH ARCHITECT.
P7	SMALL DECORATIVE MONO-POINT PENDANT WITH SPUN METAL CONICAL SHADE, MB16 (GU5.3) LAMP SOCKET, AND RUBBERIZED WHITE CORD WITH CANOPY FINISH.	TECH LIGHTING # 700-MP-SIGM-WL-S OR APPROVED EQUAL	120	8W LED	CONTRACTOR SHALL PROVIDE FIXTURE WITH 500 LUMEN, 3500K COLOR TEMP, SORRA MR16 LED REPLACEMENT LAMP. COORDINATE MOUNTING HEIGHT WITH ARCHITECT.
P8	34" ROUND DECORATIVE ACOUSTIC LED DRUM PENDANT WITH INTEGRAL VOLTAGE 0-10V (10%) LED DIMMING DRIVER, 3500K COLOR TEMPERATURE, WHITE POWER CORD, CHROME CANOPY, GEO PATTERN OUTER SHADE AND CARIBBEAN BLUE INNER ACOUSTIC SHADE	LUMETTA # PDHAL34-2LP2-DL24-D-T10 OR APPROVED EQUAL	UNV	21W LED	COORDINATE MOUNTING HEIGHT WITH ARCHITECT.
P9	LARGE DECORATIVE PENDANT WITH SPUN METAL DOUBLE CONICAL SHADE, E26 MEDIUM BASE LAMP SOCKET, AND RUBBERIZED WHITE FINISH.	TECH LIGHTING # 700-TD-BWLGP-W-S OR APPROVED EQUAL	120	10W LED	CONTRACTOR SHALL PROVIDE FIXTURE WITH 1000 LUMEN, 3500K COLOR TEMP A21 LED REPLACEMENT LAMP. COORDINATE MOUNTING HEIGHT WITH ARCHITECT.
Q2	2' LED UNDER CABINET LIGHT WITH STEEL HOUSING, DIFFUSE WHITE ACRYLIC LENS, 120 VOLT LED DRIVER, 3500K COLOR TEMPERATURE INTEGRAL ROCKER SWITCH, AND WHITE FINISH.	LITHONIA # UCEL-24IN-35K-80CRI-SWR-WH OR APPROVED EQUAL	120	12W LED	MOUNT TO UNDERSIDE OF UPPER CABINET WHERE INDICATED.
S1	CITY OF ATLANTA SPEC'D IC POST TOP ACORN SITE FIXTURE WITH CAST ALUMINUM HOUSING, 4000K COLOR TEMPERATURE, ACRYLIC REFRACTOR, POLYCARBONATE RITTER AND TOP BAND, MOUNTED TO A 11'-0" ALUMINUM TAPERED AND FLUTED POLE. FIXTURE AND POLE TO BE CITY OF ATLANTA CODA GREEN. 30" X 5" TAPERED ALUMINUM POLE	HOLOPHANE FIXTURE # ARIDB1-P40-40K-AS-M-CMQ(CODA GREEN)-5-FIP-CMQ(CODA GREEN)-RAM-CMQ(CODE GREEN) POLE # WN11-401702-CAVCM-6(C), 70X12.0ALT45)-373-CLD(CS-BEARINGPLT BREAKCOUP-AB-31-4-RPD455374 OR APPROVED EQUAL	UNV	81W LED	PROVIDE ALL NECESSARY COMPONENTS, FINISHES, AND INSTALLATION PROVISIONS IN ACCORDANCE WITH THE CITY OF ATLANTA STREET LIGHTING REQUIREMENTS.
S2	[illegible] GARAGE FIXTURE WITH CAST ALUMINUM HOUSING, MICRO PRISMATIC ACRYLIC LENS, SURFACE MOUNT, 7500 LUMEN OUTPUT WITH 500 LUMEN UPLIGHT OPTION, 3500K COLOR TEMPERATURE, UNIVERSAL VOLTAGE LED DRIVER, AND NATURAL ALUMINUM FINISH	LITHONIA # VCPG-W-P-P4-35K-80CRI-T5S-MVOLT-SRM-UPL1-DNAXD OR APPROVED EQUAL	UNV	56W LED	SURFACE MOUNT TO BOTTOM OF STRUCTURE
U1	[illegible] INGROUND UPLIGHT WITH 10" DIA. ROUND TRAFFIC RATED WALK OVER POLYMER BASE, 360 ROTATION AND UP TO 15 DEGREE TILT ADJUSTMENT, 30 DEGREE BEAM SPREAD, INTERNAL LOUVER, CLEAR LENS, 5000 LUMEN OUTPUT, 3500K COLOR TEMPERATURE, UNIVERSAL VOLTAGE 0-10V LED DIM