



1 INTERIOR WALL TYPICAL ELEVATOR JAMB/HEAD
3" = 1'-0"

2 INTERIOR WALL/FLOOR TYPICAL ELEVATOR SILL
3" = 1'-0"

3 INTERIOR WALL/FLOOR TYPICAL ELEVATOR/CORRIDOR
3" = 1'-0"

4 EXTERIOR WALL/ROOF TYPICAL ELEVATOR
3" = 1'-0"

5 EXTERIOR WALL/ROOF TYPICAL ELEVATOR OVER RUN
3" = 1'-0"

6 INTERIOR FLOOR/CEILING AT LAUNDRY CHUTE
3" = 1'-0"

No.	Description	Date

MEISTER-COX ARCHITECTS
 INFO@MEISTER-COX.COM
 PHONE: 610-375-1331 FAX: 610-375-4655
 1522 PENN AVENUE WYOMISSING, PA 19380
 WWW.MEISTER-COX.COM

TYPICAL DETAILS @ ELEVATOR / CHUTE
 HOLIDAY INN EXPRESS & SUITES
 INTERSECTION OF HAYNES PLACE & LAMM RD.
 WILSON, NC 27893

STATUS: BIDDING
 PROJ. DATE: 06-07-19
 PROJ. NO: 18-176
 PRINTED: 6/7/2019 7:11:55 PM
 DRAWN BY: RFF
 CHECKED BY: TGC
 SHEET NO. A538
 SCALE: 3" = 1'-0"

- CONSTRUCTION NOTES:**
- EIFS THICKNESS IS TYPICALLY 3/4" WHERE INDICATED ON EXTERIOR ELEVATION AS EIFS 2. ADJUST DETAIL FOR EIFS THICKNESS 3/4". SEE ALSO EIFS TRANSITION DETAILS FOR ADDITIONAL INFORMATION.
 - SEE WALL TYPE DETAILS FOR ADDITIONAL INFORMATION. STAIR AND ELEVATOR WALLS REQUIRE 2 HOUR RATED ASSEMBLIES.
 - EIFS SYSTEM SHALL BE INSTALLED WITH A MOISTURE DRAINAGE SYSTEM. SEE DRAWING A701 AND A702. SUBMIT MANUFACTURER INFORMATION WITH MOISTURE DRAINAGE DETAILS TO CODE OFFICIAL FOR REVIEW.
 - THIN BRICK CLADDING SHALL UTILIZE INTEGRAL DRAINAGE CHAMBER WITH THIN TECH AIR VENT AND FLASHING. REFER TO MANUFACTURER DETAILS FOR MORE INFORMATION.
 - USE OF BATT INSULATION OR LOOSE FILL INSULATION AT POOL IS PROHIBITED. USE MED. DENSITY CLOSED CELL SPRAY FOAM INSULATION.



N:\Active Projects\hospitality\2018 Holiday Inn Express - Wilson, NC\Drawings CAD-Rev\18-176.rvt